

[Engine & Cooling](#)
[Fuel](#)
[Ignition](#)
[Electrical](#)
[Running gear](#)
[Torque settings](#)
[Capacities](#)
[Notes & Illustrations](#)



Automotive Technical DATA BOOK

Click on one of the buttons above to view data for this car. To return to this screen and make another choice, click anywhere on the data screen.

MENU

HELP

Engine and cooling system Discovery V8 1989 to 1992

Type	V8 OHV
Capacity (cm ³) / number of cylinders	3528 / 8
Compression ratio / pressure	bar 8.13 / ≥9.3
Oil pressure	bar [1.9]
Oil temperature	°C 80
Valve clearance - inlet	mm 0: Hyd.
Valve clearance - exhaust	mm 0: Hyd.
Firing order	1-8-4-3-6-5-7-2
No 1 cylinder position	FL
Thermostat opening temperature	°C 82
Radiator cap pressure	bar 1.04

Fuel system Discovery V8 1989 to 1992

Idle speed - manual [auto]	rpm	700±50
Fast idle speed - manual [auto]	rpm	1100±50
CO @ idle speed [3000 rpm] - see page VI	%	1.0 to 2.0
HC @ idle speed [3000 rpm] - see page VI	ppm	≤1200
CO ₂ @ idle speed [3000 rpm] - see page VI	%	—
O ₂ @ idle speed [3000 rpm] - see page VI	%	—
Carburettor / fuel injection	SU	
Type / ref	2x HIF44	
Main jet / needle	0.100 / BGV	
Injection pressure	bar	—
Pump pressure	bar	0.28 to 0.42
Octane rating	RON	90[E 95 RON]

Ignition system Discovery V8 1989 to 1992

Type	Electronic	
Ignition coil	Bosch 0221-122-392	
Primary resistance	ohms	—
Ballast resistor	ohms	—
Voltage - Tmnl 15(+) to earth	V	—
Distributor	Lucas	
Points gap (air gap)	mm	[0.20 to 0.36]
Dwell angle	° (%)	—
Condenser capacity	µF	—
Rotation	Clockwise	
Ignition timing - basic [static	° Crankshaft @ rpm	6±1 BTDC @ 750±50
V = Vacuum NV = No Vacuum		NV
Total ignition advance	° Crankshaft @ rpm	—
	° Crankshaft @ rpm	—
	° Crankshaft @ rpm	—
Centrifugal check.	° Crankshaft @ rpm	0 to 3 @ 1000
	° Crankshaft @ rpm	13 to 21 @ 2400
	° Crankshaft @ rpm	22 to 28 @ 3600
Vacuum range check	mbar	—
Maximum vacuum advance	° Crankshaft	—
Spark plugs	Champion	
Type	RN9YCC	
Electrode gap	mm	0.80

Electrical system Discovery V8 1989 to 1992

Battery	V / CC / RC	12 / 380 / 120
Alternator voltage / full load current / engine rpm		14.2±0.25 / _ / 3000
Starter motor current / voltage - cranking	A / V	—
- locked	A / V	—

Running gear Discovery V8 1989 to 1992

Brakes -		
Front (min. friction material thickness)	mm	—
Rear (min. friction material thickness)	mm	—

Tyres		
Saloon	Size	—
Estate / Van	Size	205x16
Pressure - front / rear - Saloon	bar	—
- Estate / Van	bar	1.9 / 2.6

Front suspension / wheel alignment

Toe-in (+) / Toe-out (-)	mm [°]	-1.2 to -2.4
Camber		0
Castor		+3°
King pin inclination		+7°

Rear suspension / wheel alignment

Toe-in (+) / Toe-out (-)	mm [°]	—
Camber		—

Torque wrench settings Discovery V8 1989 to 1992

Cylinder head - stage 1	Nm	No 1 to 10: 88 to 95
- stage 2	Nm	No11 to 14: 54 to 61
Cylinder head - stage 3	Nm	—
- stage 4	Nm	—
Big-end bearings	Nm	47 to 54
Main bearings	Nm	¹
Clutch cover	Nm	24 to 30
Flywheel [driveplate]	Nm	74 to 81
Front hubs	Nm	—
Rear hubs	Nm	—
Wheel nuts / bolts	Nm	129
Spark plugs	Nm	—


Capacities Discovery V8 1989 to 1992

Engine oil & filter	litres	5.7
Gearbox - 4-speed [5-speed]	litres	2.7. Transfer:2.5
Automatic transmission - refill	litres	—
Final drive	litres	Front & rear: 1.7
Cooling system	litres	11.3
Fuel tank	litres	88.6


Notes and Illustrations

¹No 1 to 4: 68 to 75. Others: 88 to 95


1: Idle speed 2: CO / Mixture



3528 cm³



3528 cm³



SU HIF 44