

Engine & Cooling

Fuel

Ignition


Electrical

Running gear

Torque settings

Capacities

Notes & Illustrations



Automotive
Technical
DATA
BOOK

Click on one of the buttons above to view data for this car. To return to this screen and make another choice, click anywhere on the data screen.

MENU

HELP

Engine and cooling system

C230 Kompressor

1995 to 1997

Type		DOHC 16V 142kW
Capacity (cm³) / number of cylinders		2295 / 4
Compression ratio / pressure	bar	8.8 / _
Oil pressure	bar	0.3 [3.0 @ 3000rpm]
Oil temperature	°C	80
Valve clearance - inlet	mm	0: Hyd.
Valve clearance - exhaust	mm	0: Hyd.
Firing order		1-3-4-2
No 1 cylinder position		F
Thermostat opening temperature	°C	87±2
Radiator cap pressure	bar	1.40±0.10

Fuel system

C230 Kompressor

1995 to 1997

Idle speed - manual [auto]	rpm	700 to 800 N/A
Fast idle speed - manual [auto]	rpm	_
CO @ idle speed [3000 rpm] - see page VI	%	≤0.3
HC @ idle speed [3000 rpm] - see page VI	ppm	≤200
CO2 @ idle speed [3000 rpm] - see page VI	%	_
O2 @ idle speed [3000 rpm] - see page VI	%	_
Carburettor / fuel injection		_ Bosch
Type / ref		HFM
Main jet / needle		_
Injection pressure	bar	3.2 to 36
Pump pressure	bar	_
Octane rating	RON	95[U]

Ignition system

C230 Kompressor

1995 to 1997

Type		Computerized
Ignition coil		_
Primary resistance	ohms	0.3 to 0.6
Ballast resistor	ohms	_
Voltage - Tmnl 15(+) to earth	V	Battery
Distributor		_
Points gap (air gap)	mm	_
Dwell angle	° (%)	_
Condenser capacity	µF	_
Rotation		_
Ignition timing - basic [static	° Crankshaft @ rpm	Computer control N/A
V = Vacuum NV = No Vacuum		_
Total ignition advance	° Crankshaft @ rpm	Computer control
	° Crankshaft @ rpm	_
	° Crankshaft @ rpm	_
Centrifugal check.	° Crankshaft @ rpm	Computer control
	° Crankshaft @ rpm	_
	° Crankshaft @ rpm	_
Vacuum range check	mbar	Computer control
Maximum vacuum advance	° Crankshaft	_
Spark plugs		Bosch/Champion
Type		F8DCO / C10YCC
Electrode gap	mm	0.80

Electrical system

C230 Kompressor

1995 to 1997

Battery	V / CC / RC	12V 62Ah
Alternator voltage / full load current / engine rpm		14.0 / 90 / _
Starter motor current / voltage - cranking	A / V	75 / 11.5
- locked	A / V	_

Running gear

C230 Kompressor

1995 to 1997

Brakes -		
Front (min. friction material thickness)	mm	2.0
Rear (min. friction material thickness)	mm	2.0

Tyres		
Saloon	Size	195/65x15: 205/60x15
Estate / Van	Size	_
Pressure - front / rear - Saloon	bar	2.1 / 2.3
- Estate / Van	bar	_

Front suspension / wheel alignment

Toe-in (+) / Toe-out (-)	mm [°]	[+20' ± 10']
Camber		- 35' ± 20'. Sport: -55'±20'
Castor		4°40'±30. Sport: 5°10'±30'
King pin inclination		_

Rear suspension / wheel alignment

Toe-in (+) / Toe-out (-)	mm [°]	+0°33' ± 7'
Camber		_

Torque wrench settings

C230 Kompressor

1995 to 1997

Cylinder head - stage 1	Nm	55. Bolt length ≤105mm
- stage 2	Nm	+ 90°
Cylinder head - stage 3	Nm	+ 90°
- stage 4	Nm	_
Big-end bearings	Nm	30, + 90 to 100°
Main bearings	Nm	55, + 90 to 100°
Clutch cover	Nm	25
Flywheel [driveplate]	Nm	30, + 90 to 100°
Front hubs	Nm	WSM
Rear hubs	Nm	200 to 240
Wheel nuts / bolts	Nm	110
Spark plugs	Nm	25 to 30

Capacities

C230 Kompressor

1995 to 1997

Engine oil & filter	litres	5.8
Gearbox - 4-speed [5-speed]	litres	1.5
Automatic transmission - refill	litres	_
Final drive	litres	1.1
Cooling system	litres	8.3
Fuel tank	litres	62

Notes and Illustrations

