Haynes THE BOOK

Automotive Technical DATA BOOK

Click on one of the buttons above to view data for this car. To return to this screen and make another choice, click anywhere on the data screen.

MENU | HELP

Engine and cooling system

		E420 (124.034) 1992 to 1995
Type		119.975 V8 205kW
Capacity (cm³) / number of cylinders		4196 / 8
Compression ratio / pressure	bar	11.0 / _
Oil pressure	bar	0.3 [3.0]
Oil temperature	ºC	90
Valve clearance - inlet	mm	0: Hyd.
Valve clearance - exhaust	mm	0: Hyd.
Firing order		1-5-4-8-6-3-7-2
No 1 cylinder position		FR
Thermostat opening temperature	ºC	84±2
Radiator cap pressure	bar	1.4±0.1

Fuel system

		E420 (124.034) 1992 to 1995
Idle speed - manual [auto]	rpm	600 to 750
Fast idle speed - manual [auto]	rpm	_
CO @ idle speed [3000 rpm] - see page VI	%	≤0.5
HC @ idle speed [3000 rpm] - see page VI	ppm	≤100
CO2 @ idle speed [3000 rpm] - see page VI	%	_
O2 @ idle speed [3000 rpm] - see page VI	%	_
Carburettor / fuel injection		Bosch
Type / ref		LH Electronic
Main jet / needle		_
Injection pressure	bar	_
Pump pressure	bar	_
Octane rating	RON	95[U]

Ignition system

		E420 (124.034) 1992 to 1995
Type		EZL
Ignition coil		Bosch
Primary resistance	ohms	0.3 to 0.6
Ballast resistor	ohms	_
Voltage - Tmnl 15(+) to earth	V	Battery
Distributor		Bosch
Points gap (air gap)	mm	_
Dwell angle	º (%)	_
Condenser capacity	µF	_
Rotation		_
Ignition timing - basic [static	º Crankshaft @ rpm	N/A
V = Vacuum NV = No Vacuum		_
Total ignition advance	º Crankshaft @ rpm	_
	º Crankshaft @ rpm	_
	º Crankshaft @ rpm	_
Centrifugal check.	º Crankshaft @ rpm	Computer control
	º Crankshaft @ rpm	_
	º Crankshaft @ rpm	_
Vacuum range check	mbar	Computer control
Maximum vacuum advance	º Crankshaft	_
Spark plugs		Bosch/Champion
Type		F8DCO / C10YCC
Electrode gap	mm	0.80

Electrical system

		E420 (124.034) 1992 to 1995
Battery	V / CC / RC	12 / 190 / 62Ah
Alternator voltage / full load current / engine rpm		14.0 / 80 / 2490
Starter motor current / voltage - cranking	A / V	95 / 11.5 (no load)
- locked	A / V	650 to 840 / 3.8

Running gear

		E420 (124.034) 1992 to 1995
Brakes -		
Front (min. friction material thickness)	mm	2.0
Rear (min. friction material thickness)	mm	2.0
Tyres		
Saloon	Size	215/55x16
Estate / Van	Size	_
Pressure - front / rear - Saloon	bar	2.5 / 2.6
- Estate / Van	bar	_
Front suspension / wheel alignment		
Toe-in (+) / Toe-out (–)	mm [º]	[+20'±10']
Camber		-38'±10'
Castor		+10°32'±30'
King pin inclination		_
Rear suspension / wheel alignment		
Toe-in (+) / Toe-out (–)	mm [º]	[+20' to 35']
Camber		-1°30'±30'

Torque wrench settings

		E420 (124.034) 1992 to 1995
Cylinder head - stage 1	Nm	55[1]
- stage 2	Nm	+ 90°
Cylinder head - stage 3	Nm	+ 90°
- stage 4	Nm	_
Big-end bearings	Nm	45 + 90 to 100°
Main bearings	Nm	50
Clutch cover	Nm	25
Flywheel [driveplate]	Nm	35 + 90 to 100°
Front hubs	Nm	WSM
Rear hubs	Nm	WSM
Wheel nuts / bolts	Nm	110
Spark plugs	Nm	30

Capacities

		E420 (124.034) 1992 to 1995
Engine oil & filter	litres	8.0
Gearbox - 4-speed [5-speed]	litres	_
Automatic transmission - refill	litres	_
Final drive	litres	_
Cooling system	litres	12.5
Fuel tank	litres	70

Notes and Illustrations

[1]**Bolts marked 'a' on diagram: 25**