


Engine & CoolingFuelIgnitionElectricalRunning gearTorque settingsCapacitiesNotes & Illustrations



Automotive Technical
DATA BOOK

Click on one of the buttons above to view data for this car. To return to this screen and make another choice, click anywhere on the data screen.

MENUHELP

Engine and cooling system

309, 1.41989 to 1991

Type	TU3A (K1G) (51kW)	
Capacity (cm³) / number of cylinders	1360 / 4	
Compression ratio / pressure	bar	9.3 / _
Oil pressure	bar	1.5 [3.0]
Oil temperature	°C	80
Valve clearance - inlet	mm	0.20
Valve clearance - exhaust	mm	0.40
Firing order	1-3-4-2	
No 1 cylinder position	FE	
Thermostat opening temperature	°C	88
Radiator cap pressure	bar	1.0

Fuel system

309, 1.41989 to 1991

Idle speed - manual [auto]	rpm	750±50
Fast idle speed - manual [auto]	rpm	_
CO @ idle speed [3000 rpm] - see page VI	%	0.8 to 1.5
HC @ idle speed [3000 rpm] - see page VI	ppm	≤1200
CO2 @ idle speed [3000 rpm] - see page VI	%	_
O2 @ idle speed [3000 rpm] - see page VI	%	_
Carburettor / fuel injection	Solex	
Type / ref	S: 34 PBISA 17-481	
Main jet / needle	132	
Injection pressure	bar	_
Pump pressure	bar	0.25
Octane rating	RON	97[RA] ¹

Ignition system

309, 1.41989 to 1991

Type	Electronic - Hall effect	
Ignition coil	Bosch, Ducellier BTR01	
Primary resistance	ohms	0.7
Ballast resistor	ohms	_
Voltage - Tmnl 15(+) to earth	V	_
Distributor	Bosch/Ducellier	
Points gap (air gap)	mm	_
Dwell angle	° (%)	_
Condenser capacity	µF	_
Rotation	Clockwise	
Ignition timing - basic [static	° Crankshaft @ rpm	8 BTDC @ 750 ¹
V = Vacuum NV = No Vacuum	NV	
Total ignition advance	° Crankshaft @ rpm	C057-D044
	° Crankshaft @ rpm	_
	° Crankshaft @ rpm	_
Centrifugal check.	° Crankshaft @ rpm	7 to 11 @ 1000
	° Crankshaft @ rpm	11 to 15 @ 1600
	° Crankshaft @ rpm	31 to 35 @ 5600
Vacuum range check	mbar	160 to 385
Maximum vacuum advance	° Crankshaft	6.5 to 9.5
Spark plugs	Eyquem/Champion	
Type	FC52LS / C9YCX	
Electrode gap	mm	0.80

Electrical system

309, 1.41989 to 1991

Battery	V / CC / RC	12 / 210 / 65
Alternator voltage / full load current / engine rpm	13.8 to 14.8 / _ / 3000	
Starter motor current / voltage - cranking	A / V	_
- locked	A / V	_

Running gear

309, 1.41989 to 1991

Brakes -		
Front (min. friction material thickness)	mm	1.0
Rear (min. friction material thickness)	mm	_

Tyres		
Saloon	Size	155x14: 165/70x13
Estate / Van	Size	_
Pressure - front / rear - Saloon	bar	1.9 / 2.1
- Estate / Van	bar	_

Front suspension / wheel alignment		
Toe-in (+) / Toe-out (-)	mm [°]	+0.5±0.5 PW
Camber	-30'±30'	
Castor	+2°±30'	
King pin inclination	+10°15'±30'	

Rear suspension / wheel alignment		
Toe-in (+) / Toe-out (-)	mm [°]	+1.6±0.8 PW ²
Camber	-50'±30'	

Torque wrench settings

309, 1.41989 to 1991

Cylinder head - stage 1	Nm	20
- stage 2	Nm	+ 240°
Cylinder head - stage 3	Nm	_
- stage 4	Nm	_
Big-end bearings	Nm	40
Main bearings	Nm	WSM
Clutch cover	Nm	15
Flywheel [driveplate]	Nm	65 LkC
Front hubs	Nm	265
Rear hubs	Nm	215
Wheel nuts / bolts	Nm	85
Spark plugs	Nm	28

Capacities


309, 1.41989 to 1991

Engine oil & filter	litres	3.5
Gearbox - 4-speed [5-speed]	litres	2.0
Automatic transmission - refill	litres	_
Final drive	litres	WT
Cooling system	litres	7.5
Fuel tank	litres	55


Notes and Illustrations

¹[E 95 RON], -4°
²90 ►: +1.8±0.8


1: Idle speed2: CO / Mixture




1360 cm³



1360 cm³



Solex PBISA



Solex PBISA