

Engine & Cooling

Fuel

Ignition


Electrical

Running gear

Torque settings

Capacities

Notes & Illustrations



Automotive Technical
DATA BOOK

Click on one of the buttons above to view data for this car. To return to this screen and make another choice, click anywhere on the data screen.

MENU

HELP

Engine and cooling system

406 1.6

1996 to 1997

Type	XU5JPL3 BFZ SOHC 8V 65kW	
Capacity (cm³) / number of cylinders	1580 / 4	
Compression ratio / pressure	bar	9.25 /
Oil pressure	bar	(5.0)
Oil temperature	°C	80
Valve clearance - inlet	mm	0.20 ± 0.05
Valve clearance - exhaust	mm	0.40 ± 0.05
Firing order	1-3-4-2	
No 1 cylinder position	FE	
Thermostat opening temperature	°C	89
Radiator cap pressure	bar	1.4

Fuel system

406 1.6

1996 to 1997

Idle speed - manual [auto]	rpm	850 ± 50
Fast idle speed - manual [auto]	rpm	—
CO @ idle speed [3000 rpm] - see page VI	%	≤0.3
HC @ idle speed [3000 rpm] - see page VI	ppm	≤200
CO2 @ idle speed [3000 rpm] - see page VI	%	—
O2 @ idle speed [3000 rpm] - see page VI	%	—
Carburettor / fuel injection	_Magneti-Marelli	
Type / ref	Monopoint 8P	
Main jet / needle	—	
Injection pressure	bar	2.3 to 2.7
Pump pressure	bar	—
Octane rating	RON	95[U]

Ignition system

406 1.6

1996 to 1997

Type	Computerized	
Ignition coil	—	
Primary resistance	ohms	—
Ballast resistor	ohms	—
Voltage - Tmnl 15(+) to earth	V	—
Distributor	—	
Points gap (air gap)	mm	—
Dwell angle	° (%)	—
Condenser capacity	µF	—
Rotation	—	
Ignition timing - basic [static	° Crankshaft @ rpm	Computer control N/A
V = Vacuum NV = No Vacuum	—	
Total ignition advance	° Crankshaft @ rpm	Computer control
	° Crankshaft @ rpm	—
	° Crankshaft @ rpm	—
Centrifugal check.	° Crankshaft @ rpm	Computer control
	° Crankshaft @ rpm	—
	° Crankshaft @ rpm	—
Vacuum range check	mbar	Computer control
Maximum vacuum advance	° Crankshaft	—
Spark plugs	—	
Type	—	
Electrode gap	mm	—

Electrical system

406 1.6

1996 to 1997

Battery	V / CC / RC	—
Alternator voltage / full load current / engine rpm	—	
Starter motor current / voltage - cranking	A / V	—
- locked	A / V	—

Running gear

406 1.6

1996 to 1997

Brakes -		
Front (min. friction material thickness)	mm	2.0
Rear (min. friction material thickness)	mm	1.0

Tyres		
Saloon	Size	185/70x14
Estate / Van	Size	—
Pressure - front / rear - Saloon	bar	2.3 / 2.3
- Estate / Van	bar	—

Front suspension / wheel alignment		
Toe-in (+) / Toe-out (–)	mm [°]	+0.0±0.5
Camber	0°±30'	
Castor	3°30'±30'	
King pin inclination	11°30'±30'	

Rear suspension / wheel alignment		
Toe-in (+) / Toe-out (–)	mm [°]	+1.5±0.5
Camber	1°50'±30'	

Torque wrench settings

406 1.6

1996 to 1997

Cylinder head - stage 1	Nm	60 slacken ¹²²
- stage 2	Nm	20 +100°
Cylinder head - stage 3	Nm	+100°
- stage 4	Nm	+100°
Big-end bearings	Nm	20 +70°
Main bearings	Nm	55
Clutch cover	Nm	—
Flywheel [driveplate]	Nm	50 LcK
Front hubs	Nm	325
Rear hubs	Nm	202
Wheel nuts / bolts	Nm	90
Spark plugs	Nm	27

Capacities

406 1.6


1996 to 1997

Engine oil & filter	litres	4.75
Gearbox - 4-speed [5-speed]	litres	2.0
Automatic transmission - refill	litres	—
Final drive	litres	WT
Cooling system	litres	—
Fuel tank	litres	70

Notes and Illustrations

¹Slackening and angle tightening sequence must be carried out bolt by bolt.

²Bolt shank length ≤176.5mm



1580 cm³ 8V