

Engine & Cooling

Fuel

Ignition

Electrical

Running gear

Torque settings

Capacities

Notes & Illustrations



Automotive Technical
DATA BOOK

Click on one of the buttons above to view data for this car. To return to this screen and make another choice, click anywhere on the data screen.

MENU

HELP

Engine and cooling system19, 1.7i CAT(X53C)1990 to 1992

Type		F3N-7-42/43 71kW
Capacity (cm ³) / number of cylinders		1721 / 4
Compression ratio / pressure	bar	9.5 / _
Oil pressure	bar	2.0 [3.5]
Oil temperature	°C	80
Valve clearance - inlet	mm	0.20
Valve clearance - exhaust	mm	0.40
Firing order		1-3-4-2
No 1 cylinder position		FE
Thermostat opening temperature	°C	89
Radiator cap pressure	bar	1.2

Fuel system19, 1.7i CAT(X53C)1990 to 1992

Idle speed - manual [auto]	rpm	800±50 N/A
Fast idle speed - manual [auto]	rpm	_
CO @ idle speed [3000 rpm] - see page VI	%	≤0.3 N/A
HC @ idle speed [3000 rpm] - see page VI	ppm	≤200
CO2 @ idle speed [3000 rpm] - see page VI	%	≥14.5
O2 @ idle speed [3000 rpm] - see page VI	%	_
Carburettor / fuel injection		Siemens Bendix
Type / ref		Weber Multipoint MPI
Main jet / needle		_
Injection pressure	bar	2.5±0.05
Pump pressure	bar	3.0±0.2
Octane rating	RON	95[U]

Ignition system19, 1.7i CAT(X53C)1990 to 1992

Type		AEI
Ignition coil		Renix
Primary resistance	ohms	0.4 to 0.8
Ballast resistor	ohms	_
Voltage - Tmnl 15(+) to earth	V	_
Distributor		Renix
Points gap (air gap)	mm	_
Dwell angle	° (%)	_
Condenser capacity	µF	_
Rotation		_
Ignition timing - basic [static	° Crankshaft @ rpm	AEI control
V = Vacuum NV = No Vacuum		_
Total ignition advance	° Crankshaft @ rpm	_
	° Crankshaft @ rpm	_
	° Crankshaft @ rpm	_
Centrifugal check.	° Crankshaft @ rpm	AEI control
	° Crankshaft @ rpm	_
	° Crankshaft @ rpm	_
Vacuum range check	mbar	AEI control
Maximum vacuum advance	° Crankshaft	_
Spark plugs		AC/Champion
Type		C41CXLS / N6YC
Electrode gap	mm	0.80±0.05

Electrical system19, 1.7i CAT(X53C)1990 to 1992

Battery	V / CC / RC	12 / 50Ah
Alternator voltage / full load current / engine rpm		13.5 to 15.0 / _ / 3000
Starter motor current / voltage - cranking	A / V	_
- locked	A / V	350 to 460 / _

Running gear19, 1.7i CAT(X53C)1990 to 1992

Brakes -		
Front (min. friction material thickness)	mm	6.0 with backing
Rear (min. friction material thickness)	mm	2.5 ¹

Tyres		
Saloon	Size	175/70x13: 175/65x14
Estate / Van	Size	_
Pressure - front / rear - Saloon	bar	2.0 / 2.2 ²
- Estate / Van	bar	_

Front suspension / wheel alignment		
Toe-in (+) / Toe-out (-)	mm [°]	-1.0±1.0
Camber		-5'±30'
Castor		+1°55'. PAS: +4°
King pin inclination		+12°55'±30'

Rear suspension / wheel alignment		
Toe-in (+) / Toe-out (-)	mm [°]	+1.0 to 3.0
Camber		-50'±30'

Torque wrench settings19, 1.7i CAT(X53C)1990 to 1992

Cylinder head - stage 1	Nm	30
- stage 2	Nm	70, wait 3 min. Slacken
Cylinder head - stage 3	Nm	20
- stage 4	Nm	+ 123±2°
Big-end bearings	Nm	45 to 50
Main bearings	Nm	60 to 65
Clutch cover	Nm	25
Flywheel [driveplate]	Nm	50 to 55 [65]
Front hubs	Nm	250
Rear hubs	Nm	160
Wheel nuts / bolts	Nm	80
Spark plugs	Nm	_


Capacities19, 1.7i CAT(X53C)1990 to 1992

Engine oil & filter	litres	5.2
Gearbox - 4-speed [5-speed]	litres	3.4
Automatic transmission - refill	litres	3.5
Final drive	litres	AT: 1.0
Cooling system	litres	6.0
Fuel tank	litres	55

Notes and Illustrations

¹Discs: 5.0 with backing

²AT: 2.1 / 2.2



1721 cm³