

Engine & Cooling

Fuel

Ignition


Electrical

Running gear

Torque settings

Capacities

Notes & Illustrations



Automotive Technical
DATA BOOK

Click on one of the buttons above to view data for this car. To return to this screen and make another choice, click anywhere on the data screen.

MENU

HELP

Engine and cooling system25 Turbo (B295)1985 to 1990

Type		Z7U-A7-02
Capacity (cm³) / number of cylinders		2458 / 6
Compression ratio / pressure	bar	8.6 / _
Oil pressure	bar	2.2 [4.4]
Oil temperature	°C	80
Valve clearance - inlet	mm	0.10
Valve clearance - exhaust	mm	0.25
Firing order		1-6-3-5-2-4
No 1 cylinder position		RL
Thermostat opening temperature	°C	86
Radiator cap pressure	bar	0.8 to 1.2

Fuel system25 Turbo (B295)1985 to 1990

Idle speed - manual [auto]	rpm	700±50 N/A
Fast idle speed - manual [auto]	rpm	_
CO @ idle speed [3000 rpm] - see page VI	%	1.0±0.25
HC @ idle speed [3000 rpm] - see page VI	ppm	≤1200
CO2 @ idle speed [3000 rpm] - see page VI	%	_
O2 @ idle speed [3000 rpm] - see page VI	%	_
Carburettor / fuel injection		Renix
Type / ref		Bendix R electronic MPI
Main jet / needle		_
Injection pressure	bar	2.5±0.2
Pump pressure	bar	3.0
Octane rating	RON	98[E 98 RON]

Ignition system25 Turbo (B295)1985 to 1990

Type		AEI
Ignition coil		Renix
Primary resistance	ohms	0.4 to 0.8
Ballast resistor	ohms	_
Voltage - Tmnl 15(+) to earth	V	_
Distributor		Renix
Points gap (air gap)	mm	_
Dwell angle	° (%)	_
Condenser capacity	µF	_
Rotation		Clockwise
Ignition timing - basic [static	° Crankshaft @ rpm	AEI control
V = Vacuum NV = No Vacuum		
Total ignition advance	° Crankshaft @ rpm	AEI control
	° Crankshaft @ rpm	_
	° Crankshaft @ rpm	_
Centrifugal check.	° Crankshaft @ rpm	AEI control
	° Crankshaft @ rpm	_
	° Crankshaft @ rpm	_
Vacuum range check	mbar	AEI control
Maximum vacuum advance	° Crankshaft	_
Spark plugs		Eyquem/Champion
Type		805LJSP / S6YC
Electrode gap	mm	0.65±0.05

Electrical system25 Turbo (B295)1985 to 1990

Battery	V / CC / RC	12 / 255 / 85
Alternator voltage / full load current / engine rpm		13.5 to 14.8 / 90, 105 / 3000
Starter motor current / voltage - cranking	A / V	_
- locked	A / V	400 / _

Running gear25 Turbo (B295)1985 to 1990

Brakes -		
Front (min. friction material thickness)	mm	6.0 with backing
Rear (min. friction material thickness)	mm	6.0 with backing

Tyres		
Saloon	Size	205/60x15
Estate / Van	Size	_
Pressure - front / rear - Saloon	bar	2.5 / 2.3
- Estate / Van	bar	_

Front suspension / wheel alignment		
Toe-in (+) / Toe-out (-)	mm [°]	-3.0±1.0
Camber		0±30'
Castor		+2° PAS: +4°
King pin inclination		+12°30'±30'

Rear suspension / wheel alignment		
Toe-in (+) / Toe-out (-)	mm [°]	+1.0±1.0
Camber		-1°15'±30'

Torque wrench settings25 Turbo (B295)1985 to 1990

Cylinder head - stage 1	Nm	60, then slacken bolts
- stage 2	Nm	20 + 127°
Cylinder head - stage 3	Nm	Warm up engine, then cool
- stage 4	Nm	+ 25°
Big-end bearings	Nm	45
Main bearings	Nm	30 + 75°
Clutch cover	Nm	25
Flywheel [driveplate]	Nm	45
Front hubs	Nm	250
Rear hubs	Nm	160
Wheel nuts / bolts	Nm	100
Spark plugs	Nm	_


Capacities25 Turbo (B295)1985 to 1990

Engine oil & filter	litres	8.0
Gearbox - 4-speed [5-speed]	litres	3.4
Automatic transmission - refill	litres	_
Final drive	litres	WT
Cooling system	litres	9.7
Fuel tank	litres	72


Notes and Illustrations



1: Idle speed 2: CO / Mixture



2458 cm³



Bendix R, not CAT