

Engine & Cooling

Fuel

Ignition

Electrical

Running gear

Torque settings

Capacities

Notes & Illustrations



Automotive Technical
DATA BOOK

Click on one of the buttons above to view data for this car. To return to this screen and make another choice, click anywhere on the data screen.

MENU

HELP

Engine and cooling system5, Extra 1.1 (B/C/S/F401)1991 to 1992

Type		C1E-7-60
Capacity (cm³) / number of cylinders		1108 / 4
Compression ratio / pressure	bar	8.8 / _
Oil pressure	bar	0.7 [3.5]
Oil temperature	°C	80
Valve clearance - inlet	mm	0.15
Valve clearance - exhaust	mm	0.20
Firing order		1-3-4-2
No 1 cylinder position		FE
Thermostat opening temperature	°C	83
Radiator cap pressure	bar	0.9

Fuel system5, Extra 1.1 (B/C/S/F401)1991 to 1992

Idle speed - manual [auto]	rpm	625±50. Solex: 700±50
Fast idle speed - manual [auto]	rpm	_
CO @ idle speed [3000 rpm] - see page VI	%	1.0±0.5. Solex: 1.5±0.5
HC @ idle speed [3000 rpm] - see page VI	ppm	≤1200
CO2 @ idle speed [3000 rpm] - see page VI	%	_
O2 @ idle speed [3000 rpm] - see page VI	%	_
Carburettor / fuel injection		Solex/Zenith
Type / ref		S: 32 BIS 994. Z: 32 IF2 ...09
Main jet / needle		115 or 122
Injection pressure	bar	_
Pump pressure	bar	0.17 to 0.33
Octane rating	RON	95[E 95 RON]

Ignition system5, Extra 1.1 (B/C/S/F401)1991 to 1992

Type		Contact breaker - CIS
Ignition coil		Ducellier, SEV
Primary resistance	ohms	_
Ballast resistor	ohms	_
Voltage - Tmnl 15(+) to earth	V	_
Distributor		Ducellier
Points gap (air gap)	mm	0.40
Dwell angle	° (%)	57±3 (63±3)
Condenser capacity	µF	_
Rotation		Clockwise
Ignition timing - basic [static	° Crankshaft @ rpm	10±1 BTDC @ idle
V = Vacuum NV = No Vacuum		NV
Total ignition advance	° Crankshaft @ rpm	R350-D90
	° Crankshaft @ rpm	_
	° Crankshaft @ rpm	_
Centrifugal check.	° Crankshaft @ rpm	0 @ 1300
	° Crankshaft @ rpm	7 to 11 @ 2000
	° Crankshaft @ rpm	28 to 32 @ 4700
Vacuum range check	mbar	133 to 475
Maximum vacuum advance	° Crankshaft	17 to 21
Spark plugs		AC/Champion
Type		C42CXLS / N281YC
Electrode gap	mm	0.75 to 0.85

Electrical system5, Extra 1.1 (B/C/S/F401)1991 to 1992

Battery	V / CC / RC	12 / 175 / 60
Alternator voltage / full load current / engine rpm		13.5 / _ / 3000
Starter motor current / voltage - cranking	A / V	_
- locked	A / V	340 to 460 / _

Running gear5, Extra 1.1 (B/C/S/F401)1991 to 1992

Brakes -		
Front (min. friction material thickness)	mm	6.0 with backing
Rear (min. friction material thickness)	mm	2.5 with backing

Tyres		
Saloon	Size	145/70x13: 155/70x13
Estate / Van	Size	145x13: 145/70x13: 155/70x13
Pressure - front / rear - Saloon	bar	2.0 / 2.2
- Estate / Van	bar	2.2 / 2.2¹

Front suspension / wheel alignment

Toe-in (+) / Toe-out (-)	mm [°]	-1.0±1.0
Camber		+30'±30'
Castor		+2°±30'
King pin inclination		+12°10'±30'

Rear suspension / wheel alignment

Toe-in (+) / Toe-out (-)	mm [°]	0 to +3.0²
Camber		-50'±30'

Torque wrench settings5, Extra 1.1 (B/C/S/F401)1991 to 1992

Cylinder head - stage 1	Nm	55 to 65
- stage 2	Nm	_
Cylinder head - stage 3	Nm	_
- stage 4	Nm	_
Big-end bearings	Nm	35
Main bearings	Nm	55 to 65
Clutch cover	Nm	25
Flywheel [driveplate]	Nm	50
Front hubs	Nm	250
Rear hubs	Nm	160
Wheel nuts / bolts	Nm	80
Spark plugs	Nm	_

Capacities5, Extra 1.1 (B/C/S/F401)1991 to 1992

Engine oil & filter	litres	3.5
Gearbox - 4-speed [5-speed]	litres	Steel: 3.3 [3.4]³
Automatic transmission - refill	litres	_
Final drive	litres	WT
Cooling system	litres	5.5
Fuel tank	litres	43


Notes and Illustrations

¹Extra, 145 & 155x13: 2.1 / 2.5


²Extra: +2.0 to 5.0

³Plastic plug: 2.8 [2.9]


1: Idle speed2: CO / Mixture




1108 cm³




1108 cm³



Zenith 32 IF2



Solex 32 BIS



Solex 32 BIS, alternative