


Engine & Cooling	Fuel	Ignition	Electrical	Running gear	Torque settings	Capacities	Notes & Illustrations
------------------	------	----------	------------	--------------	-----------------	------------	-----------------------



Automotive Technical DATA BOOK

Click on one of the buttons above to view data for this car. To return to this screen and make another choice, click anywhere on the data screen.

MENU

HELP

Engine and cooling system 850, 2.0i, 10V 1995 to 1997

Type	B5202S SOHC 10V 93kW	
Capacity (cm ³) / number of cylinders	1984 / 5	
Compression ratio / pressure	bar	10.0 / ≥13.0
Oil pressure	bar	1.0 [3.5]
Oil temperature	°C	80
Valve clearance - inlet	mm	0: Hyd.
- exhaust	mm	0: Hyd.
Firing order	1-2-4-5-3	
No 1 cylinder position	TBE	
Thermostat opening temperature	°C	87 to 102
Radiator cap pressure	bar	1.50

Fuel system 850, 2.0i, 10V 1995 to 1997

Idle speed - manual [auto]	rpm	850±50 N/A
Fast idle speed - manual [auto]	rpm	—
CO @ idle speed [3000 rpm] - see page VI	%	0.6±0.2 N/A
HC @ idle speed [3000 rpm] - see page VI	ppm	≤200
CO ₂ @ idle speed [3000 rpm] - see page VI	%	—
O ₂ @ idle speed [3000 rpm] - see page VI	%	—
Carburettor / fuel injection	Siemens Bendix	
Type / ref	Fenix 5.2 SEFI	
Main jet / needle	—	
Injection pressure	bar	3.0
Pump pressure	bar	—
Octane rating	RON	95[U]

Ignition system 850, 2.0i, 10V 1995 to 1997

Type	Fenix 5.2	
Ignition coil	—	
Primary resistance	ohms	0.5 to 1.5
Ballast resistor	ohms	—
Voltage - Tmnl 15(+) to earth	V	—
Distributor	Bosch	
Points gap (air gap)	mm	—
Dwell angle	° (%)	Electronic control
Condenser capacity	µF	—
Rotation	—	
Ignition timing - basic [static V = Vacuum NV = No Vacuum]	° Crankshaft @ rpm	10±2 BTDC @ 800±50 N/A
Total ignition advance	° Crankshaft @ rpm	Computer control
	° Crankshaft @ rpm	—
	° Crankshaft @ rpm	—
Centrifugal check.	° Crankshaft @ rpm	Computer control
	° Crankshaft @ rpm	—
	° Crankshaft @ rpm	—
Vacuum range check	mbar	Computer control
Maximum vacuum advance	° Crankshaft	—
Spark plugs	Bosch/Champion	
Type	FR7DC / RC9YC	
Electrode gap	mm	0.70 to 0.80

Electrical system 850, 2.0i, 10V 1995 to 1997

Battery	V / CC / RC	12 / 420 / 75, 520 / 90
Alternator voltage / full load current / engine rpm	14 / 80, 100, 108 / 3000	
Starter motor current / voltage - cranking	A / V	—
- locked	A / V	475 to 600/3.5, 650 to 840/3.0

Running gear 850, 2.0i, 10V 1995 to 1997

Brakes -		
Front (min. friction material thickness)	mm	3.0
Rear (min. friction material thickness)	mm	2.0

Tyres		
Saloon	Size	195/60x15: 185/65x15:205/55x15
Estate / Van	Size	195/60x15: 185/65x15:205/55x15
Pressure - front / rear - Saloon	bar	2.2 / 2.0
- Estate / Van	bar	2.2 / 2.1

Front suspension / wheel alignment

Toe-in (+) / Toe-out (-)	mm [°]	[+20'±6']
Camber		0±1°
Castor		+3°20'±1°
King pin inclination		—

Rear suspension / wheel alignment

Toe-in (+) / Toe-out (-)	mm [°]	[+4'±10']
Camber		-1°±30'

Torque wrench settings 850, 2.0i, 10V 1995 to 1997


Cylinder head - stage 1	Nm	20 oiled
- stage 2	Nm	60
- stage 3	Nm	+ 130°
- stage 4	Nm	—
Big-end bearings	Nm	20 + 90°
Main bearings	Nm	1
Clutch cover	Nm	25
Flywheel [driveplate]	Nm	45 + 65°
Front hubs	Nm	120 + 60°
Rear hubs	Nm	120 + 30°
Wheel nuts / bolts	Nm	110
Spark plugs	Nm	25

Capacities 850, 2.0i, 10V 1995 to 1997

Engine oil & filter	litres	5.3
Gearbox - 4-speed [5-speed]	litres	2.1
Automatic transmission - refill	litres	3.0
Final drive	litres	WT
Cooling system	litres	7.2
Fuel tank	litres	73

Notes and Illustrations

¹M10: 20, then M10: 45, then M8: 24, then M7: 17, then M10 +90°



1984 cm³, 10V