

Engine & Cooling	Fuel	Ignition	Electrical	Running gear	Torque settings	Capacities	Notes & Illustrations
------------------	------	----------	------------	--------------	-----------------	------------	-----------------------



Automotive Technical DATA BOOK

Click on one of the buttons above to view data for this car. To return to this screen and make another choice, click anywhere on the data screen.

MENU

HELP

Engine and cooling system 740, 2.0 1987 to 1988

Type		B200K
Capacity (cm ³) / number of cylinders		1986 / 4
Compression ratio / pressure	bar	10.0 / ≥8.8
Oil pressure	bar	[2.5 to 6.0]
Oil temperature	°C	H
Valve clearance - inlet	mm	0.30 to 0.40
- exhaust	mm	0.30 to 0.40
Firing order		1-3-4-2
No 1 cylinder position		TBE
Thermostat opening temperature	°C	91 to 93
Radiator cap pressure	bar	1.0

Fuel system 740, 2.0 1987 to 1988

Idle speed - manual [auto]	rpm	900
Fast idle speed - manual [auto]	rpm	—
CO @ idle speed [3000 rpm] - see page VI	%	1.0 to 2.5
HC @ idle speed [3000 rpm] - see page VI	ppm	≤1200
CO ₂ @ idle speed [3000 rpm] - see page VI	%	—
O ₂ @ idle speed [3000 rpm] - see page VI	%	—
Carburettor / fuel injection		Solex
Type / ref		CISAC
Main jet / needle		120, 135
Injection pressure	bar	—
Pump pressure	bar	0.15 to 0.28
Octane rating	RON	98[R]

Ignition system 740, 2.0 1987 to 1988

Type		Renix - AEI
Ignition coil		Bosch
Primary resistance	ohms	0.6 to 0.8
Ballast resistor	ohms	—
Voltage - Tmnl 15(+) to earth	V	—
Distributor		Bosch
Points gap (air gap)	mm	—
Dwell angle	° (%)	—
Condenser capacity	µF	—
Rotation		Clockwise
Ignition timing - basic [static	° Crankshaft @ rpm	15 BTDC @ 750
V = Vacuum NV = No Vacuum		NV
Total ignition advance	° Crankshaft @ rpm	22 to 26 @ 2500
	° Crankshaft @ rpm	Non-adjustable, Renix system
	° Crankshaft @ rpm	—
Centrifugal check.	° Crankshaft @ rpm	Computer control
	° Crankshaft @ rpm	—
	° Crankshaft @ rpm	—
Vacuum range check	mbar	Computer control
Maximum vacuum advance	° Crankshaft	—
Spark plugs		Bosch/Champion
Type		WR7DC / N7YC
Electrode gap	mm	0.70 to 0.80

Electrical system 740, 2.0 1987 to 1988

Battery	V / CC / RC	12 / 450 / 90
Alternator voltage / full load current / engine rpm		13.8 to 14.6 / _ / 3000
Starter motor current / voltage - cranking	A / V	1.1kW: 70 / 11.5 ¹
- locked	A / V	1.1kW: 480 to 560 / 7.4 ²

Running gear 740, 2.0 1987 to 1988

Brakes -		
Front (min. friction material thickness)	mm	3.0
Rear (min. friction material thickness)	mm	2.0

Tyres		
Saloon	Size	185/70x14
Estate / Van	Size	185/70x14: 185/65x15
Pressure - front / rear - Saloon	bar	1.9 / 1.9
- Estate / Van	bar	1.9 / 2.1

Front suspension / wheel alignment

Toe-in (+) / Toe-out (-)	mm [°]	+3.5±1.0
Camber		-0.2° to +0.8°
Castor		+4.5° to 5.5°
King pin inclination		—

Rear suspension / wheel alignment

Toe-in (+) / Toe-out (-)	mm [°]	—
Camber		—

Torque wrench settings 740, 2.0 1987 to 1988

Cylinder head - stage 1	Nm	20
- stage 2	Nm	60
- stage 3	Nm	+ 90°
- stage 4	Nm	—
Big-end bearings	Nm	20 + 90°
Main bearings	Nm	110
Clutch cover	Nm	—
Flywheel [driveplate]	Nm	70 N
Front hubs	Nm	WSM
Rear hubs	Nm	WSM
Wheel nuts / bolts	Nm	85
Spark plugs	Nm	25

Capacities 740, 2.0 1987 to 1988


Engine oil & filter	litres	3.9
Gearbox - 4-speed [5-speed]	litres	1.3. Later: 1.6
Automatic transmission - refill	litres	3.9
Final drive	litres	1.6
Cooling system	litres	8.5
Fuel tank	litres	60

Notes and Illustrations


¹1.4kW: 75 / 11.5. 2kW: 65 to 95 / 11.5. Hitachi: 300 / 8.8

²1.4kW: 625 to 800 / 4.5. 2kW: 700 to 880 / 4.5. Hitachi: 880 / 3


1: Idle speed 2: CO / Mixture



1986 cm³



1986 cm³



Solex CISAC