

VOLKSWAGEN

Golf Cabrio 1.8i CAT

1990 to 1993

Engine & Cooling

Fuel

Ignition


Electrical

Running gear

Torque settings

Capacities

Notes & Illustrations



Automotive Technical
DATA BOOK

Click on one of the buttons above to view data for this car. To return to this screen and make another choice, click anywhere on the data screen.

MENU

HELP

Engine and cooling system

Golf Cabrio 1.8i CAT

1990 to 1993

Type		2H. 72kW
Capacity (cm ³) / number of cylinders		1781 / 4
Compression ratio / pressure	bar	10.0 / ≥7.5
Oil pressure	bar	[2.0]
Oil temperature	°C	80
Valve clearance - inlet	mm	0: Hyd.
Valve clearance - exhaust	mm	0: Hyd.
Firing order		1-3-4-2
No 1 cylinder position		TBE
Thermostat opening temperature	°C	87
Radiator cap pressure	bar	1.2 to 1.5

Fuel system

Golf Cabrio 1.8i CAT

1990 to 1993

Idle speed - manual [auto]	rpm	750 to 850
Fast idle speed - manual [auto]	rpm	—
CO @ idle speed [3000 rpm] - see page VI	%	0.3 to 1.1
HC @ idle speed [3000 rpm] - see page VI	ppm	≤1200
CO2 @ idle speed [3000 rpm] - see page VI	%	—
O2 @ idle speed [3000 rpm] - see page VI	%	—
Carburettor / fuel injection		Volkswagen
Type / ref		Digifant
Main jet / needle		—
Injection pressure	bar	2.5
Pump pressure	bar	3.0
Octane rating	RON	91[U]

Ignition system

Golf Cabrio 1.8i CAT

1990 to 1993

Type		Digifant
Ignition coil		—
Primary resistance	ohms	0.52 to 0.76
Ballast resistor	ohms	—
Voltage - Tmnl 15(+) to earth	V	—
Distributor		Bosch
Points gap (air gap)	mm	—
Dwell angle	° (%)	—
Condenser capacity	µF	—
Rotation		Clockwise
Ignition timing - basic [static	° Crankshaft @ rpm	6±1 BTDC @ 2000 to 2500 ¹
V = Vacuum NV = No Vacuum		NV
Total ignition advance	° Crankshaft @ rpm	30±3 BTDC @ 2300 ²
	° Crankshaft @ rpm	—
	° Crankshaft @ rpm	—
Centrifugal check.	° Crankshaft @ rpm	Computer control
	° Crankshaft @ rpm	—
	° Crankshaft @ rpm	—
Vacuum range check	mbar	Computer control
Maximum vacuum advance	° Crankshaft	—
Spark plugs		Bosch/Champion
Type		W7DTC / N7BYC
Electrode gap	mm	0.70 to 0.90

Electrical system

Golf Cabrio 1.8i CAT

1990 to 1993

Battery	V / CC / RC	12 / 220 / 75
Alternator voltage / full load current / engine rpm		—
Starter motor current / voltage - cranking	A / V	—
- locked	A / V	—

Running gear

Golf Cabrio 1.8i CAT

1990 to 1993

Brakes -		
Front (min. friction material thickness)	mm	7.0 with backing
Rear (min. friction material thickness)	mm	5 riveted. 3.5 bonded

Tyres		
Saloon	Size	175/70x13: 185/60x14
Estate / Van	Size	—
Pressure - front / rear - Saloon	bar	1.9 / 1.9
- Estate / Van	bar	—

Front suspension / wheel alignment		
Toe-in (+) / Toe-out (–)	mm [°]	[-5' to -30']
Camber		+20'±20'
Castor		+1°50'±20'
King pin inclination		—

Rear suspension / wheel alignment		
Toe-in (+) / Toe-out (–)	mm [°]	[+20'±20']
Camber		-1°15'±25'

Torque wrench settings

Golf Cabrio 1.8i CAT

1990 to 1993

Cylinder head - stage 1	Nm	40
- stage 2	Nm	60
Cylinder head - stage 3	Nm	+ 90°
- stage 4	Nm	+ 90°
Big-end bearings	Nm	30 + 90°
Main bearings	Nm	65 ³
Clutch cover	Nm	20
Flywheel [driveplate]	Nm	60 + 90° N
Front hubs	Nm	230
Rear hubs	Nm	WSM
Wheel nuts / bolts	Nm	110
Spark plugs	Nm	25

Capacities

Golf Cabrio 1.8i CAT

1990 to 1993

Engine oil & filter	litres	4.0
Gearbox - 4-speed [5-speed]	litres	1.5 [2.0]
Automatic transmission - refill	litres	3.0
Final drive	litres	AT: 0.75
Cooling system	litres	6.5
Fuel tank	litres	55

Notes and Illustrations


¹Coolant temperature sender disconnected

²Coolant temperature sender connected


³Replace with fully threaded shank bolts: 65 + 90°

1: Idle speed


2: CO / Mixture



1781 cm³, 8V



1781 cm³, 8V



Digifant, 2H