




- A 2 Accelerator Pedal Sensor Assembly
- A 3 Kick Down Switch Assembly
- A 5 Stop Light Switch Assembly
- A 6 Brake Pedal Load Sensing Switch (Brake Pedal Support Assembly)
- A 7 Headlight Swivel ECU Assembly
- A 8 Front Acceleration Sensor LH
- A 31 Front Steering Control ECU
- A 32 Blower Motor Sub-Assembly with Fan
- A 33 4WD ECU Assembly
- A 34 Certification ECU
- A 37 Absorber Control ECU
- A 51 Junction Connector
- A 52 Junction Connector
- A 57 Junction Connector
- A 75 Junction Connector
- A 80 Engine Stop & Start Solenoid Filter
- A 81 Eco-Run Vehicle Converter Assembly
- A 82 Engine Stop and Start ECU
- A 83 Engine Stop and Start ECU
- A 91 Junction Connector
- A 95 Junction Connector
- A 97 Junction Connector

- O 1 Automatic Light Control Sensor

- P 1 Headup Display (Combination Meter Mirror ECU)

- T 1 Absorber Control ECU
- T 2 Certification ECU
- T 12 Airbag Sensor Assembly
- T 13 Rear No. 2 Power Outlet Socket Assembly

- U 2 Certification ECU
- U 12 Airbag Sensor Assembly
- U 48 Junction Connector
- U 49 Junction Connector
- U 50 Junction Connector
- U 51 Junction Connector

- W 1 Console Box Illumination Light Assembly

- s 1 Instrument Panel Passenger without Door Airbag Assembly
- s 2 Instrument Panel Passenger without Door Airbag Assembly

- z 1 A/C Amplifier Assembly , A/C Harness Assembly
- z 2 Driver Side Squib Circuit (Horn Button Assembly) , Spiral Cable Sub-Assembly
- z 3 Driver Side Squib Circuit (Horn Button Assembly) , Spiral Cable Sub-Assembly
- z 4 Spiral Cable Sub-Assembly , Steering Pad Switch Assembly
- z 5 Spiral Cable Sub-Assembly , Steering Wheel Heater Control Assembly
- z 8 Cruise Control Main Switch , Spiral Cable Sub-Assembly
- z 14 Spiral Cable Sub-Assembly , Steering Wheel Assembly
- z 18 Spiral Cable Sub-Assembly , No. 1 Switch Wire
- z 19 Driver Side Squib Circuit (Horn Button Assembly) , Spiral Cable Sub-Assembly
- z 20 Driver Side Squib Circuit (Horn Button Assembly) , Spiral Cable Sub-Assembly

A diagram of a 6-pin connector, likely for a vehicle's lighting system. The connector is shown from a top-down perspective, with a central rectangular area containing six numbered pins (1 through 6) arranged in a single row. The pins are numbered 1 to 6 from left to right. The connector has a complex, multi-faceted shape with various mounting points and a central locking mechanism.



Diagram illustrating a 32-bit bus structure. The bus is divided into two 16-bit halves, labeled 1 to 16 and 17 to 32. A central block is connected to the bus lines, with a label '1' above it.



A diagram of a container with two compartments, labeled 1 and 2. The container has a handle on top and a base with a series of steps or a ramp on the right side.

A schematic diagram of a three-chambered heart. It shows a central ventricle (chamber 2) flanked by two atria (chambers 1 and 3). Arrows indicate the flow of blood: entering the atria from the top, moving into the ventricle, and then exiting through the bottom. The diagram is labeled with numbers 1, 2, and 3 inside the respective chambers.

The diagram shows a standard 24-key electronic calculator keypad layout. At the top is a display screen. Below the screen are several function keys: a row of four small keys (likely π , $\sqrt{\square}$, $\div$, $\times$), a row of three medium keys (likely $\log$, $\ln$, $\square$), and a row of four large keys (likely $\sin$, $\cos$, $\tan$, $\cot$). The main numeric keypad consists of two columns of three keys each, with a central column of two keys. The keys are numbered 1 through 24 in a specific sequence: 1, 2, 3, 4, 5, 6 in the top row; 7, 8, 9, 10, 11, 12 in the second row; 13, 14, 15, 16, 17, 18 in the third row; 19, 20, 21, 22, 23, 24 in the fourth row. The layout is symmetrical around a central vertical axis.
















A diagram of a 22-pin D-sub connector. The pins are arranged in two rows of 11 pins each. The top row is numbered 1 through 11 from left to right. The bottom row is numbered 12 through 22 from left to right. The connector has a D-shaped shield and a mounting bracket on the right side.

A diagram of a 4-bit shift register. It consists of four rectangular cells arranged horizontally, labeled 1, 2, 3, and 4 from left to right. Above each cell is a small square input port. The entire register is enclosed in a larger rectangular frame with a notch on the left side.

1	2	3	4	5	6	7	8	9	10	11
12	13	14	15	16	17	18	19	20	21	22

A schematic diagram of a 16-bit ALU. It features a central horizontal bar with eight rectangular blocks labeled 1 through 8, representing data inputs. Above this bar is a control logic section with several smaller blocks and a curved top. Below the bar is another set of eight rectangular blocks, representing data outputs. The entire unit is enclosed in a frame with vertical end caps.

Position of Parts in Instrument Panel <LHD>



Position of Parts in Instrument Panel <LHD>

