


STANDARD BOLT

HOW TO DETERMINE BOLT STRENGTH

6200F-01

	Mark	Class		Mark	Class
Hexagon head bolt	 Bolt head No. 4— 5— 6— 7— 8— 9— 10— 11—	4T	Hexagon flange bolt	 4 Protruding lines	9T
		5T	w/ washer hexagon bolt		
		6T	Hexagon flange bolt	 5 Protruding lines	10T
		7T	w/ washer hexagon bolt		
Hexagon head bolt	 Bolt head No. 8— 9— 10— 11—	8T	Hexagon flange bolt	 6 Protruding lines	11T
		9T	w/ washer hexagon bolt		
		10T	Hexagon flange bolt	 6 Protruding lines	11T
		11T	w/ washer hexagon bolt		
Hexagon head bolt	 No mark	4T	Hexagon flange bolt	 6 Protruding lines	11T
		4T	w/ washer hexagon bolt		
		4T	Hexagon flange bolt	 6 Protruding lines	11T
		4T	w/ washer hexagon bolt		
Hexagon flange bolt w/ washer hexagon bolt	 No mark	4T	Stud bolt	 No mark	4T
Hexagon head bolt	 2 Protruding lines	5T	Stud bolt	 2 Protruding lines	5T
Hexagon flange bolt w/ washer hexagon bolt	 2 Protruding lines	6T	Stud bolt	 2 Protruding lines	6T
Hexagon head bolt	 3 Protruding lines	7T	Stud bolt	 3 Protruding lines	7T
Hexagon head bolt	 4 Protruding lines	8T	Stud bolt	 4 Protruding lines	8T
			Welded bolt	 Welded bolt	4T

SS

SPECIFIED TORQUE FOR STANDARD BOLTS

Class	Diameter mm	Pitch mm	Specified torque					
			Hexagon head bolt			Hexagon flange bolt		
			N-m	kgf-cm	ft-lbf	N-m	kgf-cm	ft-lbf
4T	6	1	5	55	48 in.-lbf	6	60	52 in.-lbf
	8	1.25	12.5	130	9	14	145	10
	10	1.25	26	260	19	29	290	21
	12	1.25	47	480	35	53	540	39
	14	1.5	74	760	55	84	850	61
	16	1.5	115	1,150	83	—	—	—
5T	6	1	6.5	65	56 in.-lbf	7.5	75	65 in.-lbf
	8	1.25	15.5	160	12	17.5	175	13
	10	1.25	32	330	24	36	360	26
	12	1.25	59	600	43	65	670	48
	14	1.5	91	930	67	100	1,050	76
	16	1.5	140	1,400	101	—	—	—
6T	6	1	8	80	69 in.-lbf	9	90	78 in.-lbf
	8	1.25	19	195	14	21	210	15
	10	1.25	39	400	29	44	440	32
	12	1.25	71	730	53	80	810	59
	14	1.5	110	1,100	80	125	1,250	90
	16	1.5	170	1,750	127	—	—	—
7T	6	1	10.5	110	8	12	120	9
	8	1.25	25	260	19	28	290	21
	10	1.25	52	530	38	58	590	43
	12	1.25	95	970	70	105	1,050	76
	14	1.5	145	1,500	108	165	1,700	123
	16	1.5	230	2,300	166	—	—	—
8T	8	1.25	29	300	22	33	330	24
	10	1.25	61	620	45	68	690	50
	12	1.25	110	1,100	80	120	1,250	90
9T	8	1.25	34	340	25	37	380	27
	10	1.25	70	710	51	78	790	57
	12	1.25	125	1,300	94	140	1,450	105
10T	8	1.25	38	390	28	42	430	31
	10	1.25	78	800	58	88	890	64
	12	1.25	140	1,450	105	155	1,600	116
11T	8	1.25	42	430	31	47	480	35
	10	1.25	87	890	64	97	990	72
	12	1.25	155	1,600	116	175	1,800	130