

■ PERFORMANCE AND SPECIFICATION

1. Performance

Heater	Heater Output	W (Kcal/h)	5200 (4477)
	Air Flow Volume	m ³ /h	330
	Power Consumption	W	Less than 200
Air Conditioner	Cooling Capacity	W (Kcal/h)	5200 (4477)
	Air Flow Volume	m ³ /h	520
	Power Consumption	W	Less than 250

2. Specification

Ventilation and Heater Core	Heater Core	Type	SFA (Straight Flow Aluminum) -II
		Size W × H × L mm (in.)	263.9 × 100 × 27 (10.4 × 3.9 × 1.1)
		Fin Pitch mm (in.)	1.8 (0.07)
	Blower	Fan Type	Semi Sirocco
		Fan Size Dia. × H mm (in.)	165 × 70 (6.5 × 2.8)
Air Conditioner	Condenser	Type	MF (Multi-Flow) -IV
		Size W × H × L mm (in.)	660 × 363.8 × 16 (26.0 × 14.3 × 0.6)
		Fin Pitch mm (in.)	3.95 (0.16)
	Evaporator	Type	RS (Rotary super-slim Structure)
		Size W × H × L mm (in.)	293.1 × 211 × 38 (11.5 × 8.3 × 1.5)
		Fin Pitch mm (in.)	3.0 (0.12)
	Compressor	Type	6SBU16
		Pulley	Steel with Magnetic Clutch
	Refrigerant	Type	HFC 134a
		Charge Volume g	380 to 480