

TORQUE SPECIFICATION

Part tightened	N·m	kgf·cm	ft·lbf
Master cylinder x Piston stopper bolt	10	100	7
Master cylinder x Reservoir	1.7	17.5	15.2 in·lbf
Master cylinder x Brake booster	13	130	9
Brake line union nut	15	155	11
Brake booster clavis lock nut	25	260	19
Brake booster x Pedal bracket	13	130	9
Bleeder plug	11	110	8
Front disc brake caliper installation bolt	123	1,250	90
Front disc brake caliper x Flexible hose	30	310	22
Parking brake bellcrank x Backing plate	13	130	9
Rear disc brake caliper x Spindle pin	88	900	65
Rear disc brake caliper x Flexible hose	30	310	22
Rear disc brake torque plate x Knuckle	103	1,050	76
LSP & BV bracket x Frame	25	260	19
LSP & BV x LSP & BV bracket	13	130	9
LSP & BV spring x LSP & BV bracket	18	185	13
LSP & BV spring x Shackle No. 1	18	185	13
LSP & BV shackle lock nut	25	250	18
LSP & BV shackle x Shackle bracket	13	130	9
LSP & BV shackle bracket x Rear axle housing	19	195	14
ABS actuator assembly x Body	19	195	14
ABS actuator x Actuator bracket	5.4	55	48 in·lbf
ABS control relay x Actuator bracket	13	130	9
Front speed sensor installation bolt	18	185	13
Rear speed sensor installation bolt	18	185	13