

TORQUE SPECIFICATION

Part tightened	N·m	kgf·cm	ft·lbf
FRONT			
Axle hub x Disc	64	650	47
Axle hub bearing lock nut	64	650	47
Flange x Axle hub	35	360	26
Brake caliper x Axle carrier	123	1,250	90
Brake caliper x Flexible hose	30	310	22
Steering knuckle x Knuckle arm	96	980	71
Bearing cap x Knuckle arm	96	980	71
Knuckle arm x Tie rod	91	925	67
Steering knuckle x Knuckle spindle	47	475	34
Oil seal retainer x Knuckle arm	5.4	55	48 in.·lbf
ABS speed sensor set bolt x Steering knuckle	18	185	13
Hub bolt	103	1,050	76
Drain plug	49	500	39
Filler plug	49	500	39
Propeller shaft x Companion flange	88	900	65
Side bearing cap x Differential carrier	78	800	58
Ring gear x Differential case	97	985	71
Drive pinion x Companion flange	196 – 343	2,000 – 3,500	145 – 253
Differential LH case x RH case	47	480	35
Differential lock shift retainer	24	240	17
Differential lock screw plug	22	220	16
Differential lock indicator switch	40	410	30
Differential lock actuator	26	270	20
Differential carrier x Axle housing	27	280	20
Adjusting nut lock x Bearing cap	13	130	9
Follow spring x Frame	9.2	94	82 in.·lbf
Stabilizer bar x Axle housing	25	260	19
Shock absorber x Axle housing	69	700	51
Shock absorber x Frame	69	700	51
Stabilizer bar link x Cover	18	185	13
Stabilizer bar link x Link bracket	103	1,050	76
Lateral control rod x Frame	171	1,750	127
Lateral control rod x Axle housing	171	1,750	127
Leading arm x Frame	177	1,800	130
Leading arm x Axle housing	171	1,750	127
REAR			
Rear axle shaft x Axle hub	34	340	25
Rear axle bearing lock nut	59	600	43
Rear axle bearing lock nut screw	5.4	55	48 in.·lbf
Brake caliper x Axle carrier	103	1,050	76
ABS speed sensor set bolt	18	185	13
Hub nut	103	1,050	76

Drain plug		49	500	39
Filler plug		49	500	39
Pinion shaft pin	w/o Differential lock	27	275	20
	w/ Differential lock	58	590	43
Propeller shaft x Companion flange		74	750	54
Side bearing cap x Differential carrier	w/o Differential lock	78	800	58
	w/ Differential lock	113	1,150	83
Ring gear x Differential case		110	1,125	81
Companion flange x Drive pinion	Maximum torque	441	4,500	325
Differential carrier x Axle housing		73	740	54
Adjusting nut lock x Bearing cap		13	130	9
Differential case x Cover		58	590	43
Differential lock shift fork set bolt		20	200	14
Differential lock actuator		24	240	17
Differential lock cover		18	185	13
Differential lock indicator switch		40	410	30
Actuator protector	Nut	35	360	26
	Bolt	20	200	14
Follow spring x Frame		28	290	21
Shock absorber x Bracket		69	700	51
Shock absorber bracket x Frame		50	510	37
Shock absorber x Axle housing		64	650	47
Lateral control rod x Frame		177	1,800	130
Lateral control rod x Axle housing		245	2,500	181
Upper control rod x Frame		177	1,800	130
Upper control rod x Axle housing		177	1,800	130
Upper control arm x Frame		177	1,800	130
Upper control arm x Axle housing		177	1,800	130
Stabilizer bar x Link		25	260	19
Stabilizer bar link x Link bracket		15	153	11
Cover x Axle housing		18	185	13