

TORQUE SPECIFICATION

Part tightened		N·m	kgf·cm	ft·lbf
Fuel line	for union bolt	29	300	22
	for flare nut	30	310	22
Fuel pump bracket x Fuel tank		3.9	40	35 in.·lbf
Fuel inlet hose, Fuel inlet pipe x Fuel filter		29	300	22
Fuel filter x Intake manifold		21	210	15
Fuel pressure regulator x Delivery pipe		25	250	18
Delivery pipe x Intake manifold		21	210	15
Fuel inlet pipe x Delivery pipe	Union bolt	29	300	22
	Bolt	20	200	14
Fuel return pipe x Intake manifold		20	200	14
Air intake chamber x Intake manifold		21	210	15
Intake manifold stay x Air intake chamber, Cylinder block		36	360	26
PS reservoir x Air intake chamber		18	185	13
Heater inlet pipe x Air intake chamber		20	200	14
Drain plug x Fuel tank		6.5	65	57 in.·lbf
Fuel tank breather tube x Fuel tank		1.5	15	13 in.·lbf
Fuel tank filler pipe x Fuel tank		3.5	35	31 in.·lbf
Fuel tank band x Body		39	400	29
MAF meter x Air cleaner cap, Bracket		6.9	70	61 in.·lbf
Throttle body x Air intake chamber		21	210	15
Fuel pump resistor x Body		18	185	13
ECT sensor x Cylinder head		24.5	250	18
EGR gas temperature sensor x Air intake chamber		20	200	14
Knock sensor 1, 2 x Cylinder block		44	450	33
Heated oxygen sensor (Bank 1 Sensor 1) x Front exhaust pipe		20	200	14
Heated oxygen sensor (Bank 1 Sensor 2) x Center pipe		20	200	14