

TORQUE SPECIFICATION

Part tightened	N·m	kgf·cm	ft·lbf
Master cylinder x Piston stopper bolt	10	100	7
Master cylinder x Reservoir	1.7	17.5	15.2 in·lbf
Master cylinder x Brake booster	13	130	9
Brake line union nut	15	155	11
Brake booster clavis lock nut	25	260	19
Brake booster x Pedal bracket	13	130	9
Bleeder plug	11	110	8
Front disc brake caliper installation bolt	123	1,250	90
Front disc brake caliper x Flexible hose	30	310	22
Parking brake bellcrank x Backing plate	13	130	9
Rear disc brake caliper x Flexible hose	30	310	22
Rear disc brake torque plate x Rear backing plate	103	1,050	76
Rear disc brake cliper x Spindle pin	88	900	65
LSP & BV Bracket Frame	25	260	19
LSP & BV x LSP & BV Bracket	13	130	9
LSP & BV Spring x LSP & BV Bracket	18	185	13
LSP & BV Spring x Shackle No.1	18	185	13
LSP & BV Shackle lock nut	25	250	18
LSP & BV Shackle x Shackle bracket	13	130	9
LSP & BV Shackle bracket x Rear axle housing	19	195	14
ABS actuator assembly x Body	19	195	14
ABS actuator x Actuator bracket	5.4	55	48 in·lbf
ABS control relay x Actuator bracket	13	130	9
Front speed sensor installation bolt	18	185	13
Rear speed sensor installation bolt	18	185	13