

PROPELLER SHAFT

SS1F8-01

SERVICE DATA

Propeller shaft runout	Max.	0.8 mm (0.031 in.)
Spider bearing axial play	Max.	0.05 mm (0.0020 in.)
Bearing axial play	Max.	0.05 mm (0.0020 in.)
Snap ring thickness		
Front propeller shaft and rear propeller shaft (Type B)	Mark or Color	
	1	2.100 – 2.150 mm (0.0827 – 0.0846 in.)
	2	2.150 – 2.200 mm (0.0846 – 0.0866 in.)
	3	2.200 – 2.250 mm (0.0866 – 0.0886 in.)
	Brown	2.250 – 2.300 mm (0.0886 – 0.0906 in.)
	Blue	2.300 – 2.350 mm (0.0906 – 0.0925 in.)
	6	2.350 – 2.400 mm (0.0925 – 0.0945 in.)
	7	2.400 – 2.450 mm (0.0945 – 0.0965 in.)
	8	2.450 – 2.500 mm (0.0965 – 0.0984 in.)
Rear propeller shaft (Type A)		2.00 mm (0.0787 in.)
	Brown	2.03 mm (0.0799 in.)
	Blue	2.06 mm (0.0811 in.)
		2.09 mm (0.0823 in.)