

Item	Capacity	Classification
FRONT DRIVE SHAFT		
Outboard joint grease	368 – 378 g (13 – 13.3 oz.)	
Inboard joint grease	293 – 303 g (10.3 – 10.7 oz.)	
FRONT DIFFERENTIAL		
Hypoid gear oil	1.70 liters (1.80 US qts, 1.50 Imp. qts)	Hypoid gear oil API GL-5 Above –18 °C (0°F) SAE 90 Below –18 °C (0°F) SAE 80W-90 or 80W
REAR DIFFERENTIAL		
Hypoid gear oil Normal w/ Diff. lock	3.30 liters (3.49 US qts, 2.90 Imp. qts) 3.20 liters (3.38 US qts, 2.82 Imp. qts)	Hypoid gear oil API GL-5 Above –18 °C (0°F) SAE 90 Below –18 °C (0°F) SAE 80W-90 or 80W
Hypoid gear oil LSD w/ LSD	3.30 liters (3.49 US qts, 2.90 Imp. qts)	Hypoid gear oil LSD API GL-5 Above –18 °C (0°F) SAE 90 Below –18 °C (0°F) SAE 80W-90 or 80W
ACTIVE HEIGHT CONTROL SUSPENSION & ADAPTIVE VARIABLE SUSPENSION		
Suspension fluid AHC	3.7 liters (3.9 US qts, 3.3 Imp. qts)	–