

SFI

SERVICE DATA

SS0CB-21

Fuel pressure regulator	Fuel pressure at no vacuum	265 – 304 kPa (2.7 – 3.1 kgf/cm ² , 38 – 44 psi)
Fuel pump	Resistance at 20°C (68°F)	0.2 – 3.0 Ω
Injector	Resistance Injection volume Difference between each cylinder Fuel leakage at 20°C (68°F)	13.4 – 14.2 Ω 56 – 69 cm ³ (3.4 – 4.2 cu in.) per 15 seconds 13 cm ³ (0.8 cu in.) or less 1 drop or less per 12 minutes
MAF meter	Resistance (THA – E2) at –20°C (–4°F) at 20°C (68°F) at 60°C (140°F)	12.5 – 16.9 kΩ 2.19 – 2.67 kΩ 0.50 – 0.68 kΩ
Throttle body	Throttle body fully closed angle	5.5°
Accelerator pedal position sensor	Standard throttle valve opening percentage Sensor lever full-open position	60 % or more
Throttle control motor	Motor resistance at 20°C (68°F)	0.3 – 100 Ω
VSV for EVAP	Resistance at 20°C (68°F)	30 – 34 Ω
VSV for vapor pressure sensor	Resistance at 20°C (68°F)	30 – 36 Ω
ECT sensor	Resistance at –20°C (–4°F) 0°C (32°F) 20°C (68°F) 40°C (104°F) 60°C (140°F) 80°C (176°F)	10 – 20 kΩ 4 – 7 kΩ 2 – 3 kΩ 0.9 – 1.3 kΩ 0.4 – 0.7 kΩ 0.2 – 0.4 kΩ
Vapor pressure sensor	Power source voltage	4.5 – 5.5 V
Heated oxygen sensor	Heater coil resistance at 20°C (68°F)	11 – 16 Ω
Fuel cut rpm	Fuel return rpm	1,000 rpm
Fuel pump resistor	Resistance at 20°C (68°F)	0.70 – 0.76 Ω
VSV for CCV	Resistance at 20°C (68°F)	24 – 30 Ω