

## TORQUE SPECIFICATION

| Part tightened                                                           | N·m  | kgf·cm | ft·lbf    |
|--------------------------------------------------------------------------|------|--------|-----------|
| Fuel line                                                                |      |        |           |
| Union bolt type                                                          | 39   | 400    | 29        |
| Flare nut type for use with SST                                          | 34   | 345    | 25        |
|                                                                          | 38   | 380    | 28        |
| Fuel pressure pulsation damper x Delivery pipe for use with SST          | 33   | 340    | 24        |
|                                                                          | 39   | 400    | 29        |
| Fuel pressure regulator x RH delivery pipe                               | 7.5  | 80     | 66 in·lbf |
| Fuel tank vent tube set plate x Fuel tank                                | 3.5  | 35     | 31 in·lbf |
| Front fuel pipe x Delivery pipe                                          | 39   | 400    | 29        |
| Front fuel pipe x Lower intake manifold                                  | 7.5  | 80     | 66 in·lbf |
| Fuel return pipe x LH delivery pipe                                      | 7.5  | 80     | 66 in·lbf |
| Delivery pipe x Lower intake manifold                                    | 18   | 185    | 13        |
| Fuel sender gauge x Fuel tank                                            | 1.5  | 15     | 13 in·lbf |
| Fuel tank x Body                                                         | 39   | 400    | 29        |
| Drain plug x Fuel tank                                                   | 6.5  | 65     | 58 in·lbf |
| Fuel tank filler pipe x Fuel tank                                        | 3.5  | 35     | 31 in·lbf |
| Cutoff valve cover x Fuel tank                                           | 1.5  | 15     | 13 in·lbf |
| Accelerator pedal position sensor x Body                                 | 5.0  | 51     | 44 in·lbf |
| Throttle body x Upper intake manifold, Lower intake manifold             | 18   | 185    | 13        |
| Upper intake manifold, Accelerator cable bracket x Lower intake manifold | 18   | 185    | 13        |
| ECT sensor x Front water bypass joint                                    | 20.4 | 208    | 15        |
| Knock sensor x Cylinder block                                            | 45   | 450    | 33        |
| Heated oxygen sensor x Exhaust manifold                                  | 44   | 450    | 32        |
| Heated oxygen sensor x Front exhaust pipe                                | 20   | 200    | 14        |
| No.1 rear seat x Body                                                    | 41   | 420    | 30        |
| MAF meter x Air cleaner                                                  | 1.68 | 17     | 15 in·lbf |
| Fuel pump resistor x Body                                                | 12   | 122    | 8.8       |