0 GENERAL

VEHICLE IDENTIFICATION 0-2
MAJOR SPECIFICATIONS 0-4

VEHICLE IDENTIFICATION

MODELS

<Vehicles for Europe>

[SEDAN]

Model Code		Engine model	Transmission model	Fuel supply system
E52A	SNJEQL6/R6	4G93 (1,834 cm^3)	F5M22 (2WD-5M/T)	MPI
	SNHEQL6/R6			
	SRHEQL6/R6		F4A22 (2WD-4A/T)	
E55A	SNJEQL6/R6	4G63 (1,997 cm^3)	F5M22 (2WD-5M/T)	
	SNHEQL6/R6			
	SRHEQL6/R6		F4A22 (2WD-4A/T)	
E54A	SNGMQL6/R6	6A12 (1,999 cm^3)	F5M31 (2WD-5M/T)	
	SRGMQL6/R6		F4A23 (2WD-4A/T)	
E64A	SNGMQL6/R6		F5M31 (2WD-5M/T)	
	SRGMQL6/R6		F4A23 (2WD-4A/T)	
E57A	SNJFL6/R6	4D68 (1,998 cm^3) with intercooler and turbocharger	F5M31 (2WD-5M/T)	Fuel injection pump
	SNJFQL6			
	SNHFL6/R6			
	SNHFQL6			
E75A	SNHEQL6/R6	4G63 (1,997 cm^3)	W5M31 (4WD-5M/T)	MPI
E88A	SNGMQL6/R6	6G73 (2,497 cm^3)	W5M33 (4WD-5M/T)	
E52A	SRHEQL6B	4G93 (1,834 cm^3)	F4A22 (2WD-4A/T)	
E55A	SRHEQL6B	4G63 (1,997 cm^3)		

[HATCHBACK]

Model Code		Engine model	Transmission model	Fuel supply system
E52A	LNJEQL6/R6	4G93 (1,834 cm^3)	F5M22 (2WD-5M/T)	MPI
	LNHEQL6/R6			
	LRHEQL6/R6		F4A22 (2WD-4A/T)	
E55A	LNJEQL6/R6	4G63 (1,997 cm^3)	F5M22 (2WD-5M/T)	
	LNHEQL6/R6			
	LRHEQL6/R6		F4A22 (2WD-4A/T)	
E54A	LNGMQL6/R6	6A12 (1,999 cm^3)	F5M31 (2WD-5M/T)	
	LRGMQL6/R6		F4A23 (2WD-4A/T)	
E64A	LNGMQL6/R6		F5M31 (2WD-5M/T)	
	LRGMQL6/R6		F4A23 (2WD-4A/T)	
E57A	LNJFL6/R6	4D68 (1,998 cm^3) with intercooler and turbocharger	F5M31 (2WD-5M/T)	Fuel injection pump
	LNJFQL6			
	LNHFL6/R6			
	LNHFQL6			
E75A	LNHEQL6/R6	4G63 (1,997 cm^3)	W5M31 (4WD-5M/T)	MPI
E88A	LNGMQL6/R6	6G73 (2,497 cm^3)	W5M33 (4WD-5M/T)	

<Vehicles for General Export>
[SEDAN]

Model Code		Engine model	Transmission model	Fuel supply system
E52A	SNJL/R	4G93 (1,834 cm^3)	F5M22 (2WD-5M/T)	Conventional carburettor
	SRJL/R		F4A22 (2WD-4A/T)	
	SNHL/R		F5M22 (2WD-5M/T)	
	SRJL/R		F4A22 (2WD-4A/T)	
E55A	SNHL/R	4G63 (1,997 cm^3)	F5M22 (2WD-5M/T)	
	SRHL/R		F4A22 (2WD-4A/T)	
E54A	SNGML/R	6A12 (1,999 cm^3)	F5M31 (2WD-5M/T)	MPI
	SRGML/R		F4A23 (2WD-4A/T)	

<Vehicles For Hong Kong and Singapore>
[SEDAN]

Model Code		Engine model	Transmission model	Fuel supply system
E52A	SNHEQR	4G93 (1,834 cm^3)	F5M22 (2WD-5M/T)	MPI
	SRHEQR		F4A22 (2WD-4A/T)	
E55A	SRHEQR	4G63 (1,997 cm^3)	F4A22 (2WD-4A/T)	
E54A	SNGMQR	6A12 (1,999 cm^3)	F5M31 (2WD-5M/T)	
	SRGMQR		F4A23 (2WD-4A/T)	

<Vehicles for Chile (Metropolitan area)>
[SEDAN]

Model Code		Engine model	Transmission model	Fuel supply system
E55A	SNHEQL	4G63 (1,997 cm^3)	F5M22 (2WD-5M/T)	MPI
	SRHEQL		F4A22 (2WD-4A/T)	

<Vehicles for GCC>
[SEDAN]

Model Code		Engine model	Transmission model	Fuel supply system
E52A	SNJLW	4G93 (1,834 cm^3)	F5M22 (2WD-5M/T)	Conventional carburettor
	SRJLW		F4A22 (2WD-4A/T)	
E55A	SNJLW	4G63 (1,997 cm^3)	F5M22 (2WD-5M/T)	
	SRJLW		F4A22 (2WD-4A/T)	
	SNHLW		F5M22 (2WD-5M/T)	
	SRHLW		F4A22 (2WD-4A/T)	
E54A	SNGMLW	6A12 (1,999 cm^3)	F5M31 (2WD-5M/T)	MPI
	SRGMLW		F4A23 (2WD-4A/T)	

<Vehicles for Australia>
[HATCHBACK]

Model Code		Engine model	Transmission model	Fuel supply system
E55A	LNHER8	4G63 (1,997 cm^3)	F5M22 (2WD-5M/T)	MPI
	LRHER8		F4A22 (2WD-4A/T)	
E54A	LNGMR8	6A12 (1,999 cm^3)	F5M31 (2WD-5M/T)	
	LRGMR8		F4A23 (2WD-4A/T)	

MAJOR SPECIFICATIONS

<Vehicles for Europe>

[SEDAN]

Items	E52A	E55A	E54A
	SNJEQL6/R6 SNHEQL6/R6 SRHEQL6/R6	SNJEQL6/R6 SNHEQL6/R6 SRHEQL6/R6	SNGMQL6/R6 SRGMQL6/R6
Dimensions mm			
Overall length		4,620	
Overall width		1,730	
Overall height		1,395	
Wheelbase		2,635	
Track-front		1,510	
Track-rear		1,505	
Body overhang			
Front		920	
Rear		1,065	
Ground clearance (laden)		120	
Wheel alignment			
Front wheel alignment			
Toe-in (at the centre of tyre tread) mm		0±3	
Toe-in (at the rim of wheel disc) mm		0±1.5	
Toe angle (per wheel)		0°00'±0°09'	
Camber		0°00'±0°30'	
Caster		4°20'±1°30'	
Kingpin inclination angle		7°20'±1°30'	
Rear wheel alignment			
Toe-in (at the centre of tyre tread) mm		3±3	
Toe-in (at the rim of wheel disc) mm		1.5±1.5	
Toe angle (per wheel)		0°09'±0°09'	
Camber		−1°10'±0°30'	
Wheels and tyres			
Tyre size	185/70R14 87H	195/65R14 89V	195/60R15 88V
Wheel size	14 × 5 1/2 JJ	14 × 5 1/2 JJ	15 × 6 JJ
Offset mm	46	46	46

Items	E64A	E57A	E75A
	SNGMQL6/R6 SRGMQL6/R6	SNJFL6/R6 SNJFQL6 SNHFL6/R6 SNHFQL6	SNHEQL6/R6
Dimensions mm			
Overall length	4,620		4,620
Overall width	1,730		1,730
Overall height	1,395		1,405
Wheelbase	2,635		2,635
Track-front	1,510		1,510
Track-rear	1,505		1,505
Body overhang			
Front	920		920
Rear	1,065		1,065
Ground clearance (laden)	120		130

Items	E64A	E57A	E75A
	SNGMQL6/R6 SRGMQL6/R6	SNJFL6/R6 SNJFQL6 SNHFL6/R6 SNHFQL6	SNHEQL6/R6
Wheel alignment			
Front wheel alignment			
Toe-in (at the centre of tyre tread) mm	0±3	0±3	0±3
Toe-in (at the rim of wheel disc) mm	0±1.5	0±1.5	0±1.5
Toe angle (per wheel)	0°00'±0°09'	0°00'±0°09'	0°00'±0°09'
Camber	0°00'±0°30'	0°00'±0°30'	0°10'±0°30'
Caster	4°20'±1°30'	4°20'±1°30'	4°20'±1°30'
Kingpin inclination angle	7°20'±1°30'	7°20'±1°30'	7°20'±1°30'
Rear wheel alignment			
Toe-in (at the centre of tyre tread) mm	0±3	3±3	3±3
Toe-in (at the rim of wheel disc) mm	0±1.5	1.5±1.5	1.5±1.5
Toe angle (per wheel)	0°00'±0°09'	0°09'±0°09'	0°09'±0°09'
Camber	–1°10'±0°30'	–1°10'±0°30'	–0°55'±0°30'
Wheels and tyres			
Tyre size	195/60R15 88V	185/70R14 87H	195/65R14 89V
Wheel size	15 × 6 JJ	14 × 5 1/2 JJ	14 × 5 1/2 JJ
Offset mm	46	46	46

Items	E88A	E52A	E55A
	SNGMQL6/R6	SRHEQL6B	SRHEQL6B
Dimensions mm			
Overall length	4,620	4,620	
Overall width	1,730	1,730	
Overall height	1,405	1,395	
Wheelbase	2,635	2,635	
Track-front	1,510	1,510	
Track-rear	1,505	1,505	
Body overhang			
Front	920	920	
Rear	1,065	1,065	
Ground clearance (laden)	130	120	
Wheel alignment			
Front wheel alignment			
Toe-in (at the centre of tyre tread) mm	0±3	0±3	
Toe-in (at the rim of wheel disc) mm	0±1.5	0±1.5	
Toe angle (per wheel)	0°00'±0°09'	0°00'±0°09'	
Camber	0°10'±0°30'	0°00'±0°30'	
Caster	4°20'±1°30'	4°20'±1°30'	
Kingpin inclination angle	7°20'±1°30'	7°20'±1°30'	
Rear wheel alignment			
Toe-in (at the centre of tyre tread) mm	0±3	3±3	
Toe-in (at the rim of wheel disc) mm	0±1.5	1.5±1.5	
Toe angle (per wheel)	0°00'±0°09'	0°09'±0°09'	
Camber	–0°55'±0°30'	–1°10'±0°30'	
Wheels and tyres			
Tyre size	205/60R15 91V	185/70R14 87H	195/65R14 89V
Wheel size	15 × 6 JJ	14 × 5 1/2 JJ	14 × 5 1/2 JJ
Offset mm	46	46	46

[HATCHBACK]

Items	E52A	E55A	E54A
	LNJEQL6/R6 LNHEQL6/R6 LRHEQL6/R6	LNJEQL6/R6 LNHEQL6/R6 LRHEQL6/R6	LNGMQL6/R6 LRGMQL6/R6
Dimensions mm			
Overall length		4,620	
Overall width		1,730	
Overall height		1,395	
Wheelbase		2,635	
Track-front		1,510	
Track-rear		1,505	
Body overhang			
Front		920	
Rear		1,065	
Ground clearance (laden)		120	
Wheel alignment			
Front wheel alignment			
Toe-in (at the centre of tyre tread) mm		0±3	
Toe-in (at the rim of wheel disc) mm		0±1.5	
Toe angle (per wheel)		0°00'±0°09'	
Camber		0°00'±0°30'	
Caster		4°20'±1°30'	
Kingpin inclination angle		7°20'±1°30'	
Rear wheel alignment			
Toe-in (at the centre of tyre tread) mm		3±3	
Toe-in (at the rim of wheel disc) mm		1.5±1.5	
Toe angle (per wheel)		0°09'±0°09'	
Camber		−1°10'±0°30'	
Wheels and tyres			
Tyre size	185/70R14 87H	195/65R14 89V	195/60R15 88V
Wheel size	14 × 5 1/2 JJ	14 × 5 1/2 JJ	15 × 6 JJ
Offset mm	46	46	46

Items	E64A	E57A
	LNGMQL6/R6 LRGMQL6/R6	LNJFL6/R6 LNJFQL6 LNHFL6/R6 LNHFQL6
Dimensions mm		
Overall length	4,620	
Overall width	1,730	
Overall height	1,395	
Wheelbase	2,635	
Track-front	1,510	
Track-rear	1,505	
Body overhang		
Front	920	
Rear	1,065	
Ground clearance (laden)	120	

Items	E64A	E57A
	LNGMQL6/R6 LRGMQL6/R6	LNJFL6/R6 LNJFQL6 LNHFL6/R6 LNHFQL6
Wheel alignment		
Front wheel alignment		
Toe-in (at the centre of tyre tread) mm	0±3	0±3
Toe-in (at the rim of wheel disc) mm	0±1.5	0±1.5
Toe angle (per wheel)	0°00'±0°09'	0°00'±0°09'
Camber	0°00'±0°30'	0°00'±0°30'
Caster	4°20'±1°30'	4°20'±1°30'
Kingpin inclination angle	7°20'±1°30'	7°20'±1°30'
Rear wheel alignment		
Toe-in (at the centre of tyre tread) mm	0±3	3±3
Toe-in (at the rim of wheel disc) mm	0±1.5	1.5±1.5
Toe angle (per wheel)	0°00'±0°09'	0°09'±0°09'
Camber	−1°10'±0°30'	−1°10'±0°30'
Wheels and tyres		
Tyre size	195/60R15 88V	185/70R14 87H
Wheel size	15 × 6 JJ	14 × 5 1/2 JJ
Offset mm	46	46

Items	E75A	E88A
	LNHEQL6/R6	LNGMQL6/R6
Dimensions mm		
Overall length	4,620	
Overall width	1,730	
Overall height	1,405	
Wheelbase	2,635	
Track-front	1,510	
Track-rear	1,505	
Body overhang		
Front	920	
Rear	1,065	
Ground clearance (laden)	130	
Wheel alignment		
Front wheel alignment		
Toe-in (at the centre of tyre tread) mm	0±3	0±3
Toe-in (at the rim of wheel disc) mm	0±1.5	0±1.5
Toe angle (per wheel)	0°00'±0°09'	0°00'±0°09'
Camber	0°10'±0°30'	0°10'±0°30'
Caster	4°20'±1°30'	4°20'±1°30'
Kingpin inclination angle	7°20'±1°30'	7°20'±1°30'
Rear wheel alignment		
Toe-in (at the centre of tyre tread) mm	3±3	3±3
Toe-in (at the rim of wheel disc) mm	1.5±1.5	0±1.5
Toe angle (per wheel)	0°09'±0°09'	0°00'±0°09'
Camber	−0°55'±0°30'	−0°55'±0°30'
Wheels and tyres		
Tyre size	195/65R14 89V	205/60 R15 91V
Wheel size	14 × 5 1/2 JJ	15 × 6 JJ
Offset mm	46	46

<Vehicle for General Export>

[SEDAN]

Items	E52A	
	SNJL/R SRJL/R	SNHL/R SRHL/R
Dimensions mm		
Overall length	4,620	
Overall width	1,730	
Overall height	1,405	
Wheelbase	2,635	
Track-front	1,510	
Track-rear	1,505	
Body overhang		
Front	920	
Rear	1,065	
Ground clearance(unladen)	160	
Wheel alignment		
Front wheel alignment		
Toe-in (at the centre of tyre tread) mm	0±3	
Toe-in (at the rim of wheel disc) mm	0±1.5	
Toe angle (per wheel)	0°00'±0°09'	
Camber	0°00'±0°30'	
Caster	4°20'±1°30'	
Kingpin inclination angle	7°20'±1°30'	
Rear wheel alignment		
Toe-in (at the centre of tyre tread) mm	3±3	
Toe-in (at the rim of wheel disc) mm	1.5±1.5	
Toe angle (per wheel)	0°09'±0°09'	
Camber	–1°10'±0°30'	
Wheels and tyres		
Tyre size	165SR14	185/70R14 87H
Wheel size	14 x 5 1/2 JJ	14 x 5 1/2 JJ
Offset mm	46	46

Items	E55A	E54A
	SNHL/R SRHL/R	SNGML/R SRGML/R
Dimensions mm		
Overall length	4,620	
Overall width	1,730	
Overall height	1,405	
Wheelbase	2,635	
Track-front	1,510	
Track-rear	1,505	
Body overhang		
Front	920	
Rear	1,065	
Ground clearance (unladen)	160	

Items	E55A	E54A
	SNHL/R SRHL/R	SNGML/R SRGML/R
Wheel alignment		
Front wheel alignment		
Toe-in (at the centre of tyre tread) mm	0±3	
Toe-in (at the rim of wheel disc) mm	0±1.5	
Toe angle (per wheel)	0°00'±0°09'	
Camber	0°00'±0°30'	
Caster	4°20'±1°30'	
Kingpin inclination angle	7°20'±1°30'	
Rear wheel alignment		
Toe-in (at the centre of tyre tread) mm	3±3	
Toe-in (at the rim of wheel disc) mm	1.5±1.5	
Toe angle (per wheel)	0°09'±0°09'	
Camber	−1°10'±0°30'	
Wheels and tyres		
Tyre size	185/70R14 87H	195/60R15 88V
Wheel size	14 × 5 1/2 JJ	15 × 6 JJ
Offset mm	46	46

<Vehicles for Hong Kong and Singapore>
[SEDAN]

Items	E52A	E55A	E54A
	SNHEQR SRHEQR	SRHEQR	SNGMQR SRGMQR
Dimensions mm			
Overall length	4,620		
Overall width	1,730		
Overall height	1,405		
Wheelbase	2,635		
Track-front	1,510		
Track-rear	1,505		
Body overhang			
Front	920		
Rear	1,065		
Ground clearance (unladen)	160		
Wheel alignment			
Front wheel alignment			
Toe-in (at the centre of tyre tread) mm	0±3		
Toe-in (at the rim of wheel disc) mm	0±1.5		
Toe angle (per wheel)	0°00'±0°09'		
Camber	0°00'±0°30'		
Caster	4°20'±1°30'		
Kingpin inclination angle	7°20'±1°30'		
Rear wheel alignment			
Toe-in (at the centre of tyre tread) mm	3±3		
Toe-in (at the rim of wheel disc) mm	1.5±1.5		
Toe angle (per wheel)	0°09'±0°09'		
Camber	−1°10'±0°30'		
Wheels and tyres			
Tyre size	185/70R14 87H	195/65 R14 89V	195/60 R15 88V
Wheel size	14 × 5 1/2 JJ	14 × 5 1/2 JJ	15 × 6 JJ
Offset mm	46	46	46

<Vehicles for Chile (Metropolitan area)>

[SEDAN]

Items	E55A	
	SNHEQL	SRHEQL
Dimensions mm		
Overall length	4,620	
Overall width	1,730	
Overall height	1,405	
Wheelbase	2,635	
Track-front	1,510	
Track-rear	1,505	
Body overhang		
Front	920	
Rear	1,065	
Ground clearance (unladen)	160	
Wheel alignment		
Front wheel alignment		
Toe-in (at the centre of tyre tread) mm	0±3	
Toe-in (at the rim of wheel disc) mm	0±1.5	
Toe angle (per wheel)	0°00'±0°09'	
Camber	0°00'±0°30'	
Caster	4°20'±1°30'	
Kingpin inclination angle	7°20'±1°30'	
Rear wheel alignment		
Toe-in (at the centre of tyre tread) mm	3±3	
Toe-in (at the rim of wheel disc) mm	1.5±1.5	
Toe angle (per wheel)	0°09'±0°09'	
Camber	–1°10'±0°30'	
Wheels and tyres		
Tyre size	195/65R14 89V	
Wheel size	14 x 5 1/2 JJ	
Offset mm	46	

<Vehicles for GCC>

[SEDAN]

Items	E52A	E55A	E54A
	SNJLW SRJLW	SNJLW SRJLW SNHLW SRHLW	SNGMLW SRGMLW
Dimensions mm			
Overall length	4,620		
Overall width	1,730		
Overall height	1,405		
Wheelbase	2,635		
Track-front	1,510		
Track-rear	1,505		
Body overhang			
Front	920		
Rear	1,065		
Ground clearance (unladen)	160		

Items	E52A	E55A	E54A
	SNJLW SRJLW	SNJLW SRJLW SNHLW SRHLW	SNGMLW SRGMLW
Wheel alignment			
Front wheel alignment			
Toe-in (at the centre of tyre tread) mm		0±3	
Toe-in (at the rim of wheel disc) mm		0±1.5	
Toe angle (per wheel)		0°00'±0°09'	
Camber		0°00'±0°30'	
Caster		4°20'±1°30'	
Kingpin inclination angle		7°20'±1°30'	
Rear wheel alignment			
Toe-in (at the centre of tyre tread) mm		3±3	
Toe-in (at the rim of wheel disc) mm		1.5±1.5	
Toe angle (per wheel)		0°09'±0°09'	
Camber		−1°10'±0°30'	
Wheels and tyres			
Tyre size	165SR14	185/70R1487H	195/60R15 88V
Wheel size	14 × 5 1/2 JJ	14 × 5 1/2 JJ	15 × 6 JJ
Offset mm	46	46	46

<Vehicles for Australia>
[HATCHBACK]

Items	E55A	E54A
	LNHER8 LRHER8	LNGMR8 LRGMR8
Dimensions mm		
Overall length	4,620	
Overall width	1,730	
Overall height	1,395	
Wheelbase	2,635	
Track-front	1,510	
Track-rear	1,505	
Body overhang		
Front	920	
Rear	1,065	
Ground clearance (unladen)	150	
Wheel alignment		
Front wheel alignment		
Toe-in (at the centre of tyre tread) mm	0±3	
Toe-in (at the rim of wheel disc) mm	0±1.5	
Toe angle (per wheel)	0°00'±0°09'	
Camber	0°00'±0°30'	
Caster	4°20'±1°30'	
Kingpin inclination angle	7°20'±1°30'	
Rear wheel alignment		
Toe-in (at the centre of tyre tread) mm	3±3	
Toe-in (at the rim of wheel disc) mm	1.5±1.5	
Toe angle (per wheel)	0°09'±0°09'	
Camber	−1°10'±0°30'	
Wheels and tyres		
Tyre size	195/65R14 89V	195/60 R15 88V
Wheel size	14 × 5 1/2 JJ	15 × 6 JJ
Offset mm	46	46