

Edition: June 2013
Revision: June 2013
Pub. No. SM14E00L50U0



All rights reserved. No part of this Service Manual may be reproduced or stored in a retrieval system, or transmitted in any form, or by any means, electronic, mechanical, photo-copying, recording or otherwise, without the prior written permission of Nissan North America, Inc.

QUICK REFERENCE INDEX

A GENERAL INFORMATION	GI General Information
B ENGINE	EM Engine Mechanical
	LU Engine Lubrication System
	CO Engine Cooling System
	EC Engine Control System
	FL Fuel System
	EX Exhaust System
	STR Starting System
	ACC Accelerator Control System
C	
D TRANSMISSION & DRIVE-LINE	
	TM Transaxle & Transmission
	DLN Driveline
	FAX Front Axle
	RAX Rear Axle
E SUSPENSION	FSU Front Suspension
	RSU Rear Suspension
	WT Road Wheels & Tires
F BRAKES	BR Brake System
	PB Parking Brake System
	BRC Brake Control System
G STEERING	ST Steering System
	STC Steering Control System
H RESTRAINTS	SB Seat Belt
	SBC Seat Belt Control System
	SR SRS Airbag System
	SRC SRS Airbag Control System
I VENTILATION, HEATER & AIR CONDITIONER	VTL Ventilation System
	HA Heater & Air Conditioning System
	HAC Heater & Air Conditioning Control System
J BODY INTERIOR	INT Interior
	IP Instrument Panel
	SE Seat
	ADP Automatic Drive Positioner
K BODY EXTERIOR, DOORS, ROOF & VEHICLE SECURITY	DLK Door & Lock
	SEC Security Control System
	GW Glass & Window System
	PWC Power Window Control System
	RF Roof
	EXT Exterior
	BRM Body Repair Manual
L DRIVER CONTROLS	MIR Mirrors
	EXL Exterior Lighting System
	INL Interior Lighting System
	WW Wiper & Washer
	DEF Defogger
	HRN Horn
M ELECTRICAL & POWER CONTROL	PWO Power Outlet
	BCS Body Control System
	LAN LAN System
	PCS Power Control System
	CHG Charging System
	PG Power Supply, Ground & Circuit Elements
N DRIVER INFORMATION & MULTIMEDIA	MWI Meter, Warning Lamp & Indicator
	WCS Warning Chime System
	AV Audio, Visual & Navigation System
O CRUISE CONTROL	CCS Cruise Control System
	DAS Driver Assistance System
	DMS Drive Mode System
P MAINTENANCE	MA Maintenance

A

B

C

D

E

F

G

H

I

J

K

L

M

N

O

P

FOREWORD

This manual contains maintenance and repair procedure for the 2014 INFINITI QX60.

In order to assure your safety and the efficient functioning of the vehicle, this manual should be read thoroughly. It is especially important that the PRECAUTIONS in the GI section be completely understood before starting any repair task.

All information in this manual is based on the latest product information at the time of publication. The right is reserved to make changes in specifications and methods at any time without notice.

IMPORTANT SAFETY NOTICE

The proper performance of service is essential for both the safety of the technician and the efficient functioning of the vehicle.

The service methods in this Service Manual are described in such a manner that the service may be performed safely and accurately. Service varies with the procedures used, the skills of the technician and the tools and parts available. Accordingly, anyone using service procedures, tools or parts which are not specifically recommended by NISSAN must first be completely satisfied that neither personal safety nor the vehicle's safety will be jeopardized by the service method selected.



NISSAN NORTH AMERICA, INC.



PLEASE HELP MAKE THIS SERVICE MANUAL BETTER!

INFINITI®

Your comments are important to INFINITI and will help us to improve our Service Manuals.

Use this form to report any issues or comments you may have regarding our Service Manuals.

Please print this form and type or write your comments below. Mail or fax to:

Nissan North America, Inc.
Technical Service Information
39001 Sunrise Drive, P.O. Box 9200
Farmington Hills, MI USA 48331
FAX: (248) 488-3880

SERVICE MANUAL: Model: _____ Year: _____

PUBLICATION NO. (Refer to Quick Reference Index): _____

Please describe any Service Manual issues or problems in detail:

Page number(s) _____ *Note: Please include a copy of each page, marked with your comments.*

Are the trouble diagnosis procedures logical and easy to use? (circle your answer) YES NO

If no, what page number(s)? _____ *Note: Please include a copy of each page, marked with your comments.*

Please describe the issue or problem in detail: _____

Is the organization of the manual clear and easy to follow? (circle your answer) YES NO

Please comment: _____

What information should be included in INFINITI Service Manuals to better support you in servicing or repairing customer vehicles?

DATE: _____ YOUR NAME: _____ POSITION: _____

DEALER: _____ DEALER NO.: _____ ADDRESS: _____

CITY: _____ STATE/PROV./COUNTRY: _____ ZIP/POSTAL CODE: _____

QUICK REFERENCE CHART: QX60


Engine Tune-up Data

INFOID:000000009914939


GENERAL SPECIFICATIONS

Cylinder arrangement		V-6
Displacement cm^3 (cu in)		3,498 (213.45)
Bore and stroke mm (in)		95.5 x 81.4 (3.760 x 3.205)
Valve arrangement		DOHC
Firing order		1-2-3-4-5-6
Number of piston rings	Compression	2
	Oil	1
Number of main bearings		4
Compression ratio		10.6:1
Compression pressure kPa (kg/cm^2 , psi)/300 rpm	Standard	1,275 (13.0, 185)
	Minimum	981 (10.0, 142)
	Differential limit between cylinders	98 (1.0, 14)

Cylinder number



SEM713A

Valve timing
(Valve timing control - "OFF")

PBIC0187E

Unit: degree

a	b	c	d	e	f
240	240	-10	70	10	50

Drive Belt

INFOID:000000009914940

DRIVE BELT

Tension of drive belt	Belt tension is not necessary, as it is automatically adjusted by drive belt auto-tensioner.
-----------------------	--

Spark Plug

INFOID:000000009914941

SPARK PLUG

Unit: mm (in)

Make	DENSO	
Standard type*	FXE22HR11	
Gap	Standard	1.1 (0.043)

*: Always check with the Parts Department for the latest parts information.


Front Wheel Alignment (Unladen*¹)

INFOID:000000009914938

WARNING:

If the vehicle is equipped with the ICC cruise control system and the rear toe has been adjusted during a wheel alignment, the ICC sensor must be aligned.

Item		Standard	
Measurement wheel		(LH) side	(RH) side
Camber Degree minute (Decimal degree)	Minimum	-1° 00' (-1.00°)	-1° 15' (-1.25°)
	Nominal	-0° 15' (-0.25°)	-0° 30' (-0.50°)
	Maximum	0° 30' (0.50°)	0° 15' (0.25°)
	(LH) and (RH) difference* ²	-0° 15' ± 0° 33' (0.25° ± 0.55°)	
Caster Degree minute (Decimal degree)	Minimum	3° 55' (3.92°)	
	Nominal	4° 40' (4.67°)	
	Maximum	5° 25' (5.42°)	
	(LH) and (RH) difference* ²	0.30' (0.50°) Maximum	
Kingpin inclination Degree minute (Decimal degree)	Minimum	11° 55' (11.92°)	12° 10' (12.17°)
	Nominal	12° 40' (12.67°)	12° 55' (12.92°)
	Maximum	13° 25' (13.42°)	13° 40' (13.67°)



Total toe-in	Distance (A - B)	Minimum	Out 0.6 mm (Out 0.024 in)
		Nominal	In 1.4 mm (In 0.055 in)
		Maximum	In 3.4 mm (In 0.134 in)
	Angle (LH) and (RH) Degree minute (Decimal degree)	Minimum	Out 0° 3' 36" (Out 0.06°)
		Nominal	In 0° 6' 14" (In 0.10°)
		Maximum	In 0° 15' 36" (In 0.26°)

*¹ Fuel, engine coolant, and lubricant are full. Spare tire, jack, hand tools and mats are in designated positions.

*²: The difference when assuming the (LH) side is the standard.


Rear Wheel Alignment (Unladen*)

INFOID:000000009914936

WARNING:

If the vehicle is equipped with the ICC cruise control system and the rear toe has been adjusted during a wheel alignment, the ICC sensor must be aligned.

Item		Standard
Camber Degree minute (Decimal degree)	Minimum	-1° 05' (-1.08°)
	Nominal	-0° 35' (-0.58°)
	Maximum	-0° 05' (-0.08°)




Total toe-in	Distance (A - B)	Minimum	Out 0.8 mm (Out 0.031 in)
		Nominal	In 2.2 mm (In 0.087 in)
		Maximum	In 5.2 mm (In 0.205 in)
	Angle (LH and RH) Degree minute (Decimal degree)	Minimum	Out 0° 2' 24" (Out 0.04°)
		Nominal	In 0° 9' 36" (In 0.16°)
		Maximum	In 0° 21' 36" (In 0.36°)

*: Fuel, engine coolant, and lubricants are full. Spare tire, jack, hand tools, and mats are in designated positions.

Wheelarch Height

INFOID:000000009914937

UNITED STATES




LEIA0085E

Drive type	FWD			AWD		
Tire size	235/65R18		235/55R20	235/65R18		235/55R20
Grade	Base	Premium		Base	Premium	Premium
Front (Hf)	822 mm (32.36 in)	822 mm (32.36 in)	821 mm (32.32 in)	822 mm (32.36 in)	821 mm (32.32 in)	820 mm (32.28 in)
Rear (Hr)	828 mm (32.60 in)	827 mm (32.56 in)	826 mm (32.52 in)	827 mm (32.56 in)		825 mm (32.48 in)

*: Fuel, engine coolant, and lubricants are full. Spare tire, jack, hand tools, and mats are in designated positions.

CANADA




LEIA0085E

Drive type	AWD		
Tire size	235/65R18		235/55R20
Grade	Base	Premium	Premium
Front (Hf)	822 mm (32.36 in)	822 mm (32.36 in)	821 mm (32.32 in)
Rear (Hr)	828 mm (32.60 in)	827 mm (32.56 in)	826 mm (32.52 in)

*: Fuel, engine coolant, and lubricants are full. Spare tire, jack, hand tools, and mats are in designated positions.

MEXICO

Unit: mm (in)



LEIA0085E

Drive type	AWD		
Tire size	235/65R18		
Grade	Premium		
Front (Hf)	822 (32.36)		
Rear (Hf)	827 (32.56)		

Measure value under unladen* conditions. (Fuel, engine coolant and lubricant are full. Spare tire, jack, hand tools and mats are in designated positions).

Brake Specifications

INFOID:000000009914934

Unit: mm (in)

Front brake	Cylinder bore diameter	45.0 (1.772) × 2
	Pad length × width × thickness	131.4 (5.173) × 53.0 (2.087) × 10.0 (0.394)
	Rotor outer diameter × thickness	320.0 (12.598) × 28.0 (1.102)
Rear brake	Cylinder bore diameter	42.86 (1.6874)
	Pad length × width × thickness	83.0 (3.268) × 33.0 (1.299) × 8.5 (0.335)
	Rotor outer diameter × thickness	308 (12.126) × 16.0 (0.630)
Master cylinder	Cylinder bore diameter	26.99 (1.063)
Control valve	Valve type	Electric brake force distribution

QUICK REFERENCE CHART: QX60

2014

Brake Pedal

INFOID:000000009914935

Unit: mm (in)

Item	Standard
Brake pedal height (H1)	214.2 – 224.2 (8.43 – 8.82)
Clearance (A) between brake pedal bracket, stop lamp switch and ASCD cancel switch contact ends	0.74 – 1.96 (0.0291 – 0.0772)
Depressed brake pedal height (H2) [Depressing 490 N (50 kg, 110 lb) while turning the engine ON]	75.1 (2.96)

Front Disc Brake

INFOID:000000009914932

Unit: mm (in)

Item		Limit
Brake pad	Wear thickness	2.0 (0.079)
	Wear thickness	26.0 (1.024)
Disc rotor	Thickness variation (measured at 8 positions)	0.008 (0.0003)
	Runout (with disc rotor attached to the vehicle)	0.040 (0.0016) or less

Rear Disc Brake

INFOID:000000009914933

Unit: mm (in)

Item		Limit
Brake pad	Wear thickness	2.0 (0.079)
	Wear thickness	14.0 (0.551)
Disc rotor	Thickness variation (measured at 8 positions)	0.020 (0.0008)
	Runout (with disc rotor attached to the vehicle)	0.050 (0.0020) or less

FOR USA AND CANADA : Fluids and Lubricants

INFOID:000000009914738

Description		Capacity (Approximate)		
		Metric	US measure	Imp measure
Fuel		74.0 ℓ	19-1/2 gal	16-1/4 gal
Engine oil Drain and refill	With oil filter change	4.8 ℓ	5-1/8 qt	4-1/4 qt
	Without oil filter change	4.5 ℓ	4-3/4 qt	4 qt
	Dry engine (Over-haul)	5.1 ℓ	5-3/8 qt	4-1/2 qt
Cooling system (with reservoir at MAX level)		9.6 ℓ	10-1/8 qt	8-1/2 qt
CVT fluid		8.8 ℓ	9-1/4 qt	7-3/4 qt
Differential gear oil		0.5 ℓ	1 pt	7/8 pt
Transfer fluid		0.31 ℓ	5/8 pt	1/2 pt
Power steering fluid (E-PSF)		1.0 ℓ	2-1/8 qt	1-3/4 qt
Brake fluid		—	—	—
Multi-purpose grease		—	—	—
Windshield washer fluid		4.6 ℓ	4-7/8 qt	4 qt

QUICK REFERENCE CHART: QX60

2014

Description	Capacity (Approximate)		
	Metric	US measure	Imp measure
Air conditioning system refrigerant	0.83 ± 0.03 kg	1.83 ± 0.07 lb	1.83 ± 0.07 lb
Air conditioning system oil	230 m ℓ	7.8 fl oz	8.1 fl oz

FOR MEXICO : Fluids and Lubricants

INFOID:000000009914741

		Capacity (Approximate)		
		Metric	US measure	Imp measure
Fuel		74.0 ℓ	19-1/2 gal	16-1/4 gal
Engine oil Drain and refill	With oil filter change	4.8 ℓ	5-1/8 qt	4-1/4 qt
	Without oil filter change	4.5 ℓ	4-3/4 qt	4 qt
	Dry engine (engine overhaul)	5.1 ℓ	5-3/8 qt	4-1/2 qt
Cooling system (with reservoir at MAX line)		9.6 ℓ	10-1/8 qt	8-1/2 qt
CVT fluid		8.8 ℓ	9-1/4 qt	7-3/4 qt
Differential gear oil		0.5 ℓ	1 pt	7/8 pt
Transfer fluid		0.31 ℓ	5/8 pt	1/2 pt
Power steering fluid		1.0 ℓ	2-1/8 qt	1-3/4 qt
Brake fluid		—	—	—
Multi-purpose grease		—	—	—
Windshield washer fluid		4.6 ℓ	4-7/8 qt	4 qt
Air conditioning system refrigerant		0.83 ± 0.03 kg	1.83 ± 0.07 lb	1.83 ± 0.07 lb
Air conditioning system oil		230 m ℓ	7.8 fl oz	8.1 fl oz