

BRAKE SPECIFICATIONS													
NISSAN AXCESS, FRONTIER, PATHFINDER, PICK-UP, QUEST													
All measurements in inches unless noted													
Year	Model		Master Cylinder Bore	Brake Disc			Brake Drum Diameter			Minimum Lining Thickness		Brake Caliper	
				Original Thickness	Minimum Thickness	Maximum Runout	Original Inside Diameter	Max. Wear Limit	Maximum Machine Diameter	Front	Rear	Bracket Bolts (ft. lbs.)	Mounting Bolts (ft. lbs.)
1990	Axxess	F	0.938	NA	0.787	0.003	—	—	—	0.079	—	—	12-14
		R	—	—	—	—	⑨	NA	NA	—	0.059	—	—
	Pathfinder	F	0.938	NA	②	0.003	—	—	—	0.079	—	—	12-14
		R	—	NA	0.630	0.003	—	—	—	—	0.079	—	12-14
		R	—	—	—	—	10.24 ③	NA	NA	—	0.059	—	—
	Pick-Up	F	0.938	NA	②	0.003	—	—	—	0.079	—	53-72	16-23
		R	—	NA	0.630	0.003	—	—	—	—	0.079	53-72	16-23
		R	—	—	—	—	NA	NA	⑦	—	0.059	—	—
1991	Pathfinder	F	0.938	NA	②	0.003	—	—	—	0.079	—	—	12-14
		R	—	NA	0.630	0.003	—	—	—	—	0.079	—	12-14
		R	—	—	—	—	10.24 ③	NA	NA	—	0.059	—	—
	Pick-Up	F	0.938	NA	②	0.003	—	—	—	0.079	—	53-72	16-23
		R	—	NA	0.630	0.003	—	—	—	—	0.079	53-72	16-23
		R	—	—	—	—	NA	NA	⑦	—	0.059	—	—
1992	Pathfinder	F	①	1.020	0.945	0.003	—	—	—	0.079	—	—	12-14
		R	—	0.710	0.630	0.003	—	—	—	—	0.079	—	12-14
		R	—	—	—	—	10.24 ③	NA	10.30 ④	—	0.059	—	—
	Pick-Up	F	①	NA	②	0.003	—	—	—	0.079	—	53-72	16-23
		R	—	NA	0.630	0.003	—	—	—	—	0.079	53-72	16-23
		R	—	—	—	—	NA	NA	⑦	—	0.059	—	—
1993	Pathfinder	F	1.000	1.020	0.945	0.003	—	—	—	0.079	—	—	12-14
		R	—	0.710	0.630	0.003	—	—	—	—	0.079	—	12-14
		R	—	—	—	—	10.24 ③	NA	10.30 ④	—	0.059	—	—
	Pick-Up	F	1.000	NA	②	0.003	—	—	—	0.079	—	53-72	16-23
		R	—	—	—	—	NA	NA	⑦	—	0.059	—	—
	Quest	F	1.000	1.020	0.945	0.003	—	—	—	0.079	—	—	12-14
		R	—	—	—	—	9.84	NA	9.90	—	0.079	—	—
1994	Pathfinder	F	1.000	1.020	0.945	0.003	—	—	—	0.079	—	—	12-14
		R	—	0.710	0.630	0.003	—	—	—	—	0.079	—	12-14
		R	—	—	—	—	10.24 ③	NA	10.30 ④	—	0.059	—	—
	Pick-Up	F	1.000	NA	②	0.003	—	—	—	0.079	—	53-72	16-23
		R	—	—	—	—	NA	NA	⑦	—	0.059	—	—
	Quest	F	1.000	1.020	0.945	0.003	—	—	—	0.079	—	—	12-14
		R	—	—	—	—	9.84	NA	9.90	—	0.079	—	—
1995	Pathfinder	F	1.000	1.020	0.945	0.003	—	—	—	0.079	—	—	12-14
		R	—	0.710	0.630	0.003	—	—	—	—	0.079	—	12-14
		R	—	—	—	—	10.24 ③	NA	10.30 ④	—	0.059	—	—
	Pick-Up	F	1.000	⑤	⑥	0.003	—	—	—	0.079	—	53-72	16-23
		R	—	—	—	—	⑧	NA	⑦	—	0.059	—	—
	Quest	F	1.000	1.020	0.945	0.003	—	—	—	0.079	—	—	12-14
		R	—	—	—	—	9.84	NA	9.90	—	0.079	—	—
1996	Pathfinder	F	1.000	1.020	0.945	0.003	—	—	—	0.079	—	—	12-14
		R	—	0.710	0.630	0.003	—	—	—	—	0.079	—	12-14
		R	—	—	—	—	10.24 ③	NA	10.30 ④	—	0.059	—	—
	Pick-Up	F	1.000	⑤	⑥	0.003	—	—	—	0.079	—	53-72	16-23
		R	—	—	—	—	⑧	NA	⑦	—	0.059	—	—