

NISSAN 240SX

MODEL S14 SERIES

QUICK REFERENCE INDEX

GENERAL INFORMATION	GI
MAINTENANCE	MA
ENGINE MECHANICAL	EM
ENGINE LUBRICATION & COOLING SYSTEMS	LC
ENGINE CONTROL SYSTEM	EC
ACCELERATOR CONTROL, FUEL & EXHAUST SYSTEMS	FE
CLUTCH	CL
MANUAL TRANSMISSION	MT
AUTOMATIC TRANSMISSION	AT
PROPELLER SHAFT & DIFFERENTIAL CARRIER	PD
FRONT AXLE & FRONT SUSPENSION	FA
REAR AXLE & REAR SUSPENSION	RA
BRAKE SYSTEM	BR
STEERING SYSTEM	ST
BODY	BF
HEATER & AIR CONDITIONER	HA
ELECTRICAL SYSTEM	EL
ALPHABETICAL INDEX	IDX

FOREWORD

This manual contains maintenance and repair procedures for the 1995 Nissan 240SX.

In order to assure your safety and the efficient functioning of the vehicle, this manual should be read thoroughly. It is especially important that the PRECAUTIONS in the GI section be completely understood before starting any repair task.

All information in this manual is based on the latest product information at the time of publication. The right is reserved to make changes in specifications and methods at any time without notice.

IMPORTANT SAFETY NOTICE

The proper performance of service is essential for both the safety of the technician and the efficient functioning of the vehicle. The service methods in this Service Manual are described in such a manner that the service may be performed safely and accurately. Service varies with the procedures used, the skills of the technician and the tools and parts available. Accordingly, anyone using service procedures, tools or parts which are not specifically recommended by NISSAN must first completely satisfy himself that neither his safety nor the vehicle's safety will be jeopardized by the service method selected.



NISSAN MOTOR CO., LTD.

Overseas Service Department
Tokyo, Japan

QUICK REFERENCE CHART : 240SX 1995

ENGINE TUNE-UP DATA

Engine model	KA24DE		
Firing order	1-3-4-2		
Idle speed	rpm	700±50	
M/T		700±50	
A/T (in "N" position)		700±50	
Ignition timing (degree BTDC at idle speed)		20°±2°	
Idle "CO" (% at idle speed)		Idle mixture screw is preset and sealed at factory.	
Valve clearance (Hot)	mm (in)	0.33 - 0.41 (0.013 - 0.016)	
Intake & Exhaust			
High tension cable resistance	kΩ	Less than 30	
Spark plug		PFR5C-11	
Standard		PFR6C-11	
Type		PFR7C-11	
Cold			
Gap	mm (in)	1.0 - 1.1 (0.039 - 0.043)	
Drive belt deflection (Cold)	mm (in)	Used belt deflection	
		Limit	Deflection after adjustment
Alternator		11 (0.43)	7 - 8 (0.28 - 0.31)
Air conditioner compressor		12 (0.47)	7.5 - 8.5 (0.295 - 0.335)
Power steering pump		13 (0.51)	7.5 - 8.5 (0.295 - 0.335)
Applied pressed force	N (kg, lb)	98 (10, 22)	
Tightening torque		N-m	kg-m
Spark plug		20 - 29	2.0 - 3.0
Oil pan drain plug		29 - 39	3.0 - 4.0

CLUTCH PEDAL

	Unit: mm (in)
Pedal height	186 - 196 (7.32 - 7.72)
Pedal free play	1 - 3 (0.04 - 0.12)

FRONT WHEEL ALIGNMENT (Unladen*)

Camber	degree	-1°30' to 0°
Caster	degree	6°00' - 7°30'
Toe-in		
A-B	mm (in)	1.5 - 3.5 (0.059 - 0.138)
Total angle 2θ	degree	8' - 20'
Full turns		
Inner wheel		39° - 43°
Outer wheel		33°

* Fuel, radiator coolant and engine oil full.
Spare tire, jack, hand tools and mats in designated positions.

REAR WHEEL ALIGNMENT (Unladen*)

Camber	degree	-1°40' to -0°40'
Toe-in		
A-B	mm (in)	0 - 5.0 (0 - 0.197)
Total angle 2θ	degree	0' - 28'

* Fuel, radiator coolant and engine oil full.
Spare tire, jack, hand tools and mats in designated positions.

BRAKE

		Unit: mm (in)
Disc brake		
Pad repair limit	Front side	2.0 (0.079)
	Rear side	1.5 (0.059)
Rotor thickness	Front	CL22VF: 18.0 (0.708)
repair limit	Rear	8.0 (0.315)
Pedal free height		
M/T model		181 - 191 (7.13 - 7.52)
A/T model		191 - 201 (7.52 - 7.91)
Pedal depressed height*1		100 (3.94) or more
Parking brake		
Number of notches*2		7 - 9

*1: Under force of 490 N (50 kg, 110 lb) with engine running

*2: At pulling force: 196 N (20 kg, 44 lb)

REFILL CAPACITIES

	Unit	Liter	US measure
Engine model		KA24DE	
Fuel tank		65	17-1/8 gal
Coolant	With reservoir tank	6.7	7-1/8 qt
Engine	With oil filter	3.5	3-3/4 qt
	Without oil filter	3.2	3-3/8 qt
Transmission	M/T	2.5	5-1/4 pt
	A/T	8.3	8-3/4 qt
Differential carrier	R200	1.3±0.1	2-3/4±1/4 pt
	R200V	1.3±0.1	2-3/4±1/4 pt
Power steering system		0.9	1 qt
Air conditioning system	Lubricant	0.25	8.5 fl oz
	Refrigerant	0.6 - 0.7 kg	1.3 - 1.5 lb