

NISSAN 300ZX

MODEL Z32 SERIES

QUICK REFERENCE INDEX

GENERAL INFORMATION _____	GI
MAINTENANCE _____	MA
ENGINE MECHANICAL _____	EM
ENGINE LUBRICATION & COOLING SYSTEMS —	LC
ENGINE FUEL & EMISSION CONTROL SYSTEM —	EF & EC
ACCELERATOR CONTROL, FUEL & _____ EXHAUST SYSTEMS	FE
CLUTCH _____	CL
MANUAL TRANSMISSION _____	MT
AUTOMATIC TRANSMISSION _____	AT
PROPELLER SHAFT & DIFFERENTIAL CARRIER —	PD
FRONT AXLE & FRONT SUSPENSION _____	FA
REAR AXLE & REAR SUSPENSION _____	RA
BRAKE SYSTEM _____	BR
STEERING SYSTEM _____	ST
BODY _____	BF
HEATER & AIR CONDITIONER _____	HA
ELECTRICAL SYSTEM _____	EL
ALPHABETICAL INDEX _____	IDX

FOREWORD

This manual contains maintenance and repair procedures for the 1994 Nissan 300ZX.

In order to assure your safety and the efficient functioning of the vehicle, this manual should be read thoroughly. It is especially important that the PRECAUTIONS in the GI section be completely understood before starting any repair task.

All information in this manual is based on the latest product information at the time of publication. The right is reserved to make changes in specifications and methods at any time without notice.

IMPORTANT SAFETY NOTICE

The proper performance of service is essential for both the safety of the technician and the efficient functioning of the vehicle.

The service methods in this Service Manual are described in such a manner that the service may be performed safely and accurately.

Service varies with the procedures used, the skills of the technician and the tools and parts available. Accordingly, anyone using service procedures, tools or parts which are not specifically recommended by NISSAN must first completely satisfy himself that neither his safety nor the vehicle's safety will be jeopardized by the service method selected.



NISSAN MOTOR CO., LTD.

Overseas Service Department

Tokyo, Japan

INCH TO METRIC CONVERSION TABLE

(Rounded-off for automotive use)

inches	mm	inches	mm
.100	2.54	.610	15.49
.110	2.79	.620	15.75
.120	3.05	.630	16.00
.130	3.30	.640	16.26
.140	3.56	.650	16.51
.150	3.81	.660	16.76
.160	4.06	.670	17.02
.170	4.32	.680	17.27
.180	4.57	.690	17.53
.190	4.83	.700	17.78
.200	5.08	.710	18.03
.210	5.33	.720	18.29
.220	5.59	.730	18.54
.230	5.84	.740	18.80
.240	6.10	.750	19.05
.250	6.35	.760	19.30
.260	6.60	.770	19.56
.270	6.86	.780	19.81
.280	7.11	.790	20.07
.290	7.37	.800	20.32
.300	7.62	.810	20.57
.310	7.87	.820	20.83
.320	8.13	.830	21.08
.330	8.38	.840	21.34
.340	8.64	.850	21.59
.350	8.89	.860	21.84
.360	9.14	.870	22.10
.370	9.40	.880	22.35
.380	9.65	.890	22.61
.390	9.91	.900	22.86
.400	10.16	.910	23.11
.410	10.41	.920	23.37
.420	10.67	.930	23.62
.430	10.92	.940	23.88
.440	11.18	.950	24.11
.450	11.43	.960	24.38
.460	11.68	.970	24.64
.470	11.94	.980	24.89
.480	12.19	.990	25.15
.490	12.45	1.000	25.40
.500	12.70	2.000	50.80
.510	12.95	3.000	76.20
.520	13.21	4.000	101.60
.530	13.46	5.000	127.00
.540	13.72	6.000	152.40
.550	13.97	7.000	177.80
.560	14.22	8.000	203.20
.570	14.48	9.000	228.60
.580	14.73	10.000	254.00
.590	14.99	20.000	508.00
.600	15.24		

METRIC TO INCH CONVERSION TABLE

(Rounded-off for automotive use)

mm	inches	mm	inches
1	.0394	51	2.008
2	.079	52	2.047
3	.118	53	2.087
4	.157	54	2.126
5	.197	55	2.165
6	.236	56	2.205
7	.276	57	2.244
8	.315	58	2.283
9	.354	59	2.323
10	.394	60	2.362
11	.433	61	2.402
12	.472	62	2.441
13	.512	63	2.480
14	.551	64	2.520
15	.591	65	2.559
16	.630	66	2.598
17	.669	67	2.638
18	.709	68	2.677
19	.748	69	2.717
20	.787	70	2.756
21	.827	71	2.795
22	.866	72	2.835
23	.906	73	2.874
24	.945	74	2.913
25	.984	75	2.953
26	1.024	76	2.992
27	1.063	77	3.031
28	1.102	78	3.071
29	1.142	79	3.110
30	1.181	80	3.150
31	1.220	81	3.189
32	1.260	82	3.228
33	1.299	83	3.268
34	1.339	84	3.307
35	1.378	85	3.346
36	1.417	86	3.386
37	1.457	87	3.425
38	1.496	88	3.465
39	1.535	89	3.504
40	1.575	90	3.543
41	1.614	91	3.583
42	1.654	92	3.622
43	1.693	93	3.661
44	1.732	94	3.701
45	1.772	95	3.740
46	1.811	96	3.780
47	1.850	97	3.819
48	1.890	98	3.858
49	1.929	99	3.898
50	1.969	100	3.937

QUICK REFERENCE CHART : 300ZX 1994

ENGINE TUNE-UP DATA

Engine model		VG30DE	VG30DETT
Firing order		1-2-3-4-5-6	
Idle speed rpm		700±50	
M/T (in "N" position)	A/T	770±50	750±50
	(in "N" position)		
Ignition timing (degree BTDC at idle speed)		15±2	
CO% at idle		Idle mixture screw is preset and sealed at factory.	
Drive belt deflection (Cold) mm (in)	Used belt deflection Limit	Deflection of new belt	
Alternator	11.5 (0.453)	7 - 8 (0.28 - 0.31)	6.5 - 7.5 (0.256 - 0.295)
Air conditioner compressor	12.5 (0.492)	8 - 9 (0.31 - 0.35)	7 - 8 (0.28 - 0.31)
Power steering oil pump	Non-turbocharger	19 (0.75)	12 - 13.5 (0.472 - 0.531)
	Turbocharger	16 (0.63)	10 - 11 (0.39 - 0.43)
Applied pressed force N (kg, lb)		98 (10, 22)	
Radiator cap relief pressure kPa (kg/cm ² , psi)		78 - 98 (0.8 - 1.0, 11 - 14)	
Cooling system leakage testing pressure kPa (kg/cm ² , psi)		157 (1.6, 23)	
Compression pressure kPa (kg/cm ² , psi)/rpm	Standard	1,285 (13.1, 186)/900	1,177 (12.0, 171)
	Minimum	981 (10.0, 142)/300	883 (9.0, 128)
Spark plug	Type (Standard)	PFR6B-11	PFR5B-11B
	Gap mm (in)	1.0 - 1.1 (0.039 - 0.043)	

CLUTCH PEDAL

Engine		VG30DE	VG30DETT
Pedal height		197 - 207 (7.76 - 8.15)	183 - 193 (7.20 - 7.60)
Pedal free play		1 - 3 (0.04 - 0.12)	

FRONT WHEEL ALIGNMENT (Unladen*)

Camber	degree	-1°35' to -0°05'
Caster	degree	8°55' - 10°25'
Toe-in	A - B mm (in)	0 - 2 (0 - 0.08)
Total angle 2θ	degree	0° - 11°
Wheel turning angle (Full turn)	degree	32°30' - 36°30'
Inside		
Outside		26°30' - 30°30'

*: Fuel, radiator coolant and engine oil full.
Spare tire, jack, hand tools and mats in designated positions.

REAR WHEEL ALIGNMENT (Unladen*)

Camber	degree	-1°36' to -0°36'
Toe-in	A - B mm (in)	0.4 - 4.4 (0.016 - 0.173)
Total angle 2θ	degree	2° - 24°

*: Fuel, radiator coolant and engine oil full.
Spare tire, jack, hand tools and mats in designated positions.

BRAKE

Unit: mm (in)

Front brake		
Pad wear limit		2.0 (0.079)
Rotor repair limit		28.0 (1.102)
Rear brake		
Pad wear limit		2.0 (0.079)
Rotor repair limit		16.0 (0.630)
Pedal free height	M/T model	186 - 196 (7.32 - 7.72)
	A/T model	195 - 206 (7.68 - 8.07)
Pedal depressed height*1	M/T model	100 (3.94) or more
	A/T model	105 (4.13) or more
Parking brake		
Number of notches*2		6 - 7

*1 Under force of 490 N (50 kg, 110 lb) with engine running

*2 At outline force: 196 N (20 kg, 44 lb)

REFILL CAPACITIES

Unit		Liter	US measure
Fuel tank		72	19 gal
Coolant		9	9-1/2 qt
Engine	With oil filter	3.4	3-5/8 qt
	Without oil filter	3.0	3-1/8 qt
Transmission	M/T	2.8	5-7/8 pt
	A/T	Non-turbocharger	8.3
		Turbocharger	8.2
Differential carrier	Non-turbocharger	1.3	2-3/4 pt
	Turbocharger	1.8	3-7/8 pt
Power steering system		1.3	1-3/8 qt
Air conditioning system	Compressor oil	0.20	6.8 fl oz
	Refrigerant	0.60 - 0.70 kg	1.32 - 1.54 lb



NISSAN MOTOR CO., LTD.

Overseas Service Department

Tokyo, Japan

Edition: August 1993
Printing: August 1993 (11)
Publication No. SM4E-0Z32U0
Printed in Japan