

SCHEDULED MAINTENANCE INTERVALS

SUBARU—IMPREZA OUTBACK, SPORT, WRX, LEGACY & OUTBACK

TO BE SERVICED	OF SERVIC	VEHICLE MILEAGE INTERVAL (x1000)												
		7.5	15	22.5	30	37.5	45	52.5	60	67.5	75	82.5	90	97.5
Engine oil & filter	R	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Brake lines	S/I		✓		✓		✓		✓		✓		✓	
Clutch & hill holder system	S/I		✓		✓		✓		✓		✓		✓	
Disc brake pads & discs, front & rear axle boots & axle shaft joint portions	S/I		✓		✓		✓		✓		✓		✓	
Parking brake	S/I		✓		✓		✓		✓		✓		✓	
Steering & suspension	S/I		✓		✓		✓		✓		✓		✓	
Air filter element	R				✓				✓				✓	
Engine coolant	R				✓				✓				✓	
Fuel filter	R				✓				✓				✓	
Spark plugs	R								✓					
Automatic transmission fluid & filter	S/I				✓				✓				✓	
Brake fluid	S/I				✓				✓				✓	
Brake linings & drums	S/I				✓				✓				✓	
Camshaft drive belt A	S/I				✓				✓				✓	
Coolant level, hoses & clamps	S/I				✓				✓				✓	
Drive belts	S/I				✓				✓				✓	
Fuel system, hoses & connections	S/I				✓				✓				✓	
Transmission and/or differential gear fluid	S/I				✓								✓	
Front & rear wheel bearing repack	S/I								✓					

R: Replace S/I: Service or Inspect

A Non-California vehicles: replace every 60,000 miles.

FREQUENT OPERATION MAINTENANCE (SEVERE SERVICE)

If a vehicle is operated under any of the following conditions it is considered severe service:

- Extremely dusty areas.
- 50% or more of the vehicle operation is in 32°C (90°F) or higher temperatures, or constant operation in temperatures below 0°C (32°F).
- Prolonged idling (vehicle operation in stop and go traffic).
- Frequent short running periods (engine does not warm to normal operating temperatures).
- Police, taxi, delivery usage or trailer towing usage.

Oil & oil filter change: change every 3750 miles.

Clutch & hill holder system: service or inspect every 7500 miles.

Disc brake pads & discs, front & rear axle boots & axle shaft joint portions: service or inspect every 7500 miles.

Steering & suspension: service or inspect every 7500 miles.

Air filter element: service or inspect every 15,000 miles.

Automatic transmission fluid: service or inspect every 15,000 miles.

Brake linings & drums: service or inspect every 15,000 miles.

Coolant level, hoses & clamps: service or inspect every 15,000 miles.

Drive belts: service or inspect every 15,000 miles.

Transmission/differential gear oil (except SVX): service or inspect every 15,000 miles.

Front & rear wheel bearing repack: service or inspect every 30,000 miles.

BRAKE SPECIFICATIONS

All measurements in inches unless noted

Year	Model		Brake Disc			Brake Drum Diameter			Minimum Lining Thickness		Brake Caliper	
			Original Thickness	Minimum Thickness	Maximum Runout	Original Inside Diameter	Max. Wear Limit	Maximum Machine Diameter	Front	Rear	Bracket Bolts (ft. lbs.)	Mounting Bolts (ft. lbs.)
1999	Impreza	F	0.940	0.870	0.003	—	—	—	0.059	—	51-65	23-30
		R	0.390	0.335	0.004	9.000 A	9.079 B	NA	—	0.059	—	23-30
	Legacy	F	0.940	0.870	0.003	—	—	—	0.059	—	51-65	23-30
		R	0.390	0.335	0.004	9.000 A	9.079 B	NA	—	0.059	—	23-30
2000	Impreza	F	0.940	0.870	0.003	—	—	—	0.059	—	51-65	23-30
		R	0.390	0.335	0.004	9.000 A	9.079 B	NA	—	0.059	—	23-30
	Legacy	F	0.940	0.870	0.003	—	—	—	0.059	—	51-65	23-30
		R	0.390	0.335	0.004	9.000 A	9.079 B	NA	—	0.059	—	23-30
2001	Impreza	F	0.940	0.870	0.003	—	—	—	0.059	—	51-65	23-30
		R	0.390	0.335	0.004	9.000 A	9.079 B	NA	—	0.059	—	23-30
	Legacy	F	0.940	0.870	0.003	—	—	—	0.059	—	51-65	23-30
		R	0.390	0.335	0.004	9.000 A	9.079 B	NA	—	0.059	—	23-30
2002-03	Impreza	F	0.940	0.870	0.003	—	—	—	0.059	—	51-65	23-30
		R	0.390	0.335	0.004	9.000 A	9.079 B	NA	—	0.059	—	23-30
	WRX	F	0.940	0.870	0.003	—	—	—	0.295	—	59	19.5
		R	0.390	0.335	0.004	9.000 A	9.080 B	9.000 A	—	0.059	59	27.5
	Legacy	F	0.940	0.870	0.003	—	—	—	0.059	—	51-65	23-30
		R	0.390	0.335	0.004	9.000 A	9.079 B	NA	—	0.059	—	23-30

NA: Not Available

A Parking brake drum on vehicles with rear disc brakes: 6.69 in.

B Specification is for the parking brake drum.

CAPACITIES

Year	Model	Engine Displacement Liters (cc)	Engine ID/VIN	Engine Oil with Filter (qts.)	Transmission (pts.)		Transfer Case (pts.)	Drive Axle		Fuel Tank (gal.)	Cooling System (qts.)
					5-Spd	Auto.		Front A (pts.)	Rear (pts.)		
1999	Impreza B	2.2 (2212)	4	4.4	7.4	16.8	–	2.6	1.6	13.2	6.1
	Impreza RS	2.5 (2457)	6	4.7	7.4	20.0	–	2.6	1.6	13.2	6.3
	Legacy	2.2 (2212)	4	4.4	7.4	15.0	–	2.6	1.6	15.9	6.1
	Legacy C	2.5 (2457)	6	4.7	7.4	20.0	–	2.6	1.6	15.9	6.3
2000	Impreza B	2.2 (2212)	4	4.4	7.4	16.8	–	2.6	1.6	13.2	6.6
	Impreza RS	2.5 (2457)	6	4.7	7.4	20.0	–	2.6	1.6	13.2	6.6
	Legacy C	2.5 (2457)	6	4.7	7.4	20.0	–	2.6	1.6	16.9	6.6
2001	Impreza B	2.2 (2212)	4	4.4	7.4	16.8	–	2.6	1.6	13.2	6.6
	Impreza RS	2.5 (2457)	6	4.7	7.4	20.0	–	2.6	1.6	13.2	6.6
	Legacy C	2.5 (2457)	6	4.7	7.4	20.0	–	2.6	1.6	16.9	6.6
2002-03	Impreza B	2.2 (2212)	4	4.4	7.4	16.8	–	2.6	1.6	13.2	6.6
	Impreza RS	2.5 (2457)	6	4.7	7.4	20.0	–	2.6	1.6	13.2	6.6
	WRX	2.0 (1994)	2	4.8	7.4	19.6	–	2.6	1.6	15.9	8.0
	Legacy C	2.5 (2457)	6	4.7	7.4	20.0	–	2.6	1.6	16.9	6.6

Note: All capacities are approximate. Add fluid gradually and check to be sure a proper fluid level is obtained.

A A/T differential only

B Includes Outback

C Includes Outback and Sport Utility Sedan

CRANKSHAFT AND CONNECTING ROD SPECIFICATIONS

All measurements are given in inches.

Year	Engine Displacement Liters (cc)	Engine ID/VIN	Crankshaft				Connecting Rod		
			Main Brg. Journal Dia.	Main Brg. Oil Clearance	Shaft End-play	Thrust on No.	Journal Diameter	Oil Clearance	Side Clearance
1999	2.2 (2212)	4	2.3619- 2.3625	A	0.0012- 0.0098	3	2.0466- 2.0472	0.0006- 0.0020	0.0028- 0.0160
	2.5 (2457)	6	2.3619- 2.3625	B	0.0012- 0.0098	3	1.8891- 1.8898	0.0004- 0.0020	0.0028- 0.0160
2000	2.2 (2212)	4	2.3619- 2.3625	A	0.0012- 0.0098	3	2.0466- 2.0472	0.0006- 0.0020	0.0028- 0.0160
	2.5 (2457)	6	2.3619- 2.3625	B	0.0012- 0.0098	3	1.8891- 1.8898	0.0004- 0.0020	0.0028- 0.0160
2001	2.2 (2212)	4	2.3619- 2.3625	A	0.0012- 0.0098	3	2.0466- 2.0472	0.0006- 0.0020	0.0028- 0.0160
	2.5 (2457)	6	2.3619- 2.3625	B	0.0012- 0.0098	3	1.8891- 1.8898	0.0004- 0.0020	0.0028- 0.0160
2002-03	2.0 (1994)	2	2.3619- 2.3625	0.0004 0.0012	0.0012- 0.0048	3	1.8891- 1.8898	0.0008- 0.0018	0.0028- 0.0130
			2.3619- 2.3625	A	0.0012- 0.0098		3	2.0466- 2.0472	0.0006- 0.0020
	2.5 (2457)	6	2.3619- 2.3625	B	0.0012- 0.0098	3	1.8891- 1.8898	0.0004- 0.0020	0.0028- 0.0160
			2.3619- 2.3625		0.0012- 0.0098		3	1.8891- 1.8898	0.0004- 0.0020

A Journals 1 and 5: 0.0001 - 0.0016 in.
 Journals 2 and 4: 0.0004 - 0.0014 in.
 Journal 3: 0.0004 - 0.0014 in.

B Journals 1 and 5: 0.0001 - 0.0016 in.
 Journals 2 and 4: 0.0004 - 0.0018 in.
 Journal 3: 0.0004 - 0.0016 in.

ENGINE AND VEHICLE IDENTIFICATION CHART

Engine Code							Model Year	
Code A	Liters (cc)	Cu. In.	Cyl.	Fuel Sys	Type	Eng. Mfg.	Code B	Year
4	2.2 (2212)	135	4	MFI	SOHC	Subaru	X	1999
6	2.5 (2457)	150	4	MFI	DOHC	Subaru	Y	2000
6	2.5 (2457)	150	4	MFI	SOHC	Subaru	1	2001
2	2.0 (1994)	121	4	MFI	DOHC	Subaru	2	2002
							3	2003

MFI: Multiport Fuel Injection

SOHC: Single Overhead Camshaft

DOHC: Double Overhead Camshaft

A 6th digit of the VIN

B 10th digit of the VIN

ENGINE TUNE-UP SPECIFICATIONS

Year	Model	Engine Displacement Liters (cc)	Engine ID/VIN	Spark Plug Gap (in.)	Ignition Timing (deg.) A		Fuel Pump (psi)	Idle Speed (rpm)		Valve Clearance B	
					MT	AT		MT	AT	In.	Ex.
1999	Impreza/ Outback	2.2 (2212)	4	0.039- 0.043	6-22	12-28	34-38	600- 800	600- 800	0.0071- 0.0087	0.0090- 0.0106
	Impreza RS	2.5 (2457)	6	0.039- 0.043	7-23	7-23	34-38	600- 800	600- 800	0.0071- 0.0087	0.0090- 0.0106
	Legacy	2.2 (2212)	4	0.039- 0.043	6-22	12-28	34-38	600- 800	600- 800	0.0071- 0.0087	0.0090- 0.0106
	Legacy/ Outback/SUS C	2.5 (2457)	6	0.039- 0.043	7-23	7-23	34-38	600- 800	600- 800	0.0071- 0.0087	0.0090- 0.0106
2000	Impreza/ Outback	2.2 (2212)	4	0.039- 0.043	6-22	12-28	34-38	600- 800	600- 800	0.0071- 0.0087	0.0090- 0.0106
	Impreza RS	2.5 (2457)	6	0.039- 0.043	7-23	7-23	34-38	600- 800	600- 800	0.0071- 0.0087	0.0090- 0.0106
	Legacy/ Outback/SUS C	2.5 (2457)	6	0.039- 0.043	7-23	7-23	34-38	600- 800	600- 800	0.0071- 0.0087	0.0090- 0.0106
2001	Impreza/ Outback	2.2 (2212)	4	0.039- 0.043	6-22	12-28	34-38	600- 800	600- 800	0.0071- 0.0087	0.0090- 0.0106
	Impreza RS	2.5 (2457)	6	0.039- 0.043	7-23	7-23	34-38	600- 800	600- 800	0.0071- 0.0087	0.0090- 0.0106
	Legacy/ Outback/SUS C	2.5 (2457)	6	0.039- 0.043	7-23	7-23	34-38	600- 800	600- 800	0.0071- 0.0087	0.0090- 0.0106
2002-03	Impreza/ Outback	2.2 (2212)	4	0.039- 0.043	6-22	12-28	34-38	600- 800	600- 800	0.0071- 0.0087	0.0090- 0.0106
	Impreza RS	2.5 (2457)	6	0.039- 0.043	7-23	7-23	34-38	600- 800	600- 800	0.0071- 0.0087	0.0090- 0.0106
	WRX	2.0 (1994)	2	0.028- 0.031	2-22	2-22	33-38	650- 850	650- 850	0.0071- 0.0087	0.0090- 0.0106
	Legacy/ Outback/SUS C	2.5 (2457)	6	0.039- 0.043	7-23	7-23	34-38	600- 800	600- 800	0.0071- 0.0087	0.0090- 0.0106

Note: The Vehicle Emission Control Information label often reflects specification changes made during production. The table figures must be used if they differ from those in this chart.

A Before Top Dead Center

B Measured with engine cold

C Sport Utility Sedan

GENERAL ENGINE SPECIFICATIONS

Year		Engine Displacement Liters (cc)	Engine ID/VIN	Fuel System Type	Net Horsepower @ rpm	Net Torque @ rpm (ft. lbs.)	Bore x Stroke (in.)	Compression Ratio	Oil Pressure @ rpm
1999	Impreza A	2.2 (2212)	4	MFI	137@5400	145@4000	3.82x2.95	9.7:1	14@600
	Impreza RS	2.5 (2457)	6	MFI	165@5600	162@4000	3.92x3.11	9.7:1	14@600
	Legacy	2.2 (2212)	4	MFI	137@5400	145@4000	3.82x2.95	9.7:1	14@600
	Legacy B	2.5 (2457)	6	MFI	165@5600	162@4000	3.92x3.11	9.7:1	14@600
2000	Impreza A	2.2 (2212)	4	MFI	142@5600	149@3600	3.82x2.95	10.0:1	14@600
	Impreza RS	2.5 (2457)	6	MFI	165@5600	166@4000	3.92x3.11	10.0:1	14@600
	Legacy B	2.5 (2457)	6	MFI	165@5600	166@4000	3.92x3.11	10.0:1	14@600
2001	Impreza A	2.2 (2212)	4	MFI	142@5600	149@3600	3.82x2.95	10.0:1	14@600
	Impreza RS	2.5 (2457)	6	MFI	165@5600	166@4000	3.92x3.11	10.0:1	14@600
	Legacy B	2.5 (2457)	6	MFI	165@5600	166@4000	3.92x3.11	10.0:1	14@600
2002-03	Impreza A	2.2 (2212)	4	MFI	142@5600	149@3600	3.82x2.95	10.0:1	14@600
	Impreza RS	2.5 (2457)	6	MFI	165@5600	166@4000	3.92x3.11	10.0:1	14@600
	WRX	2.0 (1994)	2	MFI	227@6000	217@4000	3.62x2.95	8.0:1	14@800
	Legacy B	2.5 (2457)	6	MFI	165@5600	166@4000	3.92x3.11	10.0:1	14@600

MFI: Multi-port Fuel Injection

Note: All capacities are approximate. Add fluid gradually and check to be sure a proper fluid level is obtained.

A Includes Outback

B Includes Outback and Sport Utility Sedan

PISTON AND RING SPECIFICATIONS

All measurements are given in inches.

Year	Engine Displacement Liters (cc)	Engine ID/VIN	Piston Clearance	Ring Gap			Ring Side Clearance		
				Top Compression	Bottom Compression	Oil Control	Top Compression	Bottom Compressor	Oil Control
1999	2.2 (2212)	4	0.0004- 0.0020	0.0079- 0.0390	0.0079- 0.0390	0.0079- 0.0590	0.0016- 0.0590	0.0012- 0.0590	NA
	2.5 (2457)	6	0.0004- 0.0020	0.0079- 0.0390	0.0146- 0.0390	0.0079- 0.0590	0.0016- 0.0059	0.0012- 0.0059	NA
2000	2.2 (2212)	4	0.0004- 0.0020	0.0079- 0.0390	0.0079- 0.0390	0.0079- 0.0590	0.0016- 0.0590	0.0012- 0.0590	NA
	2.5 (2457)	6	0.0004- 0.0020	0.0079- 0.0390	0.0146- 0.0390	0.0079- 0.0590	0.0016- 0.0059	0.0012- 0.0059	NA
2001	2.2 (2212)	4	0.0004- 0.0020	0.0079- 0.0390	0.0079- 0.0390	0.0079- 0.0590	0.0016- 0.0590	0.0012- 0.0590	NA
	2.5 (2457)	6	0.0004- 0.0020	0.0079- 0.0390	0.0146- 0.0390	0.0079- 0.0590	0.0016- 0.0059	0.0012- 0.0059	NA
2002-03	2.0 (1994)	2	0.0004- 0.0012	0.0079- 0.0138	0.0138- 0.0197	0.0079- 0.0276	0.0016- 0.0031	0.0012- 0.0028	NA
			0.0004- 0.0020	0.0079- 0.0390	0.0079- 0.0390	0.0079- 0.0590	0.0016- 0.0590	0.0012- 0.0590	NA
	2.5 (2457)	6	0.0004- 0.0020	0.0079- 0.0390	0.0146- 0.0390	0.0079- 0.0590	0.0016- 0.0059	0.0012- 0.0059	NA

NA: Not Available

TIRE, WHEEL AND BALL JOINT SPECIFICATIONS

Year	Model	OEM Tires		Tire Pressures (psi)		Wheel Size	Ball Joint Inspection
		Standard	Optional	Front	Rear		
1999	Impreza	P195/60R15	None	32	29	6-JJ	0.012 in.
	Impreza RS	P205/55R16	None	32	29	7-JJ	0.012 in.
	Impreza Outback	P205/60R15	None	32	29	7-JJ	0.012 in.
	Legacy	P185/70R14	P195/60R15 P205/55R16 P205/70R15	32	30	6.5-JJ	0.012 in.
2000	Impreza	P195/60R15	None	32	29	6-JJ	0.012 in.
	Impreza RS	P205/55R16	None	32	29	7-JJ	0.012 in.
	Impreza Outback	P205/60R15	None	32	29	7-JJ	0.012 in.
	Legacy	P185/70R14	P195/60R15 P205/55R16 P205/70R15	32	30	6.5-JJ	0.012 in.
2001	Impreza	P195/60R15	None	32	29	6-JJ	0.012 in.
	Impreza RS	P205/55R16	None	32	29	7-JJ	0.012 in.
	Impreza Outback	P205/60R15	None	32	29	7-JJ	0.012 in.
	Legacy	P185/70R14	P195/60R15 P205/55R16 P205/70R15	32	30	6.5-JJ	0.012 in.
2002-03	Impreza	P195/60R15	None	32	29	6-JJ	0.012 in.
	Impreza RS	P205/55R16	None	32	29	7-JJ	0.012 in.
	Impreza Outback	P205/60R15	None	32	29	7-JJ	0.012 in.
	Impreza WRX	P195/60R15	P205/55R16 P215/45R17	32	29	6-JJ 7-JJ	0.012 in.
	Legacy	P185/70R14	P195/60R15 P205/55R16 P205/70R15	32	30	6.5-JJ	0.012 in.

OEM: Original Equipment Manufacturer

PSI: Pounds Per Square Inch

TORQUE SPECIFICATIONS

All readings in ft. lbs.

Year	Engine	Engine ID/VIN	Cylinder	Main A	Rod	Crankshaft	Flywheel Bolts	Manifold		Spark Plugs	Lug Nut
	Displacement Liters (cc)		Head Bolts	Bearing Bolts	Bearing Bolts	Damper Bolts		Intake	Exhaust		
1999	2.2 (2212)	4	B	C	31 - 44	87 - 101	51 - 55	17 - 20	19 - 26	13 - 17	58 - 72
	2.5 (2457)	6	B	C	31 - 44	123 - 137	51 - 55	17 - 20	19 - 26	13 - 17	58 - 72
2000	2.2 (2212)	4	B	C	31 - 44	87 - 101	51 - 55	17 - 20	19 - 26	13 - 17	58 - 72
	2.5 (2457)	6	B	C	31 - 44	123 - 137	51 - 55	17 - 20	19 - 26	13 - 17	58 - 72
2001	2.2 (2212)	4	B	C	31 - 44	87 - 101	51 - 55	17 - 20	19 - 26	13 - 17	58 - 72
	2.5 (2457)	6	B	C	31 - 44	123 - 137	51 - 55	17 - 20	19 - 26	13 - 17	58 - 72
2002-03	2.0 (1994)	2	B	C	31 - 44	94	51 - 55	18	26	13 - 17	58 - 72
	2.2 (2212)	4	B	C	31 - 44	87 - 101	51 - 55	17 - 20	19 - 26	13 - 17	58 - 72
	2.5 (2457)	6	B	C	31 - 44	123 - 137	51 - 55	17 - 20	19 - 26	13 - 17	58 - 72

A Engine block connecting bolts

B Step 1: Tighten all bolts to 22 ft. lbs.

Step 2: Tighten all bolts to 51 ft. lbs.

Step 3: Loosen all bolts 180 degrees.

Step 4: Repeat Step 3.

Step 5: Tighten bolts 1 and 2 to 25 ft. lbs.

Step 6: Tighten bolts 3, 4, 5 and 6 to 11 ft. lbs.

Step 7: Tighten all bolts 80 to 90 degrees.

Step 8: Repeat Step 7. Do not exceed 180 degrees total tightening.

C Split engine case connecting bolts:

Short bolts: 17-20 ft. lbs.

Long bolts: 33-37 ft. lbs.

Smaller short bolts (if used) 5 ft. lbs.

VALVE SPECIFICATIONS

Year	Engine Displacement Liters (cc)	Engine ID/VIN	Seat Angle (deg.)	Face Angle (deg.)	Spring Test Pressure (lbs. @ in.)	Spring Installed Height (in.)	Stem-to-Guide Clearance (in.)		Stem Diameter (in.)	
							Intake	Exhaust	Intake	Exhaust
							1999	2.2 (2212)	4	45
	2.5 (2457)	6	45	45	102 - 118@ 1.315	B	0.0014- 0.0059	0.0016- 0.0059	0.2343- 0.2348	0.2341- 0.2346
2000	2.2 (2212)	4	45	45	91 - 103@ 1.110	A	0.0014- 0.0059	0.0016- 0.0059	0.2344- 0.2350	0.2341- 0.2346
	2.5 (2457)	6	45	45	102 - 118@ 1.315	B	0.0014- 0.0059	0.0016- 0.0059	0.2343- 0.2348	0.2341- 0.2346
2001	2.2 (2212)	4	45	45	91 - 103@ 1.110	A	0.0014- 0.0059	0.0016- 0.0059	0.2344- 0.2350	0.2341- 0.2346
	2.5 (2457)	6	45	45	102 - 118@ 1.315	B	0.0014- 0.0059	0.0016- 0.0059	0.2343- 0.2348	0.2341- 0.2346
2002-03	2.0 (2212)	2	45	45	91 - 103@ 1.110	C	0.0014- 0.0059	0.0016- 0.0059	0.2343- 0.2348	0.2341- 0.2346
	2.2 (2212)	4	45	45	91 - 103@ 1.110	A	0.0014- 0.0059	0.0016- 0.0059	0.2344- 0.2350	0.2341- 0.2346
	2.5 (2457)	6	45	45	102 - 118@ 1.315	B	0.0014- 0.0059	0.0016- 0.0059	0.2343- 0.2348	0.2341- 0.2346

A Free length: 1.7342 in.

B Free length: 1.8913 in.

C Free length: 1.7587 in.

WHEEL ALIGNMENT

Year	Model		Caster		Camber		Toe-in (in.)	Steering Axis Inclination (Deg.)
			Range (+/-Deg.)	Preferred Setting (Deg.)	Range (+/-Deg.)	Preferred Setting (Deg.)		
1999	Impreza 2.2L	F	1.00	+3.00	0.50	0	0+/-0.12	—
		R	—	—	0.75	-0.92	0+/-0.12	—
	Impreza 2.5L	F	1.00	+3.05	0.50	-0.42	0+/-0.12	—
		R	—	—	0.75	-1.17	0+/-0.12	—
	Legacy Sedan	F	0.75	+3.05	0.50	-0.05	0+/-0.12	—
		R	—	—	0.75	-0.50	0+/-0.12	—
	Legacy Wagon	F	0.75	+2.05	0.50	-0.05	0+/-0.12	—
		R	—	—	0.75	-0.20	0+/-0.12	—
Outback	F	0.75	+2.40	0.50	+0.33	0+/-0.12	—	
	R	—	—	0.75	-0.17	0+/-0.12	—	
2000	Impreza 2.2L	F	1.00	+3.00	0.50	0	0+/-0.12	—
		R	—	—	0.75	-0.92	0+/-0.12	—
	Impreza 2.5L	F	1.00	+3.05	0.50	-0.42	0+/-0.12	—
		R	—	—	0.75	-1.17	0+/-0.12	—
	Legacy Sedan	F	0.75	+3.05	0.50	-0.05	0+/-0.12	—
		R	—	—	0.75	-0.50	0+/-0.12	—
	Legacy Wagon	F	0.75	+2.05	0.50	-0.05	0+/-0.12	—
		R	—	—	0.75	-0.20	0+/-0.12	—
Outback	F	0.75	+2.40	0.50	+0.33	0+/-0.12	—	
	R	—	—	0.75	-0.17	0+/-0.12	—	
2001	Impreza 2.2L	F	1.00	+3.00	0.50	0	0+/-0.12	—
		R	—	—	0.75	-0.92	0+/-0.12	—
	Impreza 2.5L	F	1.00	+3.05	0.50	-0.42	0+/-0.12	—
		R	—	—	0.75	-1.17	0+/-0.12	—
	Legacy Sedan	F	0.75	+3.05	0.50	-0.05	0+/-0.12	—
		R	—	—	0.75	-0.50	0+/-0.12	—
	Legacy Wagon	F	0.75	+2.05	0.50	-0.05	0+/-0.12	—
		R	—	—	0.75	-0.20	0+/-0.12	—
Outback	F	0.75	+2.40	0.50	+0.33	0+/-0.12	—	
	R	—	—	0.75	-0.17	0+/-0.12	—	
2002-03	Impreza 2.2L	F	1.00	+3.00	0.50	0	0+/-0.12	—
		R	—	—	0.75	-0.92	0+/-0.12	—
	Impreza 2.5L	F	1.00	+3.05	0.50	-0.42	0+/-0.12	—
		R	—	—	0.75	-1.17	0+/-0.12	—
	Legacy Sedan	F	0.75	+3.05	0.50	-0.05	0+/-0.12	—
		R	—	—	0.75	-0.50	0+/-0.12	—
	Legacy Wagon	F	0.75	+2.05	0.50	-0.05	0+/-0.12	—
		R	—	—	0.75	-0.20	0+/-0.12	—
Outback	F	0.75	+2.40	0.50	+0.33	0+/-0.12	—	
	R	—	—	0.75	-0.17	0+/-0.12	—	
WRX	F	0.75	+2.40	0.50	+0.33	0+/-0.12	—	
	R	—	—	0.75	-0.17	0+/-0.12	—	