

## 26. Engine Noise

### A: INSPECTION

Type of sound	Condition	Possible cause
Regular clicking sound	Sound increases as engine speed increases.	<ul style="list-style-type: none"><li>• Valve mechanism is defective.</li><li>• Incorrect valve clearance</li><li>• Worn camshaft</li><li>• Broken valve spring</li></ul>
Heavy and dull clank	Oil pressure is low.	<ul style="list-style-type: none"><li>• Worn crankshaft main bearing</li><li>• Worn connecting rod bearing (large end)</li></ul>
	Oil pressure is normal.	<ul style="list-style-type: none"><li>• Damaged engine mounting</li></ul>
High-pitched clank	Sound is noticeable when accelerating with an overload condition.	<ul style="list-style-type: none"><li>• Ignition timing advanced</li><li>• Accumulation of carbon inside combustion chamber</li><li>• Wrong heat range of spark plug</li><li>• Improper octane value gasoline</li></ul>
Clank when engine speed is between 1,000 and 2,000 rpm.	Noise is reduced when fuel injector connector of noisy cylinder is disconnected. *	<ul style="list-style-type: none"><li>• Worn crankshaft main bearing</li><li>• Worn connecting rod bearing (large end)</li></ul>
Knocking sound when engine is operating under idling speed and engine is warm	Noise is reduced when fuel injector connector of noisy cylinder is disconnected. *	<ul style="list-style-type: none"><li>• Worn cylinder liner and piston ring</li><li>• Broken or stuck piston ring</li><li>• Worn piston pin and hole at piston end of connecting rod</li></ul>
	Sound is not reduced if each fuel injector connector is disconnected in turn. *	<ul style="list-style-type: none"><li>• Unusually worn valve lifter</li><li>• Worn cam sprocket</li><li>• Worn camshaft journal bore in cylinder head</li></ul>
Squeaky sound	—	<ul style="list-style-type: none"><li>• Insufficient generator lubrication</li></ul>
Rubbing sound	—	<ul style="list-style-type: none"><li>• Poor contact of generator brush and rotor</li></ul>
Gear scream when starting engine	—	<ul style="list-style-type: none"><li>• Defective ignition starter switch</li><li>• Worn gear and starter pinion</li></ul>
Sound like polishing glass with a dry cloth	—	<ul style="list-style-type: none"><li>• Loose V-belt</li><li>• Defective water pump shaft</li></ul>
Hissing sound	—	<ul style="list-style-type: none"><li>• Insufficient compression</li><li>• Air leakage in air intake system, hose, connection or manifold</li></ul>
Timing belt noise	—	<ul style="list-style-type: none"><li>• Loose timing belt</li><li>• Timing belt contacting with adjacent part</li></ul>
Valve noise	—	<ul style="list-style-type: none"><li>• Incorrect valve clearance</li></ul>

\* When disconnecting the fuel injector connector, the malfunction indicator light illuminates and DTC is stored in ECM memory. Therefore, perform the Clear Memory Mode <Ref. to EN(H4DOTC)(diag)-54, OPERATION, Clear Memory Mode.> and Inspection Mode <Ref. to EN(H4DOTC)(diag)-43, PROCEDURE, Inspection Mode.> after connecting the fuel injector connector.

# **Engine Noise**

MECHANICAL

---

# EXHAUST

# *EX(H4DOTC)*

---

	Page
1. General Description .....	2
2. Front Exhaust Pipe .....	5
3. Center Exhaust Pipe .....	12
4. Rear Exhaust Pipe .....	15
5. Muffler .....	17