

4. Appendix

MAJOR TECHNICAL SPECIFICATIONS

Item		Area	Europe			
Body Type			4-Door Sedan			
Vehicle Grade			LINEA TERRA		LINEA SOL	LINEA TERRA
Model Code			AT220R-AEMNKW	AT220L-AEMNKW	AT220L-AEMEKW	AT221R-AEMNKW
Major Dimensions & Vehicle Weights	Overall	Length mm (in.)	4490 (176.8)	←	←	←
		Width mm (in.)	1710 (67.3)	←	←	←
		Height mm (in.)	1425 (56.1)	←	←	←
	Wheel Base	mm (in.)	2630 (103.5)	←	←	←
	Tread	Front mm (in.)	1480 (58.3)	←	←	←
		Rear mm (in.)	1450 (57.1)	←	←	←
	Room	Length mm (in.)	1930 (76.0)	←	←	←
		Width mm (in.)	1455 (57.3)	←	←	←
		Height mm (in.)	1160 (45.7), 1110 (43.7)* ¹	←	←	←
	Overhang	Front mm (in.)	875 (34.4)	←	←	←
		Rear mm (in.)	985 (38.8)	←	←	←
	Min. Running Ground Clearance	mm (in.)	155 (6.1)	←	←	←
	Angle of Approach	degrees	17.7°	←	←	←
	Angle of Departure	degrees	18.4°	←	←	←
	Curb Weight	Front kg (lb)	690 ~ 745 (1521 ~ 1642)	←	695 ~ 745 (1532 ~ 1642)	695 ~ 750 (1532 ~ 1653)
		Rear kg (lb)	505 ~ 540 (1113 ~ 1190)	←	510 ~ 540 (1124 ~ 1190)	←
		Total kg (lb)	1195 ~ 1285 (2634 ~ 2832)	←	1205 ~ 1285 (2656 ~ 2832)	1205 ~ 1290 (2656 ~ 2843)
Performance	Gross Vehicle Weight	Front kg (lb)	860 (1896)	←	←	890 (1962)
		Rear kg (lb)	870 (1918)	←	←	←
		Total kg (lb)	1730 (3814)	←	←	1760 (3880)
	Fuel Tank Capacity	ℓ (Imp.gal.)	60 (13.2)	←	←	←
	Luggage Compartment Capacity	m ³ (cu.ft.)	0.50 (17.7)	←	←	←
	Max. Speed	km/h (mph)	190 (118)	190 (118)* ² , 195 (121)* ³	195 (121)	←
	Max. Cruising Speed	km/h (mph)	180 (111)	←	←	←
	Acceleration	0 to 100 km/h sec.	12.1	12.1* ² , 11.7* ³	11.7	11.0
		0 to 400 m sec.	18.1	18.1* ² , 18.0* ³	18.0	17.6
	Max. Permissible Speed	1st Gear km/h (mph)	45 (27)	←	←	46 (28)
		2nd Gear km/h (mph)	83 (51)	←	←	86 (53)
		3rd Gear km/h (mph)	121 (75)	←	←	125 (77)
		4th Gear km/h (mph)	—	—	—	—
	Min. Turning Radius	Tire m (ft.)	5.4 (17.7)	←	←	←
		Body m (ft.)	5.8 (19.0)	←	←	←
Engine	Engine Type		4A-FE	←	←	7A-FE
	Valve Mechanism		16-Valve, DOHC	←	←	←
	Bore x Stroke mm (in.)		81.0 x 77.0 (3.19 x 3.03)	←	←	81.0 x 85.5 (3.19 x 3.37)
	Displacement cm ³ (cu.in.)		1587 (96.8)	←	←	1762 (107.5)
	Compression Ratio		9.5 : 1	←	←	←
	Carburetor Type or Injection Pump Type (Diesel)		EFI	←	←	←
	Research Octane No. or Cetane No. (Diesel)		95	←	←	←
	Max. Output (EEC) kW / rpm		74 / 5800	74 / 5800* ² , 81 / 6000* ³	81 / 6000	81 / 5600
	Max. Torque (EEC) N·m / rpm		136 / 4400	136 / 4400* ² , 145 / 4800* ³	145 / 4800	155 / 2800
	Battery Capacity (5HR) Voltage & Amp. hr.		12-32, 48* ⁴	←	←	←
Engine Electrical	Alternator Output Watts		960	←	←	←
	Starter Output kW		1.1	←	←	←
	Clutch Type		Dry, Single	←	←	←
	Transaxle Type		C50	←	←	C250
	Transmission Gear Ratio	In First	3.545	←	←	←
		In Second	1.904	←	←	←
		In Third	1.310	←	←	←
		In Fourth	0.969	←	←	1.031
		In Fifth	0.815	←	←	←
		In Reverse	3.250	←	←	←
	Counter Gear Ratio		—	—	—	—
	Differential Gear Ratio (Final)		4.058	←	←	3.941
	Brake Type	Front	Ventilated Disc	←	←	←
		Rear	Leading Trailing Drum	←	←	←
Chassis	Parking Brake Type		Drum	←	←	←
	Brake Booster Type and Size in.		Single, 9"	←	←	←
	Proportioning Valve Type		Dual-P Valve	←	←	←
	Suspension Type	Front	MacPherson Strut	←	←	←
		Rear	MacPherson Strut	←	←	←
	Stabilizer Bar	Front	STD	←	←	←
		Rear	STD	←	←	←
	Steering Gear Type		Rack and Pinion	←	←	←
	Steering Gear Ratio (Overall)		17.39	←	←	←
	Power Steering Type		Integral Type	←	←	←

*1: With Moon Roof

*2: For Lean-Burn Engine

*3: For Stoichiometric Engine

*4: Option

Europe					
4-Door Sedan					
LINEA TERRA			LINEA SOL		
AT221L-AEMNKW	AT221R-AEPNKW	AT221L-AEPNKW	AT221R-AEMEKW	AT221L-AEMEKW	AT221R-AEPEKW
5	←	←	←	←	←
	←	←	←	←	←
	←	←	←	←	←
	←	←	←	←	←
	←	←	←	←	←
	←	←	←	←	←
10	←	←	←	←	←
	←	←	←	←	←
	←	←	←	←	←
	←	←	←	←	←
	←	←	←	←	←
	←	←	←	←	←
15	←	←	←	←	←
	←	←	←	←	←
	←	←	←	←	←
	←	←	←	←	←
	←	←	←	←	←
	725 ~ 780 (1598 ~ 1720)	←	695 ~ 750 (1532 ~ 1653)	←	725 ~ 780 (1598 ~ 1720)
20	←	←	←	←	←
	1235 ~ 1320 (2722 ~ 2910)	←	1205 ~ 1290 (2656 ~ 2843)	←	1235 ~ 1320 (2722 ~ 2910)
	←	←	←	←	←
	←	←	←	←	←
	←	←	←	←	←
	←	←	←	←	←
25	←	←	←	←	←
	←	←	←	←	←
	←	←	←	←	←
	185 (115)	←	195 (121)	←	185 (115)
	175 (108)	←	180 (111)	←	175 (108)
	12.2	←	11.0	←	12.2
30	←	←	←	←	←
	18.5	←	18.0	←	18.5
	54 (33)	←	54 (33)	←	54 (33)
	98 (60)	←	98 (60)	←	98 (60)
	—	—	—	—	—
	—	—	—	—	—
35	←	←	←	←	←
	←	←	←	←	←
	←	←	←	←	←
	←	←	←	←	←
	←	←	←	←	←
40	←	←	←	←	←
	←	←	←	←	←
	←	←	←	←	←
	←	←	←	←	←
	←	←	←	←	←
45	←	←	←	←	←
	←	←	←	←	←
	←	←	←	←	←
	←	←	←	←	←
	←	←	←	←	←
	—	—	Dry, Single	←	—
50	←	←	C250	←	A246E
	4.005	←	3.545	←	4.005
	2.208	←	1.904	←	2.208
	1.425	←	1.310	←	1.425
	0.981	←	1.031	←	0.981
55	←	—	0.815	←	—
	3.272	←	3.250	←	3.272
	—	—	—	—	—
	2.962	←	3.941	←	2.962
	←	←	←	←	←
60	←	←	←	←	←
	←	←	←	←	←
	←	←	←	←	←
	←	←	←	←	←
65	←	←	←	←	←
	←	←	←	←	←
	←	←	←	←	←
	←	←	←	←	←
	←	←	←	←	←
70	←	←	←	←	←

Item		Area		Europe			
Body Type				4-Door Sedan			
Vehicle Grade				LINEA SDL			
Model Code				AT221L-AEPEKW	ST220R-AEMEKW	ST220L-AEMEKW	ST220R-AEPEKW
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	4490 (176.8)	←	←	←
		Width	mm (in.)	1710 (67.3)	←	←	←
		Height	mm (in.)	1425 (56.1)	←	←	←
	Wheel Base		mm (in.)	2630 (103.5)	←	←	←
	Tread	Front	mm (in.)	1480 (58.3)	←	←	←
		Rear	mm (in.)	1450 (57.1)	←	←	←
	Room	Length	mm (in.)	1930 (76.0)	←	←	←
		Width	mm (in.)	1455 (57.3)	←	←	←
		Height	mm (in.)	1160 (45.7), 1110 (43.7)*1	←	←	←
	Overhang	Front	mm (in.)	875 (34.4)	←	←	←
		Rear	mm (in.)	985 (38.8)	←	←	←
	Min. Running Ground Clearance		mm (in.)	155 (6.1)	←	←	←
	Angle of Approach		degrees	17.7°	←	←	←
	Angle of Departure		degrees	18.4°	←	←	←
	Curb Weight	Front	kg (lb)	725 ~ 780 (1598 ~ 1720)	730 ~ 780 (1609 ~ 1720)	←	755 ~ 805 (1665 ~ 1775)
		Rear	kg (lb)	510 ~ 540 (1124 ~ 1190)	515 ~ 540 (1135 ~ 1190)	←	←
		Total	kg (lb)	1235 ~ 1320 (2722 ~ 2910)	1245 ~ 1320 (2744 ~ 2910)	←	1270 ~ 1345 (2800 ~ 2965)
Performance	Gross Vehicle Weight	Front	kg (lb)	890 (1962)	920 (2028)	←	←
		Rear	kg (lb)	870 (1918)	880 (1940)	←	←
		Total	kg (lb)	1760 (3880)	1800 (3968)	←	←
	Fuel Tank Capacity		ℓ (Imp.gal.)	60 (13.2)	←	←	←
	Luggage Compartment Capacity		m ³ (cu.ft.)	0.50 (17.7)	←	←	←
	Max. Speed		km/h (mph)	185 (115)	205 (127)	←	200 (124)
	Max. Cruising Speed		km/h (mph)	175 (108)	185 (115)	←	180 (111)
	Acceleration	0 to 100 km/h	sec.	12.2	9.3	←	10.6
		0 to 400 m	sec.	18.5	16.8	←	17.6
	Max. Permissible Speed	1st Gear	km/h (mph)	54 (33)	←	←	60 (37)
		2nd Gear	km/h (mph)	98 (60)	90 (55)	←	110 (68)
		3rd Gear	km/h (mph)	—	134 (83)	←	—
		4th Gear	km/h (mph)	—	—	←	—
	Min. Turning Radius	Tire	m (ft.)	5.4 (17.7)	←	←	←
		Body	m (ft.)	5.8 (19.0)	←	←	←
Engine	Engine Type			7A-FE	3S-FE	←	←
	Valve Mechanism			16-Valve, DOHC	←	←	←
	Bore x Stroke		mm (in.)	81.0 x 85.5 (3.19 x 3.37)	86.0 x 86.0 (3.39 x 3.39)	←	←
	Displacement		cm ³ (cu.in.)	1762 (107.5)	1998 (121.9)	←	←
	Compression Ratio			9.5 : 1	9.8 : 1	←	←
	Carburetor Type or Injection Pump Type (Diesel)			EFI	←	←	←
	Research Octane No. or Cetane No. (Diesel)			95	←	←	←
	Max. Output (EEC)		kW / rpm	81 / 5600	94 / 5400	←	←
	Max. Torque (EEC)		N·m / rpm	155 / 2800	178 / 4400	←	←
	Battery Capacity (5HR)		Voltage & Amp. hr.	12-32, 48*4	←	←	←
Engine Electrical	Alternator Output		Watts	960	←	←	←
	Starter Output		kW	1.1	1.0, 1.2*4	←	←
Chassis	Clutch Type			—	Dry, Single	←	—
	Transaxle Type			A246E	S54	←	A241E
	Transmission Gear Ratio	In First		4.005	3.285	←	3.643
		In Second		2.208	1.960	←	2.008
		In Third		1.425	1.322	←	1.296
		In Fourth		0.981	1.028	←	0.892
		In Fifth		—	0.820	←	—
		In Reverse		3.272	3.153	←	2.977
	Counter Gear Ratio			—	—	←	—
	Differential Gear Ratio (Final)			2.962	3.944	←	3.178
	Brake Type	Front		Ventilated Disc	←	←	←
		Rear		Leading Trailing Drum	←	←	←
	Parking Brake Type			Drum	←	←	←
	Brake Booster Type and Size		in.	Single, 9"	←	←	←
	Proportioning Valve Type			Dual-P Valve	←	←	←
	Suspension Type	Front		MacPherson Strut	←	←	←
		Rear		MacPherson Strut	←	←	←
	Stabilizer Bar	Front		STD	←	←	←
		Rear		STD	←	←	←
	Steering Gear Type			Rack and Pinion	←	←	←
	Steering Gear Ratio (Overall)			17.39	←	←	←
	Power Steering Type			Integral Type	←	←	←

*1: With Moon Roof

*4: Option

*5: Mechanically Controlled

*6: Electronically Controlled

Europe				
4-Door Sedan				
LINEA SOL	LINEA TERRA			LINEA SOL
ST220L-AEPEKW	CT220L-AEMNXW	CT220R-AEMNTW	CT220L-AEMNTW	CT220L-AEMETW
5	←	←	←	←
	←	←	←	←
	←	←	←	←
	←	←	←	←
	←	←	←	←
10	←	←	←	←
	←	←	←	←
	←	←	←	←
	←	←	←	←
	←	←	←	←
15	←	←	←	←
	←	←	←	←
	←	←	←	←
	←	←	←	←
	←	←	←	←
	765 ~ 855 (1687 ~ 1885)	←	←	←
20	←	←	←	←
	1280 ~ 1395 (2822 ~ 3075)	←	←	←
	950 (2094)	←	←	←
	880 (1940)	←	←	←
	1830 (4034)	←	←	←
25	←	←	←	←
	←	←	←	←
	—	180 (111)	←	←
	—	170 (105)	←	←
	—	12.0	←	←
30	←	18.1	←	←
	42 (26)	←	←	←
	73 (45)	←	←	←
	113 (70)	←	←	←
	—	—	—	—
35	←	←	←	←
	←	←	←	←
	2C-T	2C-TE	←	←
	8-Valve, OHC	←	←	←
	86.0 x 85.0 (3.39 x 3.35)	←	←	←
40	1975 (120.5)	←	←	←
	23.0 : 1	←	←	←
	Distributor Type*5	Distributor Type*6	←	←
	48	←	←	←
	60 / 4000	66 / 4000	←	←
45	170 / 2000 ~ 3000	203 / 2200	←	←
	12-64	←	←	←
	1080	←	←	←
	2.0	←	←	←
	Dry, Single	←	←	←
50	S50	←	←	←
	3.538	←	←	←
	2.041	←	←	←
	1.322	←	←	←
	0.945	←	←	←
55	—	0.731	←	←
	←	3.153	←	←
	—	—	—	—
	3.736	←	←	←
	←	←	←	←
60	←	←	←	←
	←	←	←	←
	←	←	←	←
	←	←	←	←
65	←	←	←	←
	←	←	←	←
	←	←	←	←
	←	←	←	←
	←	←	←	←
70	←	←	←	←

Item		Area	Europe			
Body Type			5-Door Liftback			
Vehicle Grade			LINEA TERRA		LINEA SOL	LINEA TERRA
Model Code			AT220R-ALMKNW	AT220L-ALMKNW	AT220L-ALMEKW	AT221R-ALMKNW
Major Dimensions & Vehicle Weights	Overall	Length mm (in.)	4490 (176.8)	←	←	←
		Width mm (in.)	1710 (67.3)	←	←	←
		Height mm (in.)	1425 (56.1)	←	←	←
	Wheel Base	mm (in.)	2630 (103.5)	←	←	←
	Tread	Front mm (in.)	1480 (58.3)	←	←	←
		Rear mm (in.)	1450 (57.1)	←	←	←
	Room	Length mm (in.)	1930 (76.0)	←	←	←
		Width mm (in.)	1455 (57.3)	←	←	←
		Height mm (in.)	1160 (45.7), 1110 (43.7)*1	←	←	←
	Overhang	Front mm (in.)	875 (34.4)	←	←	←
		Rear mm (in.)	98.5 (38.8)	←	←	←
	Min. Running Ground Clearance	mm (in.)	155 (6.1)	←	←	←
	Angle of Approach	degrees	17.7°	←	←	←
	Angle of Departure	degrees	18.4°	←	←	←
	Curb Weight	Front kg (lb)	695 ~ 745 (1532 ~ 1642)	←	←	695 ~ 750 (1532 ~ 1653)
		Rear kg (lb)	530 ~ 560 (1168 ~ 1235)	←	←	←
		Total kg (lb)	1225 ~ 1305 (2700 ~ 2877)	←	←	1225 ~ 1310 (2700 ~ 2888)
	Gross Vehicle Weight	Front kg (lb)	860 (1896)	←	←	890 (1962)
		Rear kg (lb)	870 (1918)	←	←	←
		Total kg (lb)	1730 (3814)	←	←	1760 (3880)
Performance	Fuel Tank Capacity	ℓ (Imp.gal.)	60 (13.2)	←	←	←
	Luggage Compartment Capacity	m ³ (cu.ft.)	0.51 (18.0)	←	←	←
	Max. Speed	km/h (mph)	190 (118)	190 (118)*2, 195 (121)*3	195 (121)	←
	Max. Cruising Speed	km/h (mph)	180 (111)	←	←	←
	Acceleration	0 to 100 km/h sec.	12.1	12.1*2, 11.7*3	11.7	11.0
		0 to 400 m sec.	18.1	18.1*2, 18.0*3	18.0	17.6
	Max. Permissible Speed	1st Gear km/h (mph)	45 (27)	←	←	46 (28)
		2nd Gear km/h (mph)	83 (51)	←	←	86 (53)
		3rd Gear km/h (mph)	121 (75)	←	←	125 (77)
		4th Gear km/h (mph)	—	—	—	—
	Min. Turning Radius	Tire m (ft.)	5.4 (17.7)	←	←	←
		Body m (ft.)	5.8 (19.0)	←	←	←
Engine	Engine Type		4A-FE	←	←	7A-FE
	Valve Mechanism		16-Valve, DOHC	←	←	←
	Bore x Stroke mm (in.)		81.0 x 77.0 (3.19 x 3.03)	←	←	81.0 x 85.5 (3.19 x 3.37)
	Displacement cm ³ (cu.in.)		1587 (96.8)	←	←	1762 (107.5)
	Compression Ratio		9.5 : 1	←	←	9.5 : 1
	Carburetor Type or Injection Pump Type (Diesel)		EFI	←	←	←
	Research Octane No. or Cetane No. (Diesel)		95	←	←	←
	Max. Output (EEC) kW / rpm		74 / 5800	74 / 5800*2, 81 / 6000*3	81 / 6000	81 / 5600
	Max. Torque (EEC) N·m / rpm		136 / 4400	136 / 4400*2, 145 / 4800*3	145 / 4800	155 / 2800
Engine Electrical	Battery Capacity (5HR) Voltage & Amp. hr.		12-32, 48*4	←	←	←
	Alternator Output Watts		960	←	←	←
	Starter Output kW		1.1	←	←	←
Chassis	Clutch Type		Dry, Single	←	←	←
	Transaxle Type		C50	←	←	C250
	Transmission Gear Ratio	In First	3.545	←	←	←
		In Second	1.904	←	←	←
		In Third	1.310	←	←	←
		In Fourth	0.969	←	←	1.031
		In Fifth	0.815	←	←	←
		In Reverse	3.250	←	←	←
	Counter Gear Ratio		—	—	—	—
	Differential Gear Ratio (Final)		4.058	←	←	3.941
	Brake Type	Front	Ventilated Disc	←	←	←
		Rear	Leading Trailing Drum	←	←	←
	Parking Brake Type		Drum	←	←	←
	Brake Booster Type and Size in.		Single, 9"	←	←	←
	Proportioning Valve Type		Dual-P Valve	←	←	←
	Suspension Type	Front	MacPherson Strut	←	←	←
		Rear	MacPherson Strut	←	←	←
	Stabilizer Bar	Front	STD	←	←	←
		Rear	STD	←	←	←
	Steering Gear Type		Rack and Pinion	←	←	←
	Steering Gear Ratio (Overall)		17.39	←	←	←
	Power Steering Type		Integral Type	←	←	←

*1: With Moon Roof

*2: For Lean-Burn Engine

*3: For Stoichiometric Engine

*4: Option

Europe					
5-Door Liftback					
LINEA TERRA			LINEA SOL		
AT221L-ALMNKW	AT221R-ALPNKW	AT221L-ALPNKW	AT221R-ALMEKW	AT221L-ALMEKW	AT221R-ALPEKW
5	←	←	←	←	←
	←	←	←	←	←
	←	←	←	←	←
	←	←	←	←	←
	←	←	←	←	←
	←	←	←	←	←
10	←	←	←	←	←
	←	←	←	←	←
	←	←	←	←	←
	←	←	←	←	←
	←	←	←	←	←
	←	←	←	←	←
15	←	←	←	←	←
	←	←	←	←	←
	←	←	←	←	←
	←	←	←	←	←
	←	←	←	←	←
	725 ~ 780 (1598 ~ 1720)	←	695 ~ 750 (1532 ~ 1653)	←	725 ~ 780 (1598 ~ 1720)
20	←	←	←	←	←
	1255 ~ 1340 (2700 ~ 2954)	←	1225 ~ 1310 (2700 ~ 2888)	←	1255 ~ 1340 (2700 ~ 2954)
	←	←	←	←	←
	←	←	←	←	←
	←	←	←	←	←
	←	←	←	←	←
25	←	←	←	←	←
	←	←	←	←	←
	←	←	←	←	←
	185 (115)	←	195 (121)	←	185 (115)
	175 (108)	←	180 (111)	←	175 (108)
	12.2	←	11.0	←	12.2
30	←	←	←	←	←
	18.5	←	17.6	←	18.5
	54 (33)	←	46 (28)	←	54 (33)
	98 (60)	←	86 (53)	←	98 (60)
	—	—	125 (77)	←	—
	—	—	—	—	—
35	←	←	←	←	←
	←	←	←	←	←
	←	←	←	←	←
	←	←	←	←	←
	←	←	←	←	←
40	←	←	←	←	←
	←	←	←	←	←
	←	←	←	←	←
	←	←	←	←	←
	←	←	←	←	←
45	←	←	←	←	←
	←	←	←	←	←
	←	←	←	←	←
	←	←	←	←	←
	←	←	←	←	←
	—	—	Dry, Single	←	—
50	←	←	←	←	←
	A246E	←	C250	←	A246E
	4.005	←	3.545	←	4.005
	2.208	←	1.904	←	2.208
	1.425	←	1.310	←	1.425
	0.981	←	1.031	←	0.981
55	←	←	←	←	←
	—	—	0.815	←	—
	3.272	←	3.250	←	3.272
	—	—	—	—	—
	2.962	←	3.941	←	2.962
	←	←	←	←	←
60	←	←	←	←	←
	←	←	←	←	←
	←	←	←	←	←
	←	←	←	←	←
	←	←	←	←	←
65	←	←	←	←	←
	←	←	←	←	←
	←	←	←	←	←
	←	←	←	←	←
	←	←	←	←	←
70	←	←	←	←	←

Item		Area	Europe			
Body Type			5-Door Liftback			
Vehicle Grade			LINEA SOL			
Model Code			AT221L-ALPEKW	ST220R-ALMEKW	ST220L-ALMEKW	ST220R-ALPEKW
Major Dimensions & Vehicle Weights	Overall	Length mm (in.)	4490 (176.8)	←	←	←
		Width mm (in.)	1710 (67.3)	←	←	←
		Height mm (in.)	1425 (56.1)	←	←	←
	Wheel Base	mm (in.)	2630 (103.5)	←	←	←
	Tread	Front mm (in.)	1480 (58.3)	←	←	←
		Rear mm (in.)	1450 (57.1)	←	←	←
	Room	Length mm (in.)	1930 (76.0)	←	←	←
		Width mm (in.)	1455 (57.3)	←	←	←
		Height mm (in.)	1160 (45.7), 1110 (43.7)*1	←	←	←
	Overhang	Front mm (in.)	875 (34.4)	←	←	←
		Rear mm (in.)	985 (38.8)	←	←	←
	Min. Running Ground Clearance	mm (in.)	155 (6.1)	←	←	←
	Angle of Approach	degrees	17.7°	←	←	←
	Angle of Departure	degrees	18.4°	←	←	←
	Curb Weight	Front kg (lb)	725 ~ 780 (1598 ~ 1720)	730 ~ 780 (1609 ~ 1720)	←	755 ~ 805 (1664 ~ 1775)
		Rear kg (lb)	530 ~ 560 (1168 ~ 1235)	535 ~ 560 (1180 ~ 1235)	←	←
		Total kg (lb)	1255 ~ 1340 (2700 ~ 2955)	1265 ~ 1340 (2789 ~ 2955)	←	1290 ~ 1365 (2844 ~ 3010)
Performance	Gross Vehicle Weight	Front kg (lb)	890 (1962)	920 (2028)	←	←
		Rear kg (lb)	870 (1918)	880 (1940)	←	←
		Total kg (lb)	1760 (3880)	1800 (3968)	←	←
	Fuel Tank Capacity	ℓ (Imp.gal.)	60 (13.2)	←	←	←
	Luggage Compartment Capacity	m ³ (cu.ft.)	0.51 (18.0)	←	←	←
	Max. Speed	km/h (mph)	185 (115)	205 (127)	←	200 (124)
	Max. Cruising Speed	km/h (mph)	175 (108)	185 (115)	←	180 (111)
	Acceleration	0 to 100 km/h sec.	12.2	9.3	←	10.6
		0 to 400 m sec.	18.5	16.8	←	17.6
	Max. Permissible Speed	1st Gear km/h (mph)	54 (33)	←	←	60 (37)
		2nd Gear km/h (mph)	98 (60)	90 (55)	←	110 (68)
		3rd Gear km/h (mph)	—	134 (83)	←	—
		4th Gear km/h (mph)	—	—	←	—
	Min. Turning Radius	Tire m (ft.)	5.4 (17.7)	←	←	←
		Body m (ft.)	5.8 (19.0)	←	←	←
Engine	Engine Type		7A-FE	3S-FE	←	←
	Valve Mechanism		16-Valve, DOHC	←	←	←
	Bore x Stroke	mm (in.)	81.0 x 85.5 (3.19 x 3.37)	86.0 x 86.0 (3.39 x 3.39)	←	←
	Displacement	cm ³ (cu.in.)	1762 (107.5)	1998 (121.9)	←	←
	Compression Ratio		9.5 : 1	9.8 : 1	←	←
	Carburetor Type or Injection Pump Type (Diesel)		EFI	←	←	←
	Research Octane No. or Cetane No. (Diesel)		95	95	←	←
	Max. Output (EEC)	kW / rpm	81 / 5600	94 / 5400	←	←
	Max. Torque (EEC)	N·m / rpm	155 / 2800	178 / 4400	←	←
	Battery Capacity (5HR)	Voltage & Amp. hr.	12-32, 48*4	←	←	←
Engine Electrical	Alternator Output	Watts	960	←	←	←
	Starter Output	kW	1.1	1.0, 1.2*4	←	←
Chassis	Clutch Type		—	Dry, Single	←	—
	Transaxle Type		A246E	S54	←	A241E
	Transmission Gear Ratio	In First	4.005	3.285	←	3.643
		In Second	2.208	1.960	←	2.008
		In Third	1.425	1.322	←	1.296
		In Fourth	0.981	1.028	←	0.892
		In Fifth	—	0.820	←	—
		In Reverse	3.272	3.153	←	2.977
	Counter Gear Ratio		—	—	←	—
	Differential Gear Ratio (Final)		2.962	3.944	←	3.178
	Brake Type	Front	Ventilated Disc	←	←	←
		Rear	Leading Trailing Drum	←	←	←
	Parking Brake Type		Drum	←	←	←
	Brake Booster Type and Size	in.	Single, 9"	←	←	←
	Proportioning Valve Type		Dual-P Valve	←	←	←
	Suspension Type	Front	MacPherson Strut	←	←	←
		Rear	MacPherson Strut	←	←	←
	Stabilizer Bar	Front	STD	←	←	←
		Rear	STD	←	←	←
	Steering Gear Type		Rack and Pinion	←	←	←
	Steering Gear Ratio (Overall)		17.39	←	←	←
	Power Steering Type		Integral Type	←	←	←

*1: With Moon Roof

*4: Option

*6: Electronically Controlled

Europe				
5-Door Liftback				
	LINEA SOL	LINEA TERRA		LINEA SOL
	ST220L-ALPEKW	CT220R-ALMNTW	CT220L-ALMNTW	CT220L-ALMETW
5	←	←	←	←
	←	←	←	←
	←	←	←	←
	←	←	←	←
	←	←	←	←
10	←	←	←	←
	←	←	←	←
	←	←	←	←
	←	←	←	←
	←	←	←	←
15	←	←	←	←
	←	←	←	←
	←	←	←	←
	←	←	←	←
	←	765 ~ 855 (1687 ~ 1885)	←	←
20	←	←	←	←
	←	1300 ~ 1415 (2866 ~ 3120)	←	←
	←	950 (2094)	←	←
	←	880 (1940)	←	←
	←	1830 (4034)	←	←
25	←	←	←	←
	←	←	←	←
	←	180 (111)	←	←
	←	170 (105)	←	←
	←	12.0	←	←
30	←	18.1	←	←
	←	42 (26)	←	←
	←	73 (45)	←	←
	—	113 (70)	←	←
	—	—	—	—
35	←	←	←	←
	←	←	←	←
	←	2C-TE	←	←
	←	8-Valve, OHC	←	←
	←	86.0 x 85.0 (3.39 x 3.35)	←	←
40	←	1975 (120.5)	←	←
	←	23.0 : 1	←	←
	←	Distributor Type*6	←	←
	←	48	←	←
	←	66 / 4000	←	←
45	←	203 / 2200	←	←
	←	12-64	←	←
	←	1080	←	←
	←	2.0	←	←
	—	Dry, Single	←	←
50	←	S50	←	←
	←	3.538	←	←
	←	2.041	←	←
	←	1.322	←	←
	←	0.945	←	←
55	—	0.731	←	←
	←	3.153	←	←
	—	—	—	—
	←	3.736	←	←
	←	←	←	←
60	←	←	←	←
	←	←	←	←
	←	←	←	←
	←	←	←	←
65	←	←	←	←
	←	←	←	←
	←	←	←	←
	←	←	←	←
	←	←	←	←
70	←	←	←	←

Item		Area	Europe			
Body Type			5-Door Wagon			
Vehicle Grade			LINEA TERRA		LINEA SOL	LINEA TERRA
Model Code			AT220R-AWMNKKW	AT220L-AWMNKKW	AT220L-AWMEKW	AT221R-AWMNKKW
Major Dimensions & Vehicle Weights	Overall	Length mm (in.)	4570 (179.9)	←	←	←
		Width mm (in.)	1710 (67.3)	←	←	←
		Height mm (in.)	1500 (59.1)	←	←	←
	Wheel Base	mm (in.)	2630 (103.5)	←	←	←
	Tread	Front mm (in.)	1480 (58.3)	←	←	←
		Rear mm (in.)	1450 (57.1)	←	←	←
	Room	Length mm (in.)	1930 (76.0)	←	←	←
		Width mm (in.)	1455 (57.3)	←	←	←
		Height mm (in.)	1170 (46.1), 1120 (44.1)*1	←	←	←
	Overhang	Front mm (in.)	875 (34.4)	←	←	←
		Rear mm (in.)	1065 (41.9)	←	←	←
	Min. Running Ground Clearance	mm (in.)	155 (6.1)	←	←	←
	Angle of Approach	degrees	17.6°	←	←	←
	Angle of Departure	degrees	17.4°	←	←	←
	Curb Weight	Front kg (lb)	695 ~ 745 (1532 ~ 1642)	←	←	695 ~ 750 (1532 ~ 1653)
		Rear kg (lb)	545 ~ 575 (1202 ~ 1268)	←	←	←
		Total kg (lb)	1240 ~ 1320 (2734 ~ 2910)	←	←	1240 ~ 1325 (2734 ~ 2921)
	Gross Vehicle Weight	Front kg (lb)	860 (1896)	←	←	890 (1962)
		Rear kg (lb)	870 (1918)	←	←	←
		Total kg (lb)	1730 (3814)	←	←	1760 (3880)
Performance	Fuel Tank Capacity	ℓ (Imp.gal.)	60 (13.2)	←	←	←
	Luggage Compartment Capacity	m ³ (cu.ft.)	0.53 (18.7)	←	←	←
	Max. Speed	km/h (mph)	185 (115)	185 (115)*2, 190 (118)*3	190 (118)	←
	Max. Cruising Speed	km/h (mph)	175 (108)	175 (108)*2, 180 (111)*3	180 (111)	←
	Acceleration	0 to 100 km/h sec.	12.3	12.3*2, 11.7*3	11.7	11.2
		0 to 400 m sec.	18.2	18.2*2, 18.1*3	18.1	17.7
	Max. Permissible Speed	1st Gear km/h (mph)	45 (27)	←	←	46 (28)
		2nd Gear km/h (mph)	83 (51)	←	←	86 (53)
		3rd Gear km/h (mph)	121 (75)	←	←	125 (77)
		4th Gear km/h (mph)	—	—	—	—
	Min. Turning Radius	Tire m (ft.)	5.4 (17.7)	←	←	←
		Body m (ft.)	5.8 (19.0)	←	←	←
Engine	Engine Type		4A-FE	←	←	7A-FE
	Valve Mechanism		16-Valve, DOHC	←	←	←
	Bore x Stroke mm (in.)		81.0 x 77.0 (3.19 x 3.03)	←	←	81.0 x 85.5 (3.19 x 3.37)
	Displacement cm ³ (cu.in.)		1587 (96.8)	←	←	1762 (107.5)
	Compression Ratio		9.5 : 1	←	←	←
	Carburetor Type or Injection Pump Type (Diesel)		EFI	←	←	←
	Research Octane No. or Cetane No. (Diesel)		95	←	←	←
	Max. Output (EEC) kW / rpm		74 / 5800	74 / 5800*2, 81 / 6000*3	81 / 6000	81 / 5600
	Max. Torque (EEC) N·m / rpm		136 / 4400	136 / 4400*2, 145 / 4800*3	145 / 4800	155 / 2800
Engine Electrical	Battery Capacity (5HR) Voltage & Amp. hr.		12-32, 48*4	←	←	←
	Alternator Output Watts		960	←	←	←
	Starter Output kW		1.1	←	←	←
Chassis	Clutch Type		Dry, Single	←	←	←
	Transaxle Type		C50	←	←	C250
	Transmission Gear Ratio	In First	3.545	←	←	←
		In Second	1.904	←	←	←
		In Third	1.310	←	←	←
		In Fourth	0.969	←	←	1.031
		In Fifth	0.815	←	←	←
		In Reverse	3.250	←	←	←
	Counter Gear Ratio		—	—	—	—
	Differential Gear Ratio (Final)		4.058	←	←	3.941
	Brake Type	Front	Ventilated Disc	←	←	←
		Rear	Leading Trailing Drum	←	←	←
	Parking Brake Type		Drum	←	←	←
	Brake Booster Type and Size in.		Single, 9"	←	←	←
	Proportioning Valve Type		Dual-P Valve	←	←	←
	Suspension Type	Front	MacPherson Strut	←	←	←
		Rear	MacPherson Strut	←	←	←
	Stabilizer Bar	Front	STD	←	←	←
		Rear	STD	←	←	←
	Steering Gear Type		Rack and Pinion	←	←	←
	Steering Gear Ratio (Overall)		17.39	←	←	←
	Power Steering Type		Integral Type	←	←	←

*1: With Moon Roof

*2: For Lean-Burn Engine

*3: For Stoichiometric Engine

*4: Option

Europe					
5-Door Wagon					
LINEA TERRA		LINEA SOL			
AT221L-AWMNKW	AT221L-AWPNKW	AT221L-AWMEKW	AT221L-AWPEKW	ST220R-AWMEKW	ST220L-AWMEKW
5	←	←	←	←	←
	←	←	←	←	←
	←	←	←	←	←
	←	←	←	←	←
	←	←	←	←	←
	←	←	←	←	←
10	←	←	←	←	←
	←	←	←	←	←
	←	←	←	←	←
	←	←	←	←	←
	←	←	←	←	←
15	←	←	←	←	←
	←	←	←	←	←
	←	←	←	←	←
	←	←	←	←	←
	←	←	←	←	←
	725 ~ 780 (1598 ~ 1720)	695 ~ 750 (1532 ~ 1653)	725 ~ 780 (1598 ~ 1720)	730 ~ 780 (1609 ~ 1720)	←
20	←	←	←	550 ~ 575 (1213 ~ 1268)	←
	1270 ~ 1355 (2800 ~ 2988)	1240 ~ 1325 (2734 ~ 2921)	1270 ~ 1355 (2800 ~ 2988)	1280 ~ 1355 (2822 ~ 2988)	←
	←	←	←	920 (2028)	←
	←	←	←	880 (1940)	←
	←	←	←	1800 (3968)	←
25	←	←	←	←	←
	←	←	←	←	←
	←	←	←	←	←
	180 (111)	190 (118)	180 (111)	200 (124)	←
	170 (105)	180 (111)	170 (105)	180 (111)	←
	12.4	11.2	12.4	9.5	←
30	←	17.7	18.6	16.9	←
	54 (33)	46 (28)	54 (33)	←	←
	98 (60)	86 (53)	98 (60)	90 (55)	←
	—	125 (77)	—	134 (83)	←
	—	—	—	—	—
35	←	←	←	←	←
	←	←	←	←	←
	←	←	←	3S-FE	←
	←	←	←	←	←
	←	←	←	86.0 x 86.0 (3.39 x 3.39)	←
40	←	←	←	1998 (121.9)	←
	←	←	←	9.8 : 1	←
	←	←	←	←	←
	←	←	←	94 / 5400	←
45	←	←	←	178 / 4400	←
	←	←	←	←	←
	←	←	←	←	←
	←	←	←	1.0, 1.2*4	←
	←	Dry, Single	—	Dry, Single	←
50	←	A246E	C250	A246E	S54
	←	4.005	3.545	4.005	3.285
	←	2.208	1.904	2.208	1.960
	←	1.425	1.310	1.425	1.322
	←	0.981	1.031	0.981	1.028
55	←	—	0.815	—	0.820
	←	3.272	3.250	3.272	3.153
	←	—	—	—	—
	←	2.962	3.941	2.962	3.944
	←	←	←	←	←
60	←	←	←	←	←
	←	←	←	←	←
	←	←	←	←	←
	←	←	←	←	←
65	←	←	←	←	←
	←	←	←	←	←
	←	←	←	←	←
	←	←	←	←	←
	←	←	←	←	←
70	←	←	←	←	←

Item		Area	Europe			
Body Type			5-Door Wagon			
Vehicle Grade			LINEA SOL		LINEA TERRA	
Model Code			ST220R-AWPEKW	ST220L-AWPEKW	CT220R-AWMNKW	CT220L-AWMNKW
Major Dimensions & Vehicle Weights	Overall	Length mm (in.)	4570 (179.9)	←	←	←
		Width mm (in.)	1710 (67.3)	←	←	←
		Height mm (in.)	1500 (59.1)	←	←	←
	Wheel Base	mm (in.)	2630 (103.5)	←	←	←
	Tread	Front mm (in.)	1480 (58.3)	←	←	←
		Rear mm (in.)	1450 (57.1)	←	←	←
	Room	Length mm (in.)	1930 (76.0)	←	←	←
		Width mm (in.)	1455 (57.3)	←	←	←
		Height mm (in.)	1170 (46.1), 1120 (44.1)*1	←	←	←
	Overhang	Front mm (in.)	875 (34.4)	←	←	←
		Rear mm (in.)	1065 (41.9)	←	←	←
	Min. Running Ground Clearance	mm (in.)	155 (6.1)	←	←	←
	Angle of Approach	degrees	17.6°	←	←	←
	Angle of Departure	degrees	17.4°	←	←	←
	Curb Weight	Front kg (lb)	755 ~ 805 (1664 ~ 1775)	←	765 ~ 855 (1687 ~ 1885)	←
		Rear kg (lb)	550 ~ 575 (1213 ~ 1268)	←	←	←
		Total kg (lb)	1305 ~ 1380 (2877 ~ 3042)	←	1315 ~ 1430 (2900 ~ 3152)	←
Performance	Gross Vehicle Weight	Front kg (lb)	920 (2028)	←	950 (2094)	←
		Rear kg (lb)	880 (1940)	←	880 (1940)	←
		Total kg (lb)	1800 (3968)	←	1830 (4034)	←
	Fuel Tank Capacity	ℓ (Imp.gal.)	60 (13.2)	←	←	←
	Luggage Compartment Capacity	m ³ (cu.ft.)	0.53 (18.7)	←	←	←
	Max. Speed	km/h (mph)	195 (121)	←	175 (109)	←
	Max. Cruising Speed	km/h (mph)	180 (111)	←	165 (102)	←
	Acceleration	0 to 100 km/h sec.	10.8	←	12.2	←
		0 to 400 m sec.	17.7	←	18.2	←
	Max. Permissible Speed	1st Gear km/h (mph)	60 (37)	←	42 (26)	←
		2nd Gear km/h (mph)	110 (68)	←	73 (45)	←
		3rd Gear km/h (mph)	—	—	113 (70)	←
		4th Gear km/h (mph)	—	—	—	—
	Min. Turning Radius	Tire m (ft.)	5.4 (17.7)	←	←	←
		Body m (ft.)	5.8 (19.0)	←	←	←
Engine	Engine Type		3S-FE	←	2C-TE	←
	Valve Mechanism		16-Valve, DOHC	←	8-Valve, OHC	←
	Bore x Stroke mm (in.)		86.0 x 86.0 (3.39 x 3.39)	←	86.0 x 85.0 (3.39 x 3.35)	←
	Displacement cm ³ (cu.in.)		1998 (121.9)	←	1975 (120.5)	←
	Compression Ratio		9.8 : 1	←	23.0 : 1	←
	Carburetor Type or Injection Pump Type (Diesel)		EFI	←	Distributor Type*6	←
	Research Octane No. or Cetane No. (Diesel)		95	←	48	←
	Max. Output (EEC) kW / rpm		94 / 5400	←	66 / 4800	←
	Max. Torque (EEC) N·m / rpm		178 / 4400	←	203 / 2200	←
	Battery Capacity (5HR) Voltage & Amp. hr.		12-34, 48*4	←	12-64	←
Engine Electrical	Alternator Output Watts		960	←	1080	←
	Starter Output kW		1.0, 1.2*4	←	2.0	←
	Clutch Type		—	—	Dry, Single	←
Chassis	Transaxle Type		A241E	←	S50	←
	Transmission Gear Ratio	In First	3.643	←	3.538	←
		In Second	2.008	←	2.041	←
		In Third	1.296	←	1.322	←
		In Fourth	0.892	←	0.945	←
		In Fifth	—	—	0.731	←
		In Reverse	2.977	←	3.153	←
	Counter Gear Ratio		—	—	—	—
	Differential Gear Ratio (Final)		3.178	←	3.736	←
	Brake Type	Front	Ventilated Disc	←	←	←
		Rear	Leading Trailing Drum	←	←	←
	Parking Brake Type		Drum	←	←	←
	Brake Booster Type and Size in.		Single, 9"	←	←	←
	Proportioning Valve Type		Dual-P Valve	←	←	←
	Suspension Type	Front	MacPherson Strut	←	←	←
		Rear	MacPherson Strut	←	←	←
	Stabilizer Bar	Front	STD	←	←	←
		Rear	STD	←	←	←
	Steering Gear Type		Rack and Pinion	←	←	←
	Steering Gear Ratio (Overall)		17.39	←	←	←
	Power Steering Type		Integral Type	←	←	←

*1: With Moon Roof

*4: Option

*6: Electronically Controlled

	Europe
	5-Door Wagon
	LINEA SOL
	CT220L-AWMEKW
5	←
	←
	←
	←
	←
10	←
	←
	←
	←
	←
15	←
	←
	←
	←
	←
20	←
	←
	←
	←
	←
25	←
	←
	←
	←
	←
30	←
	←
	←
	←
	—
35	←
	←
	←
	←
	←
40	←
	←
	←
	←
	←
45	←
	←
	←
	←
	←
50	←
	←
	←
	←
	←
55	←
	←
	—
	←
	←
60	←
	←
	←
	←
	←
65	←
	←
	←
	←
	←
70	←

Item		Area	General Countries			
Body Type			4-Door Sedan			
Vehicle Grade			—			
Model Code			AT220R-AEMNK	AT220L-AEMNK	AT220L-AEPNK	ST220R-AEMNK
Major Dimensions & Vehicle Weights	Overall	Length mm (in.)	4490 (176.8)	←	←	←
		Width mm (in.)	1710 (67.3)	←	←	←
		Height mm (in.)	1425 (56.1)	←	←	←
	Wheel Base	mm (in.)	2630 (103.5)	←	←	←
	Tread	Front mm (in.)	1480 (58.3)	←	←	←
		Rear mm (in.)	1450 (57.1)	←	←	←
	Room	Length mm (in.)	1930 (76.0)	←	←	←
		Width mm (in.)	1455 (57.3)	←	←	←
		Height mm (in.)	1160 (45.7), 1110 (43.7)*1	←	←	←
	Overhang	Front mm (in.)	875 (34.4)	←	←	←
		Rear mm (in.)	985 (38.8)	←	←	←
	Min. Running Ground Clearance	mm (in.)	155 (6.1)	←	←	←
	Angle of Approach	degrees	17.7°	←	←	←
	Angle of Departure	degrees	18.4°	←	←	←
	Curb Weight	Front kg (lb)	685 ~ 745 (1510 ~ 1642)	←	715 ~ 775 (1576 ~ 1709)	725 ~ 780 (1598 ~ 1720)
		Rear kg (lb)	505 ~ 540 (1113 ~ 1190)	←	←	515 ~ 540 (1135 ~ 1190)
		Total kg (lb)	1190 ~ 1285 (2623 ~ 2832)	←	1220 ~ 1315 (2690 ~ 2899)	1240 ~ 1320 (2733 ~ 2910)
Performance	Gross Vehicle Weight	Front kg (lb)	860 (1896)	←	890 (1962)	920 (2028)
		Rear kg (lb)	870 (1918)	←	←	880 (1940)
		Total kg (lb)	1730 (3814)	←	1760 (3880)	1800 (3968)
	Fuel Tank Capacity	ℓ (Imp.gal.)	60 (13.2)	←	←	←
	Luggage Compartment Capacity	m ³ (cu.ft.)	0.50 (17.7)	←	←	←
	Max. Speed	km/h (mph)	—	—	—	—
	Max. Cruising Speed	km/h (mph)	—	—	—	—
	Acceleration	0 to 100 km/h sec.	—	—	—	—
		0 to 400 m sec.	—	—	—	—
	Max. Permissible Speed	1st Gear km/h (mph)	47 (29)	←	62 (38)	52 (32)
		2nd Gear km/h (mph)	87 (54)	←	114 (70)	87 (54)
		3rd Gear km/h (mph)	127 (78)	←	—	130 (80)
		4th Gear km/h (mph)	—	—	—	—
	Min. Turning Radius	Tire m (ft.)	5.4 (17.7)	←	←	←
		Body m (ft.)	5.8 (19.0)	←	←	←
Engine	Engine Type		4A-FE	←	←	3S-FE
	Valve Mechanism		16-Valve, DOHC	←	←	←
	Bore x Stroke mm (in.)		81.0 x 77.0 (3.19 x 3.03)	←	←	86.0 x 86.0 (3.39 x 3.39)
	Displacement cm ³ (cu.in.)		1587 (96.8)	←	←	1998 (121.9)
	Compression Ratio		9.5 : 1	←	←	9.8 : 1
	Carburetor Type or Injection Pump Type (Diesel)		EFI	←	←	←
	Research Octane No. or Cetane No. (Diesel)		90 or 95	←	←	←
	Max. Output (EEC) kW / rpm		81 / 6000	←	←	91 / 5600
	Max. Torque (EEC) N·m / rpm		145 / 4800	←	←	178 / 4400
	Battery Capacity (5HR) Voltage & Amp. hr.		12-32, 48*4	←	←	←
Engine Electrical	Alternator Output Watts		960	←	←	←
	Starter Output kW		1.1	←	←	1.0, 1.2*4
Chassis	Clutch Type		Dry, Single	←	—	Dry, Single
	Transaxle Type		C50	←	A245E	S54
	Transmission Gear Ratio	In First	3.545	←	3.643	3.285
		In Second	1.904	←	2.008	1.960
		In Third	1.310	←	1.296	1.322
		In Fourth	0.969	←	0.892	1.028
		In Fifth	0.815	←	—	0.820
		In Reverse	3.250	←	2.977	3.153
	Counter Gear Ratio		—	—	—	—
	Differential Gear Ratio (Final)		4.058	←	3.178	3.944
	Brake Type	Front	Ventilated Disc	←	←	←
		Rear	Leading Trailing Drum	←	←	←
	Parking Brake Type		Drum	←	←	←
	Brake Booster Type and Size in.		Single, 9"	←	←	←
	Proportioning Valve Type		Dual-P Valve	←	←	←
	Suspension Type	Front	MacPherson Strut	←	←	←
		Rear	MacPherson Strut	←	←	←
	Stabilizer Bar	Front	STD	←	←	←
		Rear	STD	←	←	←
	Steering Gear Type		Rack and Pinion	←	←	←
	Steering Gear Ratio (Overall)		17.39	←	←	←
	Power Steering Type		Integral Type	←	←	←

*1: With Moon Roof

*4: Option

*5: Mechanically Controlled

General Countries				
4-Door Sedan				
—				
	ST220L-AEMNK	ST220R-AEPNK	ST220L-AEPNK	CT220L-AEMNX
5	←	←	←	←
	←	←	←	←
	←	←	←	←
	←	←	←	←
	←	←	←	←
10	←	←	←	←
	←	←	←	←
	←	←	←	←
	←	←	←	←
	←	←	←	←
15	←	←	←	←
	←	←	←	←
	←	←	←	←
	←	←	←	←
	←	750 ~ 805 (1654 ~ 1775)	←	755 ~ 855 (1665 ~ 1885)
20	←	←	←	510 ~ 540 (1124 ~ 1190)
	←	1265 ~ 1345 (2789 ~ 2965)	←	1265 ~ 1395 (2789 ~ 3075)
	←	←	←	950 (2094)
	←	←	←	880 (1940)
	←	←	←	1830 (4034)
25	←	←	←	←
	←	←	←	←
	—	—	—	—
	—	—	—	—
	—	—	—	—
30	—	—	—	—
	←	58 (36)	←	42 (26)
	←	106 (65)	←	73 (45)
	←	—	—	113 (70)
	—	—	—	—
35	←	←	←	←
	←	←	←	←
	←	←	←	2C-T
	←	←	←	8-Valve, OHC
	←	←	←	86.0 x 85.0 (3.39 x 3.35)
40	←	←	←	1975 (120.5)
	←	←	←	23.0 : 1
	←	←	←	Distributor Type*5
	←	←	←	48
	←	←	←	60 / 4000
45	←	←	←	170 / 2000 ~ 3000
	←	←	←	12-64
	←	←	←	1080
	←	←	←	2.0
	←	—	—	Dry, Single
50	←	A241E	←	S50
	←	3.643	←	3.538
	←	2.008	←	2.041
	←	1.296	←	1.322
	←	0.892	←	0.945
55	←	—	—	0.731
	←	2.977	←	3.153
	—	—	—	—
	←	3.178	←	3.736
	←	←	←	←
60	←	←	←	←
	←	←	←	←
	←	←	←	←
	←	←	←	←
65	←	←	←	←
	←	←	←	←
	←	←	←	←
	←	←	←	←
	←	←	←	←
70	←	←	←	←

– MEMO –