TIRE & WHEEL

SERVICE DATA

032HP–02

Cold tire inflation pressure (1MZ–FE)	with 4 or less occupants		
	Tire size: 215/60R16 95V	Front, Rear*3	230 kPa (2.3 kgf/cm^2, 33 psi)
		Front, Rear*4	250 kPa (2.5 kgf/cm^2, 36 psi)
		Front, Rear*2	280 kPa (2.8 kgf/cm^2, 41 psi)
	Tire size: 205/65R15 94V	Front, Rear*1	230 kPa (2.3 kgf/cm^2, 33 psi)
		Front, Rear*2	260 kPa (2.6 kgf/cm^2, 38 psi)
	with 5 or more occupants		
	Tire size: 215/60R16 95V	Front, Rear*3	230 kPa (2.3 kgf/cm^2, 33 psi)
		Front, Rear*4	260 kPa (2.6 kgf/cm^2, 38 psi)
		Front, Rear*2	290 kPa (2.9 kgf/cm^2, 42 psi)
	Tire size: 205/65R15 94V	Front, Rear*1	260 kPa (2.6 kgf/cm^2, 38 psi)
		Front, Rear*2	280 kPa (2.8 kgf/cm^2, 41 psi)
Cold tire inflation pressure (2AZ–FE)	with 4 or less occupants		
	Tire size: 215/60R16 95V	Front, Rear*3	210 kPa (2.1 kgf/cm^2, 30 psi)
		Front, Rear*4	230 kPa (2.3 kgf/cm^2, 33 psi)
		Front, Rear*3	260 kPa (2.6 kgf/cm^2, 38 psi)
	Tire size: 205/65R15 94V	Front, Rear*1	230 kPa (2.3 kgf/cm^2, 33 psi)
		Front, Rear*2	260 kPa (2.6 kgf/cm^2, 38 psi)
	with 5 or more occupants		
	Tire size: 215/60R16 95V	Front, Rear*3	210 kPa (2.1 kgf/cm^2, 30 psi)
		Front, Rear*4	260 kPa (2.6 kgf/cm^2, 38 psi)
		Front, Rear*2	290 kPa (2.9 kgf/cm^2, 42 psi)
	Tire size: 205/65R15 94V	Front, Rear*1	260 kPa (2.6 kgf/cm^2, 38 psi)
		Front, Rear*2	280 kPa (2.8 kgf/cm^2, 41 psi)

Tire runout	1.0 mm (0.039 in.) or less
Imbalance after adjustment	8.0 g (0.018 lb) or less

***1: For driving under 210 km/h (131 mph)**

***2: For driving at 210 km/h (131 mph) or over**

***3: For driving under 160 km/h (100 mph)**

***4: For driving at 160 km/h (100 mph) to 210 km/h (131 mph)**