LUBRICATION

030F6–03

SERVICE DATA

1AZ–FE

Oil pressure	at idle speed	29 kPa (0.3 kgf·cm^2, 4.3 psi) or more
	at 3,000 rpm	245 – 539 kPa (2.5 – 5.5 kgf·cm^2, 36 – 78 psi) or more
Engine oil		
Oil capacity	Drain and refill w/ oil filter change	3.7 liters (3.9 US qts, 3.3 lmp. qts)
	Drain and refill w/o oil filter change	3.5 liters (3.7 US qts, 3.0 lmp. qts)
	Dry fill	4.4 liters (4.6 US qts, 3.9 lmp. qts)

2AZ–FE

Oil pressure	at idle speed	29 kPa (0.3 kgf·cm^2, 4.3 psi) or more
	at 3,000 rpm	245 – 539 kPa (2.5 – 5.5 kgf·cm^2, 36 – 78 psi) or more
Engine oil		
Oil capacity	Drain and refill w/ oil filter change	4.3 liters (4.5 US qts, 3.8 lmp. qts)
	Drain and refill w/o oil filter change	4.1 liters (4.3 US qts, 3.6 lmp. qts)
	Dry fill	5.0 liters (5.3 US qts, 4.4 lmp. qts)

1MZ–FE

Oil pressure	at idle speed	29 kPa (0.3 kgf·cm^2, 4.3 psi) or more
	at 3,000 rpm	294 – 539 kPa (3.0 – 5.5 kgf·cm^2, 36 – 78 psi) or more
Engine oil		
Oil capacity	Drain and refill w/ oil filter change	4.7 liters (5.0 US qts, 4.1 lmp. qts)
	Drain and refill w/o oil filter change	4.5 liters (4.8 US qts, 4.0 lmp. qts)
	Dry fill	5.5 liters (5.8 US qts, 4.8 lmp. qts)