030HB–01

TORQUE SPECIFICATION

Part Tightened		N·m	kgf·cm	ft·lbf
Bleeder plug		8.3	85	74 in.·lbf
Brake booster clevis lock nut		26	265	19
Brake pedal sub–assy set bolt		37	375	27
Stop lamp lock nut		26	265	19
Brake pedal support assy x Reinforcement		20	204	15
Brake pedal support assy x Body		13	130	9
Master cylinder piston stopper bolt	w/o VSC:	10	100	7
Brake master cylinder x Brake booster		13	130	9
Brake line union nut		15	155	11
Vacuum hose bracket set bolt		5.4	55	48 in.·lbf
Chacoal canister bracket set bolt		43	440	32
Engine cover assy No. 1 set nut		7.0	71	62 in.·lbf
Wheel nut		103	1,050	76
Front brake cylinder mounting x Steering knuckle		107	1,090	79
Front brake cylinder x Front brake cylinder mounting		34	350	25
Front brake cylinder x Flexible hose		29.4	300	22
Rear disc brake cylinder mounting set bolt		62	630	46
Rear disc brake cylinder slide pin x Rear disc brake cylinder mounting				
	Upper side:	34	350	25
	Lower side:	39	400	29
Rear disc brake cylinder x Flexible hose		29	300	22
Brake actuator assy x Actuator bracket		5.4	55	48 in.·lbf
Brake actuator bracket x Body		19	194	14
ABS & TRAC actuator assy x Actuator bracket		5.4	55	48 in.·lbf
ABS & TRACTION actuator bracket x Body		19	194	14
Front speed sensor x Steering knuckle		8.0	82	71 in.·lbf
Front speed sensor wire harness clamp x shock absorber	Bolt A:	5.0	51	44 in.·lbf
	Bolt B:	18.8	192	14
Rear axle hub set bolt		80	816	59
Yawrate sensor x Body		12.5	127	9
Skid control ECU x Body		5.5	56	49 in.·lbf