
DTC B1180/17 SHORT IN D SQUIB (2ND STEP) CIRCUIT

CIRCUIT DESCRIPTION

The D squib (2nd step) circuit consists of the airbag sensor assy center, spiral cable sub–assy and horn button assy.
It causes the SRS to deploy when the SRS deployment conditions are satisfied.
DTC B1180/17 is recorded when a short is detected in the D squib (2nd step) circuit.


DTC No.	DTC Detecting Condition	Trouble Area
B1180/17	• Short circuit between D2+ wire harness and D2– wire harness of squib (2nd step) • D squib (2nd step) malfunction • Spiral cable sub–assy malfunction • Airbag sensor assy center malfunction	• Horn button assy (D squib, 2nd step) • Spiral cable sub–assy • Airbag sensor assy center • Instrument panel wire

WIRING DIAGRAM



INSPECTION PROCEDURE

1	CHECK D SQUIB CIRCUIT(AIRBAG SENSOR ASSY CENTER – HORN BUTTON ASSY)




(a) Disconnect the negative (–) terminal cable from the battery, and wait at least for 90 seconds.
(b) Disconnect the connectors between the airbag sensor assy center and the horn button assy.
(c) Release the airbag activation prevention mechanism of the connector (on the airbag sensor assy center side) between the airbag sensor assy center and the spiral cable sub–assy (See page 05–758).
(d) For the black connector (on the spiral cable sub–assy side) between the spiral cable sub–assy and the horn button assy, measure the resistance between D2+ and D2–.
OK:
Resistance: 1 MΩ or Higher

NG	Go to step 4

OK

2	CHECK AIR BAG SENSOR ASSY CENTER

SST 09843–18040



(a) Connect the connector to the airbag sensor assy center.
(b) Connect the negative (–) terminal cable to the battery, and wait at least for 2 seconds.
(c) Turn the ignition switch to ON, and wait at least for 20 seconds.
(d) Clear the DTC stored in memory (See page 05–758).
(e) Turn the ignition switch to LOCK, and wait at least for 20 seconds.
(f) Turn the ignition switch to ON, and wait at least for 20 seconds.
(g) Check the DTC (See page 05–758).
OK:
DTC B1180/17 is not output.


HINT:
Codes other than code B1180/17 may be output at this time, but they are not relevant to this check.

NG	REPLACE AIR BAG SENSOR ASSY CENTER

OK

3	CHECK D SQUIB

SST 09843–18040



(a) Turn the ignition switch to LOCK.
(b) Disconnect the negative (–) terminal cable from the battery, and wait at least for 90 seconds.
(c) Connect the horn button assy connectors.
(d) Connect the negative (–) terminal cable to the battery, and wait at least for 2 seconds.
(e) Turn the ignition switch to ON, and wait at least for 20 seconds.
(f) Clear the DTC stored in memory (See page 05–758).
(g) Turn the ignition switch to LOCK, and wait at least for 20 seconds.
(h) Turn the ignition switch to ON, and wait at least for 20 seconds.
(i) Check the DTC (See page 05–758).

OK:

DTC B1180/17 is not output.

HINT:


Codes other than code B1180/17 may be output at this time, but they are not relevant to this check.

NG → **REPLACE HORN BUTTON ASSY**

OK

USE SIMULATION METHOD TO CHECK

4	CHECK WIRE HARNESS(AIRBAG SENSOR ASSY CENTER – SPIRAL CABLE SUB–ASSY)




(a) Disconnect the connector of the instrument panel wire.
(b) Release the airbag activation prevention mechanism of the connector (on the airbag sensor assy center side) between the airbag sensor assy center and the spiral cable sub–assy (See page 05–758).
(c) For the connector (on the spiral cable sub–assy side) between the airbag sensor assy center and the spiral cable sub–assy, measure the resistance between D2+ and D2–.
OK:
Resistance: 1 MΩ or Higher

NG	REPAIR OR REPLACE WIRE HARNESS(AIRBAG SENSOR ASSY CENTER – SPIRAL CABLE SUB–ASSY)

OK

5	CHECK SPIRAL CABLE SUB–ASSY



(a) Release the airbag activation prevention mechanism of the spiral cable sub–assy connector on the airbag sensor assy center side (See page 05–758).
(b) For the black connector (on the spiral cable sub–assy side) between the horn button assy and the spiral cable sub–assy, measure the resistance between D2+ and D2–.
OK:
Resistance: 1 MΩ or Higher

NG	REPLACE SPIRAL CABLE SUB–ASSY

OK

USE SIMULATION METHOD TO CHECK