■ PERFORMANCE AND SPECIFICATION

1. Performance

Heater	Heat Output	W	6000
	Air Flow Volume	m^3/h	360
	Power Consumption	W	Maximum 210
Air Conditioner	Cooling Capacity	W	6100
	Air Flow Volume	m^3/h	530
	Power Consumption	W	Maximum 260

2. Specifications

Ventilation and Heater Core	Heater Core	Type		SFA (Straight Flow Aluminum)-II
		Size W x H x L mm (in.)		201.5 x 150 x 27 (7.9 x 5.9 x 1.1)
		Fin Pitch mm (in.)		1.5 (0.06)
	Blower	Motor Type		K70 BMM
		Fan Type		Semi Sirocco
		Fan Size Dia. x H mm (in.)		165 x 70 (6.5 x 2.8)
Air Conditioner	Condenser	Type		MF (Multi-Flow)-IV
		Size W x H x L mm (in.)		720 x 370.2 x 16 (28.3 x 14.6 x 0.6)
		Fin Pitch mm (in.)		3.15 (0.12)
	Evaporator	Type		RS (Revolutionary super-slim Structure)
		Size W x H x L mm (in.)		266.3 x 251 x 38 (10.5 x 9.9 x 1.5)
		Fin Pitch mm (in.)		2.6 (0.1)
	Compressor	Type	2GR-FE	6SBU16
			2AZ-FE 1AZ-FE	6SEU16
		Pulley	2GR-FE	Steel with Magnetic Clutch
			2AZ-FE 1AZ-FE	DL (Damper Limiter) without Magnetic Clutch
	Refrigerant	Type		HFC 134a
		Charge Volume g		450 to 550