MAJOR TECHNICAL SPECIFICATIONS

Area			Australia			
Vehicle Grade			Altise		Ateva	Grande
Model Code			ACV40R-DEMDKQ	ACV40R-DEADKQ	ACV40R-DEANKQ	ACV40R-DEAGKQ
Major Dimensions & Vehicle Weights						
Overall	Length	mm (in.)	4805 (189.2)	4805 (189.2)	4805 (189.2)	4805 (189.2)
	Width	mm (in.)	1820 (71.7)	1820 (71.7)	1820 (71.7)	1820 (71.7)
	Height	mm (in.)	1470 (57.9)	1470 (57.9)	1470 (57.9)	1470 (57.9)
Wheel Base		mm (in.)	2775 (109.3)	2775 (109.3)	2775 (109.3)	2775 (109.3)
Tread	Front	mm (in.)	1575 (62.0)	1575 (62.0)	1575 (62.0)	1575 (62.0)
	Rear	mm (in.)	1565 (61.6)	1565 (61.6)	1565 (61.6)	1565 (61.6)
Room	Length	mm (in.)	2130 (83.8)	2130 (83.8)	2130 (83.8)	2130 (83.8)
	Width	mm (in.)	1525 (60.0)	1525 (60.0)	1525 (60.0)	1525 (60.0)
	Height	mm (in.)	1200 (47.2)	1200 (47.2)	1200 (47.2), 1140 (44.9)*1	1140 (44.9)
Overhang	Front	mm (in.)	945 (37.2)	945 (37.2)	945 (37.2)	945 (37.2)
	Rear	mm (in.)	1085 (42.7)	1085 (42.7)	1085 (42.7)	1085 (42.7)
Min. Running Ground Clearance		mm (in.)	150 (5.9)	150 (5.9)	150 (5.9)	150 (5.9)
Angle of Approach/Departure		degrees	-/-	-/-	-/-	-/-
Curb Weight	Front	kg (lb)	850 to 845 (1874 to 1863)	890 (1962)	895 to 900 (1973 to 1984)	905 (1995)
	Rear	kg (lb)	610 to 615 (1345 to 1356)	605 to 610 (1334 to 1345)	610 to 630 (1345 to 1389)	620 to 625 (1367 to 1378)
	Total	kg (lb)	1460 (3219)	1495 to 1500 (3296 to 3307)	1505 to 1530 (3318 to 3373)	1525 to 1530 (3362 to 3373)
Gross Vehicle Weight	Front	kg (lb)	925 (2039)	970 (2138)	990 (2183)	995 (2194)
	Rear	kg (lb)	1050 (2315)	1045 (2304)	1025 (2260)	1020 (2249)
	Total	kg (lb)	1975 (4354)	2015 (4442)	2015 (4442)	2015 (4442)
Luggage Compartment Capacity (VDA)		m^3 (cu.ft.)	0.535 (18.9)	0.535 (18.9)	0.535 (18.9)	0.535 (18.9)
Fuel Tank Capacity		L (Us.gal, Imp.gal)	70 (18.5, 15.5)	70 (18.5, 15.5)	70 (18.5, 15.5)	70 (18.5, 15.5)
Performance						
Max. Speed		km/h	200	200	200	200
Max. Cruising Speed		km/h	-	-	-	-
Acceleration	0 to 100 km/h	sec.	-	-	-	-
	0 to 400 m	sec.	-	-	-	-
Max. Permissible Speed	1st Gear	km/h	53	53	53	53
	2nd Gear	km/h	93	95	95	95
	3rd Gear	km/h	142	148	148	148
	4th Gear	km/h	195	-	-	-
	5th Gear	km/h	-	-	-	-
	6th Gear	km/h	-	-	-	-
Min. Turning Radius	Tire	m	5.5	5.5	5.5	5.5
	Body	m	5.9	5.9	5.9	5.9
Engine						
Engine Type			2AZ-FE	2AZ-FE	2AZ-FE	2AZ-FE
No. of Cyls. & Arrangement			4-cylinder, In-line	4-cylinder, In-line	4-cylinder, In-line	4-cylinder, In-line
Valve Mechanism			16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i
Bore × Stroke		mm (in.)	88.5 × 96.0 (3.48 × 3.78)	88.5 × 96.0 (3.48 × 3.78)	88.5 × 96.0 (3.48 × 3.78)	88.5 × 96.0 (3.48 × 3.78)
Displacement		cm^3 (cu.in.)	2362 (144.1)	2362 (144.1)	2362 (144.1)	2362 (144.1)
Compression Ratio			9.6 : 1	9.6 : 1	9.6 : 1	9.6 : 1
Fuel System			EFI	EFI	EFI	EFI
Reserch Octane No. or Cetane No.			91 or higher	91 or higher	91 or higher	91 or higher
Max. Output (EEC)		kW@rpm	117@5700	117@5700	117@5700	117@5700
Max. Torque (EEC)		N·m@rpm	218@4000	218@4000	218@4000	218@4000
Engine Electrical						
Battery Capacity (5HR)		Voltage & Amp. hr.	12-48	12-48	12-48	12-48
Alternator Output		Watts	960	960	960	960
Starter Output		kW	1.6	1.6	1.6	1.6
Chassis						
Transaxle Type			E354 M/T	U250E A/T	U250E A/T	U250E A/T
Transmission Gear Ratio	1st		3.538	3.943*3	3.943*3	3.943*3
	2nd		2.045	2.197*3	2.197*3	2.197*3
	3rd		1.333	1.413*3	1.413*3	1.413*3
	4th		1.028	0.975*3	0.975*3	0.975*3
	5th		0.820	0.703*3	0.703*3	0.703*3
	6th		-	-	-	-
	Reverse		3.583	3.145*3	3.145*3	3.145*3
Differential (Final) Gear Ratio			3.944	3.391	3.391	3.391
Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
	Rear		Solid Disc	Solid Disc	Solid Disc	Solid Disc
Suspension Type	Front		MacPherson Strut	MacPherson Strut	MacPherson Strut	MacPherson Strut
	Rear		MacPherson Strut	MacPherson Strut	MacPherson Strut	MacPherson Strut
Stabilizer Bar		Front/Rear	Standard/Standard	Standard/Standard	Standard/Standard	Standard/Standard
Steering Gear Type			Rack & Pinion	Rack & Pinion	Rack & Pinion	Rack & Pinion
Steering Gear Ratio			15.9	15.9	15.9	15.9
Power Steering Type			Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

*1: With sliding roof *3: Counter gear ratio included

*2: SAE−NET

Australia					
Sportivo		AT-X	Prodigy	Presara	Sportivo SX6
ACV40R-DEMVKQ	ACV40R-DEAVKQ	GSV40R-JETDKQ	GSV40R-JETNKQ	GSV40R-JETGKQ	GSV40R-JETSKQ
4805 (189.2)	4805 (189.2)	4825 (190.0)	4825 (190.0)	4825 (190.0)	4825 (190.0)
1820 (71.7)	1820 (71.7)	1820 (71.7)	1820 (71.7)	1820 (71.7)	1820 (71.7)
1470 (57.9)	1470 (57.9)	1470 (57.9)	1470 (57.9)	1470 (57.9)	1470 (57.9)
2775 (109.3)	2775 (109.3)	2775 (109.3)	2775 (109.3)	2775 (109.3)	2775 (109.3)
1575 (62.0)	1575 (62.0)	1575 (62.0)	1575 (62.0)	1575 (62.0)	1575 (62.0)
1565 (61.6)	1565 (61.6)	1565 (61.6)	1565 (61.6)	1565 (61.6)	1565 (61.6)
2130 (83.8)	2130 (83.8)	2130 (83.8)	2130 (83.8)	2130 (83.8)	2130 (83.8)
1525 (60.0)	1525 (60.0)	1525 (60.0)	1525 (60.0)	1525 (60.0)	1525 (60.0)
1200 (47.2), 1140 (44.9)*1	1200 (47.2), 1140 (44.9)*1	1200 (47.2)	1200 (47.2), 1140 (44.9)*1	1140 (44.9)	1200 (47.2), 1140 (44.9)*1
945 (37.2)	945 (37.2)	965 (38.0)	965 (38.0)	965 (38.0)	965 (38.0)
1085 (42.7)	1085 (42.7)	1085 (42.7)	1085 (42.7)	1085 (42.7)	1085 (42.7)
150 (5.9)	150 (5.9)	150 (5.9)	150 (5.9)	150 (5.9)	150 (5.9)
-/-	-/-	-/-	-/-	-/-	-/-
855 to 865 (1885 to 1907)	900 to 905 (1984 to 1995)	970 to 965 (2138 to 2127)	975 to 980 (2150 to 2161)	990 (2183)	975 to 980 (2150 to 2161)
620 to 630 (1367 to 1389)	615 to 630 (1356 to 1389)	615 to 625 (1356 to 1378)	620 to 630 (1367 to 1389)	630 to 635 (1389 to 1400)	625 to 635 (1378 to 1400)
1475 to 1495 (3252 to 3296)	1515 to 1535 (3340 to 3384)	1585 to 1590 (3494 to 3505)	1595 to 1610 (3516 to 3549)	1620 to 1625 (3571 to 3583)	1600 to 1615 (3527 to 3560)
955 (2105)	995 (2194)	1045 (2304)	1065 (2348)	1080 (2381)	1065 (2348)
1020 (2249)	1020 (2249)	1065 (2348)	1045 (2304)	1030 (2271)	1045 (2304)
1975 (4354)	2015 (4442)	2110 (4652)	2110 (4652)	2110 (4652)	2110 (4652)
0.504 (17.8)	0.504 (17.8)	0.504 (17.8)	0.504 (17.8)	0.504 (17.8)	0.504 (17.8)
70 (18.5, 15.5)	70 (18.5, 15.5)	70 (18.5, 15.5)	70 (18.5, 15.5)	70 (18.5, 15.5)	70 (18.5, 15.5)
200	200	228	228	228	228
-	-	-	-	-	-
-	-	-	-	-	-
-	-	-	-	-	-
53	53	60	60	60	60
93	95	104	104	104	104
142	148	139	139	139	139
195	-	198	198	198	198
-	-	-	-	-	-
-	-	-	-	-	-
5.5	5.5	5.5	5.5	5.5	5.5
5.9	5.9	5.9	5.9	5.9	5.9
2AZ-FE	2AZ-FE	2GR-FE	2GR-FE	2GR-FE	2GR-FE
4-cylinder, In-line	4-cylinder, In-line	6-cylinder, V Type	6-cylinder, V Type	6-cylinder, V Type	6-cylinder, V Type
16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i	24-valve, DOHC with Dual VVT-i	24-valve, DOHC with Dual VVT-i	24-valve, DOHC with Dual VVT-i	24-valve, DOHC with Dual VVT-i
88.5 × 96.0 (3.48 × 3.78)	88.5 × 96.0 (3.48 × 3.78)	94.0 × 83.0 (3.70 × 3.27)	94.0 × 83.0 (3.70 × 3.27)	94.0 × 83.0 (3.70 × 3.27)	94.0 × 83.0 (3.70 × 3.27)
2362 (144.1)	2362 (144.1)	3456 (210.9)	3456 (210.9)	3456 (210.9)	3456 (210.9)
9.6 : 1	9.6 : 1	10.8 : 1	10.8 : 1	10.8 : 1	10.8 : 1
EFI	EFI	EFI	EFI	EFI	EFI
91 or higher	91 or higher	91 or higher	91 or higher	91 or higher	91 or higher
117@5700	117@5700	200@6200*2	200@6200*2	200@6200*2	200@6200*2
218@4000	218@4000	336@4700*2	336@4700*2	336@4700*2	336@4700*2
12-48	12-48	12-48	12-48	12-48	12-48
960	960	1200	1200	1200	1200
1.6	1.6	1.7	1.7	1.7	1.7
E354 M/T	U250E A/T	U660E A/T	U660E A/T	U660E A/T	U660E A/T
3.538	3.943*3	3.300	3.300	3.300	3.300
2.045	2.197*3	1.900	1.900	1.900	1.900
1.333	1.413*3	1.420	1.420	1.420	1.420
1.028	0.975*3	1.000	1.000	1.000	1.000
0.820	0.703*3	0.713	0.713	0.713	0.713
-	-	0.608	0.608	0.608	0.608
3.583	3.145*3	4.148	4.148	4.148	4.148
3.944	3.391	3.685*3	3.685*3	3.685*3	3.685*3
Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
Solid Disc	Solid Disc	Solid Disc	Solid Disc	Solid Disc	Solid Disc
MacPherson Strut	MacPherson Strut	MacPherson Strut	MacPherson Strut	MacPherson Strut	MacPherson Strut
MacPherson Strut	MacPherson Strut	MacPherson Strut	MacPherson Strut	MacPherson Strut	MacPherson Strut
Standard/Standard	Standard/Standard	Standard/Standard	Standard/Standard	Standard/Standard	Standard/Standard
Rack & Pinion	Rack & Pinion	Rack & Pinion	Rack & Pinion	Rack & Pinion	Rack & Pinion
15.9	15.9	15.9	15.9	15.9	15.9
Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

Area			Australia	G.C.C. Countries		
Vehicle Grade			Sportivo ZR6	GL		GLX
Model Code			GSV40R-JETVKQ	ACV40L-DEMDKV	ACV40L-DEADKV	ACV40L-DEMNKV
Major Dimensions & Vehicle Weights						
Overall	Length	mm (in.)	4825 (190.0)	4805 (189.2)	4805 (189.2)	4805 (189.2)
	Width	mm (in.)	1820 (71.7)	1820 (71.7)	1820 (71.7)	1820 (71.7)
	Height	mm (in.)	1470 (57.9)	1470 (57.9)	1470 (57.9)	1470 (57.9)
Wheel Base		mm (in.)	2775 (109.3)	2775 (109.3)	2775 (109.3)	2775 (109.3)
Tread	Front	mm (in.)	1575 (62.0)	1575 (62.0)	1575 (62.0)	1575 (62.0)
	Rear	mm (in.)	1565 (61.6)	1565 (61.6)	1565 (61.6)	1565 (61.6)
Room	Length	mm (in.)	2130 (83.8)	2130 (83.8)	2130 (83.8)	2130 (83.8)
	Width	mm (in.)	1525 (60.0)	1525 (60.0)	1525 (60.0)	1525 (60.0)
	Height	mm (in.)	1200 (47.2), 1140 (44.9)*1	1200 (47.2)	1200 (47.2)	1200 (47.2), 1140 (44.9)*1
Overhang	Front	mm (in.)	965 (38.0)	945 (37.2)	945 (37.2)	945 (37.2)
	Rear	mm (in.)	1085 (42.7)	1085 (42.7)	1085 (42.7)	1085 (42.7)
Min. Running Ground Clearance		mm (in.)	150 (5.9)	150 (5.9)	150 (5.9)	150 (5.9)
Angle of Approach/Departure		degrees	-/-	-/-	-/-	-/-
Curb Weight	Front	kg (lb)	980 to 985 (2161 to 2172)	850 (1874)	890 (1962)	850 to 855 (1874 to 1885)
	Rear	kg (lb)	635 to 645 (1400 to 1422)	610 to 615 (1345 to 1356)	610 (1345)	615 to 620 (1356 to 1367)
	Total	kg (lb)	1615 to 1630 (3560 to 3594)	1460 to 1465 (3219 to 3230)	1500 (3307)	1465 to 1475 (3230 to 3252)
Gross Vehicle Weight	Front	kg (lb)	1075 (2370)	935 (2061)	975 (2150)	945 (2083)
	Rear	kg (lb)	1035 (2282)	1025 (2260)	1020 (2249)	1015 (2238)
	Total	kg (lb)	2110 (4652)	1960 (4321)	1995 (4398)	1960 (4321)
Luggage Compartment Capacity (VDA)		m^3 (cu.ft.)	0.504 (17.8)	0.535 (18.9)	0.535 (18.9)	0.535 (18.9)
Fuel Tank Capacity		L (Us.gal, Imp.gal)	70 (18.5, 15.5)	70 (18.5, 15.5)	70 (18.5, 15.5)	70 (18.5, 15.5)
Performance						
Max. Speed		km/h	228	200	200	200
Max. Cruising Speed		km/h	-	-	-	-
Acceleration	0 to 100 km/h	sec.	-	-	-	-
	0 to 400 m	sec.	-	-	-	-
Max. Permissible Speed	1st Gear	km/h	60	53	53	53
	2nd Gear	km/h	104	93	95	93
	3rd Gear	km/h	139	142	148	142
	4th Gear	km/h	198	195	-	195
	5th Gear	km/h	-	-	-	-
	6th Gear	km/h	-	-	-	-
Min. Turning Radius	Tire	m	5.5	5.5	5.5	5.5
	Body	m	5.9	5.9	5.9	5.9
Engine						
Engine Type			2GR-FE	2AZ-FE	2AZ-FE	2AZ-FE
No. of Cyls. & Arrangement			6-cylinder, V Type	4-cylinder, In-line	4-cylinder, In-line	4-cylinder, In-line
Valve Mechanism			24-valve, DOHC with Dual VVT-i	16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i
Bore × Stroke		mm (in.)	94.0 × 83.0 (3.70 × 3.27)	88.5 × 96.0 (3.48 × 3.78)	88.5 × 96.0 (3.48 × 3.78)	88.5 × 96.0 (3.48 × 3.78)
Displacement		cm^3 (cu.in.)	3456 (210.9)	2362 (144.1)	2362 (144.1)	2362 (144.1)
Compression Ratio			10.8 : 1	9.6 : 1	9.6 : 1	9.6 : 1
Fuel System			EFI	EFI	EFI	EFI
Reserch Octane No. or Cetane No.			91 or higher	91 or higher	91 or higher	91 or higher
Max. Output (EEC)		kW@rpm	200@6200*2	117@5700	117@5700	117@5700
Max. Torque (EEC)		N·m@rpm	336@4700*2	218@4000	218@4000	218@4000
Engine Electrical						
Battery Capacity (5HR)		Voltage & Amp. hr.	12-48	12-55, 12-60*3	12-55, 12-60*3	12-55
Alternator Output		Watts	1200	960	960	960
Starter Output		kW	1.7	1.6	1.6	1.6
Chassis						
Transaxle Type			U660E A/T	E354 M/T	U250E A/T	E354 M/T
Transmission Gear Ratio	1st		3.300	3.538	3.943*4	3.538
	2nd		1.900	2.045	2.197*4	2.045
	3rd		1.420	1.333	1.413*4	1.333
	4th		1.000	1.028	0.975*4	1.028
	5th		0.713	0.820	0.703*4	0.820
	6th		0.608	-	-	-
	Reverse		4.148	3.583	3.145*4	3.583
Differential (Final) Gear Ratio			3.685*4	3.944	3.391	3.944
Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
	Rear		Solid Disc	Solid Disc	Solid Disc	Solid Disc
Suspension Type	Front		MacPherson Strut	MacPherson Strut	MacPherson Strut	MacPherson Strut
	Rear		MacPherson Strut	MacPherson Strut	MacPherson Strut	MacPherson Strut
Stabilizer Bar		Front/Rear	Standard/Standard	Standard/Standard	Standard/Standard	Standard/Standard
Steering Gear Type			Rack & Pinion	Rack & Pinion	Rack & Pinion	Rack & Pinion
Steering Gear Ratio			15.9	15.9	15.9	15.9
Power Steering Type			Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

*1: With sliding roof *4: Counter gear ratio included
*2: SAE−NET
*3: Option

G.C.C. Countries				
GLX	SE		Touring	Grande
ACV40L-DEANKV	ACV40L-DEMSKV	ACV40L-DEASKV	GSV40L-JETDKV	GSV40L-JETGKV
4805 (189.2)	4805 (189.2)	4805 (189.2)	4825 (190.0)	4825 (190.0)
1820 (71.7)	1820 (71.7)	1820 (71.7)	1820 (71.7)	1820 (71.7)
1470 (57.9)	1470 (57.9)	1470 (57.9)	1470 (57.9)	1470 (57.9)
2775 (109.3)	2775 (109.3)	2775 (109.3)	2775 (109.3)	2775 (109.3)
1575 (62.0)	1575 (62.0)	1575 (62.0)	1575 (62.0)	1575 (62.0)
1565 (61.6)	1565 (61.6)	1565 (61.6)	1565 (61.6)	1565 (61.6)
2130 (83.8)	2130 (83.8)	2130 (83.8)	2130 (83.8)	2130 (83.8)
1525 (60.0)	1525 (60.0)	1525 (60.0)	1525 (60.0)	1525 (60.0)
1200 (47.2), 1140 (44.9)*1	1200 (47.2), 1140 (44.9)*1	1200 (47.2), 1140 (44.9)*1	1200 (47.2), 1140 (44.9)*1	1200 (47.2), 1140 (44.9)*1
945 (37.2)	945 (37.2)	945 (37.2)	965 (38.0)	965 (38.0)
1085 (42.7)	1085 (42.7)	1085 (42.7)	1085 (42.7)	1085 (42.7)
150 (5.9)	150 (5.9)	150 (5.9)	150 (5.9)	150 (5.9)
-/-	-/-	-/-	-/-	-/-
890 to 895 (1962 to 1973)	855 to 860 (1885 to 1896)	895 to 900 (1973 to 1984)	970 to 975 (2138 to 2150)	980 to 990 (2161 to 2183)
615 to 620 (1356 to 1369)	620 to 630 (1367 to 1389)	620 to 625 (1367 to 1378)	620 to 630 (1367 to 1389)	625 to 635 (1378 to 1400)
1505 to 1515 (3318 to 3340)	1475 to 1490 (3252 to 3285)	1515 to 1525 (3340 to 3362)	1590 to 1605 (3505 to 3538)	1605 to 1625 (3538 to 3583)
985 (2172)	950 (2094)	990 (2183)	1060 (2337)	1080 (2381)
1010 (2227)	1010 (2227)	1005 (2216)	1035 (2282)	1015 (2238)
1995 (4398)	1960 (4321)	1995 (4398)	2095 (4619)	2095 (4619)
0.535 (18.9)	0.504 (17.8)	0.504 (17.8)	0.535 (18.9)	0.535 (18.9)
70 (18.5, 15.5)	70 (18.5, 15.5)	70 (18.5, 15.5)	70 (18.5, 15.5)	70 (18.5, 15.5)
200	200	200	228	228
-	-	-	-	-
-	-	-	-	-
-	-	-	-	-
53	53	53	60	60
95	93	95	104	104
148	142	148	139	139
-	195	-	198	198
-	-	-	-	-
-	-	-	-	-
5.5	5.5	5.5	5.5	5.5
5.9	5.9	5.9	5.9	5.9
2AZ-FE	2AZ-FE	2AZ-FE	2GR-FE	2GR-FE
4-cylinder, In-line	4-cylinder, In-line	4-cylinder, In-line	6-cylinder, V Type	6-cylinder, V Type
16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i	24-valve, DOHC with Dual VVT-i	24-valve, DOHC with Dual VVT-i
88.5 × 96.0 (3.48 × 3.78)	88.5 × 96.0 (3.48 × 3.78)	88.5 × 96.0 (3.48 × 3.78)	94.0 × 83.0 (3.70 × 3.27)	94.0 × 83.0 (3.70 × 3.27)
2362 (144.1)	2362 (144.1)	2362 (144.1)	3456 (210.9)	3456 (210.9)
9.6 : 1	9.6 : 1	9.6 : 1	10.8 : 1	10.8 : 1
EFI	EFI	EFI	EFI	EFI
91 or higher	91 or higher	91 or higher	91 or higher	91 or higher
117@5700	117@5700	117@5700	200@6200*2	200@6200*2
218@4000	218@4000	218@4000	336@4700*2	336@4700*2
12-55	12-55	12-55	12-55	12-55
960	960	960	1200	1200
1.6	1.6	1.6	1.7	1.7
U250E A/T	E354 M/T	U250E A/T	U660E A/T	U660E A/T
3.943*4	3.538	3.943*4	3.300	3.300
2.197*4	2.045	2.197*4	1.900	1.900
1.413*4	1.333	1.413*4	1.420	1.420
0.975*4	1.028	0.975*4	1.000	1.000
0.703*4	0.820	0.703*4	0.713	0.713
-	-	-	0.608	0.608
3.145*4	3.583	3.145*4	4.148	4.148
3.391	3.944	3.391	3.685*4	3.685*4
Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
Solid Disc	Solid Disc	Solid Disc	Solid Disc	Solid Disc
MacPherson Strut	MacPherson Strut	MacPherson Strut	MacPherson Strut	MacPherson Strut
MacPherson Strut	MacPherson Strut	MacPherson Strut	MacPherson Strut	MacPherson Strut
Standard/Standard	Standard/Standard	Standard/Standard	Standard/Standard	Standard/Standard
Rack & Pinion	Rack & Pinion	Rack & Pinion	Rack & Pinion	Rack & Pinion
15.9	15.9	15.9	15.9	15.9
Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type