MAJOR TECHNICAL SPECIFICATIONS

Item \ Area				Europe			Australia
Body Type				High Roof			High Roof
Vehicle Grade				Standard		Standard (With Air Conditioner)	Standard
Model Code				XZB50R-ZRMRYW1	XZB50L-ZRMRYW1	XZB50L-ZRMSYW1	XZB50R-ZEMRYQ
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	—	—	—	6990 (275.2)
		Width	mm (in.)	—	—	—	2095 (82.5), 2195 (86.4)*1
		Height	mm (in.)	—	—	—	2445 (96.2)
	Wheel Base		mm (in.)	3935 (154.9)	3935 (154.9)	3935 (154.9)	3935 (154.9)
	Tread	Front	mm (in.)	1690 (66.5)	1690 (66.5)	1690 (66.5)	1690 (66.5)
		Rear	mm (in.)	1554 (61.2)	1554 (61.2)	1554 (61.2)	1490 (58.7)
	Room	Length	mm (in.)	—	—	—	6230 (245.3)
		Width	mm (in.)	—	—	—	1890 (74.4)
		Height	mm (in.)	—	—	—	1665 (65.6)
	Cargo Space	Length	mm (in.)	—	—	—	—
		Width	mm (in.)	—	—	—	—
		Height	mm (in.)	—	—	—	—
	Overhang	Front	mm (in.)	—	—	—	1150 (45.3)
		Rear	mm (in.)	—	—	—	1905 (75.0)
	Min. Running Ground Clearance		mm (in.)	—	—	—	185 (7.3)
	Angle of Approach		degrees	—	—	—	18
	Angle of Departure		degrees	—	—	—	14
	Curb Weight	Front	kg (lb)	—	—	—	1630 - 1635 (3594 - 3605)
		Rear	kg (lb)	—	—	—	1590 - 1615 (3505 - 3560)
		Total	kg (lb)	—	—	—	3220 - 3250 (7099 - 7165)
	Gross Vehicle Weight	Front	kg (lb)	—	—	—	2200 (4850)
		Rear	kg (lb)	—	—	—	2790 (6151)
		Total	kg (lb)	—	—	—	4990 (11001)
	Fuel Tank Capacity		ℓ (Imp.gal)	95 (20.9)	95 (20.9)	95 (20.9)	95 (20.9)
	Luggage Compartment Capacity		m^3 (cu.ft.)	—	—	—	0.411 (14.5)
Performance	Max. Speed		km / h (mph)	—	—	—	—
	Max. Cruising Speed		km / h (mph)	—	—	—	—
	Max. Permissible Speed	1st Gear	km / h (mph)	15 (9)	15 (9)	15 (9)	15 (9)
		2nd Gear	km / h (mph)	30 (19)	30 (19)	30 (19)	30 (19)
		3rd Gear	km / h (mph)	50 (31)	50 (31)	50 (31)	50 (31)
		4th Gear	km / h (mph)	85 (53)	85 (53)	85 (53)	85 (53)
		5th Gear	km / h (mph)	—	—	—	—
	Min. Turning Radius	Tire	m (ft.)	7.2 (23.6)	7.2 (23.6)	7.2 (23.6)	7.2 (23.6)
		Body	m (ft.)	7.9 (25.9)	7.9 (25.9)	7.9 (25.9)	7.9 (25.9)
Engine	Engine Type			N04C-TQ	N04C-TQ	N04C-TQ	N04C-TQ
	Valve Mechanism			16-valve OHV	16-vale OHV	16-valve OHV	16-valve OHV
	Bore x Stroke		mm (in.)	104.0 x 118.0 (4.09 x 4.65)	104.0 x 118.0 (4.09 x 4.65)	104.0 x 118.0 (4.09 x 4.65)	104.0 x 118.0 (4.09 x 4.65)
	Displacement		cm^3 (cu.in.)	4009 (244.6)	4009 (244.6)	4009 (244.6)	4009 (244.6)
	Compression Ratio			18.0 : 1	18.0 : 1	18.0 : 1	18.0 : 1
	Fuel System			Common-rail Type	Common-rail Type	Common-rail Type	Common-rail Type
	Research Octane No. or Cetane No. (Diesel)			48 or higher	48 or higher	48 or higher	48 or higher
	Max. Output		kW / rpm	110/2700 (EEC)	110/2700 (EEC)	110/2700 (EEC)	110/2700 (EEC)
	Max. Torque		N·m / rpm	397/1800 (EEC)	397/1800 (EEC)	397/1800 (EEC)	397/1800 (EEC)
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp. hr.	24	24	24	24
	Alternator Output		Watts	1920	1920	1920	1440
	Starter Output		kW	5.0	5.0	5.0	5.0
Chassis	Clutch Type			Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm
	Transmission Type			M551	M551	M551	M551
	Gear Ratio	In First		5.099	5.099	5.099	5.099
		In Second		2.910	2.910	2.910	2.910
		In Third		1.652	1.652	1.652	1.652
		In Fourth		1.000	1.000	1.000	1.000
		In Fifth		0.674	0.674	0.674	0.674
		In Reverse		4.625	4.625	4.625	4.625
	Differential Gear Ratio			5.375	5.375	5.375	5.375
	Differential Gear Size		in.	10.5	10.5	10.5	10.5
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear		Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum
	Parking Brake Type			Drum	Drum	Drum	Drum
	Brake Booster Type and Size		in.	Tandem, 9" + 10"	Tandem, 9" + 10"	Tandem, 9" + 10"	Tandem, 9" + 10"
	Proportioning Valve Type			LSP and BV	LSP and BV	LSP and BV	LSP and BV
	Suspension Type	Front		Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
		Rear		Leaf Spring	Leaf Spring	Leaf Spring	Leaf Spring
	Stabilizer Bar	Front		—	—	—	—
		Rear		Standard	Standard	Standard	—
	Steering Gear Type			Recirculating Ball	Recirculating Ball	Recirculating Ball	Recirculating Ball
	Steering Gear Ratio (Overall)			17.6	17.6	17.6	17.6
	Power Steering Type			Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

*1: With Snorkel Cleaner Air Duct
*2: 7.00 R16 Tire (Option)
*3: Option

	Australia		G.C.C. Countries			
	High Roof		Standard Roof		High Roof	Standard Roof
	Standard (With Air Conditioner)	DX	Standard (With Air Conditioner)			
	XZB50R-ZEMSYQ	XZB50R-ZEMNYQ	BB42L-BRMSSV	HZB50L-BGMSSV	HZB50L-ZGMSSV	RZB40L-BRMSKV
5	6990 (275.2)	6990 (275.2)	6255 (246.6)	6990 (275.2)	6990 (275.2)	6255 (246.6)
	2095 (82.5), 2195 (86.4)*1	2095 (82.5) 2195 (86.4)*1	2025 (79.7), 2195(86.4)*1	2025 (79.7), 2195 (86.4)*1	2025 (79.7), 2195 (86.4)*1	2025 (79.7), 2195 (86.4)*1
	2600 (102.4)	2600 (102.4)	2430 (95.7)	2445 (96.2)	2600 (102.4)	2430 (95.7)
	3935 (154.9)	3935 (154.9)	3200 (126.0)	3935 (154.9)	3935 (154.9)	3200 (126.0)
	1690 (66.5)	1690 (66.5)	1690 (66.5)	1690 (66.5)	1690 (66.5)	1690 (66.5)
10	1490 (58.7)	1490 (58.7)	1490 (58.7)	1490 (58.7)	1490 (58.7)	1490 (58.7)
	6230 (245.3)	6230 (245.3)	5490 (216.1)	6230 (245.3)	6230 (245.3)	5490 (216.1)
	1890 (74.4)	1890 (74.4)	1900 (74.8)	1890 (74.4)	1890 (74.4)	1900 (74.8)
	1830 (72.0)	1830 (72.0)	1665 (65.6)	1665 (65.6)	1830 (72.0)	1665 (65.6)
	—	—	—	—	—	—
15	—	—	—	—	—	—
	—	—	—	—	—	—
	1150 (45.3)	1150 (45.3)	1150 (45.3)	1150 (45.3)	1150 (45.3)	1150 (45.3)
	1905 (75.0)	1905 (75.0)	1905 (75.0)	1905 (75.0)	1905 (75.0)	1905 (75.0)
	185 (7.3)	175 (6.9)	175 (6.9)	185 (7.3)	185 (7.3)	175 (6.9)
20	18	17	17, 18*2	18	18	17
	14	14	14	14	14	14
	1720 - 1725 (3792 - 3803)	1730 - 1735 (3814 - 3825)	1490 - 1570 (3285 - 3461)	1645 - 1725 (3627 - 3803)	1645 - 1700 (3627 - 3748)	1335 - 1455 (2943 - 3208)
	1630 - 1655 (3593 - 3649)	1640 - 1665 (3616 - 3671)	1490 - 1660 (3285 - 3660)	1585 - 1750 (3494 - 3858)	1595 - 1705 (3516 - 3759)	1425 - 1635 (3142 - 3605)
	3350 - 3380 (7385 - 7452)	3370 - 3400 (7430 - 7496)	2980 - 3230 (6570 - 7121)	3230 - 3475 (7121 - 7661)	3240 - 3405 (7143 - 7507)	2760 - 3090 (6085 - 6812)
25	2200 (4850)	2200 (4850)	2020 (4453)	2400 (5291)	2400 (5291)	2020 (4453)
	2790 (6151)	2790 (6151)	3160 (6967)	3270 (7209)	3270 (7209)	2990 (6592)
	4990 (11001)	4990 (11001)	5180 (11420)	5670 (12500)	5670 (12500)	5010 (11045)
	95 (20.9)	95 (20.9)	95 (20.9)	95 (20.9)	95 (20.9)	95 (20.9)
	0.411 (14.5)	0.411 (14.5)	0.411 (14.5)	0.411 (14.5)	0.411 (14.5)	0.411 (14.5)
30	—	—	—	—	—	—
	—	—	—	—	—	—
	15 (9)	15 (9)	15 (9)	20 (12)	20 (12)	20 (12)
	30 (19)	30 (19)	30 (19)	35 (22)	35 (22)	40 (24)
	50 (31)	50 (31)	50 (31)	60 (37)	60 (37)	70 (43)
35	85 (53)	85 (53)	85 (53)	100 (62)	100 (62)	115 (71)
	—	—	—	—	—	—
	7.2 (23.6)	7.2 (23.6)	6.1 (20.0)	7.2 (23.6)	7.2 (23.6)	6.1 (20.0)
	7.9 (25.9)	7.9 (25.9)	6.8 (22.3)	7.9 (25.9)	7.9 (25.9)	6.8 (22.3)
	N04C-TQ	N04C-TQ	14B	1HZ	1HZ	3RZ-FE
40	16-valve OHV	16-valve OHV	8-valve OHV	12-valve OHC	12-valve OHC	16-valve DOHC
	104.0 x 118.0 (4.09 x 4.65)	104.0 x 118.0 (4.09 x 4.65)	102.0 x 112.0 (4.02 x 4.41)	94.0 x 100.0 (3.70 x 3.94)	94.0 x 100.0 (3.70 x 3.94)	95.0 x 95.0 (3.74 x 3.74)
	4009 (244.6)	4009 (244.6)	3661 (223.4)	4164 (254.1)	4164 (254.1)	2694 (164.4)
	18.0 : 1	18.0 : 1	18.0 : 1	22.4 : 1	22.4 : 1	9.5 : 1
	Common-rail Type	Common-rail Type	Distributor Type	Distributor Type	Distributor Type	EFI
45	48 or higher	48 or higher	50 or higher	50 or higher	50 or higher	90 or higher
	110/2700 (EEC)	110/2700 (EEC)	72 / 3400 (SAE-NET)	96 / 3800 (SAE-NET)	96 / 3800 (SAE-NET)	112 / 4800 (SAE-NET)
	397/1800 (EEC)	397/1800 (EEC)	240 / 1800 (SAE-NET)	280 / 2200 (SAE-NET)	280 / 2200 (SAE-NET)	240 / 4000 (SAE-NET)
	24 - 64 x 2	24 - 64 x 2	12 - 48	12 - 48	12 - 48	12 - 48
	1440	1440	1440	1440	1440	960
50	5.0	5.0	4.5	4.5	4.5	1.4
	Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm
	M551	M551	M152	M155	M155	M156
	5.099	5.099	4.802	4.535	4.535	5.657
	2.910	2.910	2.792	2.858	2.858	2.818
55	1.652	1.652	1.694	1.600	1.600	1.687
	1.000	1.000	1.000	1.000	1.000	1.000
	0.674	0.674	0.788	0.744	0.744	0.835
	4.625	4.625	5.339	5.043	5.043	5.657
	5.375	5.375	5.625	5.625	5.625	5.857
60	10.5	10.5	10.5	10.5	10.5	10.5
	Ventilated Disc	Ventilated Disc	Two Leading Drum, Ventilated Disc*3	Two Leading Drum, Ventilated Disc*3	Two Leading Drum, Ventilated Disc*3	Two Leading Drum, Ventilated Disc*3
	Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum
	Drum	Drum	Drum	Drum	Drum	Drum
	Tandem, 9” + 10”	Tandem, 9” + 10”	Single, 11”	Tandem, 9” + 10”	Tandem, 9” + 10”	Single, 11”
65	LSP and BV	LSP and BV	—	—	—	—
	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
	Leaf Spring	Leaf Spring	Leaf Spring	Leaf Spring	Leaf Spring	Leaf Spring
	—	—	—	—	—	—
	—	—	Option	Option	Option	Option
70	Recirculating Ball	Recirculating Ball	Recirculating Ball	Recirculating Ball	Recirculating Ball	Recirculating Ball
	17.6	17.6	17.6	17.6	17.6	17.6
	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

Item \ Area				G.C.C. Countries		Taiwan	General
Body Type				Standard Roof	High Roof	High Roof	High Roof
Vehicle Grade				Standard (With Air Conditioner)		Standard (With Air Conditioner)	Standard (With Air Conditioner)
Model Code				RZB50L-BGMSKV	RZB50L-ZGMSKV	XZB50L-ZEMSYR	XZB50R-ZCMSY
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	6990 (275.2)	6990 (275.2)	6990 (275.2)	6990 (275.2)
		Width	mm (in.)	2025 (79.7), 2195 (86.4)*1	2025 (79.7), 2195 (86.4)*1	2025 (79.7), 2195 (86.4)*1	2025 (79.7), 2195 (86.4)*1
		Height	mm (in.)	2445 (96.2)	2600 (102.4)	2620 (103.1)	2675 (105.3)
	Wheel Base		mm (in.)	3935 (154.9)	3935 (154.9)	3935 (154.9)	3935 (154.9)
	Tread	Front	mm (in.)	1690 (66.5)	1690 (66.5)	1690 (66.5)	1690 (66.5)
		Rear	mm (in.)	1490 (58.7)	1490 (58.7)	1490 (58.7)	1490 (58.7)
	Room	Length	mm (in.)	6230 (245.3)	6230 (245.3)	6230 (245.3)	6230 (245.3)
		Width	mm (in.)	1900 (74.8)	1900 (74.8)	1900 (74.8)	1900 (74.8)
		Height	mm (in.)	1665 (65.6)	1830 (72.0)	1860 (73.2)	1830 (72.0)
	Cargo Space	Length	mm (in.)	—	—	—	—
		Width	mm (in.)	—	—	—	—
		Height	mm (in.)	—	—	—	—
	Overhang	Front	mm (in.)	1150 (45.3)	1150 (45.3)	1150 (45.3)	1150 (45.3)
		Rear	mm (in.)	1905 (75.0)	1905 (75.0)	1905 (75.0)	1905 (75.0)
	Min. Running Ground Clearance		mm (in.)	185 (7.3)	185 (7.3)	175 (6.9)	185 (7.3)
	Angle of Approach		degrees	17	18	17, 18*2	18
	Angle of Departure		degrees	14	14	14	14
	Curb Weight	Front	kg (lb)	1435 - 1545 (3164 - 3406)	1435 - 1535 (3164 - 3384)	1760 - 1765 (3880 - 3891)	1685 - 1700 (3715 - 3748)
		Rear	kg (lb)	1485 - 1685 (3274 - 3715)	1495 - 1645 (3296 - 3627)	1640 - 1655 (3616 - 3649)	1565 - 1580 (3450 -3483)
		Total	kg (lb)	2920 - 3230 (6437 - 7121)	2930 - 3180 (6460 - 7011)	3400 - 3420 (7496 -7540)	3250 - 3280 (7165 - 7231)
	Gross Vehicle Weight	Front	kg (lb)	2170 (4784)	2170 (4784)	2305 (5082)	2100 (4630)
		Rear	kg (lb)	3140 (6923)	3140 (6923)	2990 (6592)	2700 (5952)
		Total	kg (lb)	5310 (11707)	5310 (11707)	5295 (11673)	4800 (10582)
	Fuel Tank Capacity		ℓ (Imp.gal)	95 (20.9)	95 (20.9)	95 (20.9)	95 (20.9)
	Luggage Compartment Capacity		m^3 (cu.ft.)	0.411 (14.5)	0.411 (14.5)	—	—
Performance	Max. Speed		km / h (mph)	—	—	—	—
	Max. Cruising Speed		km / h (mph)	—	—	—	—
	Max. Permissible Speed	1st Gear	km / h (mph)	20 (12)	20 (12)	—	—
		2nd Gear	km / h (mph)	40 (24)	40 (24)	—	—
		3rd Gear	km / h (mph)	70 (43)	70 (43)	—	—
		4th Gear	km / h (mph)	115 (71)	115 (71)	—	—
		5th Gear	km / h (mph)	—	—	—	—
	Min. Turning Radius	Tire	m (ft.)	7.2 (23.6)	7.2 (23.6)	7.2 (23.6)	7.2 (23.6)
		Body	m (ft.)	7.9 (25.9)	7.9 (25.9)	7.9 (25.9)	7.9 (25.9)
Engine	Engine Type			3RZ-FE	3RZ-FE	N04C-TQ	N04C-TQ
	Valve Mechanism			16-valve DOHC	16-valve DOHC	—	—
	Bore x Stroke		mm (in.)	95.0 x 95.0 (3.74 x 3.74)	95.0 x 95.0 (3.74 x 3.74)	—	—
	Displacement		cm^3 (cu.in.)	2694 (164.4)	2694 (164.4)	—	—
	Compression Ratio			9.5 : 1	9.5 : 1	—	—
	Fuel System			EFI	EFI	—	—
	Research Octane No. or Cetane No. (Diesel)			90 or higher	90 or higher	—	—
	Max. Output		kW / rpm	112 / 4800 (SAE-NET)	112 / 4800 (SAE-NET)	—	—
	Max. Torque		N·m / rpm	240 / 4000 (SAE-NET)	240 / 4000 (SAE-NET)	—	—
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp. hr.	12 - 48	12 - 48	12 - 64 x 2	12 - 64 x 2
	Alternator Output		Watts	960	960	1920	1440
	Starter Output		kW	1.4	1.4	5.0	5.0
Chassis	Clutch Type			Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm
	Transmission Type			M156	M156	M551	M551
	Gear Ratio	In First		5.657	5.657	5.099	5.099
		In Second		2.818	2.818	2.910	2.910
		In Third		1.687	1.687	1.652	1.652
		In Fourth		1.000	1.000	1.000	1.000
		In Fifth		0.835	0.835	0.674	0.674
		In Reverse		5.657	5.657	4.625	4.625
	Differential Gear Ratio			6.142	6.142	5.375	5.375
	Differential Gear Size		in.	10.5	10.5	10.5	10.5
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Two Leading Drum, Ventilated Disc*3	Two Leading Drum
		Rear		Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum
	Parking Brake Type			Drum	Drum	Drum	Drum
	Brake Booster Type and Size		in.	Tandem, 9" + 10"	Tandem, 9" + 10"	Tandem, 9" + 10"	Tandem, 9" + 10"
	Proportioning Valve Type			—	—	—	—
	Suspension Type	Front		Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
		Rear		Leaf Spring	Leaf Spring	Leaf Spring	Leaf Spring
	Stabilizer Bar	Front		—	—	—	—
		Rear		Option	Option	Standard	Standard
	Steering Gear Type			Recirculating Ball	Recirculating Ball	Recirculating Ball	Recirculating Ball
	Steering Gear Ratio (Overall)			17.6	17.6	17.6	17.6
	Power Steering Type			Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

*1: With Snorkel Cleaner Air Duct
*2: 7.00 R16 Tire (Option)
*3: Option

	General Countries					
	High Roof				Standard Roof	
	EX		Standard (With Air Conditioner)		Standard	
	XZB50R-ZEMQY	XZB59R-ZEMQY5	BZB40R-ZCMSC	BZB50R-ZCMSC	BB42L-BRMRS	BB42R-BRMRS
5	6990 (275.2)	7725 (304.1)	6255 (246.6)	6990 (275.2)	6255 (246.6)	6255 (246.6)
	2025 (79.7)	2025 (79.7)	2025 (79.7), 2195 (86.4)*1	2025 (79.7), 2195 (86.4)*1	2025 (79.7), 2195(86.4)*1	2025 (79.7), 2195 (86.4)*1
	2600 (102.4)	2600 (102.4)	2585 (101.8)	2600 (102.4)	2430 (95.7)	2430 (95.7)
	3935 (154.9)	4435 (174.6)	3935 (154.9)	3935 (154.9)	3200 (126.0)	3200 (126.0)
	1690 (66.5)	1690 (66.5)	1690 (66.5)	1690 (66.5)	1690 (66.5)	1690 (66.5)
10	1490 (58.7)	1490 (58.7)	1490 (58.7)	1490 (58.7)	1490 (58.7)	1490 (58.7)
	6230 (245.3)	6230 (245.3)	5490 (216.1)	6230 (245.3)	5490 (216.1)	5490 (216.1)
	1890 (74.4)	1890 (74.4)	1900 (74.8)	1890 (74.4)	1900 (74.8)	1900 (74.8)
	1830 (72.0)	1830 (72.0)	1830 (72.0)	1830 (72.0)	1665 (65.6)	1665 (65.6)
	—	—	—	—	—	—
15	—	—	—	—	—	—
	—	—	—	—	—	—
	1150 (45.3)	1150 (45.3)	1150 (45.3)	1150 (45.3)	1150 (45.3)	1150 (45.3)
	1905 (75.0)	2140 (84.3)	1905 (75.0)	1905 (75.0)	1905 (75.0)	1905 (75.0)
	185 (7.3)	175 (6.9)	175 (6.9)	185 (7.3)	175 (6.9)	175 (6.9)
20	17, 18*2	17	17	18	17	17, 18*2
	14	12	14	14	14	14
	1740 - 1755 (3836 - 3869)	1835 - 1850 (4045 - 4079)	1570 - 1585 (3461 - 3494)	1695 - 1710 (3737 - 3770)	1400 - 1480 (3086 - 3263)	1400 - 1480 (3086 - 3263)
	1625 - 1655 (3583 - 3649)	1815 - 1845 (4001 - 4068)	1485 - 1500 (3274 - 3307)	1545 - 1560 (3406 - 3439)	1440 - 1650 (3175 - 3638)	1440 - 1650 (3175 - 3638)
	3365 - 3410 (7419 - 7518)	3650 3695 (8047 - 8146)	3055 - 3085 (6735 - 6801)	3240 - 3270 (7143 - 7209)	2840 - 3130 (6261 - 6900)	2840 - 3130 (6261 - 6900)
25	2100 (4630)	2250 (4960)	1730 (3814)	2100 (4630)	2020 (4453)	2020 (4453)
	2700 (5952)	3050 (6724)	2620 (5776)	2700 (5952)	3160 (6967)	3160 (6967)
	4800 (10582)	5300 (11684)	4350 (9590)	4800 (10582)	5180 (11420)	5180 (11420)
	95 (20.9)	95 (20.9)	122 (26.8)	95 (20.9)	95 (20.9)	95 (20.9)
	—	—	0.411 (14.5)	0.411 (14.5)	0.411 (14.5)	0.411 (14.5)
30	—	—	—	—	—	—
	—	—	—	—	—	—
	15 (9)	15 (9)	15 (9)	15 (9)	15 (9)	15 (9)
	30 (19)	30 (19)	25 (16)	25 (16)	30 (19)	30 (19)
	50 (31)	50 (31)	50 (31)	50 (31)	50 (31)	50 (31)
35	85 (53)	85 (53)	85 (53)	85 (53)	85 (53)	85 (53)
	—	—	—	—	—	—
	7.2 (23.6)	7.2 (23.6)	6.1 (20.0)	6.1 (20.0)	6.1 (20.0)	6.1 (20.0)
	7.9 (25.9)	7.9 (25.9)	6.8 (22.3)	6.8 (22.3)	6.8 (22.3)	6.8 (22.3)
	N04C-TQ	N04C-TQ	1BZ-FPE	1BZ-FPE	14B	14B
40	—	—	16-valve OHV	16-valve OHV	8-valve OHV	8-valve OHV
	—	—	108.0 x 112.0 (4.25 x 4.41)	108.0 x 112.0 (4.25 x 4.41)	102.0 x 112.0 (4.02 x 4.41)	102.0 x 112.0 (4.02 x 4.41)
	—	—	4104 (250.4)	4104 (250.4)	3661 (223.4)	3661 (223.4)
	—	—	9.5 : 1	9.5 : 1	18.0 : 1	18.0 : 1
	—	—	Carburetor (Electronically Controlled)	Carburetor (Electronically Controlled)	Distributor Type	Distributor Type
45	—	—	100 or higher	100 or higher	50 or higher	50 or higher
	—	—	85 / 3600 (SAE-NET)	85 / 3600 (SAE-NET)	72 / 3400 (SAE-NET)	72 / 3400 (SAE-NET)
	—	—	306 / 2000 (SAE-NET)	306 / 2000 (SAE-NET)	240 / 1800 (SAE-NET)	240 / 1800 (SAE-NET)
	12 - 64 x 2	12 - 64 x 2	12 - 64	12 - 64	12 - 52, 12 - 48 x 2*3, 12 - 64 x 2*3	12 - 52, 12 - 48 x 2*3
	1440	1440	1200	1200	540, 1440*3	540, 1440*3
50	5.0	5.0	2.5	2.5	2.5, 4.5*3	2.5, 4.5*3
	Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm
	M551	M551	M155	M155	M152	M152
	5.099	5.099	4.535	4.535	4.802	4.802
	2.910	2.910	2.858	2.858	2.792	2.792
55	1.652	1.652	1.600	1.600	1.694	1.694
	1.000	1.000	1.000	1.000	1.000	1.000
	0.674	0.674	0.744	0.744	0.788	0.788
	4.625	4.625	5.043	5.043	5.339	5.339
	5.375	5.375	5.625	5.625	5.125, 5.625*3, 6.142*3	5.125, 5.625*3
60	10.5	10.5	10.5	10.5	10.5	10.5
	Two Leading Drum, Ventilated Disc*3	Ventilated Disc	Two Leading Drum, Ventilated Disc*3	Two Leading Drum	Two Leading Drum, Ventilated Disc*3	Two Leading Drum, Ventilated Disc*3
	Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum
	Drum	Drum	Drum	Drum	Drum	Drum
	Tandem, 9” + 10”	Tandem, 9” + 10”	Tandem, 9” + 10”	Tandem, 9” + 10”	Single, 11”	Single, 11”
65	—	—	—	—	—	—
	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
	Leaf Spring	Leaf Spring	Leaf Spring	Leaf Spring	Leaf Spring	Leaf Spring
	—	—	—	—	—	—
	Standard	Standard	Standard	Standard	Option	Option
70	Recirculating Ball	Recirculating Ball	Recirculating Ball	Recirculating Ball	Recirculating Ball	Recirculating Ball
	17.6	17.6	17.6	17.6	17.6	17.6
	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

Item \ Area				General Countries			
Body Type				Standard Roof	High Roof		
Vehicle Grade				Standard (With Air Conditioner)			Standard
Model Code				BB42L-BRMSS	BB42L-ZRMSS	BB42R-ZRMSS	BB50L-ZGMRW
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	6255 (246.6)	6255 (246.6)	6255 (246.6)	6990 (275.2)
		Width	mm (in.)	2025 (79.7), 2195 (86.4)*1	2025 (79.7), 2195 (86.4)*1	2025 (79.7), 2195 (86.4)*1	2025 (79.7), 2195 (86.4)*1
		Height	mm (in.)	2430 (95.7)	2585 (101.8)	2585 (101.8)	2600 (102.4)
	Wheel Base		mm (in.)	3200 (126.0)	3200 (126.0)	3200 (126.0)	3935 (154.9)
	Tread	Front	mm (in.)	1690 (66.5)	1690 (66.5)	1690 (66.5)	1690 (66.5)
		Rear	mm (in.)	1490 (58.7)	1490 (58.7)	1490 (58.7)	1490 (58.7)
	Room	Length	mm (in.)	5490 (216.1)	5490 (216.1)	5490 (216.1)	6230 (245.3)
		Width	mm (in.)	1900 (74.8)	1900 (74.8)	1900 (74.8)	1890 (74.4)
		Height	mm (in.)	1665 (65.6)	1665 (65.6)	1830 (72.0)	1830 (72.0)
	Cargo Space	Length	mm (in.)	—	—	—	—
		Width	mm (in.)	—	—	—	—
		Height	mm (in.)	—	—	—	—
	Overhang	Front	mm (in.)	1150 (45.3)	1150 (45.3)	1150 (45.3)	1150 (45.3)
		Rear	mm (in.)	1905 (75.0)	1905 (75.0)	1905 (75.0)	1905 (75.0)
	Min. Running Ground Clearance		mm (in.)	175 (6.9)	175 (6.9)	175 (6.9)	185 (7.3)
	Angle of Approach		degrees	17	17	17	18
	Angle of Departure		degrees	14	14	14	14
	Curb Weight	Front	kg (lb)	1490 - 1570 (3285 - 3461)	1490 - 1550 (3285 - 3417)	1490 - 1550 (3285 - 3417)	1630 - 1680 (3594 - 3704)
		Rear	kg (lb)	1480 - 1690 (3263 - 3726)	1490 - 1640 (3285 - 3616)	1490 - 1640 (3285 - 3616)	1525 - 1655 (3362 - 3649)
		Total	kg (lb)	2970 - 3260 (6548 - 7187)	2980 - 3190 (6570 - 7033)	2980 - 3190 (6570 - 7033)	3155 - 3335 (6956 - 7353)
	Gross Vehicle Weight	Front	kg (lb)	2020 (4453)	2020 (4453)	2020 (4453)	2400 (5291)
		Rear	kg (lb)	3160 (6967)	3160 (6967)	3160 (6967)	3270 (7209)
		Total	kg (lb)	5180 (11420)	5180 (11420)	5180 (11420)	5670 (12500)
	Fuel Tank Capacity		ℓ (Imp.gal)	95 (20.9)	95 (20.9)	95 (20.9)	95 (20.9)
	Luggage Compartment Capacity		m^3 (cu.ft.)	0.411 (14.5)	0.411 (14.5)	0.411 (14.5)	0.411 (14.5)
Performance	Max. Speed		km / h (mph)	—	—	—	—
	Max. Cruising Speed		km / h (mph)	—	—	—	—
	Max. Permissible Speed	1st Gear	km / h (mph)	15 (9)	15 (9)	15 (9)	20 (12)
		2nd Gear	km / h (mph)	30 (19)	30 (19)	30 (19)	35 (20)
		3rd Gear	km / h (mph)	50 (31)	50 (31)	50 (31)	60 (37)
		4th Gear	km / h (mph)	85 (53)	85 (53)	85 (53)	100 (62)
		5th Gear	km / h (mph)	—	—	—	—
	Min. Turning Radius	Tire	m (ft.)	6.1 (20.0)	6.1 (20.0)	6.1 (20.0)	7.2 (23.6)
		Body	m (ft.)	6.8 (22.3)	6.8 (22.3)	6.8 (22.3)	7.9 (25.9)
Engine	Engine Type			14B	14B	14B	15B-FT
	Valve Mechanism			16-valve OHC	8-valve OHV	8-valve OHV	16-valve OHV
	Bore x Stroke		mm (in.)	102.0 x 112.0 (4.02 x 4.41)	102.0 x 112.0 (4.02 x 4.41)	102.0 x 112.0 (4.02 x 4.41)	108.0 x 112.0 (4.25 x 4.41)
	Displacement		cm^3 (cu.in.)	3661 (223.4)	3661 (223.4)	3661 (223.4)	4104 (250.4)
	Compression Ratio			18.0 : 1	18.0 : 1	18.0 : 1	18.5 : 1
	Fuel System			Distributor Type	Distributor Type	Distributor Type	In-line Type
	Research Octane No. or Cetane No. (Diesel)			50 or higher	50 or higher	50 or higher	48 or higher
	Max. Output		kW / rpm	72 / 3400 (SAE-NET)	72 / 3400 (SAE-NET)	72 / 3400 (SAE-NET)	100 / 3000 (SAE-NET)
	Max. Torque		N·m / rpm	240 / 1800 (SAE-NET)	240 / 1800 (SAE-NET)	240 / 1800 (SAE-NET)	360 / 1600 (SAE-NET)
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp. hr.	12 - 48 x 2	12 - 48 x 2	12 - 48 x 2	12 - 48 x 2
	Alternator Output		Watts	1440	1440	1440	1440
	Starter Output		kW	4.5	4.5	4.5	4.5
Chassis	Clutch Type			Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm
	Transmission Type			M152	M152	M152	M155
	Gear Ratio	In First		4.802	4.802	4.802	4.535
		In Second		2.792	2.792	2.792	2.858
		In Third		1.694	1.694	1.694	1.600
		In Fourth		1.000	1.000	1.000	1.000
		In Fifth		0.788	0.788	0.788	0.744
		In Reverse		5.339	5.339	5.339	5.043
	Differential Gear Ratio			5.625, 5.857*3	5.625, 5.857*3	5.625, 5.857*3	5.625
	Differential Gear Size		in.	10.5	10.5	10.5	10.5
	Brake Type	Front		Two Leading Drum, Ventilated Disc*3	Two Leading Drum, Ventilated Disc*3	Two Leading Drum, Ventilated Disc*3	Two Leading Drum, Ventilated Disc*3
		Rear		Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum
	Parking Brake Type			Drum	Drum	Drum	Drum
	Brake Booster Type and Size		in.	Single, 11”	Single, 11”	Single, 11”	Tandem, 9” + 10”
	Proportioning Valve Type			—	—	—	—
	Suspension Type	Front		Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
		Rear		Leaf Spring	Leaf Spring	Leaf Spring	Leaf Spring
	Stabilizer Bar	Front		—	—	—	—
		Rear		Option	Option	Option	Option
	Steering Gear Type			Recirculating Ball	Recirculating Ball	Recirculating Ball	Recirculating Ball
	Steering Gear Ratio (Overall)			17.6	17.6	17.6	17.6
	Power Steering Type			Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

*1: With Snorkel Cleaner Air Duct
*3: Option
*4: With Seats Installed at Local Side
*5: For Jordan

	General Countries					
	High Roof	Standard Roof		High Roof		
	Standard (With Air Conditioner)	Standard	Standard (With Air Conditioner)	Standard	Standard (With Air Conditioner)	
	BB50L-ZGMSW	HZB50L-BGMRS	HZB50L-BGMSS	HZB50L-ZGMRS	HZB50L-ZGMSS	HZB50R-ZGMSS
5	6990 (275.2)	6990 (275.2)	6990 (275.2)	6990 (275.2)	6990 (275.2)	6990 (275.2)
	2025 (79.7), 2195 (86.4)*1	2025 (79.7), 2195 (86.4)*1	2025 (79.7), 2195 (86.4)*1	2025 (79.7), 2195 (86.4)*1	2025 (79.7), 2195 (86.4)*1	2025 (79.7), 2195 (86.4)*1
	2600 (102.4)	2600 (102.4)	2445 (96.2)	2600 (102.4)	2600 (102.4)	2600 (102.4)
	3935 (154.9)	3935 (154.9)	3935 (154.9)	3935 (154.9)	3935 (154.9)	3935 (154.9)
	1690 (66.5)	1690 (66.5)	1690 (66.5)	1690 (66.5)	1690 (66.5)	1690 (66.5)
10	1490 (58.7)	1490 (58.7), 1554(61.2)*5	1490 (58.7), 1544 (61.2)*5	1490 (58.7)	1490 (58.7)	1490 (58.7)
	6230 (245.3)	6230 (245.3)	6230 (245.3)	6230 (245.3)	6230 (245.3)	6230 (245.3)
	1890 (74.4)	1830 (72.0)	1890 (74.4)	1890 (74.4)	1890 (74.4)	1890 (74.4)
	1830 (72.0)	1665 (65.6)	1665 (65.5)	1830 (72.0)	1830 (72.0)	1830 (72.0)
	—	—	—	—	—	—
15	—	—	—	—	—	—
	—	—	—	—	—	—
	1150 (45.3)	1150 (45.3)	1150 (45.3)	1150 (45.3)	1150 (45.3)	1150 (45.3)
	1905 (75.0)	1905 (75.0)	1905 (75.0)	1905 (75.0)	1905 (75.0)	1905 (75.0)
	185 (7.3)	185 (7.3)	185 (7.3)	185 (7.3)	185 (7.3)	185 (7.3)
20	18	18	18	18	18	18
	14	14	14	14	14	14
	1720 - 1770 (3792 - 3902)	1555 - 1625 (3428 - 3583)	1645 - 1725 (3627 - 3803)	1555 - 1595 (3428 - 3516)	1645 - 1695 (3627 - 3737)	1645 - 1695 (3627 - 3737)
	1565 - 1695 (3450 - 3737)	1545 - 1745 (3406 - 3847)	1585 - 1780 (3494 - 3924)	1555 - 1675 (3428 - 3693)	1595 - 1725 (3616 - 3803)	1595 - 1725 (3516 - 3803)
	3285 - 3465 (7242- 7639)	3100 - 3370 (6834 - 7430)	3230 - 3505 (7121 - 7727)	3110 - 3270 (6856 - 7209)	3240 - 3420 (7143 - 7540)	3240 - 3420 (7143 - 7540)
25	2400 (5291)	2400 (5291)	2400 (5291)	2400 (5291)	2400 (5291)	2400 (5291)
	3270 (7209)	3270 (7209)	3270 (7209)	3270 (7209)	3270 (7209)	3270 (7209)
	5670 (12500)	5670 (12500)	5670 (12500)	5670 (12500)	5670 (12500)	5670 (12500)
	95 (20.9)	95 (20.9)	95 (20.9)	95 (20.9)	95 (20.9)	95 (20.9)
	0.411 (14.5)	0.411 (14.5)	0.411 (14.5)	0.411 (14.5)	0.411 (14.5)	0.411 (14.5)
30	—	—	—	—	—	—
	—	—	—	—	—	—
	20 (12)	20 (12)	20 (12)	20 (12)	20 (12)	20 (12)
	35 (20)	35 (20)	35 (20)	35 (20)	35 (20)	35 (20)
	60 (37)	60 (37)	60 (37)	60 (37)	60 (37)	60 (37)
35	100 (62)	100 (62)	100 (62)	100 (62)	100 (62)	100 (62)
	—	—	—	—	—	—
	7.2 (23.6)	7.2 (23.6)	7.2 (23.6)	7.2 (23.6)	7.2 (23.6)	7.2 (23.6)
	7.9 (25.9)	7.9 (25.9)	7.9 (25.9)	7.9 (25.9)	7.9 (25.9)	7.9 (25.9)
	15B-FT	1HZ	1HZ	1HZ	1HZ	1HZ
40	16-valve OHV	12-valve OHC	12-valve OHC	12-valve OHC	12-valve OHC	12-valve OHC
	108.0 x 112.0 (4.25 x 4.41)	94.0 x 100.0 (3.70 x 3.94)	94.0 x 100.0 (3.70 x 3.94)	94.0 x 100.0 (3.70 x 3.94)	94.0 x 100.0 (3.70 x 3.94)	94.0 x 100.0 (3.70 x 3.94)
	4104 (250.4)	4164 (254.1)	4164 (254.1)	4164 (254.1)	4164 (254.1)	4164 (254.1)
	18.5 : 1	22.4 : 1	22.4 : 1	22.4 : 1	22.4 : 1	22.4 : 1
	In-line Type	Distributor Type	Distributor Type	Distributor Type	Distributor Type	Distributor Type
45	48 or higher	50 or higher	50 or higher	50 or higher	50 or higher	50 or higher
	100 / 3000 (SAE-NET)	96 / 3800 (SAE-NET)	96 / 3800 (SAE-NET)	96 / 3800 (SAE-NET)	96 / 3800 (SAE-NET)	96 / 3800 (SAE-NET)
	360 / 1600 (SAE-NET)	280 / 2200 (SAE-NET)	280 / 2200 (SAE-NET)	285 / 2200 (SAE-NET)	280 / 2200 (SAE-NET)	280 / 2200 (SAE-NET)
	12 - 48 x 2	12 - 52, 12 - 48 x 2*3, 12 - 64 x 2*3	12 - 48 x 2*3, 12 - 64 x 2*3	12 - 52, 12 - 48 x 2*3	12 - 48 x 2*3, 12 - 64 x 2*3	12 - 48 x 2
	1440	540, 1440*3	1440	540, 1440*3	1440	1440
50	4.5	2.5, 4.5*3	4.5	2.5, 4.5*3	4.5	4.5
	Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm
	M155	M155	M155	M155	M155	M155
	4.535	4.535	4.535	4.535	4.535	4.535
	2.858	2.858	2.858	2.858	2.858	2.858
55	1.600	1.600	1.600	1.600	1.600	1.600
	1.000	1.000	1.000	1.000	1.000	1.000
	0.744	0.744	0.744	0.744	0.744	0.744
	5.043	5.043	5.043	5.043	5.043	5.043
	5.625	5.375, 5.625*3	5.625, 5.857*3	5.375, 5.625*3, 6.142*3	5.625, 5.857*3	5.625, 5.857*3
60	10.5	10.5	10.5	10.5	10.5	10.5
	Two Leading Drum, Ventilated Disc*3	Two Leading Drum, Ventilated Disc*3	Two Leading Drum, Ventilated Disc*3	Two Leading Drum, Ventilated Disc*3	Two Leading Drum, Ventilated Disc*3	Two Leading Drum, Ventilated Disc*3
	Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum
	Drum	Drum	Drum	Drum	Drum	Drum
	Tandem, 9” + 10”	Tamdem, 9” + 10”	Tamdem, 9” + 10”	Tamdem, 9” + 10”	Tamdem, 9” + 10”	Tamdem, 9” + 10”
65	—	—	—	—	—	—
	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
	Leaf Spring	Leaf Spring	Leaf Spring	Leaf Spring	Leaf Spring	Leaf Spring
	—	—	—	—	—	—
	Option	Option	Option	Option	Option	Option
70	Recirculating Ball	Recirculating Ball	Recirculating Ball	Recirculating Ball	Recirculating Ball	Recirculating Ball
	17.6	17.6	17.6	17.6	17.6	17.6
	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

Item \ Area				General Countries			
Body Type				Standard Roof		High Roof	
Vehicle Grade				Standard	Standard (With Air Conditioner)		
Model Code				RZB40L-BRMRK	RZB40L-BRMSK	RZB40L-ZRMSK	RZB50L-ZGMSK
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	6255 (246.6)	6255 (246.6)	6255 (246.6)	6990 (275.2)
		Width	mm (in.)	2025 (79.7), 2195 (86.4)*1	2025 (79.7), 2195 (86.4)*1	2025 (79.7), 2195 (86.4)*1	2025 (79.7), 2195 (86.4)*1
		Height	mm (in.)	2600 (102.4)	2430 (95.7)	2585 (101.8)	2600 (102.4)
	Wheel Base		mm (in.)	3200 (126.0)	3200 (126.0)	3200 (126.0)	3935 (154.9)
	Tread	Front	mm (in.)	1690 (66.5)	1690 (66.5)	1690 (66.5)	1690 (66.5)
		Rear	mm (in.)	1490 (58.7)	1490 (58.7)	1490 (58.7)	1490 (58.7)
	Room	Length	mm (in.)	5490 (216.1)	5490 (216.1)	5490 (216.1)	6230 (245.3)
		Width	mm (in.)	1900 (74.8)	1900 (74.8)	1900 (74.8)	1890 (74.4)
		Height	mm (in.)	1665 (65.6)	1665 (65.6)	1830 (72.0)	1830 (72.0)
	Cargo Space	Length	mm (in.)	—	—	—	—
		Width	mm (in.)	—	—	—	—
		Height	mm (in.)	—	—	—	—
	Overhang	Front	mm (in.)	1150 (45.3)	1150 (45.3)	1150 (45.3)	1150 (45.3)
		Rear	mm (in.)	1905 (75.0)	1905 (75.0)	1905 (75.0)	1905 (75.0)
	Min. Running Ground Clearance		mm (in.)	175 (6.9)	175 (6.9)	175 (6.9)	185 (7.3)
	Angle of Approach		degrees	17	17	17	17
	Angle of Departure		degrees	14	14	14	14
	Curb Weight	Front	kg (lb)	1240 - 1360 (2734 - 2998)	1330 - 1450 (2932 - 3197)	1330 - 1430 (2932 - 3153)	1430 - 1520 (3153 - 3351)
		Rear	kg (lb)	1380 - 1620 (3042 - 3571)	1420 - 1660 (3131 - 3660)	1430 - 1620 (3153 - 3571)	1490 - 1670 (3285 - 3682)
		Total	kg (lb)	2620 - 2980 (5776 - 6570)	2750 - 3110 (6063 - 6856)	2760 - 3050 (6086 - 6724)	2920 - 3190 (6437 - 7033)
	Gross Vehicle Weight	Front	kg (lb)	2020 (4453)	2020 (4453)	2020 (4453)	2170 (4748)
		Rear	kg (lb)	2990 (6592)	2990 (6592)	2990 (6592)	3140 (2923)
		Total	kg (lb)	5010 (11045)	5010 (11045)	5010 (11045)	5310 (11707)
	Fuel Tank Capacity		ℓ (Imp.gal)	95 (20.9)	95 (20.9)	95 (20.9)	95 (20.9)
	Luggage Compartment Capacity		m^3 (cu.ft.)	0.411 (14.5)	0.411 (14.5)	0.411 (14.5)	0.411 (14.5)
Performance	Max. Speed		km / h (mph)	—	—	—	—
	Max. Cruising Speed		km / h (mph)	—	—	—	—
	Max. Permissible Speed	1st Gear	km / h (mph)	20 (12)	20 (12)	20 (12)	20 (12)
		2nd Gear	km / h (mph)	40 (24)	40 (24)	40 (24)	40 (24)
		3rd Gear	km / h (mph)	70 (43)	70 (43)	70 (43)	70 (43)
		4th Gear	km / h (mph)	115 (71)	115 (71)	115 (71)	115 (71)
		5th Gear	km / h (mph)	—	—	—	—
	Min. Turning Radius	Tire	m (ft.)	6.1 (20.0)	6.1 (20.0)	6.1 (20.0)	7.2 (23.6)
		Body	m (ft.)	6.8 (22.3)	6.8 (22.3)	6.8 (22.3)	7.9 (25.9)
Engine	Engine Type			3RZ-FE	3RZ-FE	3RZ-FE	3RZ-FE
	Valve Mechanism			16-valve OHC	16-valve DOHC	16-valve DOHC	16-valve DOHC
	Bore x Stroke		mm (in.)	95.0 x 95.0 (3.74 x 3.74)	95.0 x 95.0 (3.74 x 3.74)	95.0 x 95.0 (3.74 x 3.74)	95.0 x 95.0 (3.74 x 3.74)
	Displacement		cm^3 (cu.in.)	2694 (164.4)	2694 (164.4)	2694 (164.4)	2694 (164.4)
	Compression Ratio			9.5 : 1	9.5 : 1	9.5 : 1	9.5 : 1
	Fuel System			EFI	EFI	EFI	EFI
	Research Octane No. or Cetane No. (Diesel)			90 or higher	90 or higher	90 or higher	90 or higher
	Max. Output		kW / rpm	112 / 4800 (SAE-NET)	112 / 4800 (SAE-NET)	112 / 4800 (SAE-NET)	112 / 4800 (SAE-NET)
	Max. Torque		N·m / rpm	240 / 4000 (SAE-NET)	240 / 4000 (SAE-NET)	240 / 4000 (SAE-NET)	240 / 4000 (SAE-NET)
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp. hr.	12 - 48	12 - 48	12 - 48	12 - 48
	Alternator Output		Watts	960	960	960	960
	Starter Output		kW	1.4	1.4	1.4	1.4
Chassis	Clutch Type			Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm
	Transmission Type			M156	M156	M156	M156
	Gear Ratio	In First		5.657	5.657	5.657	5.657
		In Second		2.818	2.818	2.818	2.818
		In Third		1.687	1.687	1.687	1.687
		In Fourth		1.000	1.000	1.000	1.000
		In Fifth		0.835	0.835	0.835	0.835
		In Reverse		5.657	5.657	5.657	5.657
	Differential Gear Ratio			5.857	5.857	5.857	6.142
	Differential Gear Size		in.	10.5	10.5	10.5	10.5
	Brake Type	Front		Two Leading Drum, Ventilated Disc*3	Two Leading Drum, Ventilated Disc*3	Two Leading Drum, Ventilated Disc*3	Ventilated Disc
		Rear		Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum
	Parking Brake Type			Drum	Drum	Drum	Drum
	Brake Booster Type and Size		in.	Single, 11”	Single, 11”	Single, 11”	Tamdem, 9” + 10”
	Proportioning Valve Type			—	—	—	—
	Suspension Type	Front		Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
		Rear		Leaf Spring	Leaf Spring	Leaf Spring	Leaf Spring
	Stabilizer Bar	Front		—	—	—	—
		Rear		Option	Option	Option	Option
	Steering Gear Type			Recirculating Ball	Recirculating Ball	Recirculating Ball	Recirculating Ball
	Steering Gear Ratio (Overall)			17.6	17.6	17.6	17.6
	Power Steering Type			Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

*1: With Snorkel Cleaner Air Duct
*3: Option