MAJOR TECHNICAL SPECIFICATIONS

Item \ Area				Europe			Australia
Body Type				High Roof			High Roof
Vehicle Grade				Standard		Standard (With Air Conditioner)	Standard
Model Code				XZB50R-ZRMRYW1	XZB50L-ZRMRYW1	XZB50L-ZRMSYW1	XZB50R-ZEMRYQ
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	—	—	—	6990 (275.2)
		Width	mm (in.)	—	—	—	2095 (82.5)
		Height	mm (in.)	—	—	—	2600 (102.4)
	Wheel Base		mm (in.)	3935 (154.9)	3935 (154.9)	3935 (154.9)	3935 (154.9)
	Tread	Front	mm (in.)	1690 (66.5)	1690 (66.5)	1690 (66.5)	1690 (66.5)
		Rear	mm (in.)	1554 (61.2)	1554 (61.2)	1554 (61.2)	1490 (58.7)
	Room	Length	mm (in.)	—	—	—	6230 (245.3)
		Width	mm (in.)	—	—	—	1890 (74.4)
		Height	mm (in.)	—	—	—	1830 (72.0)
	Cargo Space	Length	mm (in.)	—	—	—	—
		Width	mm (in.)	—	—	—	—
		Height	mm (in.)	—	—	—	—
	Overhang	Front	mm (in.)	—	—	—	1150 (45.3)
		Rear	mm (in.)	—	—	—	1905 (75.0)
	Min. Running Ground Clearance		mm (in.)	—	—	—	185 (7.3)
	Angle of Approach		degrees	—	—	—	18
	Angle of Departure		degrees	—	—	—	14
	Curb Weight	Front	kg (lb)	—	—	—	1640 - 1645 (3616 - 3627)
		Rear	kg (lb)	—	—	—	1650 - 1675 (3638 - 3693)
		Total	kg (lb)	—	—	—	3290 - 3320 (7253 - 7319)
	Gross Vehicle Weight	Front	kg (lb)	—	—	—	2150 (4740)
		Rear	kg (lb)	—	—	—	2840 (6261)
		Total	kg (lb)	6500 (14330)	6500 (14330)	6500 (14330)	4990 (11001)
	Fuel Tank Capacity		ℓ (Imp.gal.)	95 (20.9)	95 (20.9)	95 (20.9)	95 (20.9)
	Luggage Compartment Capacity		m^3 (cu.ft.)	—	—	—	0.411 (14.5)
Performance	Max. Speed		km/h (mph)	—	—	—	125 (78)
	Max. Cruising Speed		km/h (mph)	—	—	—	—
	Max. Permissible Speed	1st Gear	km/h (mph)	15 (9)	15 (9)	15 (9)	15 (9)
		2nd Gear	km/h (mph)	30 (19)	30 (19)	30 (19)	30 (19)
		3rd Gear	km/h (mph)	50 (31)	50 (31)	50 (31)	50 (31)
		4th Gear	km/h (mph)	85 (53)	85 (53)	85 (53)	85 (53)
		5th Gear	km/h (mph)	—	—	—	—
	Min. Turning Radius	Tire	m (ft.)	7.2 (23.6)	7.2 (23.6)	7.2 (23.6)	7.2 (23.6)
		Body	m (ft.)	—	—	—	7.9 (25.9)
Engine	Engine Type			N04C-TQ	N04C-TQ	N04C-TQ	N04C-TQ
	Valve Mechanism			16-valve OHV	16-valve OHV	16-valve OHV	16-valve OHV
	Bore × Stroke		mm (in.)	104.0 × 118.0 (4.09 × 4.65)	104.0 × 118.0 (4.09 × 4.65)	104.0 × 118.0 (4.09 × 4.65)	104.0 × 118.0 (4.09 × 4.65)
	Displacement		cm^3 (cu. in.)	4009 (244.6)	4009 (244.6)	4009 (244.6)	4009 (244.6)
	Compression Ratio			18.0 : 1	18.0 : 1	18.0 : 1	18.0 : 1
	Fuel System			Common-rail Type	Common-rail Type	Common-rail Type	Common-rail Type
	Research Octane No. or Cetane No. (Diesel)			48 or higher	48 or higher	48 or higher	48 or higher
	Max. Output		kW/rpm	110/2700 (EEC)	110/2700 (EEC)	110/2700 (EEC)	110/2700 (EEC)
	Max. Torque		N·m/rpm	397/1800 (EEC)	397/1800 (EEC)	397/1800 (EEC)	397/1800 (EEC)
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp. hr.	24	24	24	24 - 64
	Alternator Output		Watts	1920	1920	1920	1440
	Starter Output		kW	5.0	5.0	5.0	5.0
Chassis	Clutch Type			Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm
	Transmission Type			M551	M551	M551	M551
	Gear Ratio	In First		5.099	5.099	5.099	5.099
		In Second		2.910	2.910	2.910	2.910
		In Third		1.652	1.652	1.652	1.652
		In Fourth		1.000	1.000	1.000	1.000
		In Fifth		0.674	0.674	0.674	0.674
		In Reverse		4.625	4.625	4.625	4.625
	Differential Gear Ratio			5.375	5.375	5.375	5.375
	Differential Gear Size		in.	10.5	10.5	10.5	10.5
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear		Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum
	Parking Brake Type			Drum	Drum	Drum	Drum
	Brake Booster Type and Size		in.	Tandem, 9 + 10	Tandem, 9 + 10	Tandem, 9 + 10	Tandem, 9 + 10
	Proportioning Valve Type			LSP and BV	LSP and BV	LSP and BV	LSP and BV
	Suspension Type	Front		Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone
		Rear		Leaf Spring	Leaf Spring	Leaf Spring	Leaf Spring
	Stabilizer Bar	Front		—	—	—	—
		Rear		Standard	Standard	Standard	—
	Steering Gear Type			Recirculating Ball	Recirculating Ball	Recirculating Ball	Recirculating Ball
	Steering Gear Ratio (Overall)			17.6	17.6	17.6	17.6
	Power Steering Type			Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

*1: Option
*2: With 7.00 R16 Tire (Option)

	Australia			G.C.C. Countries		
	High Roof			Standard Roof		High Roof
	Standard (With Air Conditioner)	DX		Standard (With Air Conditioner)		
	XZB50R-ZEMSYQ	XZB50R-ZEMNYQ	XZB50R-ZEPNYQ	TRB40L-BRMSKV	TRB50L-BGMSKV	TRB50L-ZGMSKV
	6990 (275.2)	6990 (275.2)	6990 (275.2)	6255 (246.6)	6990 (275.2)	6990 (275.2)
	2095 (82.5)	2095 (82.5)	2095 (82.5)	2035 (80.1)	2035 (80.1)	2035 (80.1)
	2600 (102.4)	2600 (102.4)	2600 (102.4)	2430 (95.7), 2445 (96.3)*2	2445 (96.2)	2600 (102.4)
	3935 (154.9)	3935 (154.9)	3935 (154.9)	3200 (126.0)	3935 (154.9)	3935 (154.9)
	1690 (66.5)	1690 (66.5)	1690 (66.5)	1690 (66.5)	1690 (66.5)	1690 (66.5)
	1490 (58.7)	1490 (58.7)	1490 (58.7)	1490 (58.7)	1490 (58.7)	1490 (58.7)
	6230 (245.3)	6230 (245.3)	6230 (245.3)	5490 (216.1)	6230 (245.3)	6230 (245.3)
	1890 (74.4)	1890 (74.4)	1890 (74.4)	1900 (74.8)	1900 (74.8)	1900 (74.8)
	1830 (72.0)	1830 (72.0)	1830 (72.0)	1665 (65.6)	1665 (65.6)	1830 (72.0)
	—	—	—	—	—	—
	—	—	—	—	—	—
	—	—	—	—	—	—
	1150 (45.3)	1150 (45.3)	1150 (45.3)	1150 (45.3)	1150 (45.3)	1150 (45.3)
	1905 (75.0)	1905 (75.0)	1905 (75.0)	1905 (75.0)	1905 (75.0)	1905 (75.0)
	185 (7.3)	185 (7.3)	185 (7.3)	175 (6.9), 185 (7.3)*2	185 (7.3)	185 (7.3)
	18	18	18	17, 18*2	18	18
	14	14	14	14	14	14
	1730 - 1735 (3814 - 3825)	1740 - 1745 (3836 - 3847)	1750 - 1755 (3858 - 3869)	1335 - 1455 (2943 - 3208)	1435 - 1545 (3164 - 3406)	1435 - 1535 (3164 - 3384)
	1690 - 1715 (3726 - 3781)	1700 - 1725 (3748 - 3803)	1700 - 1725 (3748 - 3803)	1425 - 1635 (3142 - 3605)	1485 - 1685 (3274 - 3715)	1495 - 1645 (3296 - 3627)
	3420 - 3450 (7540 - 7606)	3440 - 3470 (7584 - 7650)	3450 - 3480 (7606 - 7672)	2760 - 3090 (6085 - 6812)	2920 - 3230 (6437 - 7121)	2930 - 3180 (6460 - 7011)
	2150 (4740)	2150 (4740)	2150 (4740)	2020 (4453)	2170 (4784)	2170 (4784)
	2840 (6261)	2840 (6261)	2840 (6261)	2990 (6592)	3140 (6923)	3140 (6923)
	4990 (11001)	4990 (11001)	4990 (11001)	5010 (11045)	5310 (11707)	5310 (11707)
	95 (20.9)	95 (20.9)	95 (20.9)	95 (20.9)	95 (20.9)	95 (20.9)
	0.411 (14.5)	0.411 (14.5)	0.411 (14.5)	0.411 (14.5)	0.411 (14.5)	0.411 (14.5)
	125 (78)	125 (78)	120 (74)	130 (81)	130 (81)	130 (81)
	—	—	—	—	—	—
	15 (9)	15 (9)	35 (22)	20 (12)	20 (12)	20 (12)
	30 (19)	30 (19)	68 (42)	45 (28)	45 (28)	45 (28)
	50 (31)	50 (31)	—	75 (47)	75 (47)	75 (47)
	85 (53)	85 (53)	—	125 (78)	125 (78)	125 (78)
	—	—	—	—	—	—
	7.2 (23.6)	7.2 (23.6)	7.2 (23.6)	6.1 (20.0)	7.2 (23.6)	7.2 (23.6)
	7.9 (25.9)	7.9 (25.9)	7.9 (25.9)	6.8 (22.3)	7.9 (25.9)	7.9 (25.9)
	N04C-TQ	N04C-TQ	N04C-TQ	2TR-FE	2TR-FE	2TR-FE
	16-valve OHV	16-valve OHV	16-valve OHV	16-valve DOHC	16-valve DOHC	16-valve DOHC
	104.0 × 118.0 (4.09 × 4.65)	104.0 × 118.0 (4.09 × 4.65)	104.0 × 118.0 (4.09 × 4.65)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)
	4009 (244.6)	4009 (244.6)	4009 (244.6)	2694 (164.4)	2694 (164.4)	2694 (164.4)
	18.0 : 1	18.0 : 1	18.0 : 1	9.6 : 1	9.6 : 1	9.6 : 1
	Common-rail Type	Common-rail Type	Common-rail Type	EFI	EFI	EFI
	48 or higher	48 or higher	48 or higher	91 or higher	91 or higher	91 or higher
	110/2700 (EEC)	110/2700 (EEC)	110/2700 (EEC)	108/4800	108/4800	108/4800
	397/1800 (EEC)	397/1800 (EEC)	397/1800 (EEC)	235/3800	235/3800	235/3800
	24 - 64	24 - 64	24 - 64	12 - 48	12 - 48	12 - 48
	1440	1440	1440	960	960	960
	5.0	5.0	5.0	1.4	1.4	1.4
	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	—	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm
	M551	M551	A444E	M156	M156	M156
	5.099	5.099	2.950	5.657	5.657	5.657
	2.910	2.910	1.530	2.818	2.818	2.818
	1.652	1.652	1.000	1.687	1.687	1.687
	1.000	1.000	0.703	1.000	1.000	1.000
	0.674	0.674	—	0.835	0.835	0.835
	4.625	4.625	2.678	5.657	5.657	5.657
	5.375	5.375	4.875	5.857	6.142	6.142
	10.5	10.5	10.5	10.5	10.5	10.5
	Ventilated Disc	Ventilated Disc	Ventilated Disc	Two Leading Drum, Ventilated Disc*1	Ventilated Disc	Ventilated Disc
	Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum
	Drum	Drum	Drum	Drum	Drum	Drum
	Tandem, 9 + 10	Tandem, 9 + 10	Tandem, 9 + 10	Single, 11	Tandem, 9 + 10	Tandem, 9 + 10
	LSP and BV	LSP and BV	LSP and BV	—	—	—
	Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone
	Leaf Spring	Leaf Spring	Leaf Spring	Leaf Spring	Leaf Spring	Leaf Spring
	—	—	—	—	—	—
	—	—	—	Option	Option	Option
	Recirculating Ball	Recirculating Ball	Recirculating Ball	Recirculating Ball	Recirculating Ball	Recirculating Ball
	17.6	17.6	17.6	17.6	17.6	17.6
	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

Item \ Area				G.C.C. Countries			Taiwan
Body Type				Standard Roof		High Roof	High Roof
Vehicle Grade				Standard (With Air Conditioner)			Standard (With Air Conditioner)
Model Code				BB42L-BRMSSV	HZB50L-BGMSSV	HZB50L-ZGMSSV	XZB50L-ZEMSYR
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	6255 (246.6)	6990 (275.2)	6990 (275.2)	6990 (275.2)
		Width	mm (in.)	2035 (80.1)	2035 (80.1)	2035 (80.1)	2035 (80.1)
		Height	mm (in.)	2430 (95.7), 2445 (96.3)*2	2445 (96.2)	2600 (102.4)	2620 (103.1)
	Wheel Base		mm (in.)	3200 (126.0)	3935 (154.9)	3935 (154.9)	3935 (154.9)
	Tread	Front	mm (in.)	1690 (66.5)	1690 (66.5)	1690 (66.5)	1690 (66.5)
		Rear	mm (in.)	1490 (58.7)	1490 (58.7)	1490 (58.7)	1490 (58.7)
	Room	Length	mm (in.)	5490 (216.1)	6230 (245.3)	6230 (245.3)	6230 (245.3)
		Width	mm (in.)	1900 (74.8)	1890 (74.4)	1890 (74.4)	1900 (74.8)
		Height	mm (in.)	1665 (65.6)	1665 (65.6)	1830 (72.0)	1860 (73.2)
	Cargo Space	Length	mm (in.)	—	—	—	—
		Width	mm (in.)	—	—	—	—
		Height	mm (in.)	—	—	—	—
	Overhang	Front	mm (in.)	1150 (45.3)	1150 (45.3)	1150 (45.3)	1150 (45.3)
		Rear	mm (in.)	1905 (75.0)	1905 (75.0)	1905 (75.0)	1905 (75.0)
	Min. Running Ground Clearance		mm (in.)	175 (6.9), 185 (7.3)*2	185 (7.3)	185 (7.3)	175 (6.9)
	Angle of Approach		degrees	17, 18*2	18	18	17
	Angle of Departure		degrees	14	14	14	14
	Curb Weight	Front	kg (lb)	1490 - 1570 (3285 - 3461)	1645 - 1725 (3627 - 3803)	1645 - 1700 (3627 - 3748)	1760 - 1765 (3880 - 3891)
		Rear	kg (lb)	1490 - 1660 (3285 - 3660)	1585 - 1750 (3494 - 3858)	1595 - 1705 (3516 - 3759)	1640 - 1655 (3616 - 3649)
		Total	kg (lb)	2980 - 3230 (6570 - 7121)	3230 - 3475 (7121 - 7661)	3240 - 3405 (7143 - 7507)	3400 - 3420 (7496 - 7540)
	Gross Vehicle Weight	Front	kg (lb)	2020 (4453)	2400 (5291)	2400 (5291)	2305 (5082)
		Rear	kg (lb)	3160 (6967)	3270 (7209)	3270 (7209)	2990 (6592)
		Total	kg (lb)	5180 (11420)	5670 (12500)	5670 (12500)	5295 (11673)
	Fuel Tank Capacity		ℓ (Imp.gal.)	95 (20.9)	95 (20.9)	95 (20.9)	95 (20.9)
	Luggage Compartment Capacity		m^3 (cu.ft.)	0.411 (14.5)	0.411 (14.5)	0.411 (14.5)	—
Performance	Max. Speed		km/h (mph)	115 (71)	130 (81)	130 (81)	—
	Max. Cruising Speed		km/h (mph)	—	—	—	—
	Max. Permissible Speed	1st Gear	km/h (mph)	15 (9)	20 (12)	20 (12)	15 (9)
		2nd Gear	km/h (mph)	30 (19)	35 (22)	35 (22)	30 (19)
		3rd Gear	km/h (mph)	50 (31)	60 (37)	60 (37)	50 (31)
		4th Gear	km/h (mph)	85 (53)	100 (62)	100 (62)	85 (53)
		5th Gear	km/h (mph)	—	—	—	—
	Min. Turning Radius	Tire	m (ft.)	6.1 (20.0)	7.2 (23.6)	7.2 (23.6)	7.2 (23.6)
		Body	m (ft.)	6.8 (22.3)	7.9 (25.9)	7.9 (25.9)	7.9 (25.9)
Engine	Engine Type			14B	1HZ	1HZ	N04C-TQ
	Valve Mechanism			8-valve OHV	12-valve OHC	12-valve OHC	16-valve OHV
	Bore × Stroke		mm (in.)	102.0 × 112.0 (4.02 × 4.41)	94.0 × 100.0 (3.70 × 3.94)	94.0 × 100.0 (3.70 × 3.94)	104.0 × 118.0 (4.09 × 4.65)
	Displacement		cm^3 (cu. in.)	3661 (223.4)	4164 (254.1)	4164 (254.1)	4009 (244.6)
	Compression Ratio			18.0 : 1	22.4 : 1	22.4 : 1	18.0 : 1
	Fuel System			Distributor Type	Distributor Type	Distributor Type	Common-rail Type
	Research Octane No. or Cetane No. (Diesel)			50 or higher	50 or higher	50 or higher	48 or higher
	Max. Output		kW/rpm	72/3400 (SAE-NET)	96/3800 (SAE-NET)	96/3800 (SAE-NET)	110/2700 (EEC)
	Max. Torque		N·m/rpm	240/1800 (SAE-NET)	285/2200 (SAE-NET)	285/2200 (SAE-NET)	397/1800 (EEC)
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp. hr.	24 - 48	24 - 48	24 - 48	24 - 64
	Alternator Output		Watts	1440	1440	1440	1920
	Starter Output		kW	4.5	4.5	4.5	5.0
Chassis	Clutch Type			Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm
	Transmission Type			M152	M155	M155	M551
	Gear Ratio	In First		4.802	4.535	4.535	5.099
		In Second		2.792	2.858	2.858	2.910
		In Third		1.694	1.600	1.600	1.652
		In Fourth		1.000	1.000	1.000	1.000
		In Fifth		0.788	0.744	0.744	0.674
		In Reverse		5.339	5.043	5.043	4.625
	Differential Gear Ratio			5.625	5.625	5.625	5.375
	Differential Gear Size		in.	10.5	10.5	10.5	10.5
	Brake Type	Front		Two Leading Drum, Ventilated Disc*3	Two Leading Drum, Ventilated Disc*3	Two Leading Drum, Ventilated Disc*3	Two Leading Drum, Ventilated Disc*3
		Rear		Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum
	Parking Brake Type			Drum	Drum	Drum	Drum
	Brake Booster Type and Size		in.	Single, 11	Tandem, 9 + 10	Tandem, 9 + 10	Tandem, 9 + 10
	Proportioning Valve Type			—	—	—	—
	Suspension Type	Front		Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone
		Rear		Leaf Spring	Leaf Spring	Leaf Spring	Leaf Spring
	Stabilizer Bar	Front		—	—	—	—
		Rear		Option	Option	Option	Standard
	Steering Gear Type			Recirculating Ball	Recirculating Ball	Recirculating Ball	Recirculating Ball
	Steering Gear Ratio (Overall)			17.6	17.6	17.6	17.6
	Power Steering Type			Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

*1: Without Destination Box
*2: With 7.00 R16 Tire (Option)
*3: Option
*4: With 215/70R17.5 Tire (Option)
*5: For Singapore

Hong Kong					
High Roof					
EX		Standard (With Air Conditioner)	EX	Standard (With Air Conditioner)	
XZB50R-ZEMQY	XZB50R-ZEPQY	XZB40R-ZCMSY	XZB59R-ZEMQY5	BZB40R-ZCMSC	BZB50R-ZCMSC
6990 (275.2)	6990 (275.2)	6255 (246.6)	7725 (304.1)	6255 (246.6)	6990 (275.2)
2035 (80.1)	2035 (80.1)	2035 (80.1)	2035 (80.1)	2035 (80.1)	2035 (80.1)
2600 (102.4), 2585 (101.8)*4	2600 (102.4), 2585 (101.8)*4	2665 (104.9), 2585 (101.8)*1	2600 (102.4)	2665 (104.9), 2585 (101.8)*1	2675 (105.3), 2600 (102.4)*1
3935 (154.9)	3935 (154.9)	3200 (126.0)	4435 (174.6)	3200 (126.0)	3935 (154.9)
1690 (66.5)	1690 (66.5)	1690 (66.5)	1690 (66.5)	1690 (66.5)	1690 (66.5)
1490 (58.7)	1490 (58.7)	1490 (58.7)	1490 (58.7)	1490 (58.7)	1490 (58.7)
6230 (245.3)	6230 (245.3)	5490 (216.1)	6985 (275.0)	5490 (216.1)	6230 (245.3)
1890 (74.4)	1890 (74.4)	1900 (74.8)	1890 (74.4)	1900 (74.8)	1900 (74.8)
1830 (72.0)	1830 (72.0)	1830 (72.0)	1830 (72.0)	1830 (72.0)	1830 (72.0)
—	—	—	—	—	—
—	—	—	—	—	—
—	—	—	—	—	—
1150 (45.3)	1150 (45.3)	1150 (45.3)	1150 (45.3)	1150 (45.3)	1150 (45.3)
1905 (75.0)	1905 (75.0)	1905 (75.0)	2140 (84.3)	1905 (75.0)	1905 (75.0)
185 (7.3), 175(6.9)*4	185 (7.3), 175(6.9)*4	175 (6.9)	175 (6.9)	175 (6.9)	185 (7.3)
18, 17*4	18, 17*4	17	17	17	18
14	14	14	12	14	14
1740 - 1755 (3836 - 3869), 1725 - 1740 (3803 - 3836)*5	1750 - 1765 (3858 - 3891), 1735 - 1750 (3825 - 3858)*5	1570 - 1585 (3461 - 3494)	1835 - 1850 (4045 - 4079)	1580 - 1595 (3483 - 3516)	1695 - 1710 (3737 - 3770)
1625 - 1655 (3583 - 3649), 1615 - 1635 (3560 - 3605)*5	1625 - 1655 (3583 - 3649), 1615 - 1635 (3560 - 3605)*5	1525 - 1540 (3362 - 3395)	1815 - 1845 (4001 - 4068)	1505 - 1520 (3318 - 3351)	1555 - 1570 (3428 - 3461)
3365 - 3410 (7419 - 7518), 3340 - 3375 (7363 - 7441)*5	3375 - 3420 (7441 - 7540), 3350 - 3385 (7385 - 7463)*5	3095 - 3125 (6823 - 6889)	3650 - 3695 (8047 - 8146)	3085 - 3115 (6801 - 6867)	3250 - 3280 (7165 - 7231)
2150 (4740), 2100 (4630)*5	2150 (4740), 2100 (4630)*5	1850 (4079)	2300 (5071)	1850 (4079)	2100 (4630)
2840 (6261), 2690 (5930)*5	2840 (6261), 2690 (5930)*5	2500 (5512)	3300 (7275)	2500 (5512)	2700 (5952)
4990 (11001), 4790 (10560)*5	4990 (11001), 4790 (10560)*5	4350 (9590)	5600 (12346)	4350 (9590)	4800 (10582)
95 (20.9)	95 (20.9)	95 (20.9)	95 (20.9)	122 (26.8)	122 (26.8)
—	—	0.411 (14.5)	—	0.411 (14.5)	0.411 (14.5)
—	—	—	—	—	—
—	—	—	—	—	—
15 (9)	35 (22)	15 (9)	15 (9)	15 (9)	15 (9)
30 (19)	68 (42)	30 (19)	30 (19)	25 (16)	25 (16)
50 (31)	—	50 (31)	50 (31)	50 (31)	50 (31)
85 (53)	—	85 (53)	85 (53)	85 (53)	85 (53)
—	—	—	—	—	—
7.2 (23.6)	7.2 (23.6)	6.1 (20.0)	8.1 (26.6)	6.1 (20.0)	7.2 (23.6)
7.9 (25.9)	7.9 (25.9)	6.8 (22.3)	8.8 (28.9)	6.8 (22.3)	7.9 (25.9)
N04C-TQ	N04C-TQ	N04C-TQ	N04C-TQ	1BZ-FPE	1BZ-FPE
16-valve OHV	16-valve OHV	16-valve OHV	16-valve OHV	16-valve OHV	16-valve OHV
104.0 × 118.0 (4.09 × 4.65)	104.0 × 118.0 (4.09 × 4.65)	104.0 × 118.0 (4.09 × 4.65)	104.0 × 118.0 (4.09 × 4.65)	108.0 × 112.0 (4.25 × 4.41)	108.0 × 112.0 (4.25 × 4.41)
4009 (244.6)	4009 (244.6)	4009 (244.6)	4009 (244.6)	4104 (250.4)	4104 (250.4)
18.0 : 1	18.0 : 1	18.0 : 1	18.0 : 1	9.5 : 1	9.5 : 1
Common-rail Type	Common-rail Type	Common-rail Type	Common-rail Type	Carburetor (Electronically Controlled)	Carburetor (Electronically Controlled)
48 or higher	48 or higher	48 or higher	48 or higher	100 or higher	100 or higher
110/2700 (EEC)	110/2700 (EEC)	110/2700 (EEC)	110/2700 (EEC)	85/3600 (SAE-NET)	85/3600 (SAE-NET)
397/1800 (EEC)	397/1800 (EEC)	397/1800 (EEC)	397/1800 (EEC)	306/2000 (SAE-NET)	306/2000 (SAE-NET)
24 - 64	24 - 64	24 - 64	24 - 64	12 - 64	12 - 64
1440	1440	1440	1440	1200	1200
5.0	5.0	5.0	5.0	2.5	2.5
Dry, Single Plate, Diaphragm	—	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm
M551	A444E	M551	M551	M155	M155
5.099	2.950	5.099	5.099	4.535	4.535
2.910	1.530	2.910	2.910	2.858	2.858
1.652	1.000	1.652	1.652	1.600	1.600
1.000	0.703	1.000	1.000	1.000	1.000
0.674	—	0.674	0.674	0.744	0.744
4.625	2.678	4.625	4.625	5.043	5.043
5.375	4.875	5.375	5.375	5.625	5.625
10.5	10.5	10.5	10.5	10.5	10.5
Two Leading Drum, Ventilated Disc*3	Two Leading Drum, Ventilated Disc*3	Two Leading Drum	Ventilated Disc	Two Leading Drum	Two Leading Drum
Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum
Drum	Drum	Drum	Drum	Drum	Drum
Tandem, 9 + 10	Single, 11	Tandem, 9 + 10	Tandem, 9 + 10	Tandem, 9 + 10	Tandem, 9 + 10
—	—	—	—	—	—
Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone
Leaf Spring	Leaf Spring	Leaf Spring	Leaf Spring	Leaf Spring	Leaf Spring
—	—	—	—	—	—
Standard	Standard	Standard	Standard	Standard	Standard
Recirculating Ball	Recirculating Ball	Recirculating Ball	Recirculating Ball	Recirculating Ball	Recirculating Ball
17.6	17.6	17.6	17.6	17.6	17.6
Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

Item \ Area				General Countries			
Body Type				Standard Roof		High Roof	
Vehicle Grade				Standard (With Air Conditioner)			
Model Code				TRB40L-BRMRK	TRB40L-BRMSK	TRB40L-ZRMSK	TRB50L-ZGMSK
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	6255 (246.6)	6255 (246.6)	6255 (246.6)	6990 (275.2)
		Width	mm (in.)	2025 (79.7), 2195 (86.4)*1	2025 (79.7), 2195 (86.4)*1	2025 (79.7), 2195 (86.4)*1	2025 (79.7), 2195 (86.4)*1
		Height	mm (in.)	2430 (95.7), 2445 (96.3)*2	2430 (95.7), 2445 (96.3)*2	2585 (101.8), 2600 (102.4)*2	2600 (102.4)
	Wheel Base		mm (in.)	3200 (126.0)	3200 (126.0)	3200 (126.0)	3935 (154.9)
	Tread	Front	mm (in.)	1690 (66.5)	1690 (66.5)	1690 (66.5)	1690 (66.5)
		Rear	mm (in.)	1490 (58.7)	1490 (58.7)	1490 (58.7)	1490 (58.7)
	Room	Length	mm (in.)	5490 (216.1)	5490 (216.1)	5490 (216.1)	6230 (245.3)
		Width	mm (in.)	1900 (74.8)	1900 (74.8)	1900 (74.8)	1890 (74.4)
		Height	mm (in.)	1665 (65.6)	1665 (65.6)	1830 (72.0)	1830 (72.0)
	Cargo Space	Length	mm (in.)	—	—	—	—
		Width	mm (in.)	—	—	—	—
		Height	mm (in.)	—	—	—	—
	Overhang	Front	mm (in.)	1150 (45.3)	1150 (45.3)	1150 (45.3)	1150 (45.3)
		Rear	mm (in.)	1905 (75.0)	1905 (75.0)	1905 (75.0)	1905 (75.0)
	Min. Running Ground Clearance		mm (in.)	175 (6.9), 185 (7.3)*2	175 (6.9), 185 (7.3)*2	175 (6.9), 185 (7.3)*2	185 (7.3)
	Angle of Approach		degrees	17, 18*2	17, 18*2	17, 18*2	18
	Angle of Departure		degrees	14	14	14	14
	Curb Weight	Front	kg (lb)	1240 - 1360 (2734 - 2998)	1330 - 1450 (2932 - 3197)	1330 - 1430 (2932 - 3153)	1430 - 1520 (3153 - 3351)
		Rear	kg (lb)	1380 - 1620 (3042 - 3571)	1420 - 1660 (3131 - 3660)	1430 - 1620 (3153 - 3571)	1490 - 1670 (3285 - 3682)
		Total	kg (lb)	2620 - 2980 (5776 - 6570)	2750 - 3110 (6063 - 6856)	2760 - 3050 (6085 - 6724)	2920 - 3190 (6437 - 7033)
	Gross Vehicle Weight	Front	kg (lb)	2020 (4453)	2020 (4453)	2020 (4453)	2170 (4784)
		Rear	kg (lb)	2990 (6592)	2990 (6592)	2990 (6592)	3140 (6923)
		Total	kg (lb)	5010 (11045)	5010 (11045)	5010 (11045)	5310 (11707)
	Fuel Tank Capacity		ℓ (Imp.gal.)	95 (20.9)	95 (20.9)	95 (20.9)	95 (20.9)
	Luggage Compartment Capacity		m^3 (cu.ft.)	0.411 (14.5)	0.411 (14.5)	0.411 (14.5)	0.411 (14.5)
Performance	Max. Speed		km/h (mph)	—	—	—	—
	Max. Cruising Speed		km/h (mph)	—	—	—	—
	Max. Permissible Speed	1st Gear	km/h (mph)	20 (12)	20 (12)	20 (12)	20 (12)
		2nd Gear	km/h (mph)	45 (28)	45 (28)	45 (28)	40 (25)
		3rd Gear	km/h (mph)	75 (47)	75 (47)	75 (47)	70 (43)
		4th Gear	km/h (mph)	125 (78)	125 (78)	125 (78)	115 (71)
		5th Gear	km/h (mph)	—	—	—	—
	Min. Turning Radius	Tire	m (ft.)	6.1 (20.0)	6.1 (20.0)	6.1 (20.0)	7.2 (23.6)
		Body	m (ft.)	6.8 (22.3)	6.8 (22.3)	6.8 (22.3)	7.9 (25.9)
Engine	Engine Type			2TR-FE	2TR-FE	2TR-FE	2TR-FE
	Valve Mechanism			16-valve DOHC	16-valve DOHC	16-valve DOHC	16-valve DOHC
	Bore × Stroke		mm (in.)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)
	Displacement		cm^3 (cu. in.)	2694 (164.4)	2694 (164.4)	2694 (164.4)	2694 (164.4)
	Compression Ratio			9.6 : 1	9.6 : 1	9.6 : 1	9.6 : 1
	Fuel System			EFI	EFI	EFI	EFI
	Research Octane No. or Cetane No. (Diesel)			91 or higher	91 or higher	91 or higher	91 or higher
	Max. Output		kW/rpm	109/4800	109/4800	109/4800	109/4800
	Max. Torque		N·m/rpm	245/3800	245/3800	245/3800	245/3800
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp. hr.	12 - 48	12 - 48	12 - 48	12 - 48
	Alternator Output		Watts	960	960	960	960
	Starter Output		kW	1.4	1.4	1.4	1.4
Chassis	Clutch Type			Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm
	Transmission Type			M156	M156	M156	M156
	Gear Ratio	In First		5.657	5.657	5.657	5.657
		In Second		2.818	2.818	2.818	2.818
		In Third		1.687	1.687	1.687	1.687
		In Fourth		1.000	1.000	1.000	1.000
		In Fifth		0.835	0.835	0.835	0.835
		In Reverse		5.657	5.657	5.657	5.657
	Differential Gear Ratio			5.857	5.857	5.857	6.142
	Differential Gear Size		in.	10.5	10.5	10.5	10.5
	Brake Type	Front		Two Leading Drum, Ventilated Disc*3	Two Leading Drum, Ventilated Disc*3	Two Leading Drum, Ventilated Disc*3	Ventilated Disc
		Rear		Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum
	Parking Brake Type			Drum	Drum	Drum	Drum
	Brake Booster Type and Size		in.	Single, 11	Single, 11	Single, 11	Tandem, 9 + 10
	Proportioning Valve Type			—	—	—	—
	Suspension Type	Front		Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone
		Rear		Leaf Spring	Leaf Spring	Leaf Spring	Leaf Spring
	Stabilizer Bar	Front		—	—	—	—
		Rear		Option	Option	Option	Option
	Steering Gear Type			Recirculating Ball	Recirculating Ball	Recirculating Ball	Recirculating Ball
	Steering Gear Ratio (Overall)			17.6	17.6	17.6	17.6
	Power Steering Type			Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

*1: With Snorkel Cleaner Air Duct
*2: 7.00 R16 Tire (Option)
*3: Option

General Countries					
Standard Roof		High Roof		Standard Roof	High Roof
Standard		Standard (With Air Conditioner)			
BB42L-BRMRS	BB42R-BRMRS	BB42L-ZRMSS	BB42R-ZRMSS	BB42L-BRMSS	BB50L-ZGMSW
6255 (246.6)	6255 (246.6)	6255 (246.6)	6255 (246.6)	6255 (246.6)	6990 (275.2)
2025 (79.7), 2195 (86.4)*1	2025 (79.7), 2195 (86.4)*1	2025 (79.7), 2195 (86.4)*1	2025 (79.7), 2195 (86.4)*1	2025 (79.7), 2195(86.4)*1	2025 (79.7), 2195 (86.4)*1
2430 (95.7), 2445 (96.3)*2	2430 (95.7), 2445 (96.3)*2	2585 (101.8), 2600 (102.4)*2	2585 (101.8), 2600 (102.4)*2	2430 (95.7), 2445 (96.3)*2	2600 (102.4)
3200 (126.0)	3200 (126.0)	3200 (126.0)	3200 (126.0)	3200 (126.0)	3935 (154.9)
1690 (66.5)	1690 (66.5)	1690 (66.5)	1690 (66.5)	1690 (66.5)	1690 (66.5)
1490 (58.7)	1490 (58.7)	1490 (58.7)	1490 (58.7)	1490 (58.7)	1490 (58.7)
5490 (216.1)	5490 (216.1)	5490 (216.1)	5490 (216.1)	5490 (216.1)	6230 (245.3)
1900 (74.8)	1900 (74.8)	1900 (74.8)	1900 (74.8)	1900 (74.8)	1890 (74.4)
1665 (65.6)	1665 (65.6)	1830 (72.0)	1830 (72.0)	1665 (65.6)	1830 (72.0)
—	—	—	—	—	—
—	—	—	—	—	—
—	—	—	—	—	—
1150 (45.3)	1150 (45.3)	1150 (45.3)	1150 (45.3)	1150 (45.3)	1150 (45.3)
1905 (75.0)	1905 (75.0)	1905 (75.0)	1905 (75.0)	1905 (75.0)	1905 (75.0)
175 (6.9), 185 (7.3)*2	175 (6.9), 185 (7.3)*2	175 (6.9), 185 (7.3)*2	175 (6.9), 185 (7.3)*2	175 (6.9), 185 (7.3)*2	185 (7.3)
17, 18*2	17, 18*2	17, 18*2	17, 18*2	17, 18*2	18
14	14	14	14	14	14
1400 - 1480 (3086 - 3263)	1400 - 1480 (3086 - 3263)	1490 - 1550 (3285 - 3417)	1490 - 1550 (3285 - 3417)	1490 - 1570 (3285 - 3461)	1720 - 1770 (3792 - 3902)
1440 - 1650 (3175 - 3638)	1440 - 1650 (3175 - 3638)	1490 - 1640 (3285 - 3616)	1490 - 1640 (3285 - 3616)	1480 - 1690 (3263 - 3726)	1565 - 1695 (3450 - 3737)
2840 - 3130 (6261 - 6900)	2840 - 3130 (6261 - 6900)	2980 - 3190 (6570 - 7033)	2980 - 3190 (6570 - 7033)	2970 - 3260 (6548 - 7187)	3285 - 3465 (7242 - 7639)
2020 (4453)	2020 (4453)	2020 (4453)	2020 (4453)	2020 (4453)	2400 (5291)
3160 (6967)	3160 (6967)	3160 (6967)	3160 (6967)	3160 (6967)	3270 (7209)
5180 (11420)	5180 (11420)	5180 (11420)	5180 (11420)	5180 (11420)	5670 (12500)
95 (20.9)	95 (20.9)	95 (20.9)	95 (20.9)	95 (20.9)	95 (20.9)
0.411 (14.5)	0.411 (14.5)	0.411 (14.5)	0.411 (14.5)	0.411 (14.5)	0.411 (14.5)
—	—	—	—	—	—
—	—	—	—	—	—
15 (9)	15 (9)	15 (9)	15 (9)	15 (9)	20 (12)
30 (19)	30 (19)	30 (19)	30 (19)	30 (19)	35 (20)
50 (31)	50 (31)	50 (31)	50 (31)	50 (31)	60 (37)
85 (53)	85 (53)	85 (53)	85 (53)	85 (53)	100 (62)
—	—	—	—	—	—
6.1 (20.0)	6.1 (20.0)	6.1 (20.0)	6.1 (20.0)	6.1 (20.0)	7.2 (23.6)
6.8 (22.3)	6.8 (22.3)	6.8 (22.3)	6.8 (22.3)	6.8 (22.3)	7.9 (25.9)
14B	14B	14B	14B	14B	15B-FT
8-valve OHV	8-valve OHV	8-valve OHV	8-valve OHV	8-valve OHV	16-valve OHV
102.0 × 112.0 (4.02 × 4.41)	102.0 × 112.0 (4.02 × 4.41)	102.0 × 112.0 (4.02 × 4.41)	102.0 × 112.0 (4.02 × 4.41)	102.0 × 112.0 (4.02 × 4.41)	108.0 × 112.0 (4.25 × 4.41)
3661 (223.4)	3661 (223.4)	3661 (223.4)	3661 (223.4)	3661 (223.4)	4104 (250.4)
18.0 : 1	18.0 : 1	18.0 : 1	18.0 : 1	18.0 : 1	18.5 : 1
Distributor Type	Distributor Type	Distributor Type	Distributor Type	Distributor Type	In-line Type
50 or higher	50 or higher	50 or higher	50 or higher	50 or higher	48 or higher
72/3400 (SAE-NET)	72/3400 (SAE-NET)	72/3400 (SAE-NET)	72/3400 (SAE-NET)	72/3400 (SAE-NET)	100/3000 (SAE-NET)
240/1800 (SAE-NET)	240/1800 (SAE-NET)	240/1800 (SAE-NET)	240/1800 (SAE-NET)	240/1800 (SAE-NET)	360/1600 (SAE-NET)
12 - 52, 24 - 48*3	12 - 52, 24 - 48*3	24 - 48	24 - 48	24 - 48	24 - 48
540, 1440*3	540, 1440*3	1440	1440	1440	1440
2.5, 4.5*3	2.5, 4.5*3	4.5	4.5	4.5	4.5
Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm
M152	M152	M152	M152	M152	M155
4.802	4.802	4.802	4.802	4.802	4.535
2.792	2.792	2.792	2.792	2.792	2.858
1.694	1.694	1.694	1.694	1.694	1.600
1.000	1.000	1.000	1.000	1.000	1.000
0.788	0.788	0.788	0.788	0.788	0.744
5.339	5.339	5.339	5.339	5.339	5.043
5.125, 5.625*3, 6.142*3	5.125, 5.625*3	5.625, 5.857*3	5.625, 5.857*3	5.625, 5.857*3	5.625
10.5	10.5	10.5	10.5	10.5	10.5
Two Leading Drum, Ventilated Disc*3	Two Leading Drum, Ventilated Disc*3	Two Leading Drum, Ventilated Disc*3	Two Leading Drum, Ventilated Disc*3	Two Leading Drum, Ventilated Disc*3	Two Leading Drum, Ventilated Disc*3
Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum
Drum	Drum	Drum	Drum	Drum	Drum
Single, 11	Single, 11	Single, 11	Single, 11	Single, 11	Tandem, 9 + 10
—	—	—	—	—	—
Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone
Leaf Spring	Leaf Spring	Leaf Spring	Leaf Spring	Leaf Spring	Leaf Spring
—	—	—	—	—	—
Option	Option	Option	Option	Option	Option
Recirculating Ball	Recirculating Ball	Recirculating Ball	Recirculating Ball	Recirculating Ball	Recirculating Ball
17.6	17.6	17.6	17.6	17.6	17.6
Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

AP

Item \ Area				General Countries			
Body Type				High Roof		Standard Roof	
Vehicle Grade				Standard	Standard (With Air Conditioner)	Standard	Standard (With Air Conditioner)
Model Code				BB50L-ZGMRW	HZB50R-ZGMSS	HZB50L-BGMRS	HZB50L-BGMSS
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	6990 (275.2)	6990 (275.2)	6990 (275.2)	6990 (275.2)
		Width	mm (in.)	2025 (79.7), 2195 (86.4)*1	2025 (79.7), 2195 (86.4)*1	2025 (79.7), 2195 (86.4)*1	2025 (79.7), 2195 (86.4)*1
		Height	mm (in.)	2600 (102.4)	2600 (102.4)	2445 (96.2)	2445 (96.2)
	Wheel Base		mm (in.)	3935 (154.9)	3935 (154.9)	3935 (154.9)	3935 (154.9)
	Tread	Front	mm (in.)	1690 (66.5)	1690 (66.5)	1690 (66.5)	1690 (66.5)
		Rear	mm (in.)	1490 (58.7)	1490 (58.7)	1490 (58.7)	1490 (58.7)
	Room	Length	mm (in.)	6230 (245.3)	6230 (245.3)	6230 (245.3)	6230 (245.3)
		Width	mm (in.)	1890 (74.4)	1890 (74.4)	1830 (72.0)	1890 (74.4)
		Height	mm (in.)	1830 (72.0)	1830 (72.0)	1665 (65.6)	1665 (65.5)
	Cargo Space	Length	mm (in.)	—	—	—	—
		Width	mm (in.)	—	—	—	—
		Height	mm (in.)	—	—	—	—
	Overhang	Front	mm (in.)	1150 (45.3)	1150 (45.3)	1150 (45.3)	1150 (45.3)
		Rear	mm (in.)	1905 (75.0)	1905 (75.0)	1905 (75.0)	1905 (75.0)
	Min. Running Ground Clearance		mm (in.)	185 (7.3)	185 (7.3)	185 (7.3)	185 (7.3)
	Angle of Approach		degrees	18	18	18	18
	Angle of Departure		degrees	14	14	14	14
	Curb Weight	Front	kg (lb)	1630 - 1680 (3594 - 3704)	1645 - 1695 (3627 - 3737)	1555 - 1625 (3428 - 3583)	1645 - 1725 (3627 - 3803)
		Rear	kg (lb)	1525 - 1655 (3362 - 3649)	1595 - 1725 (3516 - 3803)	1545 - 1745 (3406 - 3847)	1585 - 1780 (3494 - 3924)
		Total	kg (lb)	3155 - 3335 (6956 - 7352)	3240 - 3420 (7143 - 7540)	3100 - 3370 (6834 - 7430)	3230 - 3505 (7121 - 7727)
	Gross Vehicle Weight	Front	kg (lb)	2400 (5291)	2400 (5291)	2400 (5291)	2400 (5291)
		Rear	kg (lb)	3270 (7209)	3270 (7209)	3270 (7209)	3270 (7209)
		Total	kg (lb)	5670 (12500)	5670 (12500)	5670 (12500)	5670 (12500)
	Fuel Tank Capacity		ℓ (Imp.gal.)	95 (20.9)	95 (20.9)	95 (20.9)	95 (20.9)
	Luggage Compartment Capacity		m^3 (cu.ft.)	0.411 (14.5)	0.411 (14.5)	0.411 (14.5)	0.411 (14.5)
Performance	Max. Speed		km/h (mph)	—	—	—	—
	Max. Cruising Speed		km/h (mph)	—	—	—	—
	Max. Permissible Speed	1st Gear	km/h (mph)	20 (12)	20 (12)	20 (12)	20 (12)
		2nd Gear	km/h (mph)	35 (20)	35 (20)	35 (20)	35 (20)
		3rd Gear	km/h (mph)	60 (37)	60 (37)	60 (37)	60 (37)
		4th Gear	km/h (mph)	100 (62)	100 (62)	100 (62)	100 (62)
		5th Gear	km/h (mph)	—	—	—	—
	Min. Turning Radius	Tire	m (ft.)	7.2 (23.6)	7.2 (23.6)	7.2 (23.6)	7.2 (23.6)
		Body	m (ft.)	7.9 (25.9)	7.9 (25.9)	7.9 (25.9)	7.9 (25.9)
Engine	Engine Type			15B-FT	1HZ	1HZ	1HZ
	Valve Mechanism			16-valve OHV	12-valve OHC	12-valve OHC	12-valve OHC
	Bore × Stroke		mm (in.)	108.0 × 112.0 (4.25 × 4.41)	94.0 × 100.0 (3.70 × 3.94)	94.0 × 100.0 (3.70 × 3.94)	94.0 × 100.0 (3.70 × 3.94)
	Displacement		cm^3 (cu. in.)	4104 (250.4)	4164 (254.1)	4164 (254.1)	4164 (254.1)
	Compression Ratio			18.5 : 1	22.4 : 1	22.4 : 1	22.4 : 1
	Fuel System			In-line Type	Distributor Type	Distributor Type	Distributor Type
	Research Octane No. or Cetane No. (Diesel)			48 or higher	50 or higher	50 or higher	50 or higher
	Max. Output		kW/rpm	100/3000 (SAE-NET)	96/3800 (SAE-NET)	96/3800 (SAE-NET)	96/3800 (SAE-NET)
	Max. Torque		N·m/rpm	360/1600 (SAE-NET)	285/2200 (SAE-NET)	285/2200 (SAE-NET)	285/2200 (SAE-NET)
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp. hr.	24 - 48	24 - 48	12 - 52, 24 - 48*2	24 - 48
	Alternator Output		Watts	1440	1440	540, 1440*2	1440
	Starter Output		kW	4.5	4.5	2.5, 4.5*2	4.5
Chassis	Clutch Type			Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm
	Transmission Type			M155	M155	M155	M155
	Gear Ratio	In First		4.535	4.535	4.535	4.535
		In Second		2.858	2.858	2.858	2.858
		In Third		1.600	1.600	1.600	1.600
		In Fourth		1.000	1.000	1.000	1.000
		In Fifth		0.744	0.744	0.744	0.744
		In Reverse		5.043	5.043	5.043	5.043
	Differential Gear Ratio			5.625	5.625, 5.857*2	5.375, 5.625*2	5.625, 5.857*2
	Differential Gear Size		in.	10.5	10.5	10.5	10.5
	Brake Type	Front		Two Leading Drum, Ventilated Disc*2	Two Leading Drum, Ventilated Disc*2	Two Leading Drum, Ventilated Disc*2	Two Leading Drum, Ventilated Disc*2
		Rear		Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum
	Parking Brake Type			Drum	Drum	Drum	Drum
	Brake Booster Type and Size		in.	Tandem, 9 + 10	Tandem, 9 + 10	Tandem, 9 + 10	Tandem, 9 + 10
	Proportioning Valve Type			—	—	—	—
	Suspension Type	Front		Double-wishbone	Double-wishbone	Double-wishbone	Double-wishbone
		Rear		Leaf Spring	Leaf Spring	Leaf Spring	Leaf Spring
	Stabilizer Bar	Front		—	—	—	—
		Rear		Option	Option	Option	Option
	Steering Gear Type			Recirculating Ball	Recirculating Ball	Recirculating Ball	Recirculating Ball
	Steering Gear Ratio (Overall)			17.6	17.6	17.6	17.6
	Power Steering Type			Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

*1: With Snorkel Cleaner Air Duct
*2: Option

General Countries	
High Roof	
Standard	Standard (With Air Conditioner)
HZB50L-ZGMRS	HZB50L-ZGMSS
6990 (275.2)	6990 (275.2)
2025 (79.7), 2195 (86.4)*1	2025 (79.7), 2195 (86.4)*1
2600 (102.4)	2600 (102.4)
3935 (154.9)	3935 (154.9)
1690 (66.5)	1690 (66.5)
1490 (58.7)	1490 (58.7)
6230 (245.3)	6230 (245.3)
1890 (74.4)	1890 (74.4)
1830 (72.0)	1830 (72.0)
—	—
—	—
—	—
1150 (45.3)	1150 (45.3)
1905 (75.0)	1905 (75.0)
185 (7.3)	185 (7.3)
18	18
14	14
1555 - 1595 (3428 - 3516)	1645 - 1695 (3627 - 3737)
1555 - 1675 (3428 - 3693)	1595 - 1725 (3516 - 3803)
3110 - 3270 (6856 - 7209)	3240 - 3420 (7143 - 7540)
2400 (5291)	2400 (5291)
3270 (7209)	3270 (7209)
5670 (12500)	5670 (12500)
95 (20.9)	95 (20.9)
0.411 (14.5)	0.411 (14.5)
—	—
—	—
20 (12)	20 (12)
35 (20)	35 (20)
60 (37)	60 (37)
100 (62)	100 (62)
—	—
7.2 (23.6)	7.2 (23.6)
7.9 (25.9)	7.9 (25.9)
1HZ	1HZ
12-valve OHC	12-valve OHC
94.0 × 100.0 (3.70 × 3.94)	94.0 × 100.0 (3.70 × 3.94)
4164 (254.1)	4164 (254.1)
22.4 : 1	22.4 : 1
Distributor Type	Distributor Type
50 or higher	50 or higher
96/3800 (SAE-NET)	96/3800 (SAE-NET)
285/2200 (SAE-NET)	285/2200 (SAE-NET)
12 - 52, 24 - 48*2	24 - 48
540, 1440*2	1440
2.5, 4.5*2	4.5
Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm
M155	M155
4.535	4.535
2.858	2.858
1.600	1.600
1.000	1.000
0.744	0.744
5.043	5.043
5.375, 5.625*2, 6.142*2	5.625, 5.857*2
10.5	10.5
Two Leading Drum, Ventilated Disc*2	Two Leading Drum, Ventilated Disc*2
Dual Two Leading Drum	Dual Two Leading Drum
Drum	Drum
Tandem, 9 + 10	Tandem, 9 + 10
—	—
Double-wishbone	Double-wishbone
Leaf Spring	Leaf Spring
—	—
Option	Option
Recirculating Ball	Recirculating Ball
17.6	17.6
Hydraulic Type	Hydraulic Type