MAJOR TECHNICAL SPECIFICATIONS

Item \ Area				Australia			G.C.C. Countries
Body Type				High Roof			Standard Roof
Vehicle Grade				Standard (with Air Conditioner)	DX		Standard (with Air Conditioner)
Model Code				XZB50R-ZEMSYQ	XZB50R-ZEMNYQ	XZB50R-ZEPNYQ	TRB40L-BRMSKV
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	6990 (275.2)	6990 (275.2)	6990 (275.2)	6255 (246.6)
		Width	mm (in.)	2095 (82.5)	2095 (82.5)	2095 (82.5)	2035 (80.1)
		Height	mm (in.)	2600 (102.4)	2600 (102.4)	2600 (102.4)	2430 (95.7), 2445 (96.3)*2
	Wheel Base		mm (in.)	3935 (154.9)	3935 (154.9)	3935 (154.9)	3200 (126.0)
	Tread	Front	mm (in.)	1690 (66.5)	1690 (66.5)	1690 (66.5)	1690 (66.5)
		Rear	mm (in.)	1490 (58.7)	1490 (58.7)	1490 (58.7)	1490 (58.7)
	Room	Length	mm (in.)	6200 (244.1)	6200 (244.1)	6200 (244.1)	5465 (215.2)
		Width	mm (in.)	1890 (74.4)	1890 (74.4)	1890 (74.4)	1900 (74.8)
		Height	mm (in.)	1830 (72.0)	1830 (72.0)	1830 (72.0)	1665 (65.6)
	Cargo Space	Length	mm (in.)	—	—	—	—
		Width	mm (in.)	—	—	—	—
		Height	mm (in.)	—	—	—	—
	Overhang	Front	mm (in.)	1150 (45.3)	1150 (45.3)	1150 (45.3)	1150 (45.3)
		Rear	mm (in.)	1905 (75.0)	1905 (75.0)	1905 (75.0)	1905 (75.0)
	Min. Running Ground Clearance		mm (in.)	185 (7.3)	185 (7.3)	185 (7.3)	175 (6.9), 185 (7.3)*2
	Angle of Approach		degrees	18	18	18	17, 18*2
	Angle of Departure		degrees	14	14	14	14
	Curb Weight	Front	kg (lb)	1810 - 1815 (3990 - 4001)	1820 - 1825 (4012 - 4023)	1830 - 1835 (4034 - 4045)	1350 - 1470 (2976 - 3241)
		Rear	kg (lb)	1830 - 1855 (4034 - 4090)	1840 - 1865 (4056 - 4112)	1840 - 1865 (4056 - 4112)	1460 - 1670 (3219 - 3681)
		Total	kg (lb)	3640 - 3670 (8025 - 8091)	3660 - 3690 (8069 - 8135)	3670 - 3700 (8091 - 8157)	2810 - 3140 (6195 - 6922)
	Gross Vehicle Weight	Front	kg (lb)	2300 (5071)	2300 (5071)	2300 (5071)	2020 (4453)
		Rear	kg (lb)	3140 (6922)	3140 (6922)	3140 (6922)	2990 (6592)
		Total	kg (lb)	5440 (11993)	5440 (11993)	5440 (11993)	5010 (11045)
	Fuel Tank Capacity		ℓ (Imp. gal)	95 (20.9)	95 (20.9)	95 (20.9)	95 (20.9)
	Luggage Compartment Capacity		m^3 (cu. ft.)	0.411 (14.5)	0.411 (14.5)	0.411 (14.5)	0.411 (14.5)
Performance	Max. Speed		km/h (mph)	125 (78)	125 (78)	120 (74)	130 (81)
	Max. Cruising Speed		km/h (mph)	—	—	—	—
	Max. Permissible Speed	1st Gear	km/h (mph)	15 (9)	15 (9)	35 (22)	20 (12)
		2nd Gear	km/h (mph)	30 (19)	30 (19)	68 (42)	40 (25)
		3rd Gear	km/h (mph)	50 (31)	50 (31)	—	70 (43)
		4th Gear	km/h (mph)	85 (53)	85 (53)	—	115 (71)
		5th Gear	km/h (mph)	—	—	—	—
	Min. Turning Radius	Tire	m (ft.)	7.2 (23.6)	7.2 (23.6)	7.2 (23.6)	6.1 (20.0)
		Body	m (ft.)	7.9 (25.9)	7.9 (25.9)	7.9 (25.9)	6.8 (22.3)
Engine	Engine Type			N04C-UH	N04C-UH	N04C-UH	2TR-FE
	Valve Mechanism			16-valve OHV	16-valve OHV	16-valve OHV	16-valve DOHC
	Bore × Stroke		mm (in.)	104.0 × 118.0 (4.09 × 4.65)	104.0 × 118.0 (4.09 × 4.65)	104.0 × 118.0 (4.09 × 4.65)	95.0 × 95.0 (3.74 × 3.74)
	Displacement		cm^3 (cu. in.)	4009 (244.6)	4009 (244.6)	4009 (244.6)	2694 (164.4)
	Compression Ratio			18.0 : 1	18.0 : 1	18.0 : 1	9.6 : 1
	Fuel System			Common-rail Type	Common-rail Type	Common-rail Type	EFI
	Research Octane No. or Cetane No. (Diesel)			50 or higher	50 or higher	50 or higher	91 or higher
	Max. Output		kW/rpm	110/2700 (EEC)	110/2700 (EEC)	110/2700 (EEC)	108/4800
	Max. Torque		N·m/rpm	397/1800 (EEC)	397/1800 (EEC)	397/1800 (EEC)	235/3800
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp. hr.	12 - 64	12 - 64	12 - 64	12 - 48
	Alternator Output		Watts	1560	1560	1560	960
	Starter Output		kW	2.7	2.7	2.7	1.4
Chassis	Clutch Type			Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm	—	Dry, Single Plate Diaphragm
	Transmission Type			M551	M551	A444E	M156
	Gear Ratio	In First		5.099	5.099	2.950	5.657
		In Second		2.910	2.910	1.530	2.818
		In Third		1.652	1.652	1.000	1.687
		In Fourth		1.000	1.000	0.703	1.000
		In Fifth		0.674	0.674	—	0.835
		Reverse		4.625	4.625	2.678	5.657
	Differential Gear Ratio			5.375	5.375	4.875	5.857
	Differential Gear Size		in.	10.5	10.5	10.5	10.5
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Two Leading Drum, Ventilated Disc*1
		Rear		Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum
	Parking Brake Type			Drum	Drum	Drum	Drum
	Brake Booster Type and Size		in.	Tandem, 9" + 10"	Tandem, 9" + 10"	Tandem, 9" + 10"	Single, 11"
	Proportioning Valve Type			LSP and BV	LSP and BV	LSP and BV	—
	Suspension Type	Front		Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
		Rear		Leaf Spring	Leaf Spring	Leaf Spring	Leaf Spring
	Stabilizer Bar	Front		—	—	—	—
		Rear		—	—	—	Option
	Steering Gear Type			Recirculating Ball	Recirculating Ball	Recirculating Ball	Recirculating Ball
	Steering Gear Ratio (Overall)			17.7	17.7	17.7	17.7
	Power Steering Type			Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

*1: Option
*2: with 7.00 R16 Tire (Option)
*3: with ABS
*4: with ABS or Option

G.C.C. Countries					
Standard Roof	High Roof		Standard Roof		High Roof
Standard (with Air Conditioner)					
TRB50L-BGMSKV	TRB50L-ZGMSKV	TRB50L-ZXMSKV	BB42L-BRMSSV	HZB50L-BGMSSV	HZB50L-ZGMSSV
6990 (275.2)	6990 (275.2)	6990 (275.2)	6255 (246.6)	6990 (275.2)	6990 (275.2)
2035 (80.1)	2035 (80.1)	2035 (80.1)	2035 (80.1)	2035 (80.1)	2035 (80.1)
2445 (96.2)	2600 (102.4)	2600 (102.4)	2430 (95.7), 2445 (96.3)*2	2445 (96.2)	2600 (102.4)
3935 (154.9)	3935 (154.9)	3935 (154.9)	3200 (126.0)	3935 (154.9)	3935 (154.9)
1690 (66.5)	1690 (66.5)	1690 (66.5)	1690 (66.5)	1690 (66.5)	1690 (66.5)
1490 (58.7)	1490 (58.7)	1490 (58.7)	1490 (58.7)	1490 (58.7)	1490 (58.7)
6200 (244.1)	6200 (244.1)	5655 (222.6)	5465 (215.2)	6200 (244.1)	6200 (244.1)
1900 (74.8)	1900 (74.8)	1900 (74.8)	1900 (74.8)	1890 (74.4)	1890 (74.4)
1665 (65.6)	1830 (72.0)	1830 (72.0)	1665 (65.6)	1665 (65.6)	1830 (72.0)
—	—	—	—	—	—
—	—	—	—	—	—
—	—	—	—	—	—
1150 (45.3)	1150 (45.3)	1150 (45.3)	1150 (45.3)	1150 (45.3)	1150 (45.3)
1905 (75.0)	1905 (75.0)	1905 (75.0)	1905 (75.0)	1905 (75.0)	1905 (75.0)
185 (7.3)	185 (7.3)	185 (7.3)	175 (6.9), 185 (7.3)*2	185 (7.3)	185 (7.3)
18	18	18	17, 18*2	18	18
14	14	14	14	14	14
1455 - 1575 (3208 - 3472)	1455 - 1565 (3208 - 3450)	1450 - 1480 (3170 - 3263)	1510 - 1590 (3329 - 3505)	1710 - 1800 (3770 - 3968)	1710 - 1775 (3770 - 3913)
1525 - 1735 (3362 - 3825)	1535 - 1695 (3384 - 3737)	1540 - 2040 (3395 - 4497)	1520 - 1690 (3351 - 3275)	1600 - 1775 (3527 - 3913)	1610 - 1730 (3549 - 3814)
2980 - 3310 (6570 - 7297)	2990 - 3260 (6591 - 7187)	2990 - 3520 (6591 - 7760)	3030 - 3280 (6680 - 7231)	3310 - 3575 (7297 - 7881)	3320 - 3505 (7319 - 7727)
2170 (4784)	2170 (4784)	2170 (4784)	2020 (4453)	2400 (5291)	2400 (5291)
3140 (6923)	3140 (6923)	3140 (6923)	3160 (6967)	3270 (7209)	3270 (7209)
5310 (11707)	5310 (11707)	5310 (11707)	5180 (11420)	5670 (12500)	5670 (12500)
95 (20.9)	95 (20.9)	95 (20.9)	95 (20.9)	95 (20.9)	95 (20.9)
0.411 (14.5)	0.411 (14.5)	—	0.411 (14.5)	0.411 (14.5)	0.411 (14.5)
130 (81)	130 (81)	130 (81)	115 (71)	130 (81)	130 (81)
—	—	—	—	—	—
20 (12)	20 (12)	20 (12)	15 (9)	20 (12)	20 (12)
40 (25)	40 (25)	40 (25)	30 (19)	35 (22)	35 (22)
70 (43)	70 (43)	70 (43)	50 (31)	60 (37)	60 (37)
115 (71)	115 (71)	115 (71)	85 (53)	100 (62)	100 (62)
—	—	—	—	—	—
7.2 (23.6)	7.2 (23.6)	7.2 (23.6)	6.1 (20.0)	7.2 (23.6)	7.2 (23.6)
7.9 (25.9)	7.9 (25.9)	7.9 (25.9)	6.8 (22.3)	7.9 (25.9)	7.9 (25.9)
2TR-FE	2TR-FE	2TR-FE	14B	1HZ	1HZ
16-valve DOHC	16-valve DOHC	16-valve DOHC	8-valve OHV	12-valve OHC	12-valve OHC
95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	102.0 × 112.0 (4.02 × 4.41)	94.0 × 100.0 (3.70 × 3.94)	94.0 × 100.0 (3.70 × 3.94)
2694 (164.4)	2694 (164.4)	2694 (164.4)	3661 (223.4)	4164 (254.1)	4164 (254.1)
9.6 : 1	9.6 : 1	9.6 : 1	18.0 : 1	22.4 : 1	22.4 : 1
EFI	EFI	EFI	Distributor Type	Distributor Type	Distributor Type
91 or higher	91 or higher	91 or higher	50 or higher	50 or higher	50 or higher
108/4800	108/4800	108/4800	72/3400 (SAE-NET)	96/3800 (SAE-NET)	96/3800 (SAE-NET)
235/3800	235/3800	235/3800	240/1800 (SAE-NET)	285/2200 (SAE-NET)	285/2200 (SAE-NET)
12 - 48	12 - 48	12 - 48	24 - 48	24 - 48	24 - 48
960	960	960	1440	1440	1440
1.4	1.4	1.4	4.5	4.5	4.5
Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm
M156	M156	M156	M152	M155	M155
5.657	5.657	5.657	4.802	4.535	4.535
2.818	2.818	2.818	2.792	2.858	2.858
1.687	1.687	1.687	1.694	1.600	1.600
1.000	1.000	1.000	1.000	1.000	1.000
0.835	0.835	0.835	0.788	0.744	0.744
5.657	5.657	5.657	5.339	5.043	5.043
6.142	6.142	6.142	5.625	5.625	5.625
10.5	10.5	10.5	10.5	10.5	10.5
Ventilated Disc	Ventilated Disc	Ventilated Disc	Two Leading Drum, Ventilated Disc*1	Two Leading Drum, Ventilated Disc*4	Two Leading Drum, Ventilated Disc*4
Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum
Drum	Drum	Drum	Drum	Drum	Drum
Tandem, 9" + 10"	Tandem, 9" + 10"	Tandem, 9" + 10"	Single, 11"	Tandem, 9" + 10"	Tandem, 9" + 10"
—, LSP and BV*3	—, LSP and BV*3	—, LSP and BV*3	—	—, LSP and BV*3	—, LSP and BV*3
Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
Leaf Spring	Leaf Spring	Leaf Spring	Leaf Spring	Leaf Spring	Leaf Spring
—	—	—	—	—	—
Option	Option	Option	Option	Option	Option
Recirculating Ball	Recirculating Ball	Recirculating Ball	Recirculating Ball	Recirculating Ball	Recirculating Ball
17.7	17.7	17.7	17.7	17.7	17.7
Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

Item \ Area			G.C.C. Countries	Taiwan	Hong Kong	
Body Type			High Roof			
Vehicle Grade			Standard (with Air Conditioner)		EX	
Model Code			HZB50L-ZXMSSV	XZB50L-ZEMSYR	XZB50R-ZEMQY	XZB50R-ZEPQY
Major Dimensions & Vehicle Weights	Overall	Length mm (in.)	6990 (275.2)	6990 (275.2)	6990 (275.2)	6990 (275.2)
		Width mm (in.)	2035 (80.1)	2035 (80.1)	2035 (80.1)	2035 (80.1)
		Height mm (in.)	2600 (102.4)	2620 (103.1)	2600 (102.4)	2600 (102.4)
	Wheel Base	mm (in.)	3935 (154.9)	3935 (154.9)	3935 (154.9)	3935 (154.9)
	Tread	Front mm (in.)	1690 (66.5)	1690 (66.5)	1690 (66.5)	1690 (66.5)
		Rear mm (in.)	1490 (58.7)	1490 (58.7)	1490 (58.7)	1490 (58.7)
	Room	Length mm (in.)	6200 (244.1)	6200 (244.1)	6200 (244.1)	6200 (244.1)
		Width mm (in.)	1890 (74.4)	1900 (74.8)	1890 (74.4)	1890 (74.4)
		Height mm (in.)	1830 (72.0)	1860 (73.2)	1830 (72.0)	1830 (72.0)
	Cargo Space	Length mm (in.)	—	—	—	—
		Width mm (in.)	—	—	—	—
		Height mm (in.)	—	—	—	—
	Overhang	Front mm (in.)	1150 (45.3)	1150 (45.3)	1150 (45.3)	1150 (45.3)
		Rear mm (in.)	1905 (75.0)	1905 (75.0)	1905 (75.0)	1905 (75.0)
	Min. Running Ground Clearance	mm (in.)	185 (7.3)	175 (6.9)	175 (6.9)	175 (6.9)
	Angle of Approach	degrees	18	17	17	17
	Angle of Departure	degrees	14	14	14	14
	Curb Weight	Front kg (lb)	1705 - 1690 (3759 - 3726)	1785 - 1790 (3935 - 3946)	1780 - 1795 (3924 - 3957), 1765 - 1780 (3891 - 3924)*6	1790 - 1805 (3946 - 3979)
		Rear kg (lb)	1615 - 2075 (3560 - 4575)	1670 - 1685 (3682 - 3714)	1745 - 1775 (3847 - 3913), 1735 - 1755 (3824 - 3869)*6	1745 - 1775 (3847 - 3913)
		Total kg (lb)	3320 - 3765 (7319 - 8300)	3455 - 3475 (7616 - 7661)	3525 - 3570 (7771 - 7870), 3500 - 3535 (7716 - 7793)*6	3535 - 3580 (7793 - 7892)
	Gross Vehicle Weight	Front kg (lb)	2400 (5291)	2340 (5082)	2150 (4740)	2150 (4740)
		Rear kg (lb)	3270 (7209)	3105 (6592)	2840 (6261)	2840 (6261)
		Total kg (lb)	5670 (12500)	5445 (11673)	4990 (11001)	4990 (11001)
	Fuel Tank Capacity	ℓ (Imp. gal)	95 (20.9)	95 (20.9)	95 (20.9)	95 (20.9)
	Luggage Compartment Capacity	m^3 (cu. ft.)	—	—	—	—
Performance	Max. Speed	km/h (mph)	130 (81)	—	—	—
	Max. Cruising Speed	km/h (mph)	—	—	—	—
	Max. Permissible Speed	1st Gear km/h (mph)	20 (12)	15 (9)	15 (9)	35 (22)
		2nd Gear km/h (mph)	35 (22)	30 (19)	30 (19)	68 (42)
		3rd Gear km/h (mph)	60 (37)	50 (31)	50 (31)	—
		4th Gear km/h (mph)	100 (62)	85 (53)	85 (53)	—
		5th Gear km/h (mph)	—	—	—	—
	Min. Turning Radius	Tire m (ft.)	7.2 (23.6)	7.2 (23.6)	7.2 (23.6)	7.2 (23.6)
		Body m (ft.)	7.9 (25.9)	7.9 (25.9)	7.9 (25.9)	7.9 (25.9)
Engine	Engine Type		1HZ	N04C-UH	N04C-UH	N04C-UH
	Valve Mechanism		12-valve OHC	16-valve OHV	16-valve OHV	16-valve OHV
	Bore × Stroke	mm (in.)	94.0 × 100.0 (3.70 × 3.94)	104.0 × 118.0 (4.09 × 4.65)	104.0 × 118.0 (4.09 × 4.65)	104.0 × 118.0 (4.09 × 4.65)
	Displacement	cm^3 (cu. in.)	4164 (254.1)	4009 (244.6)	4009 (244.6)	4009 (244.6)
	Compression Ratio		22.4 : 1	18.0 : 1	18.0 : 1	18.0 : 1
	Fuel System		Distributor Type	Common-rail Type	Common-rail Type	Common-rail Type
	Research Octane No. or Cetane No. (Diesel)		50 or higher	50 or higher	50 or higher	50 or higher
	Max. Output	kW/rpm	96/3800 (SAE-NET)	110/2700 (EEC)	110/2700 (EEC)	110/2700 (EEC)
	Max. Torque	N·m/rpm	285/2200 (SAE-NET)	397/1800 (EEC)	397/1800 (EEC)	397/1800 (EEC)
Engine Electrical	Battery Capacity (5HR)	Voltage & Amp. hr.	12 - 48	12 - 64	12 - 64	12 - 64
	Alternator Output	Watts	1440	1560	1560	1560
	Starter Output	kW	4.5	2.7	2.7	2.7
Chassis	Clutch Type		Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm	—
	Transmission Type		M155	M551	M551	A441E
	Gear Ratio	In First	4.535	5.099	5.099	2.950
		In Second	2.858	2.910	2.910	1.530
		In Third	1.600	1.652	1.652	1.000
		In Fourth	1.000	1.000	1.000	0.703
		In Fifth	0.744	0.674	0.674	—
		Reverse	5.043	4.625	4.625	2.678
	Differential Gear Ratio		5.625	5.375	5.375	4.875
	Differential Gear Size	in.	10.5	10.5	10.5	10.5
	Brake Type	Front	Two Leading Drum, Ventilated Disc*4	Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear	Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum
	Parking Brake Type		Drum	Drum	Drum	Drum
	Brake Booster Type and Size	in.	Tandem, 9" + 10"	Tandem, 9" + 10"	Tandem, 9" + 10"	Tandem, 9" + 10"
	Proportioning Valve Type		—, LSP and BV*5	LSP and BV	LSP and BV	LSP and BV
	Suspension Type	Front	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
		Rear	Leaf Spring	Leaf Spring	Leaf Spring	Leaf Spring
	Stabilizer Bar	Front	—	—	—	—
		Rear	Option	Standard	Standard	Standard
	Steering Gear Type		Recirculating Ball	Recirculating Ball	Recirculating Ball	Recirculating Ball
	Steering Gear Ratio (Overall)		17.7	17.7	17.7	17.7
	Power Steering Type		Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

*1: with Snorkel Cleaner Air Duct *3: Option *5: with ABS
*2: with 7.00 R16 Tire (Option) *4: with ABS or Option *6: Models for Singapore Package

	Hong Kong				General Countries	
	High Roof				Standard Roof	
	Standard (with Air Conditioner)	EX	Standard (with Air Conditioner)		Standard	Standard (with Air Conditioner)
	XZB40R-ZCMSY	XZB59R-ZEMQY5	BZB40R-ZCMSC	BZB50R-ZCMSC5	TRB40L-BRMRK	TRB40L-BRMSK
	6255 (246.6)	7725 (304.1)	6255 (246.6)	6990 (275.2)	6255 (246.6)	6255 (246.6)
	2035 (80.1)	2035 (80.1)	2035 (80.1)	2035 (80.1)	2025 (79.7), 2195 (86.4)*1	2025 (79.7), 2195 (86.4)*1
	2665 (104.9)	2600 (102.4)	2665 (104.9)	2675 (105.3)	2430 (95.7), 2445 (96.3)*2	2430 (95.7), 2445 (96.3)*2
	3200 (126.0)	4435 (174.6)	3200 (126.0)	3935 (154.9)	3200 (126.0)	3200 (126.0)
	1690 (66.5)	1690 (66.5)	1690 (66.5)	1690 (66.5)	1690 (66.5)	1690 (66.5)
	1490 (58.7)	1490 (58.7)	1490 (58.7)	1490 (58.7)	1490 (58.7)	1490 (58.7)
	5465 (215.2)	6955 (273.8)	5465 (215.2)	6200 (244.1)	5465 (215.2)	5465 (215.2)
	1900 (74.8)	1890 (74.4)	1900 (74.8)	1890 (74.4)	1900 (74.8)	1900 (74.8)
	1830 (72.0)	1830 (72.0)	1830 (72.0)	1830 (72.0)	1665 (65.6)	1665 (65.6)
	—	—	—	—	—	—
	—	—	—	—	—	—
	—	—	—	—	—	—
	1150 (45.3)	1150 (45.3)	1150 (45.3)	1150 (45.3)	1150 (45.3)	1150 (45.3)
	1905 (75.0)	2140 (84.3)	1905 (75.0)	1905 (75.0)	1905 (75.0)	1905 (75.0)
	175 (6.9)	175 (6.9)	175 (6.9)	185 (7.3)	175 (6.9), 185 (7.3)*2	175 (6.9), 185 (7.3)*2
	17	17	17	18	17, 18*2	17, 18*2
	14	12	14	14	14	14
	1620 - 1635 (3571 - 3605)	1865 - 1880 (4112 - 4145)	1580 - 1595 (3483 - 3516)	1710 - 1725 (3770 - 3803)	1255 - 1375 (2767 - 3031)	1345 - 1465 (2965 - 3230)
	1670 - 1685 (3682 - 3715)	1850 - 1880 (4078 - 4145)	1610 - 1625 (3549 - 3582)	1650 - 1665 (3638 - 3671)	1405 - 1645 (3097 - 3626)	1445 - 1685 (3186 - 3715)
	3290 - 3320 (7253 - 7319)	3715 - 3760 (8190 - 8289)	3190 - 3220 (7033 - 7099)	3360 - 3390 (7407 - 7474)	2660 - 3020 (5864 - 6658)	2790 - 3150 (6151 - 6944)
	2100 (4630)	2300 (5071)	2100 (4630)	2100 (4630)	2020 (4453)	2020 (4453)
	2700 (5952)	3300 (7275)	2700 (5952)	2700 (5952)	2990 (6592)	2990 (6592)
	4800 (10582)	5600 (12346)	4800 (10582)	4800 (10582)	5010 (11045)	5010 (11045)
	95 (20.9)	95 (20.9)	122 (26.8)	122 (26.8)	95 (20.9)	95 (20.9)
	0.411 (14.5)	—	0.411 (14.5)	0.411 (14.5)	0.411 (14.5)	0.411 (14.5)
	—	—	—	—	—	—
	—	—	—	—	—	—
	15 (9)	15 (9)	15 (9)	15 (9)	20 (12)	20 (12)
	30 (19)	30 (19)	25 (16)	25 (16)	40 (25)	40 (25)
	50 (31)	50 (31)	50 (31)	50 (31)	70 (43)	70 (43)
	85 (53)	85 (53)	85 (53)	85 (53)	115 (71)	115 (71)
	—	—	—	—	—	—
	6.1 (20.0)	8.1 (26.6)	6.1 (20.0)	7.2 (23.6)	6.1 (20.0)	6.1 (20.0)
	6.8 (22.3)	8.8 (28.9)	6.8 (22.3)	7.9 (25.9)	6.8 (22.3)	6.8 (22.3)
	N04C-UH	N04C-UH	1BZ-FPE	1BZ-FPE	2TR-FE	2TR-FE
	16-valve OHV	16-valve OHV	16-valve OHV	16-valve OHV	16-valve DOHC	16-valve DOHC
	104.0 × 118.0 (4.09 × 4.65)	104.0 × 118.0 (4.09 × 4.65)	108.0 × 112.0 (4.25 × 4.41)	108.0 × 112.0 (4.25 × 4.41)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)
	4009 (244.6)	4009 (244.6)	4104 (250.4)	4104 (250.4)	2694 (164.4)	2694 (164.4)
	18.0 : 1	18.0 : 1	9.5 : 1	9.5 : 1	9.6 : 1	9.6 : 1
	Common-rail Type	Common-rail Type	Carburetor (Electronically Controlled)	Carburetor (Electronically Controlled)	EFI	EFI
	50 or higher	50 or higher	100 or higher	100 or higher	91 or higher	91 or higher
	110/2700 (EEC)	110/2700 (EEC)	85/3600 (SAE-NET)	85/3600 (SAE-NET)	109/4800	109/4800
	397/1800 (EEC)	397/1800 (EEC)	306/2000 (SAE-NET)	306/2000 (SAE-NET)	245/3800	245/3800
	12 - 64	12 - 64	12 - 64	12 - 64	12 - 48	12 - 48
	1560	1560	1200	1200	960	960
	2.7	2.7	2.5	2.5	1.4	1.4
	Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm
	M551	M551	M155	M155	M156	M156
	5.099	5.099	4.535	4.535	5.657	5.657
	2.910	2.910	2.858	2.858	2.818	2.818
	1.652	1.652	1.600	1.600	1.687	1.687
	1.000	1.000	1.000	1.000	1.000	1.000
	0.674	0.674	0.744	0.744	0.835	0.835
	4.625	4.625	5.043	5.043	5.657	5.657
	5.375	5.375	5.625	5.625	5.857	5.857
	10.5	10.5	10.5	10.5	10.5	10.5
	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Two Leading Drum, Ventilated Disc*3	Two Leading Drum, Ventilated Disc*3
	Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum
	Drum	Drum	Drum	Drum	Drum	Drum
	Tandem, 9" + 10"	Tandem, 9" + 10"	Tandem, 9" + 10"	Tandem, 9" + 10"	Single, 11"	Single, 11"
	LSP and BV	LSP and BV	LSP and BV	LSP and BV	—	—
	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
	Leaf Spring	Leaf Spring	Leaf Spring	Leaf Spring	Leaf Spring	Leaf Spring
	—	—	—	—	—	—
	Standard	Standard	Standard	Standard	Option	Option
	Recirculating Ball	Recirculating Ball	Recirculating Ball	Recirculating Ball	Recirculating Ball	Recirculating Ball
	17.7	17.7	17.7	17.7	17.7	17.7
	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

Item \ Area			General Countries			
Body Type			High Roof		Standard Roof	
Vehicle Grade			Standard (with Air Conditioner)		Standard	
Model Code			TRB40L-ZRMSK	TRB50L-ZGMSK	BB42L-BRMRS	BB42R-BRMRS
Major Dimensions & Vehicle Weights	Overall	Length mm (in.)	6255 (246.6)	6990 (275.2)	6255 (246.6)	6255 (246.6)
		Width mm (in.)	2025 (79.7), 2195 (86.4)*1	2025 (79.7), 2195 (86.4)*1	2025 (79.7), 2195 (86.4)*1	2025 (79.7), 2195 (86.4)*1
		Height mm (in.)	2585 (101.8), 2600 (102.4)*2	2600 (102.4)	2430 (95.7), 2445 (96.3)*2	2430 (95.7), 2445 (96.3)*2
	Wheel Base	mm (in.)	3200 (126.0)	3935 (154.9)	3200 (126.0)	3200 (126.0)
	Tread	Front mm (in.)	1690 (66.5)	1690 (66.5)	1690 (66.5)	1690 (66.5)
		Rear mm (in.)	1490 (58.7)	1490 (58.7)	1490 (58.7)	1490 (58.7)
	Room	Length mm (in.)	5465 (215.2)	6200 (244.1)	5465 (215.2)	5465 (215.2)
		Width mm (in.)	1900 (74.8)	1890 (74.4)	1900 (74.8)	1900 (74.8)
		Height mm (in.)	1830 (72.0)	1830 (72.0)	1665 (65.6)	1665 (65.6)
	Cargo Space	Length mm (in.)	—	—	—	—
		Width mm (in.)	—	—	—	—
		Height mm (in.)	—	—	—	—
	Overhang	Front mm (in.)	1150 (45.3)	1150 (45.3)	1150 (45.3)	1150 (45.3)
		Rear mm (in.)	1905 (75.0)	1905 (75.0)	1905 (75.0)	1905 (75.0)
	Min. Running Ground Clearance	mm (in.)	175 (6.9), 185 (7.3)*2	185 (7.3)	175 (6.9), 185 (7.3)*2	175 (6.9), 185 (7.3)*2
	Angle of Approach	degrees	17, 18*2	18	17, 18*2	17, 18*2
	Angle of Departure	degrees	14	14	14	14
	Curb Weight	Front kg (lb)	1345 - 1445 (2965 - 3186)	1445 - 1535 (3186 - 3384)	1415 - 1495 (3120 - 3296)	1415 - 1495 (3120 - 3296)
		Rear kg (lb)	1455 - 1645 (3207 - 3627)	1525 - 1705 (3362 - 3759)	1465 - 1675 (3230 - 3693)	1475 - 1685 (3252 - 3715)
		Total kg (lb)	2800 - 3090 (6173 - 6812)	2970 - 3240 (6548 - 7143)	2880 - 3170 (6349 - 6989)	2890 - 3180 (6371 - 7011)
	Gross Vehicle Weight	Front kg (lb)	2020 (4453)	2170 (4784)	2020 (4453)	2020 (4453)
		Rear kg (lb)	2990 (6592)	3140 (6923)	3160 (6967)	3160 (6967)
		Total kg (lb)	5010 (11045)	5310 (11707)	5180 (11420)	5180 (11420)
	Fuel Tank Capacity	ℓ (Imp. gal)	95 (20.9)	95 (20.9)	95 (20.9)	95 (20.9)
	Luggage Compartment Capacity	m^3 (cu. ft.)	0.411 (14.5)	0.411 (14.5)	0.411 (14.5)	0.411 (14.5)
Performance	Max. Speed	km/h (mph)	—	—	—	—
	Max. Cruising Speed	km/h (mph)	—	—	—	—
	Max. Permissible Speed	1st Gear km/h (mph)	20 (12)	20 (12)	15 (9)	15 (9)
		2nd Gear km/h (mph)	40 (25)	40 (25)	30 (19)	30 (19)
		3rd Gear km/h (mph)	70 (43)	70 (43)	50 (31)	50 (31)
		4th Gear km/h (mph)	115 (71)	115 (71)	85 (53)	85 (53)
		5th Gear km/h (mph)	—	—	—	—
	Min. Turning Radius	Tire m (ft.)	6.1 (20.0)	7.2 (23.6)	6.1 (20.0)	6.1 (20.0)
		Body m (ft.)	6.8 (22.3)	7.9 (25.9)	6.8 (22.3)	6.8 (22.3)
Engine	Engine Type		2TR-FE	2TR-FE	14B	14B
	Valve Mechanism		16-valve DOHC	16-valve DOHC	8-valve OHV	8-valve OHV
	Bore × Stroke	mm (in.)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	102.0 × 112.0 (4.02 × 4.41)	102.0 × 112.0 (4.02 × 4.41)
	Displacement	cm^3 (cu. in.)	2694 (164.4)	2694 (164.4)	3661 (223.4)	3661 (223.4)
	Compression Ratio		9.6 : 1	9.6 : 1	18.0 : 1	18.0 : 1
	Fuel System		EFI	EFI	Distributor Type	Distributor Type
	Research Octane No. or Cetane No. (Diesel)		91 or higher	91 or higher	50 or higher	50 or higher
	Max. Output	kW/rpm	109/4800	109/4800	72/3400 (SAE-NET)	72/3400 (SAE-NET)
	Max. Torque	N·m/rpm	245/3800	245/3800	240/1800 (SAE-NET)	240/1800 (SAE-NET)
Engine Electrical	Battery Capacity (5HR)	Voltage & Amp. hr.	12 - 48	12 - 48	12 - 52, 24 - 48*3	12 - 52, 24 - 48*3
	Alternator Output	Watts	960	960	540, 1440*3	540, 1440*3
	Starter Output	kW	1.4	1.4	2.5, 4.5*3	2.5, 4.5*3
Chassis	Clutch Type		Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm
	Transmission Type		M156	M156	M152	M152
	Gear Ratio	In First	5.657	5.657	4.802	4.802
		In Second	2.818	2.818	2.792	2.792
		In Third	1.687	1.687	1.694	1.694
		In Fourth	1.000	1.000	1.000	1.000
		In Fifth	0.835	0.835	0.788	0.788
		Reverse	5.657	5.657	5.339	5.339
	Differential Gear Ratio		5.857	6.142	5.125, 5.625*3	5.125, 5.625*3
	Differential Gear Size	in.	10.5	10.5	10.5	10.5
	Brake Type	Front	Two Leading Drum, Ventilated Disc*3	Ventilated Disc	Two Leading Drum, Ventilated Disc*3	Two Leading Drum, Ventilated Disc*3
		Rear	Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum
	Parking Brake Type		Drum	Drum	Drum	Drum
	Brake Booster Type and Size	in.	Single, 11"	Tandem, 9" + 10"	Single, 11"	Single, 11"
	Proportioning Valve Type		—	—	—	—
	Suspension Type	Front	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
		Rear	Leaf Spring	Leaf Spring	Leaf Spring	Leaf Spring
	Stabilizer Bar	Front	—	—	—	—
		Rear	Option	Option	Option	Option
	Steering Gear Type		Recirculating Ball	Recirculating Ball	Recirculating Ball	Recirculating Ball
	Steering Gear Ratio (Overall)		17.7	17.7	17.7	17.7
	Power Steering Type		Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

*1: with Snorkel Cleaner Air Duct *3: Option *5: with ABS
*2: with 7.00 R16 Tire (Option) *4: with ABS or Option

	General Countries					
	Standard Roof		High Roof	Standard Roof		High Roof
	Standard (with Air Conditioner)			Standard	Standard (with Air Conditioner)	Standard
	BB42L-BRMSS	BB42R-BRMSS	HZB50R-ZGMSS	HZB50L-BGMRS	HZB50L-BGMSS	HZB50L-ZGMRS
5	6255 (246.6)	6255 (246.6)	6990 (275.2)	6990 (275.2)	6990 (275.2)	6990 (275.2)
	2025 (79.7), 2195 (86.4)*1	2025 (79.7), 2195 (86.4)*1	2025 (79.7), 2195 (86.4)*1	2025 (79.7), 2195 (86.4)*1	2025 (79.7), 2195 (86.4)*1	2025 (79.7), 2195 (86.4)*1
	2430 (95.7), 2445 (96.3)*2	2430 (95.7), 2445 (96.3)*2	2600 (102.4)	2445 (96.2)	2445 (96.2)	2600 (102.4)
	3200 (126.0)	3200 (126.0)	3935 (154.9)	3935 (154.9)	3935 (154.9)	3935 (154.9)
	1690 (66.5)	1690 (66.5)	1690 (66.5)	1690 (66.5)	1690 (66.5)	1690 (66.5)
10	1490 (58.7)	1490 (58.7)	1490 (58.7)	1490 (58.7)	1490 (58.7)	1490 (58.7)
	5465 (215.2)	5465 (215.2)	6200 (244.1)	6200 (244.1)	6200 (244.1)	6200 (244.1)
	1900 (74.8)	1900 (74.8)	1890 (74.4)	1830 (72.0)	1890 (74.4)	1890 (74.4)
	1665 (65.6)	1665 (65.6)	1830 (72.0)	1665 (65.6)	1665 (65.5)	1830 (72.0)
	—	—	—	—	—	—
15	—	—	—	—	—	—
	—	—	—	—	—	—
	1150 (45.3)	1150 (45.3)	1150 (45.3)	1150 (45.3)	1150 (45.3)	1150 (45.3)
	1905 (75.0)	1905 (75.0)	1905 (75.0)	1905 (75.0)	1905 (75.0)	1905 (75.0)
	175 (6.9), 185 (7.3)*2	175 (6.9), 185 (7.3)*2	185 (7.3)	185 (7.3)	185 (7.3)	185 (7.3)
20	17, 18*2	17, 18*2	18	18	18	18
	14	14	14	14	14	14
	1505 - 1585 (3318 - 3494)	1505 - 1585 (3318 - 3494)	1705 - 1755 (3759 - 3869)	1615 - 1695 (3560 - 3737)	1705 - 1795 (3759 - 3957)	1615 - 1665 (3560 - 3671)
	1505 - 1715 (3318 - 3781)	1515 - 1725 (3340 - 3803)	1610 - 1740 (3549 - 3836)	1555 - 1765 (3428 - 3891)	1595 - 1800 (3516 - 3968)	1565 - 1695 (3450 - 3737)
	3010 - 3300 (6636 - 7275)	3020 - 3310 (6658 - 7297)	3315 - 3495 (7308 - 7705)	3170 - 3460 (6989 - 7628)	3300 - 3595 (7275 - 7926)	3180 - 3360 (7011 - 7407)
25	2020 (4453)	2020 (4453)	2400 (5291)	2400 (5291)	2400 (5291)	2400 (5291)
	3160 (6967)	3160 (6967)	3270 (7209)	3270 (7209)	3270 (7209)	3270 (7209)
	5180 (11420)	5180 (11420)	5670 (12500)	5670 (12500)	5670 (12500)	5670 (12500)
	95 (20.9)	95 (20.9)	95 (20.9)	95 (20.9)	95 (20.9)	95 (20.9)
	0.411 (14.5)	0.411 (14.5)	0.411 (14.5)	0.411 (14.5)	0.411 (14.5)	0.411 (14.5)
30	—	—	—	—	—	—
	—	—	—	—	—	—
	15 (9)	15 (9)	20 (12)	20 (12)	20 (12)	20 (12)
	30 (19)	30 (19)	35 (20)	35 (20)	35 (20)	35 (20)
	50 (31)	50 (31)	60 (37)	60 (37)	60 (37)	60 (37)
35	85 (53)	85 (53)	100 (62)	100 (62)	100 (62)	100 (62)
	—	—	—	—	—	—
	6.1 (20.0)	6.1 (20.0)	7.2 (23.6)	7.2 (23.6)	7.2 (23.6)	7.2 (23.6)
	6.8 (22.3)	6.8 (22.3)	7.9 (25.9)	7.9 (25.9)	7.9 (25.9)	7.9 (25.9)
	14B	14B	1HZ	1HZ	1HZ	1HZ
40	8-valve OHV	8-valve OHV	12-valve OHC	12-valve OHC	12-valve OHC	12-valve OHC
	102.0 × 112.0 (4.02 × 4.41)	102.0 × 112.0 (4.02 × 4.41)	94.0 × 100.0 (3.70 × 3.94)	94.0 × 100.0 (3.70 × 3.94)	94.0 × 100.0 (3.70 × 3.94)	94.0 × 100.0 (3.70 × 3.94)
	3661 (223.4)	3661 (223.4)	4164 (254.1)	4164 (254.1)	4164 (254.1)	4164 (254.1)
	18.0 : 1	18.0 : 1	22.4 : 1	22.4 : 1	22.4 : 1	22.4 : 1
	Distributor Type	Distributor Type	Distributor Type	Distributor Type	Distributor Type	Distributor Type
45	50 or higher	50 or higher	50 or higher	50 or higher	50 or higher	50 or higher
	72/3400 (SAE-NET)	72/3400 (SAE-NET)	96/3800 (SAE-NET)	96/3800 (SAE-NET)	96/3800 (SAE-NET)	96/3800 (SAE-NET)
	240/1800 (SAE-NET)	240/1800 (SAE-NET)	285/2200 (SAE-NET)	285/2200 (SAE-NET)	285/2200 (SAE-NET)	285/2200 (SAE-NET)
	24 - 48	24 - 48	24 - 48	12 - 52, 24 - 48*3	24 - 48	12 - 52, 24 - 48*3
	1440	1440	1440	540, 1440*3	1440	540, 1440*3
50	4.5	4.5	4.5	2.5, 4.5*3	4.5	2.5, 4.5*3
	Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm
	M152	M152	M155	M155	M155	M155
	4.802	4.802	4.535	4.535	4.535	4.535
	2.792	2.792	2.858	2.858	2.858	2.858
55	1.694	1.694	1.600	1.600	1.600	1.600
	1.000	1.000	1.000	1.000	1.000	1.000
	0.788	0.788	0.744	0.744	0.744	0.744
	5.339	5.339	5.043	5.043	5.043	5.043
	5.625	5.625	5.625	5.375, 5.625*3	5.625, 5.857*3	5.375, 5.625*3
60	10.5	10.5	10.5	10.5	10.5	10.5
	Two Leading Drum, Ventilated Disc*3	Two Leading Drum, Ventilated Disc*3	Two Leading Drum, Ventilated Disc*3	Two Leading Drum, Ventilated Disc*4	Two Leading Drum, Ventilated Disc*4	Two Leading Drum, Ventilated Disc*4
	Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum
	Drum	Drum	Drum	Drum	Drum	Drum
	Single, 11”	Single, 11”	Tandem, 9” + 10”	Tandem, 9” + 10”	Tandem, 9” + 10”	Tandem, 9” + 10”
65	—	—	—	—, LSP and BV*5	—, LSP and BV*5	—, LSP and BV*5
	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
	Leaf Spring	Leaf Spring	Leaf Spring	Leaf Spring	Leaf Spring	Leaf Spring
	—	—	—	—	—	—
	Option	Option	Option	Option	Option	Option
70	Recirculating Ball	Recirculating Ball	Recirculating Ball	Recirculating Ball	Recirculating Ball	Recirculating Ball
	17.7	17.7	17.7	17.7	17.7	17.7
	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

Item \ Area				General Countries			
Body Type				High Roof		Standard Roof	
Vehicle Grade				Standard (with Air Conditioner)		Standard	Standard (with Air Conditioner)
Model Code				HZB50L-ZGMSS	HZB50L-ZXMSS	XZB40L-BRMRY	XZB40L-BRMSY
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	6990 (275.2)	6990 (275.2)	6255 (246.3)	6255 (246.3)
		Width	mm (in.)	2025 (79.7), 2195 (86.4)*1	2035 (80.1)	2035 (80.1)	2035 (80.1)
		Height	mm (in.)	2600 (102.4)	2600 (102.4)	2430 (95.7)	2430 (95.7)
	Wheel Base		mm (in.)	3935 (154.9)	3935 (154.9)	3200 (126.0)	3200 (126.0)
	Tread	Front	mm (in.)	1690 (66.5)	1690 (66.5)	1690 (66.5)	1690 (66.5)
		Rear	mm (in.)	1490 (58.7)	1490 (58.7)	1490 (58.7)	1490 (58.7)
	Room	Length	mm (in.)	6200 (244.1)	6200 (244.1)	5465 (215.2)	5465 (215.2)
		Width	mm (in.)	1890 (74.4)	1890 (74.4)	1900 (74.8)	1900 (74.8)
		Height	mm (in.)	1830 (72.0)	1830 (72.0)	1665 (65.6)	1665 (65.6)
	Cargo Space	Length	mm (in.)	—	—	—	—
		Width	mm (in.)	—	—	—	—
		Height	mm (in.)	—	—	—	—
	Overhang	Front	mm (in.)	1150 (45.3)	1150 (45.3)	1150 (45.3)	1150 (45.3)
		Rear	mm (in.)	1905 (75.0)	1905 (75.0)	1905 (75.0)	1905 (75.0)
	Min. Running Ground Clearance		mm (in.)	185 (7.3)	185 (7.3)	185 (7.3)	185 (7.3)
	Angle of Approach		degrees	18	18	18	18
	Angle of Departure		degrees	14	14	14	14
	Curb Weight	Front	kg (lb)	1705 - 1765 (3759 - 3891), 1715 - 1765 (3781 - 3891)*5	1700 - 1680 (3748 - 3704)	1500 - 1580 (3307 - 3483)	1595 - 1675 (3516 - 3693)
		Rear	kg (lb)	1605 - 1745 (3538 - 3847), 1615 - 1745 (3560 - 3847)*5	1610 - 2090 (3549 - 4608)	1470 - 1680 (3241 - 3704)	1510 - 1720 (3329 - 3792)
		Total	kg (lb)	3310 - 3510 (7297 - 7738), 3330 - 3510 (7341 - 7738)*5	3310 - 3770 (7297 - 8311)	2970 - 3260 (6548 - 7187)	3105 - 3395 (6845 - 7485)
	Gross Vehicle Weight	Front	kg (lb)	2400 (5291)	2400 (5291)	2170 (4784)	2170 (4784)
		Rear	kg (lb)	3270 (7209)	3270 (7209)	3160 (6967)	3160 (6967)
		Total	kg (lb)	5670 (12500)	5670 (12500)	5330 (11751)	5330 (11751)
	Fuel Tank Capacity		ℓ (Imp. gal)	95 (20.9)	95 (20.9)	95 (20.9)	95 (20.9)
	Luggage Compartment Capacity		m^3 (cu. ft.)	0.411 (14.5)	—	0.411 (14.5)	0.411 (14.5)
Performance	Max. Speed		km/h (mph)	—	—	—	—
	Max. Cruising Speed		km/h (mph)	—	—	—	—
	Max. Permissible Speed	1st Gear	km/h (mph)	20 (12)	20 (12)	18 (11)	18 (11)
		2nd Gear	km/h (mph)	35 (22)	35 (22)	31 (19)	31 (19)
		3rd Gear	km/h (mph)	60 (37)	60 (37)	54 (34)	54 (34)
		4th Gear	km/h (mph)	100 (62)	100 (62)	89 (55)	89 (55)
		5th Gear	km/h (mph)	—	—	—	—
	Min. Turning Radius	Tire	m (ft.)	7.2 (23.6)	7.2 (23.6)	6.1 (20.0)	6.1 (20.0)
		Body	m (ft.)	7.9 (25.9)	7.9 (25.9)	6.8 (22.3)	6.8 (22.3)
Engine	Engine Type			1HZ	1HZ	N04C-VL	N04C-VL
	Valve Mechanism			12-valve OHC	12-valve OHC	16-valve OHV	16-valve OHV
	Bore × Stroke		mm (in.)	94.0 × 100.0 (3.70 × 3.94)	94.0 × 100.0 (3.70 × 3.94)	104.0 × 118.0 (4.09 × 4.65)	104.0 × 118.0 (4.09 × 4.65)
	Displacement		cm^3 (cu. in.)	4164 (254.1)	4164 (254.1)	4009 (244.6)	4009 (244.6)
	Compression Ratio			22.4 : 1	22.4 : 1	18.0 : 1	18.0 : 1
	Fuel System			Distributor Type	Distributor Type	Common-rail Type	Common-rail Type
	Research Octane No. or Cetane No. (Diesel)			50 or higher	50 or higher	50 or higher	50 or higher
	Max. Output		kW/rpm	96/3800 (SAE-NET)	96/3800 (SAE-NET)	100/3000 (EEC)	100/3000 (EEC)
	Max. Torque		N·m/rpm	285/2200 (SAE-NET)	285/2200 (SAE-NET)	353/1600 (EEC)	353/1600 (EEC)
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp. hr.	24 - 48	24 - 48	12 - 64	12 - 64
	Alternator Output		Watts	1440	1440	1560	1560
	Starter Output		kW	4.5	4.5	2.7	2.7
Chassis	Clutch Type			Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm
	Transmission Type			M155	M155	M551	M551
	Gear Ratio	In First		4.535	4.535	5.099	5.099
		In Second		2.858	2.858	2.910	2.910
		In Third		1.600	1.600	1.652	1.652
		In Fourth		1.000	1.000	1.000	1.000
		In Fifth		0.744	0.744	0.674	0.674
		Reverse		5.043	5.043	4.625	4.625
	Differential Gear Ratio			5.625, 5.857*6	5.625, 5.857*2	5.375, 5.625*2	5.375, 5.625*2
	Differential Gear Size		in.	10.5	10.5	10.5	10.5
	Brake Type	Front		Two Leading Drum, Ventilated Disc*4	Two Leading Drum, Ventilated Disc*4	Two Leading Drum, Ventilated Disc*2	Two Leading Drum, Ventilated Disc*2
		Rear		Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum
	Parking Brake Type			Drum	Drum	Drum	Drum
	Brake Booster Type and Size		in.	Tandem, 9" + 10"	Tandem, 9" + 10"	Single, 11"	Single, 11"
	Proportioning Valve Type			—, LSP and BV*3	—, LSP and BV*3	—	—
	Suspension Type	Front		Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
		Rear		Leaf Spring	Leaf Spring	Leaf Spring	Leaf Spring
	Stabilizer Bar	Front		—	—	—	—
		Rear		Option	Option	Option	Option
	Steering Gear Type			Recirculating Ball	Recirculating Ball	Recirculating Ball	Recirculating Ball
	Steering Gear Ratio (Overall)			17.7	17.7	17.7	17.7
	Power Steering Type			Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

*1: with Snorkel Cleaner Air Duct
*2: Option
*3: with ABS
*4: with ABS or Option
*5: Models for Egypt Package
*6: Provided as an option for other than the Egypt Package models

General Countries		
High Roof		
Standard	Standard (with Air Conditioner)	
XZB50L-ZGMRY	XZB50L-ZGMSY	XZB50L-ZXMSY
6990 (275.2)	6990 (275.2)	6990 (275.2)
2035 (80.1)	2035 (80.1)	2035 (80.1)
2600 (102.4)	2600 (102.4)	2600 (102.4)
3935 (154.9)	3935 (154.9)	3935 (154.9)
1690 (66.5)	1690 (66.5)	1690 (66.5)
1490 (58.7)	1490 (58.7)	1490 (58.7)
6200 (244.1)	6200 (244.1)	5655 (222.6)
1900 (74.8)	1900 (74.8)	1900 (74.8)
1665 (65.6)	1665 (65.6)	1665 (65.6)
—	—	—
—	—	—
—	—	—
1150 (45.3)	1150 (45.3)	1150 (45.3)
1905 (75.0)	1905 (75.0)	1905 (75.0)
185 (7.3)	185 (7.3)	185 (7.3)
18	18	18
14	14	14
1620 - 1670 (3571 - 3682)	1710 - 1770 (3770 - 3902)	1710 - 1690 (3770 - 3726)
1580 - 1710 (3483 - 3770)	1620 - 1760 (3571 - 3880)	1620 - 2100 (3571 - 4630)
3200 - 3380 (7055 - 7452)	3330 - 3530 (7341 - 7782)	3330 - 3790 (7341 - 8355)
2400 (5291)	2400 (5291)	2400 (5291)
3270 (7209)	3270 (7209)	3270 (7209)
5670 (12500)	5670 (12500)	5670 (12500)
95 (20.9)	95 (20.9)	95 (20.9)
0.411 (14.5)	0.411 (14.5)	—
—	—	—
—	—	—
18 (11)	18 (11)	18 (11)
31 (19)	31 (19)	31 (19)
54 (34)	54 (34)	54 (34)
89 (55)	89 (55)	89 (55)
—	—	—
7.2 (23.6)	7.2 (23.6)	7.2 (23.6)
7.9 (25.9)	7.9 (25.9)	7.9 (25.9)
N04C-VL	N04C-VL	N04C-VL
16-valve OHV	16-valve OHV	16-valve OHV
104.0 × 118.0 (4.09 × 4.65)	104.0 × 118.0 (4.09 × 4.65)	104.0 × 118.0 (4.09 × 4.65)
4009 (244.6)	4009 (244.6)	4009 (244.6)
18.0 : 1	18.0 : 1	18.0 : 1
Common-rail Type	Common-rail Type	Common-rail Type
50 or higher	50 or higher	50 or higher
100/3000 (EEC)	100/3000 (EEC)	100/3000 (EEC)
353/1600 (EEC)	353/1600 (EEC)	353/1600 (EEC)
12 - 64	12 - 64	12 - 64
1560	1560	1560
2.7	2.7	2.7
Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm
M551	M551	M551
5.099	5.099	5.099
2.910	2.910	2.910
1.652	1.652	1.652
1.000	1.000	1.000
0.674	0.674	0.674
4.625	4.625	4.625
5.375, 5.625*2	5.375, 5.625*2	5.375, 5.625*2
10.5	10.5	10.5
Two Leading Drum, Ventilated Disc*4	Two Leading Drum, Ventilated Disc*4	Two Leading Drum, Ventilated Disc*4
Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum
Drum	Drum	Drum
Tandem, 9" + 10"	Tandem, 9" + 10"	Tandem, 9" + 10"
—, LSP and BV*3	—, LSP and BV*3	—, LSP and BV*3
Double Wishbone	Double Wishbone	Double Wishbone
Leaf Spring	Leaf Spring	Leaf Spring
—	—	—
Option	Option	Option
Recirculating Ball	Recirculating Ball	Recirculating Ball
17.7	17.7	17.7
Hydraulic Type	Hydraulic Type	Hydraulic Type