MAJOR TECHNICAL SPECIFICATIONS

Item \ Area				General Countries			
Body Type				High Roof			
Vehicle Grade				Standard	Standard (with Air Conditioner)	Standard	Standard (with Air Conditioner)
Model Code				BB60R-ZRMRS	BB60R-ZRMSS	BB60L-ZRMRS	BB60L-ZRMSS
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	6255 (246.3)	6255 (246.3)	6255 (246.3)	6255 (246.3)
		Width	mm (in.)	2080 (81.9)	2080 (81.9)	2080 (81.9)	2080 (81.9)
		Height	mm (in.)	2630 (103.5)	2630 (103.5)	2630 (103.5)	2630 (103.5)
	Wheel Base		mm (in.)	3200 (126.0)	3200 (126.0)	3200 (126.0)	3200 (126.0)
	Tread	Front	mm (in.)	1690 (66.5)	1690 (66.5)	1690 (66.5)	1690 (66.5)
		Rear	mm (in.)	1490 (58.7)	1490 (58.7)	1490 (58.7)	1490 (58.7)
	Room	Length	mm (in.)	5495 (216.3)	5495 (216.3)	5495 (216.3)	5495 (216.3)
		Width	mm (in.)	1885 (74.2)	1885 (74.2)	1885 (74.2)	1885 (74.2)
		Height	mm (in.)	1890 (74.4)	1890 (74.4)	1890 (74.4)	1890 (74.4)
	Cargo Space	Length	mm (in.)	-	-	-	-
		Width	mm (in.)	-	-	-	-
		Height	mm (in.)	-	-	-	-
	Overhang	Front	mm (in.)	1150 (45.3)	1150 (45.3)	1150 (45.3)	1150 (45.3)
		Rear	mm (in.)	1905 (75.0)	1905 (75.0)	1905 (75.0)	1905 (75.0)
	Min. Running Ground Clearance		mm (in.)	185 (7.3)	185 (7.3)	185 (7.3)	185 (7.3)
	Angle of Approach		degrees	18	18	18	18
	Angle of Departure		degrees	14	14	14	14
	Curb Weight	Front	kg (lb)	1535 - 1570 (3384 - 3461)	1605 - 1645 (3538 - 3627)	1535 - 1570 (3384 - 3461)	1605 - 1635 (3538 - 3605)
		Rear	kg (lb)	1620 - 1705 (3571 - 3759)	1650 - 1745 (3638 - 3847)	1620 - 1705 (3571 - 3759)	1650 - 1745 (3638 - 3847)
		Total	kg (lb)	3155 - 3275 (6956 - 7220)	3255 - 3390 (7176 - 7474)	3155 - 3275 (6956 - 7220)	3255 - 3380 (7176 - 7452)
	Gross Vehicle Weight	Front	kg (lb)	2170 (4784)	2170 (4784)	2170 (4784)	2170 (4784)
		Rear	kg (lb)	3160 (6967)	3160 (6967)	3160 (6967)	3160 (6967)
		Total	kg (lb)	5330 (11751)	5330 (11751)	5330 (11751)	5330 (11751)
	Fuel Tank Capacity		ℓ (Imp. gal.)	95 (20.9)	95 (20.9)	95 (20.9)	95 (20.9)
	Luggage Compartment Capacity		m^3 (cu.ft.)	0.41 (14.5)	0.41 (14.5)	0.41 (14.5)	0.41 (14.5)
Performance	Max. Speed		km/h (mph)	115 (71)	115 (71)	115 (71)	115 (71)
	Max. Cruising Speed		km/h (mph)	-	-	-	-
	Max. Permissible Speed	1st Gear	km/h (mph)	15 (9)	15 (9)	15 (9)	15 (9)
		2nd Gear	km/h (mph)	30 (19)	30 (19)	30 (19)	30 (19)
		3rd Gear	km/h (mph)	50 (31)	50 (31)	50 (31)	50 (31)
		4th Gear	km/h (mph)	85 (53)	85 (53)	85 (53)	85 (53)
		5th Gear	km/h (mph)	-	-	-	-
	Min. Turning Radius	Tire	m (ft.)	6.1 (20.0)	6.1 (20.0)	6.1 (20.0)	6.1 (20.0)
		Body	m (ft.)	6.8 (22.3)	6.8 (22.3)	6.8 (22.3)	6.8 (22.3)
Engine	Engine Type			14B	14B	14B	14B
	Valve Mechanism			8-valve OHV	8-valve OHV	8-valve OHV	8-valve OHV
	Bore × Stroke		mm (in.)	102.0 × 112.0 (4.02 × 4.41)	102.0 × 112.0 (4.02 × 4.41)	102.0 × 112.0 (4.02 × 4.41)	102.0 × 112.0 (4.02 × 4.41)
	Displacement		cm^3 (cu.in.)	3661 (223.4)	3661 (223.4)	3661 (223.4)	3661 (223.4)
	Compression Ratio			18.0 : 1	18.0 : 1	18.0 : 1	18.0 : 1
	Fuel System			Distributor Type	Distributor Type	Distributor Type	Distributor Type
	Research Octane No. or Cetane No. (Diesel)			50 or higher	50 or higher	50 or higher	50 or higher
	Max. Output		kW/rpm	72/3400 (SAE-NET)	72/3400 (SAE-NET)	72/3400 (SAE-NET)	72/3400 (SAE-NET)
	Max. Torque		N･m/rpm	240/1800 (SAE-NET)	240/1800 (SAE-NET)	240/1800 (SAE-NET)	240/1800 (SAE-NET)
Engine Electrical	Battery Capacity(5HR)		Voltage & Amp. hr.	12 - 52	12 - 52	12 - 52	12 - 52
	Alternator Output		Watts	1560	1560	1560	1560
	Starter Output		kW	2.5	2.5	2.5	2.5
Chassis	Clutch Type			Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm
	Transmission Type			M152	M152	M152	M152
	Gear Ratio	In First		4.802	4.802	4.802	4.802
		In Second		2.792	2.792	2.792	2.792
		In Third		1.694	1.694	1.694	1.694
		In Fourth		1.000	1.000	1.000	1.000
		In Fifth		0.788	0.788	0.788	0.788
		In Reverse		5.339	5.339	5.339	5.339
	Differential Gear Ratio			5.625	5.625	5.625	5.625
	Differential Gear Size		in.	10.5	10.5	10.5	10.5
	Brake Type	Front		Two Leading Drum, Ventilated Disc[*1]	Two Leading Drum, Ventilated Disc[*1]	Two Leading Drum, Ventilated Disc[*1]	Two Leading Drum, Ventilated Disc[*1]
		Rear		Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum
	Parking Brake Type			Drum	Drum	Drum	Drum
	Brake Booster Type and Size		in.	Single, 11"	Single, 11"	Single, 11"	Single, 11"
	Proportioning Valve Type			-	-	-	-
	Suspension Type	Front		Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
		Rear		Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid
	Stabilizer Bar	Front		Standard	Standard	Standard	Standard
		Rear		Standard	Standard	Standard	Standard
	Steering Gear Type			Recirculating Ball	Recirculating Ball	Recirculating Ball	Recirculating Ball
	Steering Gear Ratio (Overall)			17.7	17.7	17.7	17.7
	Power Steering Type			Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

[*1] : Option
[*2] : with ABS or Option
[*3] : with ABS
[*4] : Except Models for Egypt Package
[*5] : Models Compliant with EURO 3 Emission Regulations
[*6] : Models Compliant with EURO 4 Emission Regulations

	General Countries					
	High Roof					
	Standard (with Air Conditioner)	Standard	Standard (with Air Conditioner)		Standard	Standard (with Air Conditioner)
	HZB70R-ZGMSS	HZB70L-ZGMRS	HZB70L-ZGMSS	HZB70L-ZXMSS	XZB70L-ZGMRY	XZB70L-ZGMSY
5	6990 (275.2)	6990 (275.2)	6990 (275.2)	6990 (275.2)	6990 (275.2)	6990 (275.2)
	2080 (81.9)	2080 (81.9)	2080 (81.9)	2080 (81.9)	2080 (81.9)	2080 (81.9)
	2635 (103.7)	2635 (103.7)	2635 (103.7)	2635 (103.7)	2635 (103.7)	2635 (103.7)
	3935 (154.9)	3935 (154.9)	3935 (154.9)	3935 (154.9)	3935 (154.9)	3935 (154.9)
	1690 (66.5)	1690 (66.5)	1690 (66.5)	1690 (66.5)	1690 (66.5)	1690 (66.5)
10	1490 (58.7)	1490 (58.7)	1490 (58.7)	1490 (58.7)	1490 (58.7)	1490 (58.7)
	6230 (245.3)	6230 (245.3)	6230 (245.3)	6230 (245.3)	6230 (245.3)	6230 (245.3)
	1885 (74.2)	1885 (74.2)	1885 (74.2)	1885 (74.2)	1885 (74.2)	1885 (74.2)
	1890 (74.4)	1890 (74.4)	1890 (74.4)	1890 (74.4)	1890 (74.4)	1890 (74.4)
	-	-	-	-	-	-
15	-	-	-	-	-	-
	-	-	-	-	-	-
	1150 (45.3)	1150 (45.3)	1150 (45.3)	1150 (45.3)	1150 (45.3)	1150 (45.3)
	1905 (75.0)	1905 (75.0)	1905 (75.0)	1905 (75.0)	1905 (75.0)	1905 (75.0)
	185 (7.3)	185 (7.3)	185 (7.3)	185 (7.3)	185 (7.3)	185 (7.3)
20	18	18	18	18	18	18
	14	14	14	14	14	14
	1750 - 1800 (3858 - 3698)	1680 - 1725 (3704 - 3803)	1750 - 1800 (3858 - 3968)	1745 - 1795 (3847 - 3957)	1735 - 1775 (3825 - 3913)	1810 - 1850 (3990 - 4079)
	1705 - 1805 (3759 - 3979)	1675 - 1805 (3693 - 3979)	1705 - 1835 (3759 - 4045)	1705 - 1780 (3759 - 3925)	1700 - 1785 (3748 - 3935)	1725 - 1815 (3803 - 4001)
	3455 - 3605 (7617 - 7948)	3355 - 3530 (7396 - 7782)	3455 - 3635 (7617 - 8014)	3450 - 3575 (7606 - 7881)	3445 - 3560 (7617 - 7848)	3535 - 3665 (7793 - 8080)
25	2400 (5291)	2400 (5291)	2400 (5291)	2400 (5291)	2400 (5291)	2400 (5291)
	3270 (7209)	3270 (7209)	3270 (7209)	3270 (7209)	3270 (7209)	3270 (7209)
	5670 (12500)	5670 (12500)	5670 (12500)	5670 (12500)	5670 (12500)	5670 (12500)
	95 (20.9)	95 (20.9)	95 (20.9)	95 (20.9)	95 (20.9)	95 (20.9)
	0.41 (14.5)	0.41 (14.5)	0.41 (14.5)	-	0.41 (14.5)	0.41 (14.5)
30	-	-	-	-	-	-
	-	-	-	-	-	-
	20 (12)	20 (12)	20 (12)	20 (12)	18 (11)	18 (11)
	35 (22)	35 (22)	35 (22)	35 (22)	31 (19)	31 (19)
	60 (37)	60 (37)	60 (37)	60 (37)	54 (34)	54 (34)
35	100 (62)	100 (62)	100 (62)	100 (62)	89 (55)	89 (55)
	-	-	-	-	-	-
	7.2 (23.6)	7.2 (23.6)	7.2 (23.6)	7.2 (23.6)	7.2 (23.6)	7.2 (23.6)
	7.9 (25.9)	7.9 (25.9)	7.9 (25.9)	7.9 (25.9)	7.9 (25.9)	7.9 (25.9)
	1HZ	1HZ	1HZ	1HZ	N04C-VL[*5], N04C-VQ[*6]	N04C-VL[*5], N04C-VQ[*6]
40	12-valve OHC	12-valve OHC	12-valve OHC	12-valve OHC	16-valve OHV	16-valve OHV
	94.0 × 100.0 (3.70 × 3.94)	94.0 × 100.0 (3.70 × 3.94)	94.0 × 100.0 (3.70 × 3.94)	94.0 × 100.0 (3.70 × 3.94)	104.0 × 118.0 (4.09 × 4.65)	104.0 × 118.0 (4.09 × 4.65)
	4164 (254.1)	4164 (254.1)	4164 (254.1)	4164 (254.1)	4009 (244.6)	4009 (244.6)
	22.4 : 1	22.4 : 1	22.4 : 1	22.4 : 1	18.0 : 1	18.0 : 1
	Distributor Type	Distributor Type	Distributor Type	Distributor Type	Common-rail Type	Common-rail Type
45	50 or higher	50 or higher	50 or higher	50 or higher	50 or higher	50 or higher
	96/3800 (SAE-NET)	96/3800 (SAE-NET)	96/3800 (SAE-NET)	96/3800 (SAE-NET)	100/3000[*5], 100/2500[*6] (EEC)	100/3000[*5], 100/2500[*6] (EEC)
	285/2200 (SAE-NET)	285/2200 (SAE-NET)	285/2200 (SAE-NET)	285/2200 (SAE-NET)	353/1600[*5], 390/1400 - 2400[*6] (EEC)	353/1600[*5], 390/1400 - 2400[*6] (EEC)
	12 - 52	12 - 52	12 - 52	12 - 52	12 - 64 × 2	12 - 64 × 2
	1560	1560	1560	1560	1560	1560
50	2.5	2.5	2.5	2.5	2.7	2.7
	Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm
	M155	M155	M155	M155	M155	M155
	4.535	4.535	4.535	4.535	4.535	4.535
	2.858	2.858	2.858	2.858	2.858	2.858
55	1.600	1.600	1.600	1.600	1.600	1.600
	1.000	1.000	1.000	1.000	1.000	1.000
	0.744	0.744	0.744	0.744	0.744	0.744
	5.043	5.043	5.043	5.043	5.043	5.043
	5.625	5.375, 5.625[*1]	5.625, 5.857[*4]	5.625, 5.857[*1]	5.375, 5.625[*1]	5.375, 5.625[*1]
60	10.5	10.5	10.5	10.5	10.5	10.5
	Two Leading Drum, Ventilated Disc[*2]	Two Leading Drum, Ventilated Disc[*2]	Two Leading Drum, Ventilated Disc[*2]	Two Leading Drum, Ventilated Disc[*2]	Two Leading Drum, Ventilated Disc[*2]	Two Leading Drum, Ventilated Disc[*2]
	Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum
	Drum	Drum	Drum	Drum	Drum	Drum
	Tandem, 9" + 10"	Tandem, 9" + 10"	Tandem, 9" + 10"	Tandem, 9" + 10"	Tandem, 9" + 10"	Tandem, 9" + 10"
65	-, LSP and BV[*3]	-, LSP and BV[*3]	-, LSP and BV[*3]	-, LSP and BV[*3]	-	-
	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid
	Standard	Standard	Standard	Standard	Standard	Standard
	Standard	Standard	Standard	Standard	Standard	Standard
70	Recirculating Ball	Recirculating Ball	Recirculating Ball	Recirculating Ball	Recirculating Ball	Recirculating Ball
	17.7	17.7	17.7	17.7	17.7	17.7
	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

Item \ Area				General Countries			
Body Type				High Roof			
Vehicle Grade				Standard (with Air Conditioner)	Standard	Standard (with Air Conditioner)	
Model Code				XZB70L-ZXMSY	TRB60L-ZRMRK	TRB60L-ZRMSK	TRB70L-ZGMSK
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	6990 (275.2)	6255 (246.3)	6255 (246.3)	6990 (275.2)
		Width	mm (in.)	2080 (81.9)	2080 (81.9)	2080 (81.9)	2080 (81.9)
		Height	mm (in.)	2635 (103.7)	2630 (103.5)	2630 (103.5)	2635 (103.7)
	Wheel Base		mm (in.)	3935 (154.9)	3200 (126.0)	3200 (126.0)	3935 (154.9)
	Tread	Front	mm (in.)	1690 (66.5)	1690 (66.5)	1690 (66.5)	1690 (66.5)
		Rear	mm (in.)	1490 (58.7)	1490 (58.7)	1490 (58.7)	1490 (58.7)
	Room	Length	mm (in.)	6230 (245.3)	5495 (216.3)	5495 (216.3)	6230 (245.3)
		Width	mm (in.)	1885 (74.2)	1885 (74.2)	1885 (74.2)	1885 (74.2)
		Height	mm (in.)	1890 (74.4)	1890 (74.4)	1890 (74.4)	1890 (74.4)
	Cargo Space	Length	mm (in.)	-	-	-	-
		Width	mm (in.)	-	-	-	-
		Height	mm (in.)	-	-	-	-
	Overhang	Front	mm (in.)	1150 (45.3)	1150 (45.3)	1150 (45.3)	1150 (45.3)
		Rear	mm (in.)	1905 (75.0)	1905 (75.0)	1905 (75.0)	1905 (75.0)
	Min. Running Ground Clearance		mm (in.)	185 (7.3)	185 (7.3)	185 (7.3)	185 (7.3)
	Angle of Approach		degrees	18	18	18	18
	Angle of Departure		degrees	14	14	14	14
	Curb Weight	Front	kg (lb)	1800 - 1850 (3968 - 4079)	1375 - 1415 (3031 - 3120)	1455 - 1495 (3208 - 3296)	1565 - 1610 (3456 - 3549)
		Rear	kg (lb)	1725 - 1800 (3803 - 3968)	1650 - 1740 (3638 - 3836)	1655 - 1745 (3649 - 3847)	1695 - 1800 (3737 - 3968)
		Total	kg (lb)	3525 - 3650 (7771 - 8047)	3025 - 3155 (6669 - 6956)	3110 - 3240 (6856 - 7143)	3260 - 3410 (7187 - 7518)
	Gross Vehicle Weight	Front	kg (lb)	2400 (5291)	2020 (4453)	2020 (4453)	2020 (4453)
		Rear	kg (lb)	3270 (7209)	3160 (6967)	3160 (6967)	3160 (6967)
		Total	kg (lb)	5670 (12500)	5180 (11420)	5180 (11420)	5180 (11420)
	Fuel Tank Capacity		ℓ (Imp. gal.)	95 (20.9)	95 (20.9)	95 (20.9)	95 (20.9)
	Luggage Compartment Capacity		m^3 (cu.ft.)	-	0.41 (14.5)	0.41 (14.5)	0.41 (14.5)
Performance	Max. Speed		km/h (mph)	-	-	-	-
	Max. Cruising Speed		km/h (mph)	-	-	-	-
	Max. Permissible Speed	1st Gear	km/h (mph)	18 (11)	20 (12)	20 (12)	20 (12)
		2nd Gear	km/h (mph)	31 (19)	40 (25)	40 (25)	40 (25)
		3rd Gear	km/h (mph)	54 (34)	70 (43)	70 (43)	70 (43)
		4th Gear	km/h (mph)	89 (55)	115 (71)	115 (71)	115 (71)
		5th Gear	km/h (mph)	-	-	-	-
	Min. Turning Radius	Tire	m (ft.)	7.2 (23.6)	6.1 (20.0)	6.1 (20.0)	7.2 (23.6)
		Body	m (ft.)	7.9 (25.9)	6.8 (22.3)	6.8 (22.3)	7.9 (25.9)
Engine	Engine Type			N04C-VL[*1], N04C-VQ[*2]	2TR-FE	2TR-FE	2TR-FE
	Valve Mechanism			16-valve OHV	16-valve DOHC	16-valve DOHC	16-valve DOHC
	Bore × Stroke		mm (in.)	104.0 × 118.0 (4.09 × 4.65)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)
	Displacement		cm^3 (cu.in.)	4009 (244.6)	2694 (164.4)	2694 (164.4)	2694 (164.4)
	Compression Ratio			18.0 : 1	9.6 : 1	9.6 : 1	9.6 : 1
	Fuel System			Common-rail Type	EFI	EFI	EFI
	Research Octane No. or Cetane No. (Diesel)			50 or higher	91 or higher	91 or higher	91 or higher
	Max. Output		kW/rpm	100/3000[*1], 100/2500[*2] (EEC)	108/4800	108/4800	108/4800
	Max. Torque		N·m/rpm	353/1600[*1], 390/1400 - 2400[*2] (EEC)	235/3800	235/3800	235/3800
Engine Electrical	Battery Capacity(5HR)		Voltage & Amp. hr.	12 - 64 × 2	12 - 48	12 - 48	12 - 48
	Alternator Output		Watts	1560	960	1200	1200
	Starter Output		kW	2.7	1.4	1.4	1.4
Chassis	Clutch Type			Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm
	Transmission Type			M551	M155	M155	M155
	Gear Ratio	In First		5.099	4.535	4.535	4.535
		In Second		2.910	2.858	2.858	2.858
		In Third		1.652	1.600	1.600	1.600
		In Fourth		1.000	1.000	1.000	1.000
		In Fifth		0.674	0.744	0.744	0.744
		In Reverse		4.625	5.043	5.043	5.043
	Differential Gear Ratio			5.375, 5.625[*3]	5.857	5.857	6.142
	Differential Gear Size		in.	10.5	10.5	10.5	10.5
	Brake Type	Front		Two Leading Drum, Ventilated Disc[*4]	Two Leading Drum, Ventilated Disc[*4]	Two Leading Drum, Ventilated Disc[*4]	Ventilated Disc
		Rear		Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum
	Parking Brake Type			Drum	Drum	Drum	Drum
	Brake Booster Type and Size		in.	Tandem, 9" + 10"	Single 11", Tandem, 9" + 10"[*4]	Single 11", Tandem, 9" + 10"[*4]	Tandem, 9" + 10"
	Proportioning Valve Type			-	-	-	-
	Suspension Type	Front		Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
		Rear		Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid
	Stabilizer Bar	Front		Standard	Standard	Standard	Standard
		Rear		Standard	Standard	Standard	Standard
	Steering Gear Type			Recirculating Ball	Recirculating Ball	Recirculating Ball	Recirculating Ball
	Steering Gear Ratio (Overall)			17.7	17.7	17.7	17.7
	Power Steering Type			Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

[*1]: Models Compliant with EURO 3 Emission Regulations
[*2]: Models Compliant with EURO 4 Emission Regulations
[*3] : Option
[*4] : with ABS or Option

	Hong Kong					Taiwan
	High Roof					
	Standard (with Air Conditioner)	EX		Standard (with Air Conditioner)		
	XZB60R-ZCMSY	XZB70R-ZEMQY	XZB70R-ZEPQY	BZB60R-ZCMSC	BZB70R-ZCMSC5	XZB70L-ZEMSYR
5	6255 (246.3)	6990 (275.2)	6990 (275.2)	6255 (246.3)	6990 (275.2)	6990 (275.2)
	2080 (81.9)	2080 (81.9)	2080 (81.9)	2080 (81.9)	2080 (81.9)	2080 (81.9)
	2630 (103.5)	2635 (103.7)	2635 (103.7)	2630 (103.5)	2635 (103.7)	2635 (103.7)
	3200 (126.0)	3935 (154.9)	3935 (154.9)	3200 (126.0)	3935 (154.9)	3935 (154.9)
	1690 (66.5)	1690 (66.5)	1690 (66.5)	1690 (66.5)	1690 (66.5)	1690 (66.5)
10	1490 (58.7)	1490 (58.7)	1490 (58.7)	1490 (58.7)	1490 (58.7)	1490 (58.7)
	5495 (216.3)	6230 (245.3)	6230 (245.3)	5495 (216.3)	6230 (245.3)	6230 (245.3)
	1885 (74.2)	1885 (74.2)	1885 (74.2)	1885 (74.2)	1885 (74.2)	1885 (74.2)
	1890 (74.4)	1890 (74.4)	1890 (74.4)	1890 (74.4)	1890 (74.4)	1890 (74.4)
	-	-	-	-	-	-
15	-	-	-	-	-	-
	-	-	-	-	-	-
	1150 (45.3)	1150 (45.3)	1150 (45.3)	1150 (45.3)	1150 (45.3)	1150 (45.3)
	1905 (75.0)	1905 (75.0)	1905 (75.0)	1905 (75.0)	1905 (75.0)	1905 (75.0)
	185 (7.3)	185 (7.3)	185 (7.3)	185 (7.3)	185 (7.3)	185 (7.3)
20	18	18	18	18	18	18
	14	14	14	14	14	14
	1715 - 1720 (3781 - 3792)	1815 (4001)	1840 - 1845 (4056 - 4067)	1675 - 1680 (3693 - 3704)	1795 - 1805 (3957 - 3979)	1830 (4034)
	1740 - 1755 (3836 - 3869)	1795 - 1815 (3957 - 4001)	1795 - 1815 (3957 - 4001)	1780 - 1795 (3924 - 3957)	1870 - 1890 (4123 - 4167)	1780 - 1805 (3924 - 3979)
	3455 - 3475 (7617 - 7661)	3610 - 3630 (7959 - 8003)	3635 - 3660 (8014 - 8069)	3455 - 3475 (7617 - 7661)	3665 - 3695 (8080 - 8146)	3615 - 3635 (7970 - 8014)
25	2100 (4630)	2150 (4740)	2150 (4740)	2100 (4630)	2150 (4740)	2340 (5159)
	2700 (5952)	2840 (6261)	2840 (6261)	2700 (5952)	2840 (6261)	3105 (6845)
	4800 (10582)	4990 (11001)	4990 (11001)	4800 (10582)	4990 (11001)	5445 (12004)
	95 (20.9)	95 (20.9)	95 (20.9)	95 (20.9)	122 (26.8)	122 (26.8)
	0.41 (14.5)	-	-	0.41 (14.5)	0.41 (14.5)	-
30	-	-	-	-	-	-
	-	-	-	-	-	-
	15 (9)	15 (9)	35 (22)	15 (9)	15 (9)	15 (9)
	30 (19)	30 (19)	68 (42)	25 (16)	25 (16)	30 (19)
	50 (31)	50 (31)	-	50 (31)	50 (31)	50 (31)
35	85 (53)	85 (53)	-	85 (53)	85 (53)	85 (53)
	-	-	-	-	-	-
	6.1 (20.0)	7.2 (23.6)	7.2 (23.6)	6.1 (20.0)	7.2 (23.6)	7.2 (23.6)
	6.8 (22.3)	7.9 (25.9)	7.9 (25.9)	6.8 (22.3)	7.9 (25.9)	7.9 (25.9)
	N04C-UH	N04C-UH	N04C-UH	1BZ-FPE	1BZ-FPE	N04C-UH
40	16-valve OHV	16-valve OHV	16-valve OHV	16-valve OHV	16-valve OHV	16-valve OHV
	104.0 × 118.0 (4.09 × 4.65)	104.0 × 118.0 (4.09 × 4.65)	104.0 × 118.0 (4.09 × 4.65)	108.0 × 112.0 (4.25 × 4.41)	108.0 × 112.0 (4.25 × 4.41)	104.0 × 118.0 (4.09 × 4.65)
	4009 (244.6)	4009 (244.6)	4009 (244.6)	4104 (250.4)	4104 (250.4)	4009 (244.6)
	18.0 : 1	18.0 : 1	18.0 : 1	9.5 : 1	9.5 : 1	18.0 : 1
	Common-rail Type	Common-rail Type	Common-rail Type	Carburetor (Electronically Controlled)	Carburetor (Electronically Controlled)	Common-rail Type
45	50 or higher	50 or higher	50 or higher	100 or higher	100 or higher	50 or higher
	110/2700 (EEC)	110/2700 (EEC)	110/2700 (EEC)	85/3600 (SAE-NET)	85/3600 (SAE-NET)	110/2700 (EEC)
	397/1800 (EEC)	397/1800 (EEC)	397/1800 (EEC)	306/2000 (SAE-NET)	306/2000 (SAE-NET)	397/1800 (EEC)
	12 - 64 × 2	12 - 64 × 2	12 - 64 × 2	12 - 64	12 - 64	12 - 64 × 2
	1560	1560	1560	1200	1200	1560
50	2.7	2.7	2.7	2.5	2.5	2.7
	Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm	-	Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm
	M551	M551	A444E	M155	M155	M551
	5.099	5.099	2.950	4.535	4.535	5.099
	2.910	2.910	1.530	2.858	2.858	2.910
55	1.652	1.652	1.000	1.600	1.600	1.652
	1.000	1.000	0.703	1.000	1.000	1.000
	0.674	0.674	-	0.744	0.744	0.674
	4.625	4.625	2.678	5.043	5.043	4.625
	5.375	5.375	4.875	5.625	5.625	5.375
60	10.5	10.5	10.5	10.5	10.5	10.5
	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
	Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum
	Drum	Drum	Drum	Drum	Drum	Drum
	Tandem, 9" + 10"	Tandem, 9" + 10"	Tandem, 9" + 10"	Tandem, 9" + 10"	Tandem, 9" + 10"	Tandem, 9" + 10"
65	LSP and BV	LSP and BV	LSP and BV	LSP and BV	LSP and BV	-
	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid
	Standard	Standard	Standard	Standard	Standard	Standard
	Standard	Standard	Standard	Standard	Standard	Standard
70	Recirculating Ball	Recirculating Ball	Recirculating Ball	Recirculating Ball	Recirculating Ball	Recirculating Ball
	17.7	17.7	17.7	17.7	17.7	17.7
	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

Item \ Area				Australia			G.C.C. Countries
Body Type				High Roof			
Vehicle Grade				Standard (with Air Conditioner)		DX	Standard (with Air Conditioner)
Model Code				XZB70R-ZEMSYQ	XZB70R-ZEPSYQ	XZB70R-ZEPNYQ	HZB70L-ZGMSSV
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	6990 (275.2)	6990 (275.2)	6990 (275.2)	6990 (275.2)
		Width	mm (in.)	2080 (81.9)	2080 (81.9)	2080 (81.9)	2080 (81.9)
		Height	mm (in.)	2635 (103.7)	2635 (103.7)	2635 (103.7)	2635 (103.7)
	Wheel Base		mm (in.)	3935 (154.9)	3935 (154.9)	3935 (154.9)	3935 (154.9)
	Tread	Front	mm (in.)	1690 (66.5)	1690 (66.5)	1690 (66.5)	1690 (66.5)
		Rear	mm (in.)	1490 (58.7)	1490 (58.7)	1490 (58.7)	1490 (58.7)
	Room	Length	mm (in.)	6230 (245.3)	6230 (245.3)	6230 (245.3)	6230 (245.3)
		Width	mm (in.)	1885 (74.2)	1885 (74.2)	1885 (74.2)	1885 (74.2)
		Height	mm (in.)	1890 (74.4)	1890 (74.4)	1890 (74.4)	1890 (74.4)
	Cargo Space	Length	mm (in.)	-	-	-	-
		Width	mm (in.)	-	-	-	-
		Height	mm (in.)	-	-	-	-
	Overhang	Front	mm (in.)	1150 (45.3)	1150 (45.3)	1150 (45.3)	1150 (45.3)
		Rear	mm (in.)	1905 (75.0)	1905 (75.0)	1905 (75.0)	1905 (75.0)
	Min. Running Ground Clearance		mm (in.)	185 (7.3)	185 (7.3)	185 (7.3)	185 (7.3)
	Angle of Approach		degrees	18	18	18	18
	Angle of Departure		degrees	14	14	14	14
	Curb Weight	Front	kg (lb)	1875 - 1890 (4134 - 4167)	1925 - 1945 (4244 - 4288)	1935 - 1955 (4266 - 4310)	1810 - 1835 (3990 - 4045)
		Rear	kg (lb)	1840 - 1855 (4056 - 4090)	1840 - 1855 (4056 - 4090)	1845- 1860 (4067 - 4101)	1705 - 1765 (3759 - 3891)
		Total	kg (lb)	3715 - 3745 (8190 - 8256)	3765 - 3800 (8300 - 8377)	3780 - 3815 (8333 - 8411)	3515 - 3600 (7759 - 7937)
	Gross Vehicle Weight	Front	kg (lb)	2400 (5291)	2400 (5291)	2400 (5291)	2400 (5291)
		Rear	kg (lb)	3140 (6922)	3140 (6922)	3140 (6922)	3270 (7209)
		Total	kg (lb)	5540 (12213)	5540 (12213)	5540 (12213)	5670 (12500)
	Fuel Tank Capacity		ℓ (Imp. gal.)	95 (20.9)	95 (20.9)	95 (20.9)	95 (20.9)
	Luggage Compartment Capacity		m^3 (cu.ft.)	0.41 (14.5)	0.41 (14.5)	0.41 (14.5)	0.41 (14.5)
Performance	Max. Speed		km/h (mph)	100 (62)	100 (62)	100 (62)	130 (81)
	Max. Cruising Speed		km/h (mph)	-	-	-	-
	Max. Permissible Speed	1st Gear	km/h (mph)	15 (9)	35 (22)	35 (22)	20 (12)
		2nd Gear	km/h (mph)	30 (19)	68 (42)	68 (42)	35 (22)
		3rd Gear	km/h (mph)	50 (31)	-	-	60 (37)
		4th Gear	km/h (mph)	85 (53)	-	-	100 (62)
		5th Gear	km/h (mph)	-	-	-	-
	Min. Turning Radius	Tire	m (ft.)	7.2 (23.6)	7.2 (23.6)	7.2 (23.6)	7.2 (23.6)
		Body	m (ft.)	7.9 (25.9)	7.9 (25.9)	7.9 (25.9)	7.9 (25.9)
Engine	Engine Type			N04C-UH	N04C-UH	N04C-UH	1HZ
	Valve Mechanism			16-valve OHV	16-valve OHV	16-valve OHV	12-valve OHC
	Bore × Stroke		mm (in.)	104.0 × 118.0 (4.09 × 4.65)	104.0 × 118.0 (4.09 × 4.65)	104.0 × 118.0 (4.09 × 4.65)	94.0 × 100.0 (3.70 × 3.94)
	Displacement		cm^3 (cu.in.)	4009 (244.6)	4009 (244.6)	4009 (244.6)	4164 (254.1)
	Compression Ratio			18.0 : 1	18.0 : 1	18.0 : 1	22.4 : 1
	Fuel System			Common-rail Type	Common-rail Type	Common-rail Type	Distributor Type
	Research Octane No. or Cetane No. (Diesel)			50 or higher	50 or higher	50 or higher	50 or higher
	Max. Output		kW/rpm	110/2700 (EEC)	110/2700 (EEC)	110/2700 (EEC)	96/3800 (SAE-NET)
	Max. Torque		N·m/rpm	397/1800 (EEC)	397/1800 (EEC)	397/1800 (EEC)	285/2200 (SAE-NET)
Engine Electrical	Battery Capacity(5HR)		Voltage & Amp. hr.	12 - 64 × 2	12 - 64 × 2	12 - 64 × 2	12 - 59
	Alternator Output		Watts	1560	1560	1560	1560
	Starter Output		kW	2.7	2.7	2.7	2.5
Chassis	Clutch Type			Dry, Single Plate Diaphragm	-	-	Dry, Single Plate Diaphragm
	Transmission Type			M551	A444E	A444E	M155
	Gear Ratio	In First		5.099	2.950	2.950	4.535
		In Second		2.910	1.530	1.530	2.858
		In Third		1.632	1.000	1.000	1.600
		In Fourth		1.000	0.703	0.703	1.000
		In Fifth		0.674	-	-	0.744
		In Reverse		4.625	2.678	2.678	5.043
	Differential Gear Ratio			5.375	4.875	4.875	5.625
	Differential Gear Size		in.	10.5	10.5	10.5	10.5
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear		Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum
	Parking Brake Type			Drum	Drum	Drum	Drum
	Brake Booster Type and Size		in.	Tandem, 9" + 10"	Tandem, 9" + 10"	Tandem, 9" + 10"	Tandem, 9" + 10"
	Proportioning Valve Type			LSP and BV	LSP and BV	LSP and BV	LSP and BV
	Suspension Type	Front		Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
		Rear		Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid
	Stabilizer Bar	Front		Standard	Standard	Standard	Standard
		Rear		Standard	Standard	Standard	Standard
	Steering Gear Type			Recirculating Ball	Recirculating Ball	Recirculating Ball	Recirculating Ball
	Steering Gear Ratio (Overall)			17.7	17.7	17.7	17.7
	Power Steering Type			Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

G.C.C. Countries			
High Roof			
Standard (with Air Conditioner)			
HZB70L-ZXMSSV	TRB60L-ZRMSKV	TRB70L-ZGMSKV	TRB70L-ZXMSKV
6990 (275.2)	6255 (246.3)	6990 (275.2)	6990 (275.2)
2080 (81.9)	2080 (81.9)	2080 (81.9)	2080 (81.9)
2635 (103.7)	2630 (103.5)	2635 (103.7)	2635 (103.7)
3935 (154.9)	3200 (126.0)	3935 (154.9)	3935 (154.9)
1690 (66.5)	1690 (66.5)	1690 (66.5)	1690 (66.5)
1490 (58.7)	1490 (58.7)	1490 (58.7)	1490 (58.7)
6230 (245.3)	5495 (216.3)	6230 (245.3)	6230 (245.3)
1885 (74.2)	1885 (74.2)	1885 (74.2)	1885 (74.2)
1890 (74.4)	1890 (74.4)	1890 (74.4)	1890 (74.4)
-	-	-	-
-	-	-	-
-	-	-	-
1150 (45.3)	1150 (45.3)	1150 (45.3)	1150 (45.3)
1905 (75.0)	1905 (75.0)	1905 (75.0)	1905 (75.0)
185 (7.3)	185 (7.3)	185 (7.3)	185 (7.3)
18	18	18	18
14	14	14	14
1805 - 1830 (3979 - 4034)	1495 - 1520 (3296 - 3351)	1605 - 1630 (3538 - 3593)	1605 - 1625 (3538 - 3582)
1705 - 1725 (3759 - 3803)	1660 - 1675 (3660 - 3693)	1700 - 1765 (3748 - 3891)	1700 - 1720 (3747 - 3792)
3510 - 3555 (7738 - 7837)	3155 - 31950 (6956 - 7044)	3305 - 3295 (7286 - 7485)	3305 - 3345 (7286- 7374)
2400 (5291)	2020 (4453)	2250 (4960)	2250 (4960)
3270 (7209)	2990 (6592)	3270 (7209)	3270 (7209)
5670 (12500)	5010 (11045)	5520 (12169)	5520 (12169)
95 (20.9)	95 (20.9)	95 (20.9)	95 (20.9)
-	0.41 (14.5)	0.41 (14.5)	-
130 (81)	130 (81)	130 (81)	130 (81)
-	-	-	-
20 (12)	20 (12)	20 (12)	20 (12)
35 (22)	40 (25)	40 (25)	40 (25)
60 (37)	70 (43)	70 (43)	70 (43)
100 (62)	115 (71)	115 (71)	115 (71)
-	-	-	-
7.2 (23.6)	6.1 (20.0)	7.2 (23.6)	7.2 (23.6)
7.9 (25.9)	6.8 (22.3)	7.9 (25.9)	7.9 (25.9)
1HZ	2TR-FE	2TR-FE	2TR-FE
12-valve OHC	16-valve DOHC	16-valve DOHC	16-valve DOHC
94.0 × 100.0 (3.70 × 3.94)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)
4164 (254.1)	2694 (164.4)	2694 (164.4)	2694 (164.4)
22.4 : 1	9.6 : 1	9.6 : 1	9.6 : 1
Distributor Type	EFI	EFI	EFI
50 or higher	91 or higher	91 or higher	91 or higher
96/3800 (SAE-NET)	108/4800	108/4800	108/4800
285/2200 (SAE-NET)	235/3800	235/3800	235/3800
12 - 59	12 - 48	12 - 48	12 - 48
1560	1200	1200	1200
2.5	1.4	1.4	1.4
Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm	Dry, Single Plate Diaphragm
M155	M156	M156	M156
4.535	5.657	5.657	5.657
2.858	2.818	2.818	2.818
1.600	1.687	1.687	1.687
1.000	1.000	1.000	1.000
0.744	0.835	0.835	0.835
5.043	5.657	5.657	5.657
5.625	5.857	6.142	6.142
10.5	10.5	10.5	10.5
Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum	Dual Two Leading Drum
Drum	Drum	Drum	Drum
Tandem, 9" + 10"	Tandem, 9" + 10"	Tandem, 9" + 10"	Tandem, 9" + 10"
LSP and BV	-	-	-
Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid
Standard	Standard	Standard	Standard
Standard	Standard	Standard	Standard
Recirculating Ball	Recirculating Ball	Recirculating Ball	Recirculating Ball
17.7	17.7	17.7	17.7
Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type