



PREPARATION

SST (SPECIAL SERVICE TOOLS)


SA0Y0-01

	09308–10010 Oil Seal Puller	
	09309–36010 Transmission Rear Bearing Replacer	
	(09316–00010) Replacer Pipe	
	09330–00021 Companion Flange Holding Tool	
	09504–00011 Differential Side Bearing Adjusting Nut Wrench	
	09506–35010 Differential Drive Pinion Rear Bearing Replacer	
	09556–22010 Drive Pinion Front Bearing Remover	
	09608–35014 Axle Hub & Drive Pinion Bearing Tool Set	
	(09608–06020) Handle	
	(09608–06120) Front Hub Outer Bearing Cup Replacer	
	(09608–06160) Rear Hub Inner Bearing Cup Replacer	
	09950–00020 Bearing Remover	
	09950–20017 Universal Puller	

SA

RECOMMENDED TOOLS

8A0Y1-01

	09025–00010 Small Torque Wrench	

EQUIPMENT

8A0Y2-01

Dial indicator	
Torque wrench	

LUBRICANT

8A0Y3-01

SA

Item	Capacity	Classification
Differential oil	3.8 liters (4.0 US qts, 3.3 Imp.qts)	API GL–5 Hypoid gear oil [Above – 18°C (0°F)] SAE 90 [Below –18°C (0°F)] SAE 80W or 80W–90