SERVICE SPECIFICATIONS

SERVICE DATA

E30UX–02

Carburetor	Part. No.	21100–75080
		21100–75090
	Float level (Raised positiion)	9.8 mm (0.386 in.)
	Float level (Lowered position)	0.9 – 1.1 mm (0.035–0.043 in.)
	Secondary throttle valve full open angle (Primary)	90° from horizontal
	Secondary throttle valve full open angle (Secondary)	90° from horizontal
	Secondary touch angle	50° from horizontal
	Fast idle angle (Pre–setting)	17.5° from horizontal
	Unloder angle	25° from horizontal
	Choke breaker angle	25 – 36° from horizontal
	Throttle positioner angle (RCK series)	9.5° from horizontal
	Throttle positioner angle (RZB series)	10.5° from horizontal
	Idle speed angle (Pre–setting)	5.5° from horizontal
	Idle mixture adjusting sorew (Pre–setting)	Screw out approx. 2 1/4 turns
	Choke heater resistance	1.7 – 1.9 Ω
	OVCV resistance	32 – 38 Ω

TORQUE SPECIFICATIONS

E00UY–02

Part tightened	N·m	kgf·cm	ft·lbf
Carbulator x Intake manifold	13	130	9
Fuel pump x Cylinder head	28	290	21