SERVICE SPECIFICATIONS

SERVICE DATA

EG61C-08

Automatic timer	Thrust clearance	Flange plate side	0.12 – 0.22 mm (0.0047 – 0.0087 in.)
		Housing side	0.02 – 0.12 mm (0.0008 – 0.0047 in.)

TORQUE SPECIFICATIONS

EG0EE-08

Part tightened	N·m	kgf·cm	ft·lbf
Injection pipe x Injection nozzle	25	257	18
Injection pipe x Injection pump	35	357	26
Clamp for injection pipe	7.5	76	66 in.·lbf
Oil dipstick guide x Intake manifold	18	185	14
Oil dipstick guide x Intake air connector	21	214	16
Fuel filter bracket x Intake manifold	44	449	33
Fuel inlet pipe x Injection pump	36.8	375	27
Fuel outlet pipe x Injection pump	36.8	375	27
Injection pump x Timing gear case	42	429	31
Pump stay x Cylinder block	29	295	21
Pump stay x Injection pump	48.1	491	36
Injection pump x Automatic timer	137	1,400	101
Automatic timer cover x Timing gear case	18.5	189	14
Oil pipe x Timer cover, Injection pump	10.3	105	8
Oil pipe x Vacuum pump	16.5	168	12