SS1AZ–02

TORQUE SPECIFICATION

Part tightened	N·m	kgf·cm	ft·lbf
Injector x Carburetor	8	80	70 in.·lbf
Carburetor x Intake manifold	25	255	18
Intake air connector x Carburetor	18.5	190	14
Air adjust screw plug x Carburetor	3.9	40	35 in.·lbf
Union No. 2 x LPG regulator	25	250	18
Union for slow x LPG regulator	10	100	7
Union No. 3 x LPG regulator	10	100	7
Drain cock x LPG regulator	10	100	7
First valve assembly x LPG regulator body	3.9	40	35 in.·lbf
LPG solenoid valve x LPG Filter	37	380	27
First regulator cover x LPG regulator body	3.9	40	35 in.·lbf
Primary pressure adjusting screw set nut	10	100	7
Slow Lock solenoid valve x LPG regulator	3.9	40	35 in.·lbf
Pre–heater cover x LPG regulator body	3.9	40	35 in.·lbf
Second valve assembly x LPG regulator body	3.9	40	35 in.·lbf
Second regulator cover x LPG regulator body	3.9	40	35 in.·lbf
LPG regulator x LPG regulator bracket	18	184	13
LPG regulator pipe x LPG regulator	37	377	27
LPG solenoid x LPG filter	37	377	27
LPG regulator pipe x LPG filter	37	377	27
LPG regulator pipe x LPG solenid	37	377	27