SS0SM–03

# TORQUE SPECIFICATION

| Part tightened | N·m | kgf·cm | ft·lbf |
|---|---|---|---|
| No.1 turbo water pipe (with turbo water hose) x Turbocharger | 26 | 265 | 19 |
| Turbocharger x Exhaust manifold | 52 | 530 | 38 |
| Turbine outlet elbow x Turbocharger | 52 | 530 | 38 |
| Compressor outlet elbow x Turbocharger | 21 | 214 | 15 |
| Compressor inlet elbow x Turbocharger | 21 | 214 | 15 |
| Turbo oil inlet pipe x Turbocharger | 13 | 133 | 10 |
| Turbo oil inlet pipe x Oil filter bracket | 13 | 133 | 10 |
| Turbo oil outlet pipe x Turbocharger | 18.5 | 189 | 14 |
| Turbo oil outlet pipe x Cylinder block | 18.5 | 189 | 14 |
| Turbocharger stay x Turbocherger, Oil filter bracket | 44 | 449 | 32 |
| No.2 Turbo water pipe x Bearing housing | 26 | 265 | 19 |
| Clamp plate x Bearing housing, Compressor housing | 4.7 | 48 | 42 in.·lbf |
| V–band bolt x V–band nut | 8.3 | 85 | 73 in.·lbf |
| Actuator x Bearing housing, Compressor housing | 4.7 | 48 | 42 in.·lbf |