

TORQUE SPECIFICATION

Part tightened	N·m	kgf·cm	ft·lbf
No. 2 cylinder head cover	7.0	71	62 in.·lbf
Clutch line bracket set bolt	4.9	50	43 in.·lbf
Clutch release cylinder x Transaxle	12	120	9
Transaxle x Engine	33	340	25
Starter x Transaxle	39	400	29
No. 1 engine hanger	40	400	29
Engine left mounting bracket x Engine left mounting insulator	49	490	35
Engine rear mounting insulator x Engine rear mounting bracket	64	650	47
Engine rear mounting bracket x Transaxle	49	500	36
Shift lever assembly x Body	12	120	9
Shift and select control cable x Body	4.9	50	43 in.·lbf
Clutch release fork support	37	375	27
Filler and drain plugs	39	400	29
Vehicle speed sensor	11	115	8
Back-up light switch	40	410	30
Control lever housing support bracket x Transaxle case	11	115	8
Selecting bellcrank assembly x Transmission case	25	250	18
Transmission case x Transmission case cover	18	185	13
Shift and select lever shaft assembly lock bolt	29	300	22
Shift and select lever assembly	20	200	14
Output shaft lock nut	118	1,200	87
Shift fork and shift head x Shift fork shaft	16	160	12
Rear bearing retainer	27	280	20
Reverse idler gear shaft lock bolt	29	300	22
Straight screw plug (Shift fork shaft)	25	250	18
Lock ball assembly	39	400	29
Transmission case x Transaxle case	29	300	22
Oil receiver pipe x Transmission case	17	175	13
Reverse shift arm bracket	17	175	13
Output shaft front bearing lock plate set bolt	11	115	8
Transaxle case receiver x Transaxle case	11	115	8
Straight screw plug (Reverse restrict pin)	13	130	9
Ring gear x Differential case	124	1,260	91