
5. Tire and Disc Wheel

Aluminum alloy wheels are available as an option on all models except Malaysian models and Thai automatic transmission model and some general country models (automatic transmission model for Philippine package).

Tire Size	195R15C
Disc Wheel Size	15 × 6J
Disc Wheel Material	Aluminum
P.C.D.* mm (in.)	139.7 (5.5)
Offset mm (in.)	35 (1.4)
Wheel Design	 04Z1HA07TE

*: Pitch Circle Diameter

6. Engine

- The 2TR-FE engine control has been optimized in order to conform to the Euro IV emission regulations only on Russian and Ukraine models and some general country models (for Chinese package).
- The 2KD-FTV engine control has been optimized in order to conform to the Euro II emission regulations only on Vietnamese models and some general country models (for Philippine package).

7. Differential

A BD20B type differential is used on all models. BD20B type is the same as B200A type except for the differential model code.

8. Air Conditioner

- The air outlet mode control in the air conditioner unit has been changed on Boost/Vent models and Boost/Vent and Cooler models.
- Clean air filter (semi-standard type particle filter) is provided as standard equipment on the all models.
- The conventional K62-13.5T type blower assembly has been replaced with K62-12.5 type one on the following engines: 2TR-FE, 2KD-FTV and 1KD-FTV.

● For details, see page 31.

9. Seat

- The seat layout has been rearranged on some general country models (for Mexican and Venezuelan packages).
- The rear seat lock release lever has been redesigned on van models.
- The rear seatback frame has been redesigned.

● For details, see page 29.