MAJOR TECHNICAL SPECIFICATIONS

Item \ Area				Australia			
Body Type				4-door Van (Standard)		5-door Van (Super Long)	
Vehicle Grade				DX			
Model Code				TRH201R-RBMDKQ	TRH201R-RBPDKQ	TRH221R-MBMDKQ	TRH221R-MBPDKQ
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	4695 (184.8)	4695 (184.8)	5380 (211.8)	5380 (211.8)
		Width	mm (in.)	1695 (66.7)	1695 (66.7)	1880 (74.0)	1880 (74.0)
		Height	mm (in.)	1980 (78.0)	1980 (78.0)	2285 (90.0)	2285 (90.0)
	Wheel Base		mm (in.)	2570 (101.2)	2570 (101.2)	3110 (122.4)	3110 (122.4)
	Tread	Front	mm (in.)	1470 (57.9)	1470 (57.9)	1655 (65.2)	1655 (65.2)
		Rear	mm (in.)	1465 (57.7)	1465 (57.7)	1650 (65.0)	1650 (65.0)
	Room	Length	mm (in.)	910 (35.8)	910 (35.8)	910 (35.8)	910 (35.8)
		Width	mm (in.)	1545 (60.8)	1545 (60.8)	1730 (68.1)	1730 (68.1)
		Height	mm (in.)	1320 (52.0)	1320 (52.0)	1565 (61.6)	1565 (61.6)
	Cargo Space	Length	mm (in.)	2930 (115.4)	2930 (115.4)	3470 (136.6)	3470 (136.6)
		Width	mm (in.)	1545 (60.8)	1545 (60.8)	1730 (68.1)	1730 (68.1)
		Height	mm (in.)	1335 (52.6)	1335 (52.6)	1635 (64.4)	1635 (64.4)
	Overhang	Front	mm (in.)	1050 (41.3)	1050 (41.3)	1190 (46.9)	1190 (46.9)
		Rear	mm (in.)	1075 (42.3)	1075 (42.3)	1080 (42.5)	1080 (42.5)
	Min. Running Ground Clearance		mm (in.)	195 (7.7)	195 (7.7)	195 (7.7)	195 (7.7)
	Angle of Approach		degrees	18.5	18.5	17.5	17.5
	Angle of Departure		degrees	19.5	19.5	19.5	19.5
	Curb Weight	Front	kg (lb)	990 - 1025 (2183 - 2260)	990 - 1025 (2183 - 2260)	1085 - 1120 (2392 - 2469)	1090 - 1125 (2403 - 2480)
		Rear	kg (lb)	675 - 690 (1488 - 1521)	675 - 690 (1488 - 1521)	760 - 775 (1676 - 1709)	765 - 780 (1678 - 1720)
		Total	kg (lb)	1665 - 1715 (3671 - 3781)	1665 - 1715 (3671 - 3781)	1845 - 1895 (4068 - 4178)	1855 - 1905 (4090 - 4200)
	Gross Vehicle Weight	Front	kg (lb)	1360 - 1385 (2998 - 3053)	1360 - 1385 (2998 - 3053)	1560 - 1585 (3439 - 3494)	1565 - 1585 (3450 - 3494)
		Rear	kg (lb)	1415 - 1440 (3120 - 3175)	1415 - 1440 (3120 - 3175)	1615 - 1640 (3560 - 3616)	1615 - 1635 (3560 - 3605)
		Total	kg (lb)	2800 (6173)	2800 (6173)	3200 (7055)	3200 (7055)
	Fuel Tank Capacity		ℓ (Imp.gal.)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)
	Luggage Compartment Capacity		m^3 (cu.ft.)	6.0	6.0	9.8	9.8
Performance	Max. Speed		km/h (mph)	170 (105)	170 (105)	155 (96)	155 (96)
	Max. Cruising Speed		km/h (mph)	—	—	—	—
	Max. Permissible Speed	1st Gear	km/h (mph)	38 (24)	54 (33)	38 (24)	54 (33)
		2nd Gear	km/h (mph)	70 (43)	98 (61)	70 (43)	98 (61)
		3rd Gear	km/h (mph)	114 (71)	150 (93)	114 (71)	150 (93)
		4th Gear	km/h (mph)	163 (101)	—	163 (101)	—
	Min. Turning Radius	Tire	m (ft.)	5.0 (16.4)	5.0 (16.4)	6.2 (20.3)	6.2 (20.3)
		Body	m (ft.)	5.7 (18.7)	5.7 (18.7)	6.9 (22.6)	6.9 (22.6)
Engine	Engine Type			2TR-FE	2TR-FE	2TR-FE	2TR-FE
	Valve Mechanism			16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i
	Bore × Stroke		mm (in.)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)
	Displacement		cm^3 (cu.in.)	2694 (164.4)	2694 (164.4)	2694 (164.4)	2694 (164.4)
	Compression Ratio			9.6 : 1	9.6 : 1	9.6 : 1	9.6 : 1
	Fuel System			EFI	EFI	EFI	EFI
	Research Octane No. or Cetane No. (Diesel)			91 or higher	91 or higher	91 or higher	91 or higher
	Max. Output (EEC)		kW/rpm	111/4800	111/4800	111/4800	111/4800
	Max. Torque (EEC)		N·m/rpm	241/3800	241/3800	241/3800	241/3800
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp.hr.	12 - 48	12 - 48	12 - 48	12 - 48
	Alternator Output		Watts	1560	1560	1560	1560
	Starter Output		kW	1.6	1.6	1.6	1.6
Chassis	Clutch Type			Dry, Single Plate, Diaphragm	—	Dry, Single Plate, Diaphragm	—
	Transmission Type			R351	A343E	R351	A343E
	Gear Ratio	In First		4.313	2.804	4.313	2.804
		In Second		2.330	1.531	2.330	1.531
		In Third		1.436	1.000	1.436	1.000
		In Fourth		1.000	0.753	1.000	0.753
		In Fifth		0.838	—	0.838	—
		Reverse		4.220	2.393	4.220	2.393
	Differential Gear Ratio			4.300	4.556	4.300	4.556
	Differential Gear Size		mm (in.)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear		Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum
	Parking Brake Type			Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
	Brake Booster Type and Size		in.	Single, Single with BA*1 10”	Single, Single with BA*1 10”	Single, Single with BA*1 10”	Single, Single with BA*1 10”
	Proportioning Valve Type			LSP and BV	LSP and BV	LSP and BV	LSP and BV
	Suspension Type	Front		Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
		Rear		Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid
	Stabilizer Bar	Front		Standard	Standard	Standard	Standard
		Rear		—	—	—	—
	Steering Gear Type			Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
	Steering Gear Ratio (Overall)			20.84	20.84	20.84	20.84
	Power Steering Type			Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

*1: With ABS

	Australia					
	4-door Commuter (Super Long)		4-door Van (Standard)		5-door Van (Super Long)	
	DX					
	TRH223R-LEMDKQ	TRH223R-LEPDKQ	KDH201R-RBMDYQ	KDH201R-RBPDYQ	KDH221R-MBMDYQ	KDH221R-MBPDYQ
5	5380 (211.8)	5380 (211.8)	4695 (184.8)	4695 (184.8)	5380 (211.8)	5380 (211.8)
	1880 (74.0)	1880 (74.0)	1695 (66.7)	1695 (66.7)	1880 (74.0)	1880 (74.0)
	2285 (90.0)	2285 (90.0)	1980 (78.0)	1980 (78.0)	2285 (90.0)	2285 (90.0)
	3110 (122.4)	3110 (122.4)	2570 (101.2)	2570 (101.2)	3110 (122.4)	3110 (122.4)
	1655 (65.2)	1655 (65.2)	1470 (57.9)	1470 (57.9)	1655 (65.2)	1655 (65.2)
10	1650 (65.0)	1650 (65.0)	1465 (57.7)	1465 (57.7)	1650 (65.0)	1650 (65.0)
	4250 (167.3)	4250 (167.3)	910 (35.8)	910 (35.8)	910 (35.8)	910 (35.8)
	1730 (68.1)	1730 (68.1)	1545 (60.8)	1545 (60.8)	1730 (68.1)	1730 (68.1)
	1565 (61.6)	1565 (61.6)	1320 (52.0)	1320 (52.0)	1565 (61.6)	1565 (61.6)
	—	—	2930 (115.4)	2930 (115.4)	3470 (136.6)	3470 (136.6)
15	—	—	1545 (60.8)	1545 (60.8)	1730 (68.1)	1730 (68.1)
	—	—	1335 (52.6)	1335 (52.6)	1635 (64.4)	1635 (64.4)
	1190 (46.9)	1190 (46.9)	1050 (41.3)	1050 (41.3)	1190 (46.9)	1190 (46.9)
	1080 (42.5)	1080 (42.5)	1075 (42.3)	1075 (42.3)	1080 (42.5)	1080 (42.5)
	185 (7.3)	185 (7.3)	195 (7.7)	195 (7.7)	195 (7.7)	195 (7.7)
20	17.0	17.0	18.5	18.5	17.5	17.5
	19.2	19.2	19.5	19.5	19.5	19.5
	1125 - 1145 (2480 - 2524)	1125 - 1145 (2480 - 2524)	1070 - 1105 (2359 - 2436)	1075 - 1110 (2370 - 2447)	1160 - 1195 (2557 - 2635)	1165 - 1200 (2568 - 2646)
	910 - 920 (2006 - 2028)	915 - 925 (2017 - 2039)	700 - 715 (1543 - 1576)	705 - 720 (1554 - 1587)	775 - 790 (1709 - 1742)	780 - 795 (1720 - 1753)
	2035 - 2065 (4486 - 4553)	2040 - 2070 (4497 - 4564)	1770 - 1820 (3902 - 4012)	1780 - 1830 (3924 - 4034)	1935 - 1985 (4266 - 4376)	1945 - 1995 (4288 - 4398)
25	1410 - 1425 (3109 - 3142)	1410 - 1420 (3109 - 3131)	1420 - 1445 (3131 - 3186)	1425 - 1450 (3142 - 3197)	1615 - 1640 (3560 - 3616)	1615 - 1640 (3560 - 3616)
	1725 - 1740 (3803 - 3836)	1730 - 1740 (3814 - 3836)	1355 - 1380 (2987 - 3042)	1350 - 1375 (2976 - 3031)	1560 - 1585 (3439 - 3494)	1560 - 1585 (3439 - 3494)
	3150 (6945)	3150 (6945)	2800 (6173)	2800 (6173)	3200 (7055)	3200 (7055)
	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)
	—	—	6.0	6.0	9.8	9.8
30	155 (96)	155 (96)	145 (90)	145 (90)	140 (87)	135 (84)
	—	—	—	—	—	—
	38 (24)	54 (33)	32 (20)	48 (30)	32 (20)	48 (30)
	70 (43)	98 (61)	59 (37)	88 (55)	59 (37)	88 (55)
	114 (71)	150 (93)	96 (60)	135 (84)	96 (60)	135 (84)
35	163 (101)	—	138 (86)	—	138 (86)	—
	6.2 (20.3)	6.2 (20.3)	5.0 (16.4)	5.0 (16.4)	6.2 (20.3)	6.2 (20.3)
	6.9 (22.6)	6.9 (22.6)	5.7 (18.7)	5.7 (18.7)	6.9 (22.6)	6.9 (22.6)
	2TR-FE	2TR-FE	1KD-FTV	1KD-FTV	1KD-FTV	1KD-FTV
	16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i	16-valve, DOHC	16-valve, DOHC	16-valve, DOHC	16-valve, DOHC
40	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	96.0 × 103.0 (3.78 × 4.06)	96.0 × 103.0 (3.78 × 4.06)	96.0 × 103.0 (3.78 × 4.06)	96.0 × 103.0 (3.78 × 4.06)
	2694 (164.4)	2694 (164.4)	2982 (182.0)	2982 (182.0)	2982 (182.0)	2982 (182.0)
	9.6 : 1	9.6 : 1	16.0 : 1	16.0 : 1	16.0 : 1	16.0 : 1
	EFI	EFI	Common-rail Type	Common-rail Type	Common-rail Type	Common-rail Type
	91 or higher	91 or higher	48 or higher	48 or higher	48 or higher	48 or higher
45	111/4800	111/4800	100/3400	100/3400	100/3400	100/3400
	241/3800	241/3800	300/1200 - 2400	300/1200 - 2400	300/1200 - 2400	300/1200 - 2400
	12 - 48	12 - 48	12 - 60	12 - 60	12 - 60	12 - 60
	1560	1560	1560	1560	1560	1560
	1.6	1.6	2.2	2.7	2.2	2.7
50	Dry, Single Plate, Diaphragm	—	Dry, Single Plate, Diaphragm	—	Dry, Single Plate, Diaphragm	—
	R351	A343E	R351	A340E	R351	A340E
	4.313	2.804	4.313	2.804	4.313	2.804
	2.330	1.531	2.330	1.531	2.330	1.531
	1.436	1.000	1.436	1.000	1.436	1.000
55	1.000	0.753	1.000	0.705	1.000	0.705
	0.838	—	0.838	—	0.838	—
	4.220	2.393	4.220	2.393	4.220	2.393
	4.300	4.556	3.727	4.100	3.727	4.100
	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)
60	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum
	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
	Single, Single with BA*1 10”	Single, Single with BA*1 10”	Single, Single with BA*1 10”	Single, Single with BA*1 10”	Single, Single with BA*1 10”	Single, Single with BA*1 10”
	LSP and BV	LSP and BV	LSP and BV	LSP and BV	LSP and BV	LSP and BV
65	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid
	Standard	Standard	Standard	Standard	Standard	Standard
	—	—	—	—	—	—
	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
70	20.84	20.84	20.84	20.84	20.84	20.84
	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

Item \ Area				Australia		G.C.C. Countries	
Body Type				4-door Commuter (Super Long)		5-door Van (Standard)	
Vehicle Grade				DX			
Model Code				KDH223R-LEMDYQ	KDH223R-LEPDYQ	TRH201L-SBMDKV	TRH201L-SRMDKV
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	5380 (211.8)	5380 (211.8)	4695 (184.8)	4695 (184.8)
		Width	mm (in.)	1880 (74.0)	1880 (74.0)	1695 (66.7)	1695 (66.7)
		Height	mm (in.)	2285 (90.0)	2285 (90.0)	1980 (78.0)	1980 (78.0)
	Wheel Base		mm (in.)	3110 (122.4)	3110 (122.4)	2570 (101.2)	2570 (101.2)
	Tread	Front	mm (in.)	1655 (65.2)	1655 (65.2)	1470 (57.9)	1470 (57.9)
		Rear	mm (in.)	1650 (65.0)	1650 (65.0)	1465 (57.7)	1465 (57.7)
	Room	Length	mm (in.)	4250 (167.3)	4250 (167.3)	910 (35.8)	1905 (75.0), 910 (35.8)*1
		Width	mm (in.)	1730 (68.1)	1730 (68.1)	1545 (60.8)	1545 (60.8)
		Height	mm (in.)	1565 (61.6)	1565 (61.6)	1320 (52.0)	1320 (52.0)
	Cargo Space	Length	mm (in.)	—	—	2930 (115.4)	1960 (77.2), 2930 (115.4)*1
		Width	mm (in.)	—	—	1545 (60.8)	1545 (60.8)
		Height	mm (in.)	—	—	1335 (52.6)	1335 (52.6)
	Overhang	Front	mm (in.)	1190 (46.9)	1190 (46.9)	1050 (41.3)	1045 (41.1)
		Rear	mm (in.)	1080 (42.5)	1080 (42.5)	1075 (42.3)	1080 (42.5)
	Min. Running Ground Clearance		mm (in.)	185 (7.3)	185 (7.3)	195 (7.7)	195 (7.7)
	Angle of Approach		degrees	17.0	17.0	18.5	18.5
	Angle of Departure		degrees	19.2	19.2	19.5	19.5
	Curb Weight	Front	kg (lb)	1210 - 1230 (2668 - 2712)	1215 - 1235 (2679 - 2723)	985 - 1020 (2172 - 2249)	1005 - 1040 (2216 - 2293)
		Rear	kg (lb)	920 - 930 (2028 - 2050)	925 - 935 (2039 - 2061)	695 - 710 (1532 - 1565)	695 - 710 (1532 - 1565)
		Total	kg (lb)	2130 - 2160 (4696 - 4762)	2140 - 2170 (4718 - 4784)	1680 - 1730 (3704 - 3814)	1700 - 1750 (3748 - 3858)
	Gross Vehicle Weight	Front	kg (lb)	1485 - 1495 (3274 - 3296)	1485 - 1500 (3274 - 3307)	1350 - 1380 (2976 - 3042)	1330 - 1360 (2932 - 2998), 1340 - 1365 (2954 - 3009)*1
		Rear	kg (lb)	1705 - 1715 (3759 - 3781)	1700 - 1715 (3748 - 3781)	1420 - 1450 (3131 - 3197)	1440 - 1470 (3175 - 3241), 1435 - 1460 (3164 - 3219)*1
		Total	kg (lb)	3200 (7055)	3200 (7055)	2800 (6173)	2800 (6173)
	Fuel Tank Capacity		ℓ (Imp.gal.)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)
	Luggage Compartment Capacity		m^3 (cu.ft.)	—	—	6.0	6.0
Performance	Max. Speed		km/h (mph)	140 (87)	135 (84)	170 (105)	170 (105)
	Max. Cruising Speed		km/h (mph)	—	—	—	—
	Max. Permissible Speed	1st Gear	km/h (mph)	32 (20)	48 (30)	38 (24)	38 (24)
		2nd Gear	km/h (mph)	59 (37)	88 (55)	70 (43)	70 (43)
		3rd Gear	km/h (mph)	96 (60)	135 (84)	114 (71)	114 (71)
		4th Gear	km/h (mph)	138 (86)	—	163 (101)	163 (101)
	Min. Turning Radius	Tire	m (ft.)	6.2 (20.3)	6.2 (20.3)	5.0 (16.4)	5.0 (16.4)
		Body	m (ft.)	6.9 (22.6)	6.9 (22.6)	5.7 (18.7)	5.7 (18.7)
Engine	Engine Type			1KD-FTV	1KD-FTV	2TR-FE	2TR-FE
	Valve Mechanism			16-valve, DOHC	16-valve, DOHC	16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i
	Bore × Stroke		mm (in.)	96.0 × 103.0 (3.78 × 4.06)	96.0 × 103.0 (3.78 × 4.06)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)
	Displacement		cm^3 (cu.in.)	2982 (182.0)	2982 (182.0)	2694 (164.4)	2694 (164.4)
	Compression Ratio			16.0 : 1	16.0 : 1	9.6 : 1	9.6 : 1
	Fuel System			Common-rail Type	Common-rail Type	EFI	EFI
	Research Octane No. or Cetane No. (Diesel)			48 or higher	48 or higher	91 or higher	91 or higher
	Max. Output (EEC)		kW/rpm	100/3400	100/3400	111/4800	111/4800
	Max. Torque (EEC)		N·m/rpm	300/1200 - 2400	300/1200 - 2400	241/3800	241/3800
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp.hr.	12 - 60	12 - 60	12 - 48, 12 - 55*2	12 - 48, 12 - 55*2
	Alternator Output		Watts	1560	1560	1560	1560
	Starter Output		kW	2.2	2.7	1.6	1.6
Chassis	Clutch Type			Dry, Single Plate, Diaphragm	—	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm
	Transmission Type			R351	A340E	R351	R351
	Gear Ratio	In First		4.313	2.804	4.313	4.313
		In Second		2.330	1.531	2.330	2.330
		In Third		1.436	1.000	1.436	1.436
		In Fourth		1.000	0.705	1.000	1.000
		In Fifth		0.838	—	0.838	0.838
		Reverse		4.220	2.393	4.220	4.220
	Differential Gear Ratio			3.727	4.100	4.300	4.300
	Differential Gear Size		mm (in.)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear		Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum
	Parking Brake Type			Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
	Brake Booster Type and Size		in.	Single, Single with BA*3 10"	Single, Single with BA*3 10"	Single, Single with BA*3 10"	Single, Single with BA*3 10"
	Proportioning Valve Type			LSP and BV	LSP and BV	LSP and BV	LSP and BV
	Suspension Type	Front		Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
		Rear		Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid
	Stabilizer Bar	Front		Standard	Standard	Standard	Standard
		Rear		—	—	—	—
	Steering Gear Type			Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
	Steering Gear Ratio (Overall)			20.84	20.84	20.84	20.84
	Power Steering Type			Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

*1: Folded Seat
*2: Option
*3: With ABS

	G.C.C. Countries					
	5-door Van (Super Long)	4-door Commuter (Standard)		4-door Commuter (Super Long)		5-door Van (Standard)
		DX			GL	DX
	TRH221L-MBMDKV	TRH203L-REMDKV	TRH213L-JEMDKV	TRH223L-LEMDKV	TRH223L-LEMNKV	KDH200L-SBMDYV
5	5380 (211.8)	4695 (184.8)	4840 (190.6)	5380 (211.8)	5380 (211.8)	4695 (184.8)
	1880 (74.0)	1695 (66.7)	1880 (74.0)	1880 (74.0)	1880 (74.0)	1695 (66.7)
	2285 (90.0)	1980 (78.0)	2105 (82.9)	2285 (90.0)	2285 (90.0)	1980 (78.0)
	3110 (122.4)	2570 (101.2)	2570 (101.2)	3110 (122.4)	3110 (122.4)	2570 (101.2)
	1655 (65.2)	1470 (57.9)	1655 (65.2)	1655 (65.2)	1655 (65.2)	1470 (57.9)
10	1650 (65.0)	1465 (57.7)	1650 (65.0)	1650 (65.0)	1650 (65.0)	1465 (57.7)
	910 (35.8)	3470 (136.6)	3525 (138.8)	4205 (165.6)	4250 (167.3)	910 (35.8)
	1730 (68.1)	1545 (60.8)	1730 (68.1)	1730 (68.1)	1695 (66.7)	1545 (60.8)
	1565 (61.6)	1335 (52.6)	1390 (54.7)	1565 (61.6)	1565 (61.6)	1320 (52.0)
	3470 (136.6)	—	—	—	—	2930 (115.4)
15	1730 (68.1)	—	—	—	—	1545 (60.8)
	1635 (64.4)	—	—	—	—	1335 (52.6)
	1190 (46.9)	1050 (41.3)	1190 (46.9)	1190 (46.9)	1190 (46.9)	1050 (41.3)
	1080 (42.5)	1075 (42.3)	1080 (42.5)	1080 (42.5)	1080 (42.5)	1075 (42.3)
	195 (7.7)	185 (7.3)	185 (7.3)	185 (7.3)	185 (7.3)	195 (7.7)
20	17.5	18.5	16.6	17.0	17.0	18.5
	19.5	19.5	19.7	19.2	19.2	19.5
	1085 - 1120 (2392 - 2469)	1005 - 1045 (2216 - 2304)	1050 - 1090 (2315 - 2403)	1090 - 1140 (2403 - 2513)	1110 - 1165 (2447 - 2568)	1035 - 1070 (2282 - 2359)
	765 - 780 (1687 - 1720)	755 - 770 (1664 - 1698)	805 - 825 (1775 - 1819)	850 - 865 (1874 - 1907)	890 - 910 (1962 - 2006)	710 - 725 (1565 - 1598)
	1850 - 1900 (4079 - 4189)	1760 - 1815 (3880 - 4001)	1855 - 1915 (4090 - 4222)	1940 - 2005 (4277 - 4420)	2000 - 2075 (4409 - 4575)	1745 - 1795 (3847 - 3957)
25	1560 - 1585 (3439 - 3494)	1355 - 1385 (2987 - 3053)	1380 - 1405 (3042 - 3097)	1485 - 1520 (3274 - 3351)	1500 - 1540 (3307 - 3395)	1390 - 1415 (3064 - 3120)
	1615 - 1640 (3560 - 3616)	1565 - 1595 (3450 - 3516)	1695 - 1720 (3737 - 3792)	1680 - 1715 (3704 - 3781)	1710 - 1750 (3770 - 3858)	1385 - 1410 (3053 - 3109)
	3200 (7055)	2950 (6504)	3100 (6834)	3200 (7055)	3250 (7165)	2800 (6173)
	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)
	9.8	—	—	—	—	6.0
30	155 (96)	170 (105)	155 (96)	155 (96)	155 (96)	145 (90)
	—	—	—	—	—	—
	38 (24)	38 (24)	38 (24)	38 (24)	38 (24)	32 (20)
	70 (43)	70 (43)	70 (43)	70 (43)	70 (43)	59 (37)
	114 (71)	114 (71)	114 (71)	114 (71)	114 (71)	96 (60)
35	163 (101)	163 (101)	163 (101)	163 (101)	163 (101)	138 (86)
	6.2 (20.3)	5.0 (16.4)	5.3 (17.4)	6.2 (20.3)	6.2 (20.3)	5.0 (16.4)
	6.9 (22.6)	5.7 (18.7)	5.9 (19.4)	6.9 (22.6)	6.9 (22.6)	5.7 (18.7)
	2TR-FE	2TR-FE	2TR-FE	2TR-FE	2TR-FE	2KD-FTV
	16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i	16-valve, DOHC
40	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	92.0 × 93.8 (3.62 × 3.69)
	2694 (164.4)	2694 (164.4)	2694 (164.4)	2694 (164.4)	2694 (164.4)	2494 (152.2)
	9.6 : 1	9.6 : 1	9.6 : 1	9.6 : 1	9.6 : 1	18.5 : 1
	EFI	EFI	EFI	EFI	EFI	Common-rail Type
	91 or higher	91 or higher	91 or higher	91 or higher	91 or higher	48 or higher
45	111/4800	111/4800	111/4800	111/4800	111/4800	75/3600
	241/3800	241/3800	241/3800	241/3800	241/3800	260/1600 - 2400
	12 - 48, 12 - 55*2	12 - 48, 12 - 55*2	12 - 48, 12 - 55*2	12 - 48, 12 - 55*2	12 - 48, 12 - 55*2	12 - 55
	1560	1560	1560	1560	1560	1200, 1560*2
	1.6	1.6	1.6	1.6	1.6	2.0
50	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm
	R351	R351	R351	R351	R351	R351
	4.313	4.313	4.313	4.313	4.313	4.313
	2.330	2.330	2.330	2.330	2.330	2.330
	1.436	1.436	1.436	1.436	1.436	1.436
55	1.000	1.000	1.000	1.000	1.000	1.000
	0.838	0.838	0.838	0.838	0.838	0.838
	4.220	4.220	4.220	4.220	4.220	4.220
	4.300	4.300	4.300	4.300	4.300	4.100
	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)
60	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum
	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
	Single, Single with BA*3 10”	Single, Single with BA*3 10”	Single, Single with BA*3 10”	Single, Single with BA*3 10”	Single, Single with BA*3 10”	Single, Single with BA*3 10”
	LSP and BV	LSP and BV	LSP and BV	LSP and BV	LSP and BV	LSP and BV
65	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid
	Standard	Standard	Standard	Standard	Standard	Standard
	—	—	—	—	—	—
	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
70	20.84	20.84	20.84	20.84	20.84	20.84
	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

Item \ Area				G.C.C. Countries			
Body Type				4-door Commuter (Standard)		4-door Commuter (Super Long)	
Vehicle Grade				DX			GL
Model Code				KDH202L-REMDYV	KDH212L-JEMDYV	KDH222L-LEMDYV	KDH222L-LEMNYV
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	4695 (184.8)	4840 (190.6)	5380 (211.8)	5380 (211.8)
		Width	mm (in.)	1695 (66.7)	1880 (74.0)	1880 (74.0)	1880 (74.0)
		Height	mm (in.)	1980 (78.0)	2105 (82.9)	2285 (90.0)	2285 (90.0)
	Wheel Base		mm (in.)	2570 (101.2)	2570 (101.2)	3110 (122.4)	3110 (122.4)
	Tread	Front	mm (in.)	1470 (57.9)	1655 (65.2)	1655 (65.2)	1655 (65.2)
		Rear	mm (in.)	1465 (57.7)	1650 (65.0)	1650 (65.0)	1650 (65.0)
	Room	Length	mm (in.)	3470 (136.6)	3525 (138.8)	4205 (165.6)	4250 (167.3)
		Width	mm (in.)	1545 (60.8)	1730 (68.1)	1730 (68.1)	1695 (66.7)
		Height	mm (in.)	1335 (52.6)	1390 (54.7)	1565 (61.6)	1565 (61.6)
	Cargo Space	Length	mm (in.)	—	—	—	—
		Width	mm (in.)	—	—	—	—
		Height	mm (in.)	—	—	—	—
	Overhang	Front	mm (in.)	1050 (41.3)	1190 (46.9)	1190 (46.9)	1190 (46.9)
		Rear	mm (in.)	1075 (42.3)	1080 (42.5)	1080 (42.5)	1080 (42.5)
	Min. Running Ground Clearance		mm (in.)	185 (7.3)	185 (7.3)	185 (7.3)	185 (7.3)
	Angle of Approach		degrees	18.5	16.6	17.0	17.0
	Angle of Departure		degrees	19.5	19.7	19.2	19.2
	Curb Weight	Front	kg (lb)	1055 - 1095 (2326 - 2414)	1105 - 1145 (2436 - 2524)	1140 - 1190 (2513 - 2623)	1160 - 1215 (2557 - 2679)
		Rear	kg (lb)	760 - 775 (1676 - 1709)	810 - 830 (1786 - 1830)	855 - 870 (1885 - 1918)	895 - 915 (1973 - 2017)
		Total	kg (lb)	1815 - 1870 (4001 - 4123)	1915 - 1975 (4222 - 4354)	1995 - 2060 (4398 - 4542)	2055 - 2130 (4530 - 4696)
	Gross Vehicle Weight	Front	kg (lb)	1405 - 1430 (3097 - 3153)	1430 - 1460 (3153 - 3219)	1535 - 1565 (3384 - 3450)	1550 - 1585 (3417 - 3494)
		Rear	kg (lb)	1570 - 1595 (3461 - 3516)	1690 - 1720 (3726 - 3792)	1685 - 1715 (3715 - 3781)	1715 - 1750 (3781 - 3858)
		Total	kg (lb)	3000 (6614)	3150 (6945)	3250 (7165)	3300 (7275)
	Fuel Tank Capacity		ℓ (Imp.gal.)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)
	Luggage Compartment Capacity		m^3 (cu.ft.)	—	—	—	—
Performance	Max. Speed		km/h (mph)	145 (90)	135 (84)	135 (84)	135 (84)
	Max. Cruising Speed		km/h (mph)	—	—	—	—
	Max. Permissible Speed	1st Gear	km/h (mph)	32 (20)	32 (20)	32 (20)	32 (20)
		2nd Gear	km/h (mph)	59 (37)	59 (37)	59 (37)	59 (37)
		3rd Gear	km/h (mph)	96 (60)	96 (60)	96 (60)	96 (60)
		4th Gear	km/h (mph)	138 (86)	138 (86)	138 (86)	138 (86)
	Min. Turning Radius	Tire	m (ft.)	5.0 (16.4)	5.3 (17.4)	6.2 (20.3)	6.2 (20.3)
		Body	m (ft.)	5.7 (18.7)	5.9 (19.4)	6.9 (22.6)	6.9 (22.6)
Engine	Engine Type			2KD-FTV	2KD-FTV	2KD-FTV	2KD-FTV
	Valve Mechanism			16-valve, DOHC	16-valve, DOHC	16-valve, DOHC	16-valve, DOHC
	Bore × Stroke		mm (in.)	92.0 × 93.8 (3.62 × 3.69)	92.0 × 93.8 (3.62 × 3.69)	92.0 × 93.8 (3.62 × 3.69)	92.0 × 93.8 (3.62 × 3.69)
	Displacement		cm^3 (cu.in.)	2494 (152.2)	2494 (152.2)	2494 (152.2)	2494 (152.2)
	Compression Ratio			18.5 : 1	18.5 : 1	18.5 : 1	18.5 : 1
	Fuel System			Common-rail Type	Common-rail Type	Common-rail Type	Common-rail Type
	Research Octane No. or Cetane No. (Diesel)			48 or higher	48 or higher	48 or higher	48 or higher
	Max. Output (EEC)		kW/rpm	75/3600	75/3600	75/3600	75/3600
	Max. Torque (EEC)		N·m/rpm	260/1600 - 2400	260/1600 - 2400	260/1600 - 2400	260/1600 - 2400
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp.hr.	12 - 55	12 - 55, 12 - 55 × 2*1	12 - 55, 12 - 55 × 2*1	12 - 55, 12 - 55 × 2*1
	Alternator Output		Watts	1200, 1560*1	1200, 1560*1	1200, 1560*1	1560
	Starter Output		kW	2.0	2.0	2.0	2.0
Chassis	Clutch Type			Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm
	Transmission Type			R351	R351	R351	R351
	Gear Ratio	In First		4.313	4.313	4.313	4.313
		In Second		2.330	2.330	2.330	2.330
		In Third		1.436	1.436	1.436	1.436
		In Fourth		1.000	1.000	1.000	1.000
		In Fifth		0.838	0.838	0.838	0.838
		Reverse		4.220	4.220	4.220	4.220
	Differential Gear Ratio			4.100	4.100	4.100	4.100
	Differential Gear Size		mm (in.)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear		Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum
	Parking Brake Type			Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
	Brake Booster Type and Size		in.	Single, Single with BA*2 10"	Single, Single with BA*2 10"	Single, Single with BA*2 10"	Single, Single with BA*2 10"
	Proportioning Valve Type			LSP and BV	LSP and BV	LSP and BV	LSP and BV
	Suspension Type	Front		Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
		Rear		Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid
	Stabilizer Bar	Front		Standard	Standard	Standard	Standard
		Rear		—	—	—	—
	Steering Gear Type			Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
	Steering Gear Ratio (Overall)			20.84	20.84	20.84	20.84
	Power Steering Type			Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

*1: Option
*2: With ABS

	South Africa					
	4-door Van (Standard)	5-door Van (Super Long)	4-door Commuter (Super Long)	4-door Commuter (Standard)	4-door Commuter (Super Long)	4-door Van (Standard)
	DX			GL		DX
	TRH201R-RBMDKN	TRH221R-MBMDKN	TRH223R-LEMDKN	TRH213R-JDMNKN	TRH223R-LEMNKN	KDH200R-RBMDYN
5	4695 (184.8)	5380 (211.8)	5380 (211.8)	4840 (190.6)	5380 (211.8)	4695 (184.8)
	1695 (66.7)	1880 (74.0)	1880 (74.0)	1880 (74.0)	1880 (74.0)	1695 (66.7)
	1980 (78.0)	2285 (90.0)	2285 (90.0)	2105 (82.9)	2285 (90.0)	1980 (78.0)
	2570 (101.2)	3110 (122.4)	3110 (122.4)	2570 (101.2)	3110 (122.4)	2570 (101.2)
	1470 (57.9)	1655 (65.2)	1655 (65.2)	1655 (65.2)	1655 (65.2)	1470 (57.9)
10	1465 (57.7)	1650 (65.0)	1650 (65.0)	1650 (65.0)	1650 (65.0)	1465 (57.7)
	910 (35.8)	910 (35.8)	4250 (167.3)	3525 (138.8)	4250 (167.3)	910 (35.8)
	1545 (60.8)	1730 (68.1)	1730 (68.1)	1695 (66.7)	1695 (66.7)	1545 (60.8)
	1320 (52.0)	1565 (61.6)	1565 (61.6)	1390 (54.7)	1565 (61.6)	1320 (52.0)
	2930 (115.4)	3470 (136.6)	—	—	—	2930 (115.4)
15	1545 (60.8)	1730 (68.1)	—	—	—	1545 (60.8)
	1335 (52.6)	1635 (64.4)	—	—	—	1335 (52.6)
	1050 (41.3)	1190 (46.9)	1190 (46.9)	1190 (46.9)	1190 (46.9)	1050 (41.3)
	1075 (42.3)	1080 (42.5)	1080 (42.5)	1080 (42.5)	1080 (42.5)	1075 (42.3)
	195 (7.7)	195 (7.7)	185 (7.3)	185 (7.3)	185 (7.3)	195 (7.7)
20	18.5	17.5	17	16.6	17	18.5
	19.5	19.5	19.2	19.7	19.2	19.5
	990 - 1030 (2183 - 2271)	1085 - 1125 (2392 - 2480)	1110 - 1125 (2447 - 2480)	1070 - 1095 (2359 - 2414)	1135 - 1160 (2502 - 2557)	1035 - 1085 (2282 - 2392)
	675 - 695 (1488 - 1532)	760 - 780 (1676 - 1720)	900 - 910 (1984 - 2006)	815 - 825 (1767 - 1819)	925 - 935 (2039 - 2061)	695 - 725 (1532 - 1598)
	1665 - 1725 (3671 - 3803)	1845 - 1905 (4068 - 4200)	2010 - 2035 (4431 - 4486)	1885 - 1920 (4156 - 4233)	2060 - 2095 (4542 - 4619)	1730 - 1810 (3814 - 3990)
25	1360 - 1390 (2988 - 3064)	1560 - 1585 (3439 - 3494)	1425 - 1435 (3142 - 3164)	1315 - 1335 (2899 - 2943)	1415 - 1430 (3120 - 3153)	1395 - 1430 (3075 - 3153)
	1410 - 1440 (3109 - 3175)	1615 - 1640 (3560 - 3616)	1715 - 1725 (3781 - 3803)	1415 - 1435 (3120 - 3164)	1720 - 1735 (3792 - 3825)	1370 - 1405 (3020 - 3097)
	2800 (6173)	3200 (7055)	3150 (6945)	2750 (6063)	3150 (6945)	2800 (6173)
	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)
	6.0	9.8	—	—	—	6.0
30	155 (96)	155 (96)	155 (96)	155 (96)	155 (96)	135 (84)
	—	—	—	—	—	—
	38 (24)	38 (24)	38 (24)	38 (24)	38 (24)	32 (20)
	70 (43)	70 (43)	70 (43)	70 (43)	70 (43)	59 (37)
	114 (71)	114 (71)	114 (71)	114 (71)	114 (71)	96 (60)
35	163 (101)	163 (101)	163 (101)	163 (101)	163 (101)	138 (86)
	5.0 (16.4)	6.2 (20.3)	6.2 (20.3)	5.3 (17.4)	6.2 (20.3)	5.0 (16.4)
	5.7 (18.7)	6.9 (22.6)	6.9 (22.6)	5.9 (19.4)	6.9 (22.6)	5.7 (18.7)
	2TR-FE	2TR-FE	2TR-FE	2TR-FE	2TR-FE	2KD-FTV
	16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i	16-valve, DOHC
40	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	92.0 × 93.8 (3.62 × 3.69)
	2694 (164.4)	2694 (164.4)	2694 (164.4)	2694 (164.4)	2694 (164.4)	2494 (152.2)
	9.6 : 1	9.6 : 1	9.6 : 1	9.6 : 1	9.6 : 1	18.5 : 1
	EFI	EFI	EFI	EFI	EFI	Common-rail Type
	91 or higher	91 or higher	91 or higher	91 or higher	91 or higher	48 or higher
45	111/4800	111/4800	111/4800	111/4800	111/4800	75/3600
	241/3800	241/3800	241/3800	241/3800	241/3800	260/1600 - 2400
	12 - 48, 12 - 55*1	12 - 48, 12 - 55*1	12 - 48 × 2	12 - 48, 12 - 55*1	12 - 48, 12 - 55*1	12 - 55, 12 - 55 × 2*1
	1560	1560	1560	1560	1560	1200, 1560*1
	1.6	1.6	1.4	1.6	1.6	2.0
50	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm
	R351	R351	R351	R351	R351	R351
	4.313	4.313	4.313	4.313	4.313	4.313
	2.330	2.330	2.330	2.330	2.330	2.330
	1.436	1.436	1.436	1.436	1.436	1.436
55	1.000	1.000	1.000	1.000	1.000	1.000
	0.838	0.838	0.838	0.838	0.838	0.838
	4.220	4.220	4.220	4.220	4.220	4.220
	4.300	4.300	4.300	4.300	4.300	4.100
	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)
60	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum
	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
	Single with BA 10”	Single with BA 10”	Single with BA 10”	Single with BA 10”	Single with BA 10”	Single with BA 10”
	LSP and BV	LSP and BV	LSP and BV	LSP and BV	LSP and BV	LSP and BV
65	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid
	Standard	Standard	Standard	Standard	Standard	Standard
	—	—	—	—	—	—
	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
70	20.84	20.84	20.84	20.84	20.84	20.84
	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

Item \ Area				South Africa			
Body Type				5-door Van (Super Long)	4-door Commuter (Standard)	4-door Commuter (Super Long)	
Vehicle Grade				DX	GL	DX	GL
Model Code				KDH220R-MBMDYN	KDH212R-JDMNYN	KDH222R-LEMDYN	KDH222R-LEMNYN
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	5380 (211.8)	4840 (190.6)	5380 (211.8)	5380 (211.8)
		Width	mm (in.)	1880 (74.0)	1880 (74.0)	1880 (74.0)	1880 (74.0)
		Height	mm (in.)	2285 (90.0)	2105 (82.9)	2285 (90.0)	2285 (90.0)
	Wheel Base		mm (in.)	3110 (122.4)	2570 (101.2)	3110 (122.4)	3110 (122.4)
	Tread	Front	mm (in.)	1655 (65.2)	1655 (65.2)	1655 (65.2)	1655 (65.2)
		Rear	mm (in.)	1650 (65.0)	1650 (65.0)	1650 (65.0)	1650 (65.0)
	Room	Length	mm (in.)	910 (35.8)	3525 (138.8)	—	4250 (167.3)
		Width	mm (in.)	1730 (68.1)	1695 (66.7)	—	1695 (66.7)
		Height	mm (in.)	1565 (61.6)	1390 (54.7)	—	1565 (61.6)
	Cargo Space	Length	mm (in.)	3470 (136.6)	—	—	—
		Width	mm (in.)	1730 (68.1)	—	—	—
		Height	mm (in.)	1635 (64.4)	—	—	—
	Overhang	Front	mm (in.)	1190 (46.9)	1190 (46.9)	1190 (46.9)	1190 (46.9)
		Rear	mm (in.)	1080 (42.5)	1080 (42.5)	1080 (42.5)	1080 (42.5)
	Min. Running Ground Clearance		mm (in.)	195 (7.7)	185 (7.3)	185 (7.3)	185 (7.3)
	Angle of Approach		degrees	17.5	16.6	—	17.0
	Angle of Departure		degrees	19.5	19.7	—	19.2
	Curb Weight	Front	kg (lb)	1150 - 1200 (2535 - 2646)	1130 - 1175 (2491 - 2590)	1175 - 1220 (2590 - 2690)	1200 - 1245 (2646 - 2745)
		Rear	kg (lb)	765 - 795 (1687 - 1753)	820 - 830 (1808 - 1830)	905 - 915 (1995 - 2017)	930 - 940 (2050 - 2072)
		Total	kg (lb)	1915 - 1995 (4222 - 4398)	1950 - 2005 (4299 - 4420)	2080 - 2135 (4586 - 4707)	2130 - 2185 (4696 - 4817)
	Gross Vehicle Weight	Front	kg (lb)	1610 - 1640 (3549 - 3616)	1375 - 1410 (3031 - 3109)	1460 - 1495 (3219 - 3296)	1475 - 1505 (3252 - 3318)
		Rear	kg (lb)	1560 - 1590 (3439 - 3505)	1390 - 1425 (3064 - 3142)	1705 - 1740 (3759 - 3836)	1695 - 1725 (3737 - 3803)
		Total	kg (lb)	3200 (7055)	2800 (6173)	3200 (7055)	3200 (7055)
	Fuel Tank Capacity		ℓ (Imp.gal.)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)
	Luggage Compartment Capacity		m^3 (cu.ft.)	9.8	—	—	—
Performance	Max. Speed		km/h (mph)	135 (84)	135 (84)	—	135 (84)
	Max. Cruising Speed		km/h (mph)	—	—	—	—
	Max. Permissible Speed	1st Gear	km/h (mph)	32 (20)	32 (20)	—	32 (20)
		2nd Gear	km/h (mph)	59 (37)	59 (37)	—	59 (37)
		3rd Gear	km/h (mph)	96 (60)	96 (60)	—	96 (60)
		4th Gear	km/h (mph)	138 (86)	138 (86)	—	138 (86)
	Min. Turning Radius	Tire	m (ft.)	6.2 (20.3)	5.3 (17.4)	—	6.2 (20.3)
		Body	m (ft.)	6.9 (22.6)	5.9 (19.4)	—	6.9 (22.6)
Engine	Engine Type			2KD-FTV	2KD-FTV	2KD-FTV	2KD-FTV
	Valve Mechanism			16-valve, DOHC	16-valve, DOHC	16-valve, DOHC	16-valve, DOHC
	Bore × Stroke		mm (in.)	92.0 × 93.8 (3.62 × 3.69)	92.0 × 93.8 (3.62 × 3.69)	92.0 × 93.8 (3.62 × 3.69)	92.0 × 93.8 (3.62 × 3.69)
	Displacement		cm^3 (cu.in.)	2494 (152.2)	2494 (152.2)	2494 (152.2)	2494 (152.2)
	Compression Ratio			18.5 : 1	18.5 : 1	18.5 : 1	18.5 : 1
	Fuel System			Common-rail Type	Common-rail Type	Common-rail Type	Common-rail Type
	Research Octane No. or Cetane No. (Diesel)			48 or higher	48 or higher	48 or higher	48 or higher
	Max. Output (EEC)		kW/rpm	75/3600	75/3600	75/3600	75/3600
	Max. Torque (EEC)		N·m/rpm	260/1600 - 2400	260/1600 - 2400	260/1600 - 2400	260/1600 - 2400
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp.hr.	12 - 55, 12 - 55 × 2*1	12 - 55, 12 - 55 × 2*1	12 - 55, 12 - 55 × 2*1	12 - 55, 12 - 55 × 2*1
	Alternator Output		Watts	1200, 1560*1	1560	1200	1560
	Starter Output		kW	2.0	2.0	2.0	2.0
Chassis	Clutch Type			Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm
	Transmission Type			R351	R351	R351	R351
	Gear Ratio	In First		4.313	4.313	4.313	4.313
		In Second		2.330	2.330	2.330	2.330
		In Third		1.436	1.436	1.436	1.436
		In Fourth		1.000	1.000	1.000	1.000
		In Fifth		0.838	0.838	0.838	0.838
		Reverse		4.220	4.220	4.220	4.220
	Differential Gear Ratio			4.100	4.100	4.100	4.100
	Differential Gear Size		mm (in.)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear		Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum
	Parking Brake Type			Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
	Brake Booster Type and Size		in.	Single with BA 10"	Single with BA 10"	Single with BA 10"	Single with BA 10"
	Proportioning Valve Type			LSP and BV	LSP and BV	LSP and BV	LSP and BV
	Suspension Type	Front		Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
		Rear		Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid
	Stabilizer Bar	Front		Standard	Standard	Standard	Standard
		Rear		—	—	—	—
	Steering Gear Type			Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
	Steering Gear Ratio (Overall)			20.84	20.84	20.84	20.84
	Power Steering Type			Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

*1: Option
*2: With ABS

	Malaysia			Vietnam		
	4-door Commuter (Standard)	4-door Van (Standard)	4-door Commuter (Standard)			
	DX				GL	DX
	TRH203R-EDMDKE	KDH200R-RBMDYE	KDH202R-EDMDYE	TRH213L-JEMDKU	TRH213L-JDMNKU	KDH212L-JEMDYU
	4695 (184.8)	4695 (184.8)	4695 (184.8)	4840 (190.6)	4840 (190.6)	4840 (190.6)
	1695 (66.7)	1695 (66.7)	1695 (66.7)	1880 (74.0)	1880 (74.0)	1880 (74.0)
	2240 (88.2)	1980 (78.0)	2240 (88.2)	2105 (82.9)	2105 (82.9)	2105 (82.9)
	2570 (101.2)	2570 (101.2)	2570 (101.2)	2570 (101.2)	2570 (101.2)	2570 (101.2)
	1470 (57.9)	1470 (57.9)	1470 (57.9)	1655 (65.2)	1655 (65.2)	1655 (65.2)
	1465 (57.7)	1465 (57.7)	1465 (57.7)	1650 (65.0)	1650 (65.0)	1650 (65.0)
	3470 (136.2)	910 (35.8)	3470 (136.2)	3525 (138.8)	3525 (138.8)	3525 (138.8)
	1545 (60.8)	1545 (60.8)	1545 (60.8)	1695 (66.7)	1695 (66.7)	1695 (66.7)
	1335 (52.6)	1320 (52.0)	1335 (52.6)	1390 (54.7)	1390 (54.7)	1390 (54.7)
	—	2930 (115.4)	—	—	—	—
	—	1545 (60.8)	—	—	—	—
	—	1335 (52.6)	—	—	—	—
	1050 (41.3)	1050 (41.3)	1050 (41.3)	1190 (46.9)	1190 (46.9)	1190 (46.9)
	1075 (42.3)	1075 (42.3)	1075 (42.3)	1080 (42.5)	1080 (42.5)	1080 (42.5)
	185 (7.3)	195 (7.7)	195 (7.7)	185 (7.3)	185 (7.3)	185 (7.3)
	18.5	18.5	18.5	16.6	16.6	16.6
	19.5	19.5	19.5	19.7	19.7	19.7
	1000 - 1040 (2205 - 2293)	1020 - 1055 (2249 - 2326)	1050 - 1090 (2315 - 2403)	1050 - 1090 (2315 - 2403)	1070 - 1110 (2359 - 2447)	1105 - 1145 (2436 - 2524)
	750 - 770 (1653 - 1698)	690 - 710 (1521 - 1565)	755 - 775 (1664 - 1709)	805 - 825 (1775 - 1819)	805 - 825 (1775 - 1819)	810 - 830 (1786 - 1830)
	1750 - 1810 (3858 - 3990)	1710 - 1765 (3770 - 3891)	1805 - 1865 (3979 - 4112)	1855 - 1915 (4090 - 4222)	1875 - 1935 (4134 - 4266)	1915 - 1975 (4222 - 4354)
	1350 - 1375 (2676 - 3031)	1380 - 1405 (3042 - 3097)	1395 - 1425 (3075 - 3142)	1380 - 1405 (3042 - 3097)	1320 - 1350 (2910 - 2976)	1430 - 1460 (3153 - 3219)
	1375 - 1400 (3031 - 3086)	1395 - 1420 (3075 - 3131)	1375 - 1405 (3031 - 3097)	1695 - 1720 (3737 - 3792)	1400 - 1430 (3086 - 3153)	1690 - 1720 (3726 - 3792)
	2750 (6062)	2800 (6173)	2800 (6173)	3100 (6834)	2750 (6063)	3150 (6945)
	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)
	—	6.0	—	—	—	—
	170 (105)	145 (90)	145 (90)	155 (96)	145 (90)	135 (84)
	—	—	—	—	—	—
	38 (24)	32 (20)	32 (20)	38 (24)	38 (24)	32 (20)
	70 (43)	59 (37)	59 (37)	70 (43)	70 (43)	59 (37)
	114 (71)	96 (60)	96 (60)	114 (71)	114 (71)	96 (60)
	163 (101)	138 (86)	138 (86)	163 (101)	163 (101)	138 (86)
	5.0 (16.4)	5.0 (16.4)	5.0 (16.4)	5.3 (17.4)	5.3 (17.4)	5.3 (17.4)
	5.7 (18.7)	5.7 (18.7)	5.7 (18.7)	5.9 (19.4)	5.9 (19.4)	5.9 (19.4)
	2TR-FE	2KD-FTV	2KD-FTV	2TR-FE	2TR-FE	2KD-FTV
	16-valve, DOHC with VVT-i	16-valve, DOHC	16-valve, DOHC	16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i	16-valve, DOHC
	95.0 × 95.0 (3.74 × 3.74)	92.0 × 93.8 (3.62 × 3.69)	92.0 × 93.8 (3.62 × 3.69)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	92.0 × 93.8 (3.62 × 3.69)
	2694 (164.4)	2494 (152.2)	2494 (152.2)	2694 (164.4)	2694 (164.4)	2494 (152.2)
	9.6 : 1	18.5 : 1	18.5 : 1	9.6 : 1	9.6 : 1	18.5 : 1
	EFI	Common-rail Type	Common-rail Type	EFI	EFI	Common-rail Type
	91 or higher	48 or higher	48 or higher	91 or higher	91 or higher	48 or higher
	111/4800	75/3600	75/3600	111/4800	111/4800	75/3600
	241/3800	260/1600 - 2400	260/1600 - 2400	241/3800	241/3800	260/1600 - 2400
	12 - 55	12 - 55, 12 - 55 × 2*1	12 - 55	—	—	—
	1560	1200	1560	1560	1560	1560
	1.6	2.0	2.0	1.6	1.6	2.0
	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm
	R351	R351	R351	R351	R351	R351
	4.313	4.313	4.313	4.313	4.313	4.313
	2.330	2.330	2.330	2.330	2.330	2.330
	1.436	1.436	1.436	1.436	1.436	1.436
	1.000	1.000	1.000	1.000	1.000	1.000
	0.838	0.838	0.838	0.838	0.838	0.838
	4.220	4.220	4.220	4.220	4.220	4.220
	4.300	4.100	4.100	4.300	4.300	4.100
	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)
	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum
	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
	Single 10”	Single 10”	Single 10”	Single, Single with BA*2 10”	Single, Single with BA*2 10”	Single, Single with BA*2 10”
	LSP and BV	LSP and BV	LSP and BV	LSP and BV	LSP and BV	LSP and BV
	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid
	Standard	Standard	Standard	Standard	Standard	Standard
	—	—	—	—	—	—
	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
	20.84	20.84	20.84	20.84	20.84	20.84
	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

Item \ Area				Thailand			
Body Type				4-door Commuter (Super Long)	5-door Commuter (Standard)	4-door Van (Standard)	4-door Commuter (Standard)
Vehicle Grade				DX	GL	DX	GL
Model Code				TRH223R-LEMDKT	TRH213R-KDPNKT	KDH200R-RBMDYT	KDH202R-RDMNYT
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	5380 (211.8)	4840 (190.6)	4695 (184.8)	4695 (184.8)
		Width	mm (in.)	1880 (74.0)	1880 (74.0)	1695 (66.7)	1695 (66.7)
		Height	mm (in.)	2285 (90.0)	2105 (82.9)	1980 (78.0)	1980 (78.0)
	Wheel Base		mm (in.)	3110 (122.4)	2570 (101.2)	2570 (101.2)	2570 (101.2)
	Tread	Front	mm (in.)	1655 (65.2)	1655 (65.2)	1470 (57.9)	1470 (57.9)
		Rear	mm (in.)	1650 (65.0)	1650 (65.0)	1465 (57.7)	1465 (57.7)
	Room	Length	mm (in.)	4205 (165.6)	3525 (138.8)	910 (35.8)	3460 (136.2)
		Width	mm (in.)	1730 (68.1)	1695 (66.7)	1545 (60.8)	1545 (60.8)
		Height	mm (in.)	1565 (61.6)	1390 (54.7)	1320 (52.0)	1335 (52.6)
	Cargo Space	Length	mm (in.)	—	—	2930 (115.4)	—
		Width	mm (in.)	—	—	1545 (60.8)	—
		Height	mm (in.)	—	—	1335 (52.6)	—
	Overhang	Front	mm (in.)	1190 (46.9)	1190 (46.9)	1050 (41.3)	1050 (41.3)
		Rear	mm (in.)	1080 (42.5)	1080 (42.5)	1075 (42.3)	1075 (42.3)
	Min. Running Ground Clearance		mm (in.)	185 (7.3)	185 (7.3)	195 (7.7)	185 (7.3)
	Angle of Approach		degrees	17.0	16.6	18.5	18.5
	Angle of Departure		degrees	19.2	19.7	19.5	19.5
	Curb Weight	Front	kg (lb)	1115 - 1150 (2458 - 2535)	1095 - 1115 (2414 - 2458)	1020 - 1055 (2249 - 2326)	1060 - 1095 (2337 - 2414)
		Rear	kg (lb)	880 - 900 (1940 - 1984)	860 - 870 (1896 - 1918)	690 - 705 (1521 - 1554)	740 - 760 (1631 - 1676)
		Total	kg (lb)	1995 - 2050 (4398 - 1519)	1955 - 1985 (4310 - 4376)	1710 - 1760 (3770 - 3880)	1800 - 1855 (3968 - 4090)
	Gross Vehicle Weight	Front	kg (lb)	1520 - 1540 (3351 - 3395)	1270 - 1285 (2800 - 2833)	1380 - 1405 (3042 - 3097)	1335 - 1360 (2943 - 2998)
		Rear	kg (lb)	1760 - 1780 (3880 - 3924)	1565 - 1580 (3450 - 3483)	1395 - 1420 (3075 - 3131)	1340 - 1365 (2954 - 3009)
		Total	kg (lb)	3300 (7275)	2850 (6283)	2800 (6173)	2700 (5952)
	Fuel Tank Capacity		ℓ (Imp.gal.)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)
	Luggage Compartment Capacity		m^3 (cu.ft.)	—	—	6.0	—
Performance	Max. Speed		km/h (mph)	—	155 (96)	145 (90)	145 (90)
	Max. Cruising Speed		km/h (mph)	—	—	—	—
	Max. Permissible Speed	1st Gear	km/h (mph)	—	54 (33)	32 (20)	32 (20)
		2nd Gear	km/h (mph)	—	98 (61)	59 (37)	59 (37)
		3rd Gear	km/h (mph)	—	150 (93)	96 (60)	96 (60)
		4th Gear	km/h (mph)	—	—	138 (86)	138 (86)
	Min. Turning Radius	Tire	m (ft.)	6.2 (20.3)	5.3 (17.4)	5.0 (16.4)	5.0 (16.4)
		Body	m (ft.)	6.9 (22.6)	5.9 (19.4)	5.7 (18.7)	5.7 (18.7)
Engine	Engine Type			2TR-FE	2TR-FE	2KD-FTV	2KD-FTV
	Valve Mechanism			16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i	16-valve, DOHC	16-valve, DOHC
	Bore × Stroke		mm (in.)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	92.0 × 93.8 (3.62 × 3.69)	92.0 × 93.8 (3.62 × 3.69)
	Displacement		cm^3 (cu.in.)	2694 (164.4)	2694 (164.4)	2494 (152.2)	2494 (152.2)
	Compression Ratio			9.6 : 1	9.6 : 1	18.5 : 1	18.5 : 1
	Fuel System			EFI	EFI	Common-rail Type	Common-rail Type
	Research Octane No. or Cetane No. (Diesel)			91 or higher	91 or higher	48 or higher	48 or higher
	Max. Output (EEC)		kW/rpm	111/4800	111/4800	75/3600	75/3600
	Max. Torque (EEC)		N·m/rpm	241/3800	241/3800	260/1600 - 2400	260/1600 - 2400
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp.hr.	12 - 48	12 - 55	12 - 55	12 - 55
	Alternator Output		Watts	1560	1560	1200, 1560*2	1560
	Starter Output		kW	1.6	1.6	2.0	2.0
Chassis	Clutch Type			Dry, Single Plate, Diaphragm	—	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm
	Transmission Type			R351	A343E	R351	R351
	Gear Ratio	In First		4.313	2.804	4.313	4.313
		In Second		2.330	1.531	2.330	2.330
		In Third		1.436	1.000	1.436	1.436
		In Fourth		1.000	0.753	1.000	1.000
		In Fifth		0.838	—	0.838	0.838
		Reverse		4.220	2.393	4.220	4.220
	Differential Gear Ratio			4.300	4.556	4.100	4.100
	Differential Gear Size		mm (in.)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear		Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum
	Parking Brake Type			Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
	Brake Booster Type and Size		in.	Single, Single with BA*4 10”	Single with BA 10”	Single, Single with BA*4 10”	Single, Single with BA*4 10”
	Proportioning Valve Type			LSP and BV	LSP and BV	LSP and BV	LSP and BV
	Suspension Type	Front		Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
		Rear		Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid
	Stabilizer Bar	Front		Standard	Standard	Standard	Standard
		Rear		—	—	—	—
	Steering Gear Type			Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
	Steering Gear Ratio (Overall)			20.84	20.84	20.84	20.84
	Power Steering Type			Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

*1: Folded Seat
*2: Option
*3: Cold Area Specification Model
*4: With ABS

Thailand	Russia	General Countries			
4-door Commuter (Super Long)		5-door Van (Standard)			
DX	GL	DX			
KDH222R-LEMDYT	TRH223L-LEMNKX	TRH201R-SSMDK	TRH201R-SRMDK	TRH201R-SRPDK	TRH201L-SBMDK
5380 (211.8)	5380 (211.8)	4695 (184.8)	4695 (184.8)	4695 (184.8)	4695 (184.8)
1880 (74.0)	1880 (74.0)	1695 (66.7)	1695 (66.7)	1695 (66.7)	1695 (66.7)
2285 (90.0)	2285 (90.0)	1980 (78.0)	1980 (78.0)	1980 (78.0)	1980 (78.0)
3110 (122.4)	3110 (122.4)	2570 (101.2)	2570 (101.2)	2570 (101.2)	2570 (101.2)
1655 (65.2)	1655 (65.2)	1470 (57.9)	1470 (57.9)	1470 (57.9)	1470 (57.9)
1650 (65.0)	1650 (65.0)	1465 (57.7)	1465 (57.7)	1465 (57.7)	1465 (57.7)
4205 (165.6)	4250 (167.3)	1905 (75.0), 910 (35.8)*1	1905 (75.0), 910 (35.8)*1	1905 (75.0), 910 (35.8)*1	910 (35.8)
1730 (68.1)	1695 (66.7)	1545 (60.8)	1545 (60.8)	1545 (60.8)	1545 (60.8)
1565 (61.6)	1565 (61.6)	1320 (52.0)	1320 (52.0)	1320 (52.0)	1320 (52.0)
—	—	1960 (77.2), 2930 (115.4)*1	1960 (77.2), 2930 (115.4)*1	1960 (77.2), 2930 (115.4)*1	2930 (115.4)
—	—	1545 (60.8)	1545 (60.8)	1545 (60.8)	1545 (60.8)
—	—	1335 (52.6)	1335 (52.6)	1335 (52.6)	1335 (52.6)
1190 (46.9)	1190 (46.9)	1050 (41.3)	1050 (41.3)	1050 (41.3)	1050 (41.3)
1080 (42.5)	1080 (42.5)	1075 (42.3)	1075 (42.3)	1075 (42.3)	1075 (42.3)
185 (7.3)	185 (7.3)	195 (7.7)	195 (7.7)	195 (7.7)	195 (7.7)
17.0	17.0	18.5	18.5	18.5	18.5
19.2	19.2	19.5	19.5	19.5	19.5
1170 - 1205 (2579 - 2657)	1115 - 1140 (2458 - 2513)	1020 - 1045 (2249 - 2304)	1005 - 1040 (2216 - 2293)	1010 - 1045 (2227 - 2304)	1000 - 1040 (2205 - 2293)
885 - 905 (1951 - 1995)	895 - 910 (1973 - 2006)	695 - 705 (1532 - 1554)	695 - 715 (1532 - 1576)	695 - 715 (1532 - 1576)	665 - 685 (1466 - 1510)
2055 - 2110 (4531 - 4652)	2010 - 2050 (4431 - 4519)	1715 - 1750 (3781 - 3858)	1700 - 1755 (3748 - 3869)	1705 - 1760 (3759 - 2880)	1665 - 1725 (3671 - 3803)
1560 - 1580 (3439 - 3483)	1405 - 1420 (3097 - 3131)	1340 - 1365 (2954 - 3009), 1350 - 1370 (2976 - 3020)*1	1330 - 1360 (2932 - 2998), 1340 - 1365 (2954 - 3009)*1	1335 - 1365 (2943 - 3009), 1345 - 1370 (2965 - 3020)*1	1370 - 1400 (3020 - 3086)
1720 - 1740 (3792 - 3836)	1630 - 1645 (3594 - 3627)	1435 - 1460 (3164 - 3219), 1430 - 1450 (3153 - 3197)*1	1440 - 1470 (3175 - 3241), 1435 - 1460 (3164 - 3219)*1	1435 - 1465 (3164 - 3230), 1430 - 1455 (3153 - 3208)*1	1400 - 1430 (3086 - 3153)
3300 (7275)	3050 (6724)	2800 (6173)	2800 (6173)	2800 (6173)	2800 (6173)
70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)
—	—	6.0	6.0	6.0	6.0
140 (87)	155 (96)	170 (105)	170 (105)	170 (105)	170 (105)
—	—	—	—	—	—
32 (20)	38 (24)	38 (24)	38 (24)	54 (33)	38 (24)
59 (37)	70 (43)	70 (43)	70 (43)	98 (61)	70 (43)
96 (60)	114 (71)	114 (71)	114 (71)	150 (93)	114 (71)
138 (86)	163 (101)	163 (101)	163 (101)	—	163 (101)
6.2 (20.3)	6.2 (20.3)	5.0 (16.4)	5.0 (16.4)	5.0 (16.4)	5.0 (16.4)
6.9 (22.6)	6.9 (22.6)	5.7 (18.7)	5.7 (18.7)	5.7 (18.7)	5.7 (18.7)
2KD-FTV	2TR-FE	2TR-FE	2TR-FE	2TR-FE	2TR-FE
16-valve, DOHC	16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i
92.0 × 93.8 (3.62 × 3.69)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)
2494 (152.2)	2694 (164.4)	2694 (164.4)	2694 (164.4)	2694 (164.4)	2694 (164.4)
18.5 : 1	9.6 : 1	9.6 : 1	9.6 : 1	9.6 : 1	9.6 : 1
Common-rail Type	EFI	EFI	EFI	EFI	EFI
48 or higher	91 or higher	91 or higher	91 or higher	91 or higher	91 or higher
80/3600	111/4800	111/4800	111/4800	111/4800	111/4800
260/1600 - 2600	241/3800	241/3800	241/3800	241/3800	241/3800
12 - 55	12 - 55	12 - 48	12 - 48	12 - 48	12 - 48, 12 - 55*3
1200, 1560*2	1560	1560	1560	1560	1560
2.0	1.6	1.6	1.6	1.6	1.6
Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	—	Dry, Single Plate, Diaphragm
R351	R351	R351	R351	A343E	R351
4.313	4.313	4.313	4.313	2.804	4.313
2.330	2.330	2.330	2.330	1.531	2.330
1.436	1.436	1.436	1.436	1.000	1.436
1.000	1.000	1.000	1.000	0.753	1.000
0.838	0.838	0.838	0.838	—	0.838
4.220	4.220	4.220	4.220	2.393	4.220
4.100	4.300	4.300	4.300	4.556	4.300
205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)
Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum
Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
Single with BA 10”	Single with BA 10”	Single, Single with BA*4 10”	Single, Single with BA*4 10”	Single, Single with BA*4 10”	Single, Single with BA*4 10”
LSP and BV	LSP and BV	LSP and BV	LSP and BV	LSP and BV	LSP and BV
Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid
Standard	Standard	Standard	Standard	Standard	Standard
—	—	—	—	—	—
Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
20.84	20.84	20.84	20.84	20.84	20.84
Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

Item \ Area				General Countries			
Body Type				4-door Van (Standard)	5-door Van (Super Long)	4-door Van (Super Long)	4-door Van (Standard)
Vehicle Grade				DX			
Model Code				TRH201L-EFMDK	TRH221L-MBMDK	TRH221L-LFMDK	KDH200R-RBMDY
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	4695 (184.8)	5380 (211.8)	5380 (211.8)	4695 (184.8)
		Width	mm (in.)	1695 (66.7)	1880 (74.0)	1880 (74.0)	1695 (66.7)
		Height	mm (in.)	2240 (88.2)	2285 (90.0)	2285 (90.0)	1980 (78.0)
	Wheel Base		mm (in.)	2570 (101.2)	3110 (122.4)	3110 (122.4)	2570 (101.2)
	Tread	Front	mm (in.)	1470 (57.9)	1655 (65.2)	1655 (65.2)	1470 (57.9)
		Rear	mm (in.)	1465 (57.7)	1650 (65.0)	1650 (65.0)	1465 (57.7)
	Room	Length	mm (in.)	910 (35.8)	910 (35.8)	910 (35.8)	910 (35.8)
		Width	mm (in.)	1545 (60.8)	1730 (68.1)	1730 (68.1)	1545 (60.8)
		Height	mm (in.)	1520 (59.8)	1565 (61.6)	1565 (61.6)	1320 (52.0)
	Cargo Space	Length	mm (in.)	2930 (115.4)	3470 (136.6)	3470 (136.6)	2930 (115.4)
		Width	mm (in.)	1545 (60.8)	1730 (68.1)	1730 (68.1)	1545 (60.8)
		Height	mm (in.)	1590 (62.6)	1635 (64.4)	1635 (64.4)	1335 (52.6)
	Overhang	Front	mm (in.)	1050 (41.3)	1190 (46.9)	1190 (46.9)	1050 (41.3)
		Rear	mm (in.)	1075 (42.3)	1080 (42.5)	1080 (42.5)	1075 (42.3)
	Min. Running Ground Clearance		mm (in.)	195 (7.7)	195 (7.7)	195 (7.7)	195 (7.7)
	Angle of Approach		degrees	18.5	17.5	17.5	18.5
	Angle of Departure		degrees	19.5	19.5	19.5	19.5
	Curb Weight	Front	kg (lb)	1000 - 1040 (2205 - 2293)	1090 - 1130 (2403 - 2491)	1080 - 1120 (2381 - 2469)	1020 - 1080 (2249 - 2381)
		Rear	kg (lb)	680 - 700 (1499 - 1543)	775 - 795 (1709 - 1753)	760 - 780 (1676 - 1720)	690 - 710 (1521 - 1565)
		Total	kg (lb)	1680 - 1740 (3704 - 3836)	1865 - 1925 (4112 - 4244)	1840 - 1900 (4057 - 4189)	1710 - 1790 (3770 - 3946)
	Gross Vehicle Weight	Front	kg (lb)	1365 - 1395 (3009 - 3075)	1560 - 1585 (3439 - 3494)	1560 - 1585 (3439 - 3494)	1380 - 1425 (3042 - 3142)
		Rear	kg (lb)	1405 - 1435 (3097 - 3164)	1615 - 1640 (3560 - 3616)	1615 - 1640 (3560 - 3616)	1375 - 1420 (3031 - 3131)
		Total	kg (lb)	2800 (6173)	3200 (7055)	3200 (7055)	2800 (6173)
	Fuel Tank Capacity		ℓ (Imp.gal.)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)
	Luggage Compartment Capacity		m^3 (cu.ft.)	—	9.8	9.8	6.0
Performance	Max. Speed		km/h (mph)	170 (105)	155 (96)	155 (96)	145 (90)
	Max. Cruising Speed		km/h (mph)	—	—	—	—
	Max. Permissible Speed	1st Gear	km/h (mph)	38 (24)	38 (24)	38 (24)	32 (20)
		2nd Gear	km/h (mph)	70 (43)	70 (43)	70 (43)	59 (37)
		3rd Gear	km/h (mph)	114 (71)	114 (71)	114 (71)	96 (60)
		4th Gear	km/h (mph)	163 (101)	163 (101)	163 (101)	138 (86)
	Min. Turning Radius	Tire	m (ft.)	5.0 (16.4)	6.2 (20.3)	6.2 (20.3)	5.0 (16.4)
		Body	m (ft.)	5.7 (18.7)	6.9 (22.6)	6.9 (22.6)	5.7 (18.7)
Engine	Engine Type			2TR-FE	2TR-FE	2TR-FE	2KD-FTV
	Valve Mechanism			16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i	16-valve, DOHC
	Bore × Stroke		mm (in.)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	92.0 × 93.8 (3.62 × 3.69)
	Displacement		cm^3 (cu.in.)	2694 (164.4)	2694 (164.4)	2694 (164.4)	2494 (152.2)
	Compression Ratio			9.6 : 1	9.6 : 1	9.6 : 1	18.5 : 1
	Fuel System			EFI	EFI	EFI	Common-rail Type
	Research Octane No. or Cetane No. (Diesel)			91 or higher	91 or higher	91 or higher	48 or higher
	Max. Output (EEC)		kW/rpm	111/4800	111/4800	111/4800	75/3600
	Max. Torque (EEC)		N·m/rpm	241/3800	241/3800	241/3800	260/1600 - 2400
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp.hr.	12 - 48	12 - 48, 12 - 55*1	12 - 48	12 - 55, 12 - 55 × 2*1
	Alternator Output		Watts	1560	1560	1560	1200, 1560*3
	Starter Output		kW	1.6	1.6	1.6	2.0, 2.7*1
Chassis	Clutch Type			Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm
	Transmission Type			R351	R351	R351	R351
	Gear Ratio	In First		4.313	4.313	4.313	4.313
		In Second		2.330	2.330	2.330	2.330
		In Third		1.436	1.436	1.436	1.436
		In Fourth		1.000	1.000	1.000	1.000
		In Fifth		0.838	0.838	0.838	0.838
		Reverse		4.220	4.220	4.220	4.220
	Differential Gear Ratio			4.300	4.300	4.300	4.100
	Differential Gear Size		mm (in.)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear		Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum
	Parking Brake Type			Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
	Brake Booster Type and Size		in.	Single, Single with BA*2 10"	Single, Single with BA*2 10"	Single, Single with BA*2 10"	Single, Single with BA*2 10"
	Proportioning Valve Type			LSP and BV	LSP and BV	LSP and BV	LSP and BV
	Suspension Type	Front		Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
		Rear		Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid
	Stabilizer Bar	Front		Standard	Standard	Standard	Standard
		Rear		—	—	—	—
	Steering Gear Type			Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
	Steering Gear Ratio (Overall)			20.84	20.84	20.84	20.84
	Power Steering Type			Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

*1: Cold Area Specification Model
*2: With ABS
*3: Option

General Countries					
4-door Van (Standard)	5-door Van (Standard)			4-door Van (Standard)	5-door Van (Standard)
DX					
KDH200L-RBMDY	KDH200R-SBMDY	KDH200L-SBMDY	KDH201L-SBMDY	KDH201R-RBPDY	KDH201R-SBMDY
4695 (184.8)	4695 (184.8)	4695 (184.8)	4695 (184.8)	4695 (184.8)	4695 (184.8)
1695 (66.7)	1695 (66.7)	1695 (66.7)	1695 (66.7)	1695 (66.7)	1695 (66.7)
1980 (78.0)	1980 (78.0)	1980 (78.0)	1980 (78.0)	1980 (78.0)	1980 (78.0)
2570 (101.2)	2570 (101.2)	2570 (101.2)	2570 (101.2)	2570 (101.2)	2570 (101.2)
1470 (57.9)	1470 (57.9)	1470 (57.9)	1470 (57.9)	1470 (57.9)	1470 (57.9)
1465 (57.7)	1465 (57.7)	1465 (57.7)	1465 (57.7)	1465 (57.7)	1465 (57.7)
910 (35.8)	910 (35.8)	910 (35.8)	—	910 (35.8)	910 (35.8)
1545 (60.8)	1545 (60.8)	1545 (60.8)	—	1545 (60.8)	1545 (60.8)
1320 (52.0)	1320 (52.0)	1320 (52.0)	—	1320 (52.0)	1320 (52.0)
2930 (115.4)	2930 (115.4)	2930 (115.4)	—	2930 (115.4)	2930 (115.4)
1545 (60.8)	1545 (60.8)	1545 (60.8)	—	1545 (60.8)	1545 (60.8)
1335 (52.6)	1335 (52.6)	1335 (52.6)	—	1335 (52.6)	1335 (52.6)
1050 (41.3)	1050 (41.3)	1050 (41.3)	1050 (41.3)	1050 (41.3)	1050 (41.3)
1075 (42.3)	1075 (42.3)	1075 (42.3)	1075 (42.3)	1075 (42.3)	1075 (42.3)
195 (7.7)	195 (7.7)	195 (7.7)	195 (7.7)	195 (7.7)	195 (7.7)
18.5	18.5	18.5	—	18.5	18.5
19.5	19.5	19.5	—	19.5	19.5
1025 - 1085 (2260 - 2392)	1035 - 1095 (2282 - 2414)	1040 - 1100 (2293 - 2425)	1075 - 1110 (2370 - 2447)	1060 - 1095 (2337 - 2414)	1065 - 1100 (2348 - 2425)
690 - 710 (1521 - 1565)	710 - 730 (1565 - 1609)	710 - 730 (1565 - 1609)	720 - 740 (1587 - 1631)	700 - 715 (1543 - 1576)	715 - 730 (1576 - 1609)
1715 - 1795 (3781 - 3957)	1745 - 1825 (3847 - 4023)	1750 - 1830 (3858 - 4034)	1795 - 1850 (3957 - 4079)	1760 - 1810 (3880 - 3990)	1780 - 1830 (3924 - 4034)
1385 - 1430 (3053 - 3153)	1390 - 1435 (3064 - 3164)	1395 - 1440 (3075 - 3175)	1420 - 1445 (3131 - 3186)	1410 - 1440 (3109 - 3175)	1415 - 1440 (3120 - 3175)
1370 - 1415 (3020 - 3120)	1365 - 1410 (3009 - 3109)	1360 - 1405 (2998 - 3097)	1355 - 1380 (2987 - 3042)	1360 - 1390 (2998 - 3064)	1360 - 1385 (2998 - 3053)
2800 (6173)	2800 (6173)	2800 (6173)	2800 (6173)	2800 (6173)	2800 (6173)
70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)
6.0	6.0	6.0	—	6.0	6.0
145 (90)	145 (90)	145 (90)	—	—	—
—	—	—	—	—	—
32 (20)	32 (20)	32 (20)	—	—	—
59 (37)	59 (37)	59 (37)	—	—	—
96 (60)	96 (60)	96 (60)	—	—	—
138 (86)	138 (86)	138 (86)	—	—	—
5.0 (16.4)	5.0 (16.4)	5.0 (16.4)	—	5.0 (16.4)	5.0 (16.4)
5.7 (18.7)	5.7 (18.7)	5.7 (18.7)	—	5.7 (18.7)	5.7 (18.7)
2KD-FTV	2KD-FTV	2KD-FTV	1KD-FTV	1KD-FTV	1KD-FTV
16-valve, DOHC	16-valve, DOHC	16-valve, DOHC	16-valve, DOHC	16-valve, DOHC	16-valve, DOHC
92.0 × 93.8 (3.62 × 3.69)	92.0 × 93.8 (3.62 × 3.69)	92.0 × 93.8 (3.62 × 3.69)	96.0 × 103.0 (3.78 × 4.06)	96.0 × 103.0 (3.78 × 4.06)	96.0 × 103.0 (3.78 × 4.06)
2494 (152.2)	2494 (152.2)	2494 (152.2)	2982 (182.0)	2982 (182.0)	2982 (182.0)
18.5 : 1	18.5 : 1	18.5 : 1	16.0 : 1	16.0 : 1	16.0 : 1
Common-rail Type	Common-rail Type	Common-rail Type	Common-rail Type	Common-rail Type	Common-rail Type
48 or higher	48 or higher	48 or higher	48 or higher	48 or higher	48 or higher
75/3600	75/3600	75/3600	100/3400	100/3400	100/3400
260/1600 - 2400	260/1600 - 2400	260/1600 - 2400	300/1200 - 2400	300/1200 - 2400	300/1200 - 2400
12 - 55, 12 - 55 × 2*1	12 - 55, 12 - 55 × 2*1	12 - 55, 12 - 55 × 2*1	12 - 60, 12 - 55 × 2*1	12 - 60	12 - 60
1200	1200, 1560*3	1200, 1560*3	1560	1560	1560
2.0, 2.7*1	2.0, 2.7*1	2.0, 2.7*1	2.0, 2.7*1	2.7	2.2
Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	—	Dry, Single Plate, Diaphragm
R351	R351	R351	R351	A340E	R351
4.313	4.313	4.313	4.313	2.804	4.313
2.330	2.330	2.330	2.330	1.531	2.330
1.436	1.436	1.436	1.436	1.000	1.436
1.000	1.000	1.000	1.000	0.705	1.000
0.838	0.838	0.838	0.838	—	0.838
4.220	4.220	4.220	4.220	2.393	4.220
4.100	4.100	4.100	3.727	4.100	3.727
205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)
Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum
Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
Single, Single with BA*2 10”	Single, Single with BA*2 10”	Single, Single with BA*2 10”	Single, Single with BA*2 10”	Single, Single with BA*2 10”	Single, Single with BA*2 10”
LSP and BV	LSP and BV	LSP and BV	LSP and BV	LSP and BV	LSP and BV
Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid
Standard	Standard	Standard	Standard	Standard	Standard
—	—	—	—	—	—
Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
20.84	20.84	20.84	20.84	20.84	20.84
Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

Item \ Area				General Countries			
Body Type				5-door Van (Standard)			
Vehicle Grade				DX		GL	DX
Model Code				KDH201R-SSMDY	KDH201R-SSPDY	KDH201R-SSPNY	KDH201R-SRMDY
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	4695 (184.8)	4695 (184.8)	4695 (184.8)	4695 (184.8)
		Width	mm (in.)	1695 (66.7)	1695 (66.7)	1695 (66.7)	1695 (66.7)
		Height	mm (in.)	1980 (78.0)	1980 (78.0)	1980 (78.0)	1980 (78.0)
	Wheel Base		mm (in.)	2570 (101.2)	2570 (101.2)	2570 (101.2)	2570 (101.2)
	Tread	Front	mm (in.)	1470 (57.9)	1470 (57.9)	1470 (57.9)	1470 (57.9)
		Rear	mm (in.)	1465 (57.7)	1465 (57.7)	1465 (57.7)	1465 (57.7)
	Room	Length	mm (in.)	1905 (75.0), 910 (35.8)*1	1905 (75.0), 910 (35.8)*1	1905 (75.0), 910 (35.8)*1	1905 (75.0), 910 (35.8)*1
		Width	mm (in.)	1545 (60.8)	1545 (60.8)	1545 (60.8)	1545 (60.8)
		Height	mm (in.)	1320 (52.0)	1320 (52.0)	1320 (52.0)	1320 (52.0)
	Cargo Space	Length	mm (in.)	1960 (77.2), 2930 (115.4)*1	1960 (77.2), 2930 (115.4)*1	1960 (77.2), 2930 (115.4)*1	1960 (77.2), 2930 (115.4)*1
		Width	mm (in.)	1545 (60.8)	1545 (60.8)	1545 (60.8)	1545 (60.8)
		Height	mm (in.)	1335 (52.6)	1335 (52.6)	1335 (52.6)	1335 (52.6)
	Overhang	Front	mm (in.)	1050 (41.3)	1050 (41.3)	1050 (41.3)	1050 (41.3)
		Rear	mm (in.)	1075 (42.3)	1075 (42.3)	1075 (42.3)	1075 (42.3)
	Min. Running Ground Clearance		mm (in.)	195 (7.7)	195 (7.7)	195 (7.7)	195 (7.7)
	Angle of Approach		degrees	18.5	18.5	18.5	18.5
	Angle of Departure		degrees	19.5	19.5	19.5	19.5
	Curb Weight	Front	kg (lb)	1105 - 1130 (2436 - 2491)	1110 - 1135 (2447 - 2502)	1120 - 1145 (2469 - 2524)	1090 - 1140 (2403 - 2513)
		Rear	kg (lb)	705 - 715 (1554 - 1576)	710 - 720 (1565 - 1587)	715 - 725 (1576 - 1598)	705 - 730 (1554 - 1609)
		Total	kg (lb)	1810 - 1845 (3990 - 4068)	1820 - 1855 (4012 - 4090)	1835 - 1870 (4045 - 4123)	1795 - 1870 (3957 - 4123)
	Gross Vehicle Weight	Front	kg (lb)	1425 - 1450 (3142 - 3197), 1425 - 1440 (3142 - 3175)*1	1430 - 1455 (3153 - 3208), 1425 - 1445 (3142 - 3186)*1	1440 - 1465 (3175 - 3230), 1410 - 1435 (3109 - 3164)*1	1410 - 1460 (3109 - 3219), 1410 - 1450 (3109 - 3197)*1
		Rear	kg (lb)	1350 - 1375 (2976 - 3031), 1360 - 1375 (2998 - 3031)*1	1345 - 1370 (2965 - 3020), 1355 - 1375 (2987 - 3031)*1	1335 - 1360 (2943 - 2998), 1365 - 1390 (3009 - 3064)*1	1340 - 1390 (2954 - 3064), 1350 - 1390 (2976 - 3064)*1
		Total	kg (lb)	2800 (6173)	2800 (6173)	2800 (6173)	2800 (6173)
	Fuel Tank Capacity		ℓ (Imp.gal.)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)
	Luggage Compartment Capacity		m^3 (cu.ft.)	6.0	6.0	6.0	6.0
Performance	Max. Speed		km/h (mph)	—	—	—	—
	Max. Cruising Speed		km/h (mph)	—	—	—	—
	Max. Permissible Speed	1st Gear	km/h (mph)	—	—	—	—
		2nd Gear	km/h (mph)	—	—	—	—
		3rd Gear	km/h (mph)	—	—	—	—
		4th Gear	km/h (mph)	—	—	—	—
	Min. Turning Radius	Tire	m (ft.)	5.0 (16.4)	5.0 (16.4)	5.0 (16.4)	5.0 (16.4)
		Body	m (ft.)	5.7 (18.7)	5.7 (18.7)	5.7 (18.7)	5.7 (18.7)
Engine	Engine Type			1KD-FTV	1KD-FTV	1KD-FTV	1KD-FTV
	Valve Mechanism			16-valve, DOHC	16-valve, DOHC	16-valve, DOHC	16-valve, DOHC
	Bore × Stroke		mm (in.)	96.0 × 103.0 (3.78 × 4.06)	96.0 × 103.0 (3.78 × 4.06)	96.0 × 103.0 (3.78 × 4.06)	96.0 × 103.0 (3.78 × 4.06)
	Displacement		cm^3 (cu.in.)	2982 (182.0)	2982 (182.0)	2982 (182.0)	2982 (182.0)
	Compression Ratio			16.0 : 1	16.0 : 1	16.0 : 1	16.0 : 1
	Fuel System			Common-rail Type	Common-rail Type	Common-rail Type	Common-rail Type
	Research Octane No. or Cetane No. (Diesel)			48 or higher	48 or higher	48 or higher	48 or higher
	Max. Output (EEC)		kW/rpm	100/3400	100/3400	100/3400	100/3400
	Max. Torque (EEC)		N·m/rpm	300/1200 - 2400	300/1200 - 2400	300/1200 - 2400	300/1200 - 2400
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp.hr.	12 - 60	12 - 60	12 - 60	12 - 60
	Alternator Output		Watts	1560	1560	1560	1560
	Starter Output		kW	2.2	2.7	2.7	2.2
Chassis	Clutch Type			Dry, Single Plate, Diaphragm	—	—	Dry, Single Plate, Diaphragm
	Transmission Type			R351	A340E	A340E	R351
	Gear Ratio	In First		4.313	2.804	2.804	4.313
		In Second		2.330	1.531	1.531	2.330
		In Third		1.436	1.000	1.000	1.436
		In Fourth		1.000	0.705	0.705	1.000
		In Fifth		0.838	—	—	0.838
		Reverse		4.220	2.393	2.393	4.220
	Differential Gear Ratio			3.727	4.100	4.100	3.727
	Differential Gear Size		mm (in.)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear		Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum
	Parking Brake Type			Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
	Brake Booster Type and Size		in.	Single, Single with BA*4 10"	Single, Single with BA*4 10"	Single, Single with BA*4 10"	Single, Single with BA*4 10"
	Proportioning Valve Type			LSP and BV	LSP and BV	LSP and BV	LSP and BV
	Suspension Type	Front		Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
		Rear		Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid
	Stabilizer Bar	Front		Standard	Standard	Standard	Standard
		Rear		—	—	—	—
	Steering Gear Type			Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
	Steering Gear Ratio (Overall)			20.84	20.84	20.84	20.84
	Power Steering Type			Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

*1: Folded Seat
*2: Option
*3: Cold Area Specification Model
*4: With ABS

General Countries					
5-door Van (Standard)	5-door Van (Super Long)		5-door Van (Super Long)	4-door Van (Standard)	
DX					
KDH201R-SRPDY	KDH221R-MFMDY	KDH221R-MFPDY	KDH220L-MBMDY	LH200R-RBMDE	LH200L-RBMDE
4695 (184.8)	5380 (211.8)	5380 (211.8)	5380 (211.8)	4695 (184.8)	4695 (184.8)
1695 (66.7)	1880 (74.0)	1880 (74.0)	1880 (74.0)	1695 (66.7)	1695 (66.7)
1980 (78.0)	2285 (90.0)	2285 (90.0)	2285 (90.0)	1980 (78.0)	1980 (78.0)
2570 (101.2)	3110 (122.4)	3110 (122.4)	3110 (122.4)	2570 (101.2)	2570 (101.2)
1470 (57.9)	1655 (65.2)	1655 (65.2)	1655 (65.2)	1470 (57.9)	1470 (57.9)
1465 (57.7)	1650 (65.0)	1650 (65.0)	1650 (65.0)	1465 (57.7)	1465 (57.7)
1905 (75.0), 910 (35.8)*1	910 (35.8)	910 (35.8)	910 (35.8)	910 (35.8)	910 (35.8)
1545 (60.8)	1730 (68.1)	1730 (68.1)	1730 (68.1)	1545 (60.8)	1545 (60.8)
1320 (52.0)	1565 (61.6)	1565 (61.6)	1565 (61.6)	1320 (52.0)	1320 (52.0)
1960 (77.2), 2930 (115.4)*1	3470 (136.6)	3470 (136.6)	3470 (136.6)	2930 (115.4)	2930 (115.4)
1545 (60.8)	1730 (68.1)	1730 (68.1)	1730 (68.1)	1545 (60.8)	1545 (60.8)
1335 (52.6)	1635 (64.4)	1635 (64.4)	1635 (64.4)	1335 (52.6)	1335 (52.6)
1050 (41.3)	1190 (46.9)	1190 (46.9)	1190 (46.9)	1050 (41.3)	1050 (41.3)
1075 (42.3)	1080 (42.5)	1080 (42.5)	1080 (42.5)	1075 (42.3)	1075 (42.3)
195 (7.7)	195 (7.7)	195 (7.7)	195 (7.7)	195 (7.7)	195 (7.7)
18.5	17.5	17.5	17.5	18.5	18.5
19.5	19.5	19.5	19.5	19.5	19.5
1100 - 1150 (2425 - 2535)	1160 - 1210 (2557 - 2668)	1165 - 1215 (2568 - 2679)	1140 - 1200 (2513 - 2646)	1015 - 1075 (2238 - 2370)	1020 - 1080 (2249 - 2381)
705 - 730 (1554 - 1609)	795 - 820 (1753 - 1808)	800 - 825 (1764 - 1819)	770 - 790 (1698 - 1742)	680 - 700 (1499 - 1543)	680 - 700 (1499 - 1543)
1805 - 1880 (3979 - 4145)	1955 - 2030 (4310 - 4475)	1965 - 2040 (4332 - 4497)	1910 - 1990 (4211 - 4387)	1695 - 1775 (3737 - 3913)	1700 - 1780 (3748 - 3924)
1420 - 1470 (3131 - 3241), 1420 - 1455 (3131 - 3208)*1	1610 - 1640 (3549 - 3616)	1615 - 1645 (3560 - 3627)	1600 - 1640 (3527 - 3616)	1380 - 1425 (3042 - 3142)	1385 - 1430 (3053 - 3153)
1330 - 1380 (2932 - 3042), 1345 - 1380 (2965 - 3042)*1	1560 - 1590 (3439 - 3505)	1555 - 1580 (3428 - 3483)	1560 - 1600 (3439 - 3527)	1375 - 1420 (3031 - 3131)	1370 - 1415 (3020 - 3120)
2800 (6173)	3200 (7055)	3200 (7055)	3200 (7055)	2800 (6173)	2800 (6173)
70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)
6.0	9.8	9.8	9.8	6.0	6.0
—	—	—	145 (90)	140 (87)	140 (87)
—	—	—	—	—	—
—	—	—	32 (20)	29 (18)	29 (18)
—	—	—	59 (37)	50 (31)	50 (31)
—	—	—	96 (60)	86 (53)	86 (53)
—	—	—	138 (86)	131 (81)	131 (81)
5.0 (16.4)	6.2 (20.3)	6.2 (20.3)	6.2 (20.3)	5.0 (16.4)	5.0 (16.4)
5.7 (18.7)	6.9 (22.6)	6.9 (22.6)	6.9 (22.6)	5.7 (18.7)	5.7 (18.7)
1KD-FTV	1KD-FTV	1KD-FTV	2KD-FTV	5L-E	5L-E
16-valve, DOHC	16-valve, DOHC	16-valve, DOHC	16-valve, DOHC	8-valve, OHC	8-valve, OHC
96.0 × 103.0 (3.78 × 4.06)	96.0 × 103.0 (3.78 × 4.06)	96.0 × 103.0 (3.78 × 4.06)	92.0 × 93.8 (3.62 × 3.69)	99.5 × 96.0 (3.92 × 3.78)	99.5 × 96.0 (3.92 × 3.78)
2982 (182.0)	2982 (182.0)	2982 (182.0)	2494 (152.2)	2986 (182.2)	2986 (182.2)
16.0 : 1	16.0 : 1	16.0 : 1	18.5 : 1	22.2 : 1	22.2 : 1
Common-rail Type	Common-rail Type	Common-rail Type	Common-rail Type	Distributor Type	Distributor Type
48 or higher	48 or higher	48 or higher	48 or higher	48 or higher	48 or higher
100/3400	100/3400	100/3400	75/3600	68/4000	68/4000
300/1200 - 2400	300/1200 - 2400	300/1200 - 2400	260/1600 - 2400	197/2400	197/2400
12 - 60	12 - 60	12 - 60	12 - 55, 12 - 55 × 2*2	12 - 60, 12 - 55 × 2*3	12 - 60, 12 - 55 × 2*3
1560	1560	1560	1200, 1560*2	1440	1440
2.7	2.2	2.7	2.0	2.2, 2.7*3	2.2, 2.7*3
—	Dry, Single Plate, Diaphragm	—	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm
A340E	R351	A340E	R351	G55	G55
2.804	4.313	2.804	4.313	4.452	4.452
1.531	2.330	1.531	2.330	2.619	2.619
1.000	1.436	1.000	1.436	1.517	1.517
0.705	1.000	0.705	1.000	1.000	1.000
—	0.838	—	0.838	0.854	0.854
2.393	4.220	2.393	4.220	4.472	4.472
4.100	3.727	4.100	4.100	4.300	4.300
205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)
Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum
Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
Single, Single with BA*4 10”	Single, Single with BA*4 10”	Single, Single with BA*4 10”	Single, Single with BA*4 10”	Single, Single with BA*4 10”	Single, Single with BA*4 10”
LSP and BV	LSP and BV	LSP and BV	LSP and BV	LSP and BV	LSP and BV
Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid
Standard	Standard	Standard	Standard	Standard	Standard
—	—	—	—	—	—
Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
20.84	20.84	20.84	20.84	20.84	20.84
Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

Item \ Area				General Countries			
Body Type				5-door Van (Standard)	4-door Commuter (Standard)		
Vehicle Grade				DX			
Model Code				LH200R-SBMDE	TRH203R-REMDK	TRH203L-REMDK	TRH213R-JEMDK
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	4695 (184.8)	4695 (184.8)	4695 (184.8)	4840 (190.6)
		Width	mm (in.)	1695 (66.7)	1695 (66.7)	1695 (66.7)	1880 (74.0)
		Height	mm (in.)	1980 (78.0)	1980 (78.0)	1980 (78.0)	2105 (82.9)
	Wheel Base		mm (in.)	2570 (101.2)	2570 (101.2)	2570 (101.2)	2570 (101.2)
	Tread	Front	mm (in.)	1470 (57.9)	1470 (57.9)	1470 (57.9)	1655 (65.2)
		Rear	mm (in.)	1465 (57.7)	1465 (57.7)	1465 (57.7)	1650 (65.0)
	Room	Length	mm (in.)	910 (35.8)	3470 (136.6)	3470 (136.6)	3525 (138.8)
		Width	mm (in.)	1545 (60.8)	1545 (60.8)	1545 (60.8)	1730 (68.1)
		Height	mm (in.)	1320 (52.0)	1335 (52.6)	1335 (52.6)	1390 (54.7)
	Cargo Space	Length	mm (in.)	2930 (115.4)	—	—	—
		Width	mm (in.)	1545 (60.8)	—	—	—
		Height	mm (in.)	1335 (52.6)	—	—	—
	Overhang	Front	mm (in.)	1050 (41.3)	1050 (41.3)	1050 (41.3)	1190 (46.9)
		Rear	mm (in.)	1075 (42.3)	1075 (42.3)	1075 (42.3)	1080 (42.5)
	Min. Running Ground Clearance		mm (in.)	195 (7.7)	185 (7.3)	185 (7.3)	185 (7.3)
	Angle of Approach		degrees	18.5	18.5	18.5	16.6
	Angle of Departure		degrees	19.5	19.5	19.5	19.7
	Curb Weight	Front	kg (lb)	1025 - 1085 (2260 - 2392)	995 - 1040 (2194 - 2293)	1005 - 1050 (2216 - 2315)	1050 - 1090 (2315 - 2403)
		Rear	kg (lb)	700 - 720 (1543 - 1587)	755 - 780 (1664 - 1720)	755 - 780 (1664 - 1720)	805 - 825 (1775 - 1819)
		Total	kg (lb)	1725 - 1805 (3803 - 3979)	1750 - 1820 (3858 - 4012)	1760 - 1830 (3880 - 4034)	1855 - 1915 (4090 - 4222)
	Gross Vehicle Weight	Front	kg (lb)	1385 - 1430 (3053 - 3153)	1345 - 1375 (2965 - 3031)	1355 - 1385 (2987 - 3053)	1380 - 1405 (3042 - 3097)
		Rear	kg (lb)	1370 - 1415 (3020 - 3120)	1575 - 1605 (3472 - 3538)	1565 - 1595 (3450 - 3516)	1695 - 1720 (3737 - 3792)
		Total	kg (lb)	2800 (6173)	2950 (6504)	2950 (6504)	3100 (6834)
	Fuel Tank Capacity		ℓ (Imp.gal.)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)
	Luggage Compartment Capacity		m^3 (cu.ft.)	6.0	—	—	—
Performance	Max. Speed		km/h (mph)	140 (87)	170 (105)	170 (105)	155 (96)
	Max. Cruising Speed		km/h (mph)	—	—	—	—
	Max. Permissible Speed	1st Gear	km/h (mph)	29 (18)	38 (24)	38 (24)	38 (24)
		2nd Gear	km/h (mph)	50 (31)	70 (43)	70 (43)	70 (43)
		3rd Gear	km/h (mph)	86 (53)	114 (71)	114 (71)	114 (71)
		4th Gear	km/h (mph)	131 (81)	163 (101)	163 (101)	163 (101)
	Min. Turning Radius	Tire	m (ft.)	5.0 (16.4)	5.0 (16.4)	5.0 (16.4)	5.3 (17.4)
		Body	m (ft.)	5.7 (18.7)	5.7 (18.7)	5.7 (18.7)	5.9 (19.4)
Engine	Engine Type			5L-E	2TR-FE	2TR-FE	2TR-FE
	Valve Mechanism			8-valve, OHC	16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i
	Bore × Stroke		mm (in.)	99.5 × 96.0 (3.92 × 3.78)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)
	Displacement		cm^3 (cu.in.)	2986 (182.2)	2694 (164.4)	2694 (164.4)	2694 (164.4)
	Compression Ratio			22.2 : 1	9.6 : 1	9.6 : 1	9.6 : 1
	Fuel System			Distributor Type	EFI	EFI	EFI
	Research Octane No. or Cetane No. (Diesel)			48 or higher	91 or higher	91 or higher	91 or higher
	Max. Output (EEC)		kW/rpm	68/4000	111/4800	111/4800	111/4800
	Max. Torque (EEC)		N·m/rpm	197/2400	241/3800	241/3800	241/3800
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp.hr.	12 - 60, 12 - 55 × 2*1	12 - 48, 12 - 55*3	12 - 48, 12 - 55*1	12 - 48, 12 - 55*1
	Alternator Output		Watts	1440	1560	1560	1560
	Starter Output		kW	2.2, 2.7*1	1.6	1.6	1.6
Chassis	Clutch Type			Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm
	Transmission Type			G55	R351	R351	R351
	Gear Ratio	In First		4.452	4.313	4.313	4.313
		In Second		2.619	2.330	2.330	2.330
		In Third		1.517	1.436	1.436	1.436
		In Fourth		1.000	1.000	1.000	1.000
		In Fifth		0.854	0.838	0.838	0.838
		Reverse		4.472	4.220	4.220	4.220
	Differential Gear Ratio			4.300	4.300	4.300	4.300
	Differential Gear Size		mm (in.)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear		Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum
	Parking Brake Type			Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
	Brake Booster Type and Size		in.	Single, Single with BA*2 10"	Single, Single with BA*2 10"	Single, Single with BA*2 10"	Single, Single with BA*2 10"
	Proportioning Valve Type			LSP and BV	LSP and BV	LSP and BV	LSP and BV
	Suspension Type	Front		Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
		Rear		Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid
	Stabilizer Bar	Front		Standard	Standard	Standard	Standard
		Rear		—	—	—	—
	Steering Gear Type			Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
	Steering Gear Ratio (Overall)			20.84	20.84	20.84	20.84
	Power Steering Type			Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

*1: Cold Area Specification Model
*2: With ABS
*3: Option

	General Countries					
	4-door Commuter (Standard)		4-door Commuter (Super Long)			
	DX	GL	DX		GL	
	TRH213L-JEMDK	TRH213L-JDMNK	TRH223R-LEMDK	TRH223L-LEMDK	TRH223L-LEMNK	TRH223L-LEPNK
5	4840 (190.6)	4840 (190.6)	5380 (211.8)	5380 (211.8)	5380 (211.8)	5380 (211.8)
	1880 (74.0)	1880 (74.0)	1880 (74.0)	1880 (74.0)	1880 (74.0)	1880 (74.0)
	2105 (82.9)	2105 (82.9)	2285 (90.0)	2285 (90.0)	2285 (90.0)	2285 (90.0)
	2570 (101.2)	2570 (101.2)	3110 (122.4)	3110 (122.4)	3110 (122.4)	3110 (122.4)
	1655 (65.2)	1655 (65.2)	1655 (65.2)	1655 (65.2)	1655 (65.2)	1655 (65.2)
10	1650 (65.0)	1650 (65.0)	1650 (65.0)	1650 (65.0)	1650 (65.0)	1650 (65.0)
	3525 (138.8)	3525 (138.8)	4205 (165.6)	4205 (165.6)	4250 (167.3)	4250 (167.3)
	1695 (66.7)	1695 (66.7)	1730 (68.1)	1730 (68.1)	1695 (66.7)	1695 (66.7)
	1390 (54.7)	1390 (54.7)	1565 (61.6)	1565 (61.6)	1565 (61.6)	1565 (61.6)
	—	—	—	—	—	—
15	—	—	—	—	—	—
	—	—	—	—	—	—
	1190 (46.9)	1190 (46.9)	1190 (46.9)	1190 (46.9)	1190 (46.9)	1190 (46.9)
	1080 (42.5)	1080 (42.5)	1080 (42.5)	1080 (42.5)	1080 (42.5)	1080 (42.5)
	185 (7.3)	185 (7.3)	185 (7.3)	185 (7.3)	185 (7.3)	185 (7.3)
20	16.6	16.6	17.0	17.0	17.0	17.0
	19.7	19.7	19.2	19.2	19.2	19.2
	1050 - 1090 (2315 - 2403)	1105 (2436)	1090 - 1135 (2403 - 2502)	1100 - 1145 (2425 - 2524)	1120 - 1165 (2469 - 2568)	1195 (2635)
	805 - 825 (1775 - 1819)	805 (1775)	850 - 875 (1874 - 1929)	850 - 875 (1874 - 1929)	890 - 915 (1962 - 2017)	910 (2006)
	1855 - 1915 (4090 - 4222)	1910 (4211)	1940 - 2010 (4277 - 4431)	1950 - 2020 (4299 - 4453)	2010 - 2080 (4431 - 4586)	2105 (4641)
25	1380 - 1405 (3042 - 3097)	1350 (2976)	1485 - 1510 (3274 - 3329)	1490 - 1520 (3285 - 3351)	1510 - 1535 (3329 - 3384)	1485 (3274)
	1695 - 1720 (3737 - 3792)	1400 (3086)	1690 - 1715 (3726 - 3781)	1680 - 1710 (3704 - 3770)	1715 - 1740 (3781 - 3836)	1635 (3605)
	3100 (6834)	2750 (6063)	3200 (7055)	3200 (7055)	3250 (7165)	3120 (6878)
	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)
	—	—	—	—	—	—
30	155 (96)	145 (90)	155 (96)	155 (96)	155 (96)	145 (90)
	—	—	—	—	—	—
	38 (24)	38 (24)	38 (24)	38 (24)	38 (24)	54 (33)
	70 (43)	70 (43)	70 (43)	70 (43)	70 (43)	98 (61)
	114 (71)	114 (71)	114 (71)	114 (71)	114 (71)	150 (93)
35	163 (101)	163 (101)	163 (101)	163 (101)	163 (101)	—
	5.3 (17.4)	5.3 (17.4)	6.2 (20.3)	6.2 (20.3)	6.2 (20.3)	6.2 (20.3)
	5.9 (19.4)	5.9 (19.4)	6.9 (22.6)	6.9 (22.6)	6.9 (22.6)	6.9 (22.6)
	2TR-FE	2TR-FE	2TR-FE	2TR-FE	2TR-FE	2TR-FE
	16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i
40	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)
	2694 (164.4)	2694 (164.4)	2694 (164.4)	2694 (164.4)	2694 (164.4)	2694 (164.4)
	9.6 : 1	9.6 : 1	9.6 : 1	9.6 : 1	9.6 : 1	9.6 : 1
	EFI	EFI	EFI	EFI	EFI	EFI
	91 or higher	91 or higher	91 or higher	91 or higher	91 or higher	91 or higher
45	111/4800	111/4800	111/4800	111/4800	111/4800	111/4800
	241/3800	241/3800	241/3800	241/3800	241/3800	241/3800
	12 - 48, 12 - 55*1	12 - 55, 12 - 48*3	12 - 48, 12 - 55*1	12 - 48, 12 - 55*1	12 - 48, 12 - 55*1	12 - 55
	1560	1560	1560	1560	1560	1560
	1.6	1.6	1.6	1.6	1.6	1.6
50	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	—
	R351	R351	R351	R351	R351	A343E
	4.313	4.313	4.313	4.313	4.313	2.804
	2.330	2.330	2.330	2.330	2.330	1.531
	1.436	1.436	1.436	1.436	1.436	1.000
55	1.000	1.000	1.000	1.000	1.000	0.753
	0.838	0.838	0.838	0.838	0.838	—
	4.220	4.220	4.220	4.220	4.220	2.393
	4.300	4.300	4.300	4.300	4.300	4.556
	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)
60	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum
	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
	Single, Single with BA*2 10”	Single, Single with BA*2 10”	Single, Single with BA*2 10”	Single, Single with BA*2 10”	Single, Single with BA*2 10”	Single with BA 10”
	LSP and BV	LSP and BV	LSP and BV	LSP and BV	LSP and BV	LSP and BV
65	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid
	Standard	Standard	Standard	Standard	Standard	Standard
	—	—	—	—	—	—
	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
70	20.84	20.84	20.84	20.84	20.84	20.84
	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

Item \ Area				General Countries			
Body Type				4-door Commuter (Standard)			
Vehicle Grade				DX			
Model Code				KDH202R-REMDY	KDH202L-REMDY	KDH203R-REMDY	KDH203L-RDMDY
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	4695 (184.8)	4695 (184.8)	4695 (184.8)	4695 (184.8)
		Width	mm (in.)	1695 (66.7)	1695 (66.7)	1695 (66.7)	1695 (66.7)
		Height	mm (in.)	1980 (78.0)	1980 (78.0)	1980 (78.0)	1980 (78.0)
	Wheel Base		mm (in.)	2570 (101.2)	2570 (101.2)	2570 (101.2)	2570 (101.2)
	Tread	Front	mm (in.)	1470 (57.9)	1470 (57.9)	1470 (57.9)	1470 (57.9)
		Rear	mm (in.)	1465 (57.7)	1465 (57.7)	1465 (57.7)	1465 (57.7)
	Room	Length	mm (in.)	3470 (136.6)	3470 (136.6)	4210 (165.7)	—
		Width	mm (in.)	1545 (60.8)	1545 (60.8)	1545 (60.8)	—
		Height	mm (in.)	1335 (52.6)	1335 (52.6)	1335 (52.6)	—
	Cargo Space	Length	mm (in.)	—	—	—	—
		Width	mm (in.)	—	—	—	—
		Height	mm (in.)	—	—	—	—
	Overhang	Front	mm (in.)	1050 (41.3)	1050 (41.3)	1050 (41.3)	1050 (41.3)
		Rear	mm (in.)	1075 (42.3)	1075 (42.3)	1075 (42.3)	1075 (42.3)
	Min. Running Ground Clearance		mm (in.)	185 (7.3)	185 (7.3)	185 (7.3)	185 (7.3)
	Angle of Approach		degrees	18.5	18.5	18.5	—
	Angle of Departure		degrees	19.5	19.5	19.5	—
	Curb Weight	Front	kg (lb)	1050 - 1110 (2315 - 2447)	1050 - 1110 (2315 - 2447)	1080 - 1120 (2381 - 2469)	1090 - 1130 (2403 - 2491)
		Rear	kg (lb)	760 - 790 (1676 - 1742)	760 - 790 (1676 - 1742)	765 - 785 (1687 - 1731)	745 - 770 (1642 - 1698)
		Total	kg (lb)	1810 - 1900 (3990 - 4189)	1810 - 1900 (3990 - 4189)	1845 - 1905 (4068 - 4200)	1835 - 1900 (4045 - 4189)
	Gross Vehicle Weight	Front	kg (lb)	1410 - 1450 (3109 - 3197)	1410 - 1450 (3109 - 3197)	1360 - 1390 (2998 - 3064)	1430 - 1460 (3153 - 3219)
		Rear	kg (lb)	1600 - 1640 (3527 - 3616)	1600 - 1640 (3527 - 3616)	1560 - 1590 (3439 - 3505)	1340 - 1370 (2954 - 3020)
		Total	kg (lb)	3050 (6724)	3050 (6724)	2950 (6504)	2800 (6173)
	Fuel Tank Capacity		ℓ (Imp.gal.)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)
	Luggage Compartment Capacity		m^3 (cu.ft.)	—	—	—	—
Performance	Max. Speed		km/h (mph)	145 (90)	145 (90)	145 (90)	—
	Max. Cruising Speed		km/h (mph)	—	—	—	—
	Max. Permissible Speed	1st Gear	km/h (mph)	32 (20)	32 (20)	32 (20)	—
		2nd Gear	km/h (mph)	59 (37)	59 (37)	59 (37)	—
		3rd Gear	km/h (mph)	96 (60)	96 (60)	96 (60)	—
		4th Gear	km/h (mph)	138 (86)	138 (86)	138 (86)	—
	Min. Turning Radius	Tire	m (ft.)	5.0 (16.4)	5.0 (16.4)	5.0 (16.4)	—
		Body	m (ft.)	5.7 (18.7)	5.7 (18.7)	5.7 (18.7)	—
Engine	Engine Type			2KD-FTV	2KD-FTV	1KD-FTV	1KD-FTV
	Valve Mechanism			16-valve, DOHC	16-valve, DOHC	16-valve, DOHC	16-valve, DOHC
	Bore × Stroke		mm (in.)	92.0 × 93.8 (3.62 × 3.69)	92.0 × 93.8 (3.62 × 3.69)	96.0 × 103.0 (3.78 × 4.06)	96.0 × 103.0 (3.78 × 4.06)
	Displacement		cm^3 (cu.in.)	2494 (152.2)	2494 (152.2)	2982 (182.0)	2982 (182.0)
	Compression Ratio			18.5 : 1	18.5 : 1	16.0 : 1	16.0 : 1
	Fuel System			Common-rail Type	Common-rail Type	Common-rail Type	Common-rail Type
	Research Octane No. or Cetane No. (Diesel)			48 or higher	48 or higher	48 or higher	48 or higher
	Max. Output (EEC)		kW/rpm	75/3600	75/3600	100/3400	100/3400
	Max. Torque (EEC)		N·m/rpm	260/1600 - 2400	260/1600 - 2400	300/1200 - 2400	300/1200 - 2400
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp.hr.	12 - 55, 12 - 55 × 2*1	12 - 55, 12 - 55 × 2*1	12 - 60	12 - 60, 12 - 55 × 2*1
	Alternator Output		Watts	1200, 1560*2	1200, 1560*2	1560	1560
	Starter Output		kW	2.0, 2.7*1	2.0, 2.7*1	2.2	2.2, 2.7*1
Chassis	Clutch Type			Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm
	Transmission Type			R351	R351	R351	R351
	Gear Ratio	In First		4.313	4.313	4.313	4.313
		In Second		2.330	2.330	2.330	2.330
		In Third		1.436	1.436	1.436	1.436
		In Fourth		1.000	1.000	1.000	1.000
		In Fifth		0.838	0.838	0.838	0.838
		Reverse		4.220	4.220	4.220	4.220
	Differential Gear Ratio			4.100	4.100	3.727	3.727
	Differential Gear Size		mm (in.)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear		Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum
	Parking Brake Type			Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
	Brake Booster Type and Size		in.	Single, Single with BA*3 10"	Single, Single with BA*3 10"	Single, Single with BA*3 10"	Single, Single with BA*3 10"
	Proportioning Valve Type			LSP and BV	LSP and BV	LSP and BV	LSP and BV
	Suspension Type	Front		Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
		Rear		Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid
	Stabilizer Bar	Front		Standard	Standard	Standard	Standard
		Rear		—	—	—	—
	Steering Gear Type			Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
	Steering Gear Ratio (Overall)			20.84	20.84	20.84	20.84
	Power Steering Type			Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

*1: Cold Area Specification Model
*2: Option
*3: With ABS

	General Countries					
	4-door Commuter (Standard)				5-door Commuter (Standard)	4-door Commuter (Super Long)
	DX			GL		DX
	KDH202L-RDMDY	KDH212R-JEMDY	KDH212L-JEMDY	KDH212L-JDMNY	KDH212L-KDPNY	KDH222R-LEMDY
5	4695 (184.8)	4840 (190.6)	4840 (190.6)	4840 (190.6)	4840 (190.6)	5380 (211.8)
	1695 (66.7)	1880 (74.0)	1880 (74.0)	1880 (74.0)	1880 (74.0)	1880 (74.0)
	1980 (78.0)	2105 (82.9)	2105 (82.9)	2105 (82.9)	2105 (82.9)	2285 (90.0)
	2570 (101.2)	2570 (101.2)	2570 (101.2)	2570 (101.2)	2570 (101.2)	3110 (122.4)
	1470 (57.9)	1655 (65.2)	1655 (65.2)	1655 (65.2)	1655 (65.2)	1655 (65.2)
10	1465 (57.7)	1650 (65.0)	1650 (65.0)	1650 (65.0)	1650 (65.0)	1650 (65.0)
	3460 (136.2)	3525 (138.8)	3525 (138.8)	3525 (138.8)	3525 (138.8)	4205 (165.6)
	1545 (60.8)	1695 (66.7)	1695 (66.7)	1695 (66.7)	1695 (66.7)	1730 (68.1)
	1335 (52.6)	1390 (54.7)	1390 (54.7)	1390 (54.7)	1390 (54.7)	1565 (61.6)
	—	—	—	—	—	—
15	—	—	—	—	—	—
	—	—	—	—	—	—
	1050 (41.3)	1190 (46.9)	1190 (46.9)	1190 (46.9)	1190 (46.9)	1190 (46.9)
	1075 (42.3)	1080 (42.5)	1080 (42.5)	1080 (42.5)	1080 (42.5)	1080 (42.5)
	185 (7.3)	185 (7.3)	185 (7.3)	185 (7.3)	185 (7.3)	185 (7.3)
20	18.5	16.6	16.6	16.6	16.6	17.0
	19.5	19.7	19.7	19.7	19.7	19.2
	1055 - 1115 (2326 - 2458)	1105 - 1145 (2436 - 2524)	1105 - 1145 (2436 - 2524)	1120 - 1155 (2469 - 2546)	1155 - 1175 (2546 - 2590)	1170 - 1205 (2579 - 2657)
	735 - 765 (1620 - 1687)	810 - 830 (1786 - 1830)	810 - 830 (1786 - 1830)	805 - 825 (1775 - 1819)	870 - 880 (1918 - 1940)	885 - 905 (1951 - 1995)
	1790 - 1880 (3946 - 4145)	1915 - 1975 (4222 - 4354)	1915 - 1975 (4222 - 4354)	1925 - 1980 (4244 - 4365)	2025 - 2055 (4464 - 4530)	2055 - 2110 (4530 - 4652)
25	1405 - 1450 (3097 - 3197)	1430 - 1460 (3153 - 3219)	1430 - 1460 (3153 - 3219)	1410 - 1435 (3109 - 3164)	1325 - 1340 (2921 - 2954)	1560 - 1580 (3439 - 3483)
	1350 - 1395 (2976 - 3075)	1690 - 1720 (3726 - 3792)	1690 - 1720 (3726 - 3792)	1465 - 1490 (3230 - 3285)	1560 - 1575 (3439 - 3472)	1720 - 1740 (3792 - 3836)
	2800 (6173)	3150 (6945)	3150 (6945)	2900 (6393)	2900 (6393)	3300 (7275)
	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)
	—	—	—	—	—	—
30	145 (90)	135 (84)	135 (84)	135 (84)	135 (84)	140 (87)
	—	—	—	—	—	—
	32 (20)	32 (20)	32 (20)	32 (20)	48 (30)	32 (20)
	59 (37)	59 (37)	59 (37)	59 (37)	88 (55)	59 (37)
	96 (60)	96 (60)	96 (60)	96 (60)	135 (84)	96 (60)
35	138 (86)	138 (86)	138 (86)	138 (86)	—	138 (86)
	5.0 (16.4)	5.3 (17.4)	5.3 (17.4)	5.3 (17.4)	5.3 (17.4)	6.2 (20.3)
	5.7 (18.7)	5.9 (19.4)	5.9 (19.4)	5.9 (19.4)	5.9 (19.4)	6.9 (22.6)
	2KD-FTV	2KD-FTV	2KD-FTV	2KD-FTV	2KD-FTV	2KD-FTV
	16-valve, DOHC	16-valve, DOHC	16-valve, DOHC	16-valve, DOHC	16-valve, DOHC	16-valve, DOHC
40	92.0 × 93.8 (3.62 × 3.69)	92.0 × 93.8 (3.62 × 3.69)	92.0 × 93.8 (3.62 × 3.69)	92.0 × 93.8 (3.62 × 3.69)	92.0 × 93.8 (3.62 × 3.69)	92.0 × 93.8 (3.62 × 3.69)
	2494 (152.2)	2494 (152.2)	2494 (152.2)	2494 (152.2)	2494 (152.2)	2494 (152.2)
	18.5 : 1	18.5 : 1	18.5 : 1	18.5 : 1	18.5 : 1	18.5 : 1
	Common-rail Type	Common-rail Type	Common-rail Type	Common-rail Type	Common-rail Type	Common-rail Type
	48 or higher	48 or higher	48 or higher	48 or higher	48 or higher	48 or higher
45	75/3600	75/3600	75/3600	75/3600	75/3600	75/3600
	260/1600 - 2400	260/1600 - 2400	260/1600 - 2400	260/1600 - 2400	260/1600 - 2400	260/1600 - 2400
	12 - 55, 12 - 55 × 2*1	12 - 55, 12 - 55 × 2*2	12 - 55, 12 - 55 × 2*2	12 - 55	12 - 55	12 - 55
	1200, 1560*2	1200, 1560*2	1200, 1560*2	1560	1560	1200, 1560*2
	2.0, 2.7*1	2.0	2.0	2.0	2.7	2.0
50	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	—	Dry, Single Plate, Diaphragm
	R351	R351	R351	R351	A340E	R351
	4.313	4.313	4.313	4.313	2.804	4.313
	2.330	2.330	2.330	2.330	1.531	2.330
	1.436	1.436	1.436	1.436	1.000	1.436
55	1.000	1.000	1.000	1.000	0.705	1.000
	0.838	0.838	0.838	0.838	—	0.838
	4.220	4.220	4.220	4.220	2.393	4.220
	4.100	4.100	4.100	4.100	4.100	4.100
	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)
60	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum
	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
	Single, Single with BA*3 10”	Single, Single with BA*3 10”	Single, Single with BA*3 10”	Single, Single with BA*3 10”	Single with BA 10”	Single, Single with BA*3 10”
	LSP and BV	LSP and BV	LSP and BV	LSP and BV	LSP and BV	LSP and BV
65	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid
	Standard	Standard	Standard	Standard	Standard	Standard
	—	—	—	—	—	—
	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
70	20.84	20.84	20.84	20.84	20.84	20.84
	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

Item \ Area				General Countries			
Body Type				4-door Commuter (Super Long)	4-door Commuter (Standard)		
Vehicle Grade				DX			
Model Code				KDH222L-LEMDY	LH202R-REMDE	LH202L-REMDE	LH202L-RDMDE
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	5380 (211.8)	4695 (184.8)	4695 (184.8)	4695 (184.8)
		Width	mm (in.)	1880 (74.0)	1695 (66.7)	1695 (66.7)	1695 (66.7)
		Height	mm (in.)	2285 (90.0)	1980 (78.0)	1980 (78.0)	1980 (78.0)
	Wheel Base		mm (in.)	3110 (122.4)	2570 (101.2)	2570 (101.2)	2570 (101.2)
	Tread	Front	mm (in.)	1655 (65.2)	1470 (57.9)	1470 (57.9)	1470 (57.9)
		Rear	mm (in.)	1650 (65.0)	1465 (57.7)	1465 (57.7)	1465 (57.7)
	Room	Length	mm (in.)	4205 (165.6)	4210 (165.7)	4210 (165.7)	4210 (165.7)
		Width	mm (in.)	1730 (68.1)	1545 (52.6)	1545 (60.8)	1545 (60.8)
		Height	mm (in.)	1565 (61.6)	1335 (52.6)	1335 (52.6)	1335 (52.6)
	Cargo Space	Length	mm (in.)	—	—	—	—
		Width	mm (in.)	—	—	—	—
		Height	mm (in.)	—	—	—	—
	Overhang	Front	mm (in.)	1190 (46.9)	1050 (41.3)	1050 (41.3)	1050 (41.3)
		Rear	mm (in.)	1080 (42.5)	1075 (42.3)	1075 (42.3)	1075 (42.3)
	Min. Running Ground Clearance		mm (in.)	185 (7.3)	185 (7.3)	185 (7.3)	185 (7.3)
	Angle of Approach		degrees	17.0	18.5	18.5	18.5
	Angle of Departure		degrees	19.2	19.5	19.5	19.5
	Curb Weight	Front	kg (lb)	1150 - 1210 (2535 - 2668)	1040 - 1100 (2293 - 2425)	1045 - 1105 (2304 - 2436)	1045 - 1105 (2304 - 2436)
		Rear	kg (lb)	855 - 885 (1885 - 1951)	750 - 780 (1653 - 1720)	750 - 780 (1653 - 1720)	725 - 755 (1598 - 1664)
		Total	kg (lb)	2005 - 2095 (4420 - 4619)	1790 - 1880 (3946 - 4145)	1795 - 1885 (3957 - 4156)	1770 - 1860 (3902 - 4101)
	Gross Vehicle Weight	Front	kg (lb)	1540 - 1580 (3395 - 3483)	1390 - 1435 (3064 - 3164)	1395 - 1440 (3075 - 3175)	1400 - 1440 (3086 - 3175)
		Rear	kg (lb)	1670 - 1710 (3682 - 3770)	1565 - 1610 (3450 - 3549)	1560 - 1605 (3439 - 3538)	1360 - 1400 (2998 - 3086)
		Total	kg (lb)	3250 (7165)	3000 (6614)	3000 (6614)	2800 (6173)
	Fuel Tank Capacity		ℓ (Imp.gal.)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)
	Luggage Compartment Capacity		m^3 (cu.ft.)	—	—	—	—
Performance	Max. Speed		km/h (mph)	135 (84)	140 (87)	140 (87)	140 (87)
	Max. Cruising Speed		km/h (mph)	—	—	—	—
	Max. Permissible Speed	1st Gear	km/h (mph)	32 (20)	29 (18)	29 (18)	29 (18)
		2nd Gear	km/h (mph)	59 (37)	50 (31)	50 (31)	50 (31)
		3rd Gear	km/h (mph)	96 (60)	86 (53)	86 (53)	86 (53)
		4th Gear	km/h (mph)	138 (86)	131 (81)	131 (81)	131 (81)
	Min. Turning Radius	Tire	m (ft.)	6.2 (20.3)	5.0 (16.4)	5.0 (16.4)	5.0 (16.4)
		Body	m (ft.)	6.9 (22.6)	5.7 (18.7)	5.7 (18.7)	5.7 (18.7)
Engine	Engine Type			2KD-FTV	5L-E	5L-E	5L-E
	Valve Mechanism			16-valve, DOHC	8-valve, OHC	8-valve, OHC	8-valve, OHC
	Bore × Stroke		mm (in.)	92.0 × 93.8 (3.62 × 3.69)	99.5 × 96.0 (3.92 × 3.78)	99.5 × 96.0 (3.92 × 3.78)	99.5 × 96.0 (3.92 × 3.78)
	Displacement		cm^3 (cu.in.)	2494 (152.2)	2986 (182.2)	2986 (182.2)	2986 (182.2)
	Compression Ratio			18.5 : 1	22.2 : 1	22.2 : 1	22.2 : 1
	Fuel System			Common-rail Type	Distributor Type	Distributor Type	Distributor Type
	Research Octane No. or Cetane No. (Diesel)			48 or higher	48 or higher	48 or higher	48 or higher
	Max. Output (EEC)		kW/rpm	75/3600	68/4000	68/4000	68/4000
	Max. Torque (EEC)		N·m/rpm	260/1600 - 2400	197/2400	197/2400	197/2400
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp.hr.	12 - 55, 12 - 55 × 2*1	12 - 60, 12 - 55 × 2*2	12 - 60, 12 - 55 × 2*2	12 - 60, 12 - 55 × 2*2
	Alternator Output		Watts	1200, 1560*1	1440	1440	1440
	Starter Output		kW	2.0	2.2, 2.7*2	2.2, 2.7*2	2.2, 2.7*2
Chassis	Clutch Type			Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm
	Transmission Type			R351	G55	G55	G55
	Gear Ratio	In First		4.313	4.452	4.452	4.452
		In Second		2.330	2.619	2.619	2.619
		In Third		1.436	1.517	1.517	1.517
		In Fourth		1.000	1.000	1.000	1.000
		In Fifth		0.838	0.854	0.854	0.854
		Reverse		4.220	4.472	4.472	4.472
	Differential Gear Ratio			4.100	4.300	4.300	4.300
	Differential Gear Size		mm (in.)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear		Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum
	Parking Brake Type			Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
	Brake Booster Type and Size		in.	Single, Single with BA*3 10"	Single, Single with BA*3 10"	Single, Single with BA*3 10"	Single, Single with BA*3 10"
	Proportioning Valve Type			LSP and BV	LSP and BV	LSP and BV	LSP and BV
	Suspension Type	Front		Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
		Rear		Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid
	Stabilizer Bar	Front		Standard	Standard	Standard	Standard
		Rear		—	—	—	—
	Steering Gear Type			Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
	Steering Gear Ratio (Overall)			20.84	20.84	20.84	20.84
	Power Steering Type			Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

*1: Option
*2: Cold Area Specification Model
*3: With ABS

General Countries			
4-door Commuter (Standard)		4-door Commuter (Super Long)	
DX			
LH212R-JEMDE	LH212L-JEMDE	LH222R-LEMDE	LH222L-LEMDE
4840 (190.6)	4840 (190.6)	5380 (211.8)	5380 (211.8)
1880 (74)	1880 (74)	1880 (74.0)	1880 (74.0)
2105 (82.9)	2105 (82.9)	2285 (90.0)	2285 (90.0)
2570 (101.2)	2570 (101.2)	3110 (122.4)	3110 (122.4)
1655 (65.2)	1655 (65.2)	1655 (65.2)	1655 (65.2)
1650 (65.0)	1650 (65.0)	1650 (65.0)	1650 (65.0)
3460 (136.2)	3460 (136.2)	4205 (165.6)	4205 (165.6)
1730 (68.1)	1730 (68.1)	1730 (68.1)	1730 (68.1)
1390 (54.7)	1390 (54.7)	1565 (61.6)	1565 (61.6)
—	—	—	—
—	—	—	—
—	—	—	—
1190 (46.9)	1190 (46.9)	1190 (46.9)	1190 (46.9)
1080 (42.5)	1080 (42.5)	1080 (42.5)	1080 (42.5)
185 (7.3)	185 (7.3)	185 (7.3)	185 (7.3)
16.6	16.6	17.0	17.0
19.7	19.7	19.2	19.2
1085 - 1125 (2392 - 2480)	1085 - 1125 (2392 - 2480)	1135 - 1195 (2502 - 2635)	1140 - 1200 (2513 - 2646)
800 - 820 (1764 - 1808)	800 - 820 (1764 - 1808)	840 - 870 (1852 - 1918)	840 - 870 (1852 - 1918)
1885 - 1945 (4156 - 4288)	1885 - 1945 (4156 - 4288)	1975 - 2065 (4354 - 4553)	1980 - 2070 (4365 - 4564)
1415 - 1445 (3120 - 3186)	1415 - 1445 (3120 - 3186)	1535 - 1570 (3384 - 3461)	1535 - 1575 (3384 - 3472)
1705 - 1735 (3759 - 3825)	1705 - 1735 (3759 - 3825)	1680 - 1715 (3704 - 3781)	1675 - 1715 (3693 - 3781)
3150 (6945)	3150 (6945)	3250 (7165)	3250 (7165)
70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)
—	—	—	—
130 (81)	130 (81)	130 (81)	130 (81)
—	—	—	—
29 (18)	29 (18)	29 (18)	29 (18)
50 (31)	50 (31)	50 (31)	50 (31)
86 (53)	86 (53)	86 (53)	86 (53)
131 (81)	131 (81)	131 (81)	131 (81)
5.3 (17.4)	5.3 (17.4)	6.2 (20.3)	6.2 (20.3)
5.9 (19.4)	5.9 (19.4)	6.9 (22.6)	6.9 (22.6)
5L-E	5L-E	5L-E	5L-E
8-valve, OHC	8-valve, OHC	8-valve, OHC	8-valve, OHC
99.5 × 96.0 (3.92 × 3.78)	99.5 × 96.0 (3.92 × 3.78)	99.5 × 96.0 (3.92 × 3.78)	99.5 × 96.0 (3.92 × 3.78)
2986 (182.2)	2986 (182.2)	2986 (182.2)	2986 (182.2)
22.2 : 1	22.2 : 1	22.2 : 1	22.2 : 1
Distributor Type	Distributor Type	Distributor Type	Distributor Type
48 or higher	48 or higher	48 or higher	48 or higher
68/4000	68/4000	68/4000	68/4000
197/2400	197/2400	197/2400	197/2400
12 - 60, 12 - 55 × 2*1	12 - 60, 12 - 55 × 2*1	12 - 60, 12 - 55 × 2*1	12 - 60, 12 - 55 × 2*1
1440	1440	1440	1440
2.2	2.2	2.2	2.2
Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm
G55	G55	G55	G55
4.452	4.452	4.452	4.452
2.619	2.619	2.619	2.619
1.517	1.517	1.517	1.517
1.000	1.000	1.000	1.000
0.854	0.854	0.854	0.854
4.472	4.472	4.472	4.472
4.300	4.300	4.300	4.300
205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)
Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum
Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
Single, Single with BA*3 10”	Single, Single with BA*3 10”	Single, Single with BA*3 10”	Single, Single with BA*3 10”
LSP and BV	LSP and BV	LSP and BV	LSP and BV
Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid
Standard	Standard	Standard	Standard
—	—	—	—
Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
20.84	20.84	20.84	20.84
Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type