MAJOR TECHNICAL SPECIFICATIONS

Item \ Area				Australia			
Body Type				4-door Van (Standard)		5-door Van (Super Long)	
Vehicle Grade				DX			
Model Code				TRH201R-RBMDKQ	TRH201R-RBPDKQ	TRH221R-MBMDKQ	TRH221R-MBPDKQ
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	4695 (184.8)	4695 (184.8)	5380 (211.8)	5380 (211.8)
		Width	mm (in.)	1695 (66.7)	1695 (66.7)	1880 (74.0)	1880 (74.0)
		Height	mm (in.)	1980 (78.0)	1980 (78.0)	2285 (90.0)	2285 (90.0)
	Wheel Base		mm (in.)	2570 (101.2)	2570 (101.2)	3110 (122.4)	3110 (122.4)
	Tread	Front	mm (in.)	1470 (57.9)	1470 (57.9)	1655 (65.2)	1655 (65.2)
		Rear	mm (in.)	1465 (57.7)	1465 (57.7)	1650 (65.0)	1650 (65.0)
	Room	Length	mm (in.)	910 (35.8)	910 (35.8)	910 (35.8)	910 (35.8)
		Width	mm (in.)	1545 (60.8)	1545 (60.8)	1730 (68.1)	1730 (68.1)
		Height	mm (in.)	1320 (52.0)	1320 (52.0)	1565 (61.6)	1565 (61.6)
	Cargo Space	Length	mm (in.)	2930 (115.4)	2930 (115.4)	3470 (136.6)	3470 (136.6)
		Width	mm (in.)	1545 (60.8)	1545 (60.8)	1730 (68.1)	1730 (68.1)
		Height	mm (in.)	1335 (52.6)	1335 (52.6)	1635 (64.4)	1635 (64.4)
	Overhang	Front	mm (in.)	1050 (41.3)	1050 (41.3)	1190 (46.9)	1190 (46.9)
		Rear	mm (in.)	1075 (42.3)	1075 (42.3)	1080 (42.5)	1080 (42.5)
	Min. Running Ground Clearance		mm (in.)	195 (7.7)	195 (7.7)	195 (7.7)	195 (7.7)
	Angle of Approach		degrees	18.5	18.5	17.5	17.5
	Angle of Departure		degrees	19.5	19.5	19.5	19.5
	Curb Weight	Front	kg (lb)	990 - 1035 (2183 - 2282)	1000 - 1045 (2205 - 2304)	1100 - 1130 (2425 - 2491)	1105 - 1135 (2436 - 2502)
		Rear	kg (lb)	675 - 685 (1488 - 1510)	675 - 685 (1488 - 1510)	755 - 760 (1664 - 1675)	760 - 765 (1675 - 1687)
		Total	kg (lb)	1665 - 1720 (3671 - 3792)	1675 - 1730 (3693 - 3814)	1855 - 1890 (4090 - 4167)	1865 - 1900 (4111 - 4189)
	Gross Vehicle Weight	Front	kg (lb)	1360 - 1395 (2998 - 3075)	1370 - 1405 (3020 - 3097)	1575 - 1595 (3472 - 3516)	1575 - 1600 (3472 - 3527)
		Rear	kg (lb)	1405 - 1440 (3097 - 3175)	1395 - 1430 (3075 - 3153)	1605 - 1625 (3538 - 3582)	1600 - 1625 (3527 - 3582)
		Total	kg (lb)	2800 (6173)	2800 (6173)	3200 (7055)	3200 (7055)
	Fuel Tank Capacity		ℓ (Imp.gal.)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)
	Luggage Compartment Capacity		m^3 (cu.ft.)	6.0	6.0	9.8	9.8
Performance	Max. Speed		km/h (mph)	170 (105)	170 (105)	155 (96)	155 (96)
	Max. Cruising Speed		km/h (mph)	—	—	—	—
	Max. Permissible Speed	1st Gear	km/h (mph)	38 (24)	54 (33)	38 (24)	54 (33)
		2nd Gear	km/h (mph)	70 (43)	98 (61)	70 (43)	98 (61)
		3rd Gear	km/h (mph)	114 (71)	150 (93)	114 (71)	150 (93)
		4th Gear	km/h (mph)	163 (101)	—	163 (101)	—
	Min. Turning Radius	Tire	m (ft.)	5.0 (16.4)	5.0 (16.4)	6.2 (20.3)	6.2 (20.3)
		Body	m (ft.)	5.7 (18.7)	5.7 (18.7)	6.9 (22.6)	6.9 (22.6)
Engine	Engine Type			2TR-FE	2TR-FE	2TR-FE	2TR-FE
	Valve Mechanism			16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i
	Bore × Stroke		mm (in.)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)
	Displacement		cm^3 (cu.in.)	2694 (164.4)	2694 (164.4)	2694 (164.4)	2694 (164.4)
	Compression Ratio			9.6 : 1	9.6 : 1	9.6 : 1	9.6 : 1
	Fuel System			EFI	EFI	EFI	EFI
	Research Octane No. or Cetane No. (Diesel)			91 or higher	91 or higher	91 or higher	91 or higher
	Max. Output (EEC)		kW/rpm	111/4800	111/4800	111/4800	111/4800
	Max. Torque (EEC)		N·m/rpm	241/3800	241/3800	241/3800	241/3800
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp.hr.	12 - 48	12 - 48	12 - 48	12 - 48
	Alternator Output		Watts	1560	1560	1560	1560
	Starter Output		kW	1.6	1.6	1.6	1.6
Chassis	Clutch Type			Dry, Single Plate, Diaphragm	—	Dry, Single Plate, Diaphragm	—
	Transmission Type			R351	A343E	R351	A343E
	Gear Ratio	In First		4.313	2.804	4.313	2.804
		In Second		2.330	1.531	2.330	1.531
		In Third		1.436	1.000	1.436	1.000
		In Fourth		1.000	0.753	1.000	0.753
		In Fifth		0.838	—	0.838	—
		In Reverse		4.220	2.393	4.220	2.393
	Differential Gear Ratio			4.300	4.556	4.300	4.556
	Differential Gear Size		mm (in.)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear		Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum
	Parking Brake Type			Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
	Brake Booster Type and Size		in.	Single with BA 10”	Single with BA 10”	Single with BA 10”	Single with BA 10”
	Proportioning Valve Type			LSP and BV	LSP and BV	LSP and BV	LSP and BV
	Suspension Type	Front		Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
		Rear		Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid
	Stabilizer Bar	Front		Standard	Standard	Standard	Standard
		Rear		—	—	—	—
	Steering Gear Type			Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
	Steering Gear Ratio (Overall)			20.84	20.84	20.84	20.84
	Power Steering Type			Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

	Australia					
	4-door Commuter (Super Long)		4-door Van (Standard)		5-door Van (Super Long)	
	DX					
	TRH223R-LEMDKQ	TRH223R-LEPDKQ	KDH201R-RBMDYQ	KDH201R-RBPDYQ	KDH221R-MBMDYQ	KDH221R-MBPDYQ
5	5380 (211.8)	5380 (211.8)	4695 (184.8)	4695 (184.8)	5380 (211.8)	5380 (211.8)
	1880 (74.0)	1880 (74.0)	1695 (66.7)	1695 (66.7)	1880 (74.0)	1880 (74.0)
	2285 (90.0)	2285 (90.0)	1980 (78.0)	1980 (78.0)	2285 (90.0)	2285 (90.0)
	3110 (122.4)	3110 (122.4)	2570 (101.2)	2570 (101.2)	3110 (122.4)	3110 (122.4)
	1655 (65.2)	1655 (65.2)	1470 (57.9)	1470 (57.9)	1655 (65.2)	1655 (65.2)
10	1650 (65.0)	1650 (65.0)	1465 (57.7)	1465 (57.7)	1650 (65.0)	1650 (65.0)
	4250 (167.3)	4250 (167.3)	910 (35.8)	910 (35.8)	910 (35.8)	910 (35.8)
	1730 (68.1)	1730 (68.1)	1545 (60.8)	1545 (60.8)	1730 (68.1)	1730 (68.1)
	1565 (61.6)	1565 (61.6)	1320 (52.0)	1320 (52.0)	1565 (61.6)	1565 (61.6)
	—	—	2930 (115.4)	2930 (115.4)	3470 (136.6)	3470 (136.6)
15	—	—	1545 (60.8)	1545 (60.8)	1730 (68.1)	1730 (68.1)
	—	—	1335 (52.6)	1335 (52.6)	1635 (64.4)	1635 (64.4)
	1190 (46.9)	1190 (46.9)	1050 (41.3)	1050 (41.3)	1190 (46.9)	1190 (46.9)
	1080 (42.5)	1080 (42.5)	1075 (42.3)	1075 (42.3)	1080 (42.5)	1080 (42.5)
	185 (7.3)	185 (7.3)	195 (7.7)	195 (7.7)	195 (7.7)	195 (7.7)
20	17.0	17.0	18.5	18.5	17.5	17.5
	19.2	19.2	19.5	19.5	19.5	19.5
	1145 - 1155 (2524 - 2546)	1155 - 1165 (2546 - 2568)	1085 - 1120 (2392 - 2469)	1095 - 1130 (2414 - 2491)	1170 - 1200 (2579 - 2657)	1175 - 1205 (2590 - 2657)
	915 - 925 (2017 - 2039)	915 - 925 (2017 - 2039)	695 - 705 (1532 - 1554)	695 - 705 (1532 - 1554)	800 - 805 (1764 - 1775)	805 - 810 (1775 - 1786)
	2060 - 2080 (4541 - 4586)	2070 - 2090 (4564 - 4608)	1780 - 1825 (3924 - 4023)	1790 - 1835 (3946 - 4045)	1970 - 2005 (4343 - 4420)	1980 - 2015 (4365 - 4442)
25	1425 - 1430 (3142 - 3153)	1430 - 1435 (3153 - 3164)	1435 - 1460 (3164 - 3219)	1440 - 1470 (3175 - 3241)	1615 - 1640 (3560 - 3616)	1620 - 1640 (3571 - 3616)
	1720 - 1725 (3792 - 3803)	1715 - 1720 (3781 - 3792)	1340 - 1365 (2954 - 3010)	1330 - 1360 (2932 - 2998)	1560 - 1585 (3439 - 3494)	1560 - 1580 (3439 - 3483)
	3150 (6945)	3150 (6945)	2800 (6173)	2800 (6173)	3200 (7055)	3200 (7055)
	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)
	—	—	6.0	6.0	9.8	9.8
30	155 (96)	155 (96)	145 (90)	145 (90)	140 (87)	135 (84)
	—	—	—	—	—	—
	38 (24)	54 (33)	32 (20)	48 (30)	32 (20)	48 (30)
	70 (43)	98 (61)	59 (37)	88 (55)	59 (37)	88 (55)
	114 (71)	150 (93)	96 (60)	135 (84)	96 (60)	135 (84)
35	163 (101)	—	138 (86)	—	138 (86)	—
	6.2 (20.3)	6.2 (20.3)	5.0 (16.4)	5.0 (16.4)	6.2 (20.3)	6.2 (20.3)
	6.9 (22.6)	6.9 (22.6)	5.7 (18.7)	5.7 (18.7)	6.9 (22.6)	6.9 (22.6)
	2TR-FE	2TR-FE	1KD-FTV	1KD-FTV	1KD-FTV	1KD-FTV
	16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i	16-valve, DOHC	16-valve, DOHC	16-valve, DOHC	16-valve, DOHC
40	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	96.0 × 103.0 (3.78 × 4.06)	96.0 × 103.0 (3.78 × 4.06)	96.0 × 103.0 (3.78 × 4.06)	96.0 × 103.0 (3.78 × 4.06)
	2694 (164.4)	2694 (164.4)	2982 (182.0)	2982 (182.0)	2982 (182.0)	2982 (182.0)
	9.6 : 1	9.6 : 1	16.0 : 1	16.0 : 1	16.0 : 1	16.0 : 1
	EFI	EFI	Common-rail Type	Common-rail Type	Common-rail Type	Common-rail Type
	91 or higher	91 or higher	48 or higher	48 or higher	48 or higher	48 or higher
45	111/4800	111/4800	100/3400	100/3400	100/3400	100/3400
	241/3800	241/3800	300/1200 - 2400	300/1200 - 2400	300/1200 - 2400	300/1200 - 2400
	12 - 48	12 - 48	12 - 60	12 - 60	12 - 60	12 - 60
	1560	1560	1560	1560	1560	1560
	1.6	1.6	2.2	2.7	2.2	2.7
50	Dry, Single Plate, Diaphragm	—	Dry, Single Plate, Diaphragm	—	Dry, Single Plate, Diaphragm	—
	R351	A343E	R351	A340E	R351	A340E
	4.313	2.804	4.313	2.804	4.313	2.804
	2.330	1.531	2.330	1.531	2.330	1.531
	1.436	1.000	1.436	1.000	1.436	1.000
55	1.000	0.753	1.000	0.705	1.000	0.705
	0.838	—	0.838	—	0.838	—
	4.220	2.393	4.220	2.393	4.220	2.393
	4.300	4.556	3.727	4.100	3.727	4.100
	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)
60	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum
	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
	Single with BA 10”	Single with BA 10”	Single with BA 10”	Single with BA 10”	Single with BA 10”	Single with BA 10”
	LSP and BV	LSP and BV	LSP and BV	LSP and BV	LSP and BV	LSP and BV
65	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid
	Standard	Standard	Standard	Standard	Standard	Standard
	—	—	—	—	—	—
	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
70	20.84	20.84	20.84	20.84	20.84	20.84
	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

Item \ Area				Australia		G.C.C. Countries	
Body Type				4-door Commuter (Super Long)		5-door Van (Standard)	
Vehicle Grade				DX			
Model Code				KDH223R-LEMDYQ	KDH223R-LEPDYQ	TRH201L-SBMDKV	TRH201L-SRMDKV
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	5380 (211.8)	5380 (211.8)	4695 (184.8)	4695 (184.8)
		Width	mm (in.)	1880 (74.0)	1880 (74.0)	1695 (66.7)	1695 (66.7)
		Height	mm (in.)	2285 (90.0)	2285 (90.0)	1980 (78.0)	1980 (78.0)
	Wheel Base		mm (in.)	3110 (122.4)	3110 (122.4)	2570 (101.2)	2570 (101.2)
	Tread	Front	mm (in.)	1655 (65.2)	1655 (65.2)	1470 (57.9)	1470 (57.9)
		Rear	mm (in.)	1650 (65.0)	1650 (65.0)	1465 (57.7)	1465 (57.7)
	Room	Length	mm (in.)	4250 (167.3)	4250 (167.3)	910 (35.8)	1905 (75.0), 910 (35.8)*1
		Width	mm (in.)	1730 (68.1)	1730 (68.1)	1545 (60.8)	1545 (60.8)
		Height	mm (in.)	1565 (61.6)	1565 (61.6)	1320 (52.0)	1320 (52.0)
	Cargo Space	Length	mm (in.)	—	—	2930 (115.4)	1960 (77.2), 2930 (115.4)*1
		Width	mm (in.)	—	—	1545 (60.8)	1545 (60.8)
		Height	mm (in.)	—	—	1335 (52.6)	1335 (52.6)
	Overhang	Front	mm (in.)	1190 (46.9)	1190 (46.9)	1050 (41.3)	1045 (41.1)
		Rear	mm (in.)	1080 (42.5)	1080 (42.5)	1075 (42.3)	1080 (42.5)
	Min. Running Ground Clearance		mm (in.)	185 (7.3)	185 (7.3)	195 (7.7)	195 (7.7)
	Angle of Approach		degrees	17.0	17.0	18.5	18.5
	Angle of Departure		degrees	19.2	19.2	19.5	19.5
	Curb Weight	Front	kg (lb)	1250 - 1260 (2756 - 2778)	1260 - 1270 (2778 - 2800)	980 - 1025 (2161 - 2260)	995 - 1040 (2194 - 2293)
		Rear	kg (lb)	925 - 935 (2039 - 2061)	925 - 935 (2039 - 2061)	685 - 690 (1510 - 1521)	700 - 710 (1543 - 1565)
		Total	kg (lb)	2175 - 2195 (4795 - 4839)	2185 - 2205 (4817 - 4861)	1665 - 1715 (3671 - 3781)	1695 - 1750 (3737 - 3858)
	Gross Vehicle Weight	Front	kg (lb)	1525 - 1530 (3362 - 3373)	1535 - 1540 (3384 - 3395)	1350 - 1385 (2976 - 3053)	1330 - 1365 (2932 - 3009), 1320 - 1360 (2910 - 2998)*1
		Rear	kg (lb)	1720 - 1725 (3792 - 3803)	1710 - 1715 (3770 - 3781)	1415 - 1450 (3120 - 3197)	1435 - 1470 (3164 - 3241), 1440 - 1480 (3179 - 3263)*1
		Total	kg (lb)	3250 (7165)	3250 (7165)	2800 (6173)	2800 (6173)
	Fuel Tank Capacity		ℓ (Imp.gal.)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)
	Luggage Compartment Capacity		m^3 (cu.ft.)	—	—	6.0	6.0
Performance	Max. Speed		km/h (mph)	140 (87)	135 (84)	170 (105)	170 (105)
	Max. Cruising Speed		km/h (mph)	—	—	—	—
	Max. Permissible Speed	1st Gear	km/h (mph)	32 (20)	48 (30)	38 (24)	38 (24)
		2nd Gear	km/h (mph)	59 (37)	88 (55)	70 (43)	70 (43)
		3rd Gear	km/h (mph)	96 (60)	135 (84)	114 (71)	114 (71)
		4th Gear	km/h (mph)	138 (86)	—	163 (101)	163 (101)
	Min. Turning Radius	Tire	m (ft.)	6.2 (20.3)	6.2 (20.3)	5.0 (16.4)	5.0 (16.4)
		Body	m (ft.)	6.9 (22.6)	6.9 (22.6)	5.7 (18.7)	5.7 (18.7)
Engine	Engine Type			1KD-FTV	1KD-FTV	2TR-FE	2TR-FE
	Valve Mechanism			16-valve, DOHC	16-valve, DOHC	16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i
	Bore × Stroke		mm (in.)	96.0 × 103.0 (3.78 × 4.06)	96.0 × 103.0 (3.78 × 4.06)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)
	Displacement		cm^3 (cu.in.)	2982 (182.0)	2982 (182.0)	2694 (164.4)	2694 (164.4)
	Compression Ratio			16.0 : 1	16.0 : 1	9.6 : 1	9.6 : 1
	Fuel System			Common-rail Type	Common-rail Type	EFI	EFI
	Research Octane No. or Cetane No. (Diesel)			48 or higher	48 or higher	91 or higher	91 or higher
	Max. Output (EEC)		kW/rpm	100/3400	100/3400	111/4800	111/4800
	Max. Torque (EEC)		N·m/rpm	300/1200 - 2400	300/1200 - 2400	241/3800	241/3800
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp.hr.	12 - 60	12 - 60	12 - 48, 12 - 55*2	12 - 48, 12 - 55*2
	Alternator Output		Watts	1560	1560	1560	1560
	Starter Output		kW	2.2	2.7	1.6	1.6
Chassis	Clutch Type			Dry, Single Plate, Diaphragm	—	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm
	Transmission Type			R351	A340E	R351	R351
	Gear Ratio	In First		4.313	2.804	4.313	4.313
		In Second		2.330	1.531	2.330	2.330
		In Third		1.436	1.000	1.436	1.436
		In Fourth		1.000	0.705	1.000	1.000
		In Fifth		0.838	—	0.838	0.838
		In Reverse		4.220	2.393	4.220	4.220
	Differential Gear Ratio			3.727	4.100	4.300	4.300
	Differential Gear Size		mm (in.)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear		Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum
	Parking Brake Type			Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
	Brake Booster Type and Size		in.	Single with BA 10”	Single with BA 10”	Single, Single with BA*3 10”	Single, Single with BA*3 10”
	Proportioning Valve Type			LSP and BV	LSP and BV	LSP and BV	LSP and BV
	Suspension Type	Front		Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
		Rear		Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid
	Stabilizer Bar	Front		Standard	Standard	Standard	Standard
		Rear		—	—	—	—
	Steering Gear Type			Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
	Steering Gear Ratio (Overall)			20.84	20.84	20.84	20.84
	Power Steering Type			Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

*1: Folded Seat *3: with ABS
*2: Option

G.C.C. Countries					
5-door Van (Super Long)	4-door Commuter (Standard)				4-door Commuter (Super Long)
DX					
TRH221L-MBMDKV	TRH203L-REMDKV	TRH203L-REPDKV	TRH213L-JEMDKV	TRH213L-JEPDKV	TRH223L-LEMDKV
5380 (211.8)	4695 (184.8)	4695 (184.8)	4840 (190.6)	4840 (190.6)	5380 (211.8)
1880 (74.0)	1695 (66.7)	1695 (66.7)	1880 (74.0)	1880 (74.0)	1880 (74.0)
2285 (90.0)	1980 (78.0)	1980 (78.0)	2105 (82.9)	2105 (82.9)	2285 (90.0)
3110 (122.4)	2570 (101.2)	2570 (101.2)	2570 (101.2)	2570 (101.2)	3110 (122.4)
1655 (65.2)	1470 (57.9)	1470 (57.9)	1655 (65.2)	1655 (65.2)	1655 (65.2)
1650 (65.0)	1465 (57.7)	1465 (57.7)	1650 (65.0)	1650 (65.0)	1650 (65.0)
910 (35.8)	3470 (136.6)	3470 (136.6)	3525 (138.8)	3525 (138.8)	4205 (165.6)
1730 (68.1)	1545 (60.8)	1545 (60.8)	1730 (68.1)	1730 (68.1)	1730 (68.1)
1565 (61.6)	1335 (52.6)	1335 (52.6)	1390 (54.7)	1390 (54.7)	1565 (61.6)
3470 (136.6)	—	—	—	—	—
1730 (68.1)	—	—	—	—	—
1635 (64.4)	—	—	—	—	—
1190 (46.9)	1050 (41.3)	1050 (41.3)	1190 (46.9)	1190 (46.9)	1190 (46.9)
1080 (42.5)	1075 (42.3)	1075 (42.3)	1080 (42.5)	1080 (42.5)	1080 (42.5)
195 (7.7)	185 (7.3)	185 (7.3)	185 (7.3)	185 (7.3)	185 (7.3)
17.5	18.5	18.5	16.6	16.6	17.0
19.5	19.5	19.5	19.7	19.7	19.2
1080 - 1125 (2381 - 2480)	985 - 1030 (2172 - 2271)	985 - 1035 (2172 - 2282)	1020 - 1065 (2249 - 2348)	1025 - 1070 (2260 - 2359)	1105 - 1165 (2436 - 2568)
755 - 760 (1664 - 1675)	765 - 770 (1687 - 1675)	765 - 770 (1687 - 1698)	820 - 825 (1808 - 1819)	820 - 825 (1808 - 1819)	870 - 920 (1918 - 2028)
1835 - 1885 (4045 - 4156)	1750 - 1800 (3858 - 3968)	1750 - 1805 (3858 - 3979)	1840 - 1890 (4056 - 4167)	1845 - 1895 (4067 - 4178)	1975 - 2085 (4354 - 4597)
1560 - 1590 (3439 - 3505)	1335 - 1370 (2943 - 3020)	1335 - 1375 (2943 - 3031)	1350 - 1385 (2976 - 3053)	1355 - 1390 (2987 - 3064)	1515 - 1550 (3340 - 3417)
1610 - 1640 (3549 - 3616)	1580 - 1615 (3483 - 3560)	1575 - 1615 (3472 - 3560)	1715 - 1750 (3781 - 3858)	1710 - 1745 (3770 - 3847)	1750 - 1785 (3858 - 3935)
3200 (7055)	2950 (6504)	2950 (6504)	3100 (6834)	3100 (6834)	3300 (7275)
70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)
9.8	—	—	—	—	—
155 (96)	170 (105)	—	155 (96)	—	155 (96)
—	—	—	—	—	—
38 (24)	38 (24)	—	38 (24)	—	38 (24)
70 (43)	70 (43)	—	70 (43)	—	70 (43)
114 (71)	114 (71)	—	114 (71)	—	114 (71)
163 (101)	163 (101)	—	163 (101)	—	163 (101)
6.2 (20.3)	5.0 (16.4)	—	5.3 (17.4)	—	6.2 (20.3)
6.9 (22.6)	5.7 (18.7)	—	5.9 (19.4)	—	6.9 (22.6)
2TR-FE	2TR-FE	2TR-FE	2TR-FE	2TR-FE	2TR-FE
16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i
95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)
2694 (164.4)	2694 (164.4)	2694 (164.4)	2694 (164.4)	2694 (164.4)	2694 (164.4)
9.6 : 1	9.6 : 1	9.6 : 1	9.6 : 1	9.6 : 1	9.6 : 1
EFI	EFI	EFI	EFI	EFI	EFI
91 or higher	91 or higher	91 or higher	91 or higher	91 or higher	91 or higher
111/4800	111/4800	111/4800	111/4800	111/4800	111/4800
241/3800	241/3800	241/3800	241/3800	241/3800	241/3800
12 - 48, 12 - 55*2	12 - 48, 12 - 55*2	12 - 48, 12 - 55*2	12 - 48, 12 - 55*2	12 - 48, 12 - 55*2	12 - 48, 12 - 55*2
1560	1560	1560	1560	1560	1560
1.6	1.6	1.6	1.6	1.6	1.6
Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	—	Dry, Single Plate, Diaphragm	—	Dry, Single Plate, Diaphragm
R351	R351	A343E	R351	A343E	R351
4.313	4.313	2.804	4.313	2.804	4.313
2.330	2.330	1.531	2.330	1.531	2.330
1.436	1.436	1.000	1.436	1.000	1.436
1.000	1.000	0.753	1.000	0.753	1.000
0.838	0.838	—	0.838	—	0.838
4.220	4.220	2.393	4.220	2.393	4.220
4.300	4.300	4.556	4.300	4.556	4.300
205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)
Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum
Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
Single, Single with BA*3 10”	Single, Single with BA*3 10”	Single, Single with BA*3 10”	Single, Single with BA*3 10”	Single, Single with BA*3 10”	Single, Single with BA*3 10”
LSP and BV	LSP and BV	LSP and BV	LSP and BV	LSP and BV	LSP and BV
Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid
Standard	Standard	Standard	Standard	Standard	Standard
—	—	—	—	—	—
Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
20.84	20.84	20.84	20.84	20.84	20.84
Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

Item \ Area				G.C.C. Countries			
Body Type				4-door Commuter (Super Long)			5-door Van (Standard)
Vehicle Grade				DX	GL		DX
Model Code				TRH223L-LEPDKV	TRH223L-LEMNKV	TRH223L-LEPNKV	KDH200L-SBMDYV
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	5380 (211.8)	5380 (211.8)	5380 (211.8)	4695 (184.8)
		Width	mm (in.)	1880 (74.0)	1880 (74.0)	1880 (74.0)	1695 (66.7)
		Height	mm (in.)	2285 (90.0)	2285 (90.0)	2285 (90.0)	1980 (78.0)
	Wheel Base		mm (in.)	3110 (122.4)	3110 (122.4)	3110 (122.4)	2570 (101.2)
	Tread	Front	mm (in.)	1655 (65.2)	1655 (65.2)	1655 (65.2)	1470 (57.9)
		Rear	mm (in.)	1650 (65.0)	1650 (65.0)	1650 (65.0)	1465 (57.7)
	Room	Length	mm (in.)	4205 (165.6)	4250 (167.3)	4250 (167.3)	910 (35.8)
		Width	mm (in.)	1730 (68.1)	1695 (66.7)	1695 (66.7)	1545 (60.8)
		Height	mm (in.)	1565 (61.6)	1565 (61.6)	1565 (61.6)	1320 (52.0)
	Cargo Space	Length	mm (in.)	—	—	—	2930 (115.4)
		Width	mm (in.)	—	—	—	1545 (60.8)
		Height	mm (in.)	—	—	—	1335 (52.6)
	Overhang	Front	mm (in.)	1190 (46.9)	1190 (46.9)	1190 (46.9)	1050 (41.3)
		Rear	mm (in.)	1080 (42.5)	1080 (42.5)	1080 (42.5)	1075 (42.3)
	Min. Running Ground Clearance		mm (in.)	185 (7.3)	185 (7.3)	185 (7.3)	195 (7.7)
	Angle of Approach		degrees	17.0	17.0	17.0	18.5
	Angle of Departure		degrees	19.2	19.2	19.2	19.5
	Curb Weight	Front	kg (lb)	1110 - 1170 (2447 - 2579)	1145 - 1170 (2524 - 2579)	1150 - 1175 (2535 - 2590)	1075 - 1120 (2370 - 2469)
		Rear	kg (lb)	875 - 925 (1929 - 2039)	915 - 925 (2017 - 2039)	920 - 930 (2028 - 2050)	710 - 715 (1565 - 1576)
		Total	kg (lb)	1985 - 2095 (4376 - 4619)	2060 - 2095 (4541 - 4619)	2070 - 2105 (4564 - 4641)	1785 - 1835 (3935 - 4045)
	Gross Vehicle Weight	Front	kg (lb)	1515 - 1550 (3340 - 3417)	1535 - 1550 (3384 - 3417)	1535 - 1555 (3384 - 3428)	1425 - 1460 (3142 - 3219)
		Rear	kg (lb)	1750 - 1785 (3858 - 3935)	1750 - 1765 (3858 - 3891)	1745 - 1765 (3847 - 3891)	1340 - 1375 (2954 - 3031)
		Total	kg (lb)	3300 (7275)	3300 (7275)	3300 (7275)	2800 (6173)
	Fuel Tank Capacity		ℓ (Imp.gal.)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)
	Luggage Compartment Capacity		m^3 (cu.ft.)	—	—	—	6.0
Performance	Max. Speed		km/h (mph)	—	155 (96)	—	145 (90)
	Max. Cruising Speed		km/h (mph)	—	—	—	—
	Max. Permissible Speed	1st Gear	km/h (mph)	—	38 (24)	—	32 (20)
		2nd Gear	km/h (mph)	—	70 (43)	—	59 (37)
		3rd Gear	km/h (mph)	—	114 (71)	—	96 (60)
		4th Gear	km/h (mph)	—	163 (101)	—	138 (86)
	Min. Turning Radius	Tire	m (ft.)	—	6.2 (20.3)	—	5.0 (16.4)
		Body	m (ft.)	—	6.9 (22.6)	—	5.7 (18.7)
Engine	Engine Type			2TR-FE	2TR-FE	2TR-FE	2KD-FTV
	Valve Mechanism			16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i	16-valve, DOHC
	Bore × Stroke		mm (in.)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	92.0 × 93.8 (3.62 × 3.69)
	Displacement		cm^3 (cu.in.)	2694 (164.4)	2694 (164.4)	2694 (164.4)	2494 (152.2)
	Compression Ratio			9.6 : 1	9.6 : 1	9.6 : 1	18.5 : 1
	Fuel System			EFI	EFI	EFI	Common-rail Type
	Research Octane No. or Cetane No. (Diesel)			91 or higher	91 or higher	91 or higher	48 or higher
	Max. Output (EEC)		kW/rpm	111/4800	111/4800	111/4800	75/3600
	Max. Torque (EEC)		N·m/rpm	241/3800	241/3800	241/3800	260/1600 - 2400
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp.hr.	12 - 48, 12 - 55*1	12 - 48, 12 - 55*1	12 - 48, 12 - 55*1	12 - 55
	Alternator Output		Watts	1560	1560	1560	1200, 1560*1
	Starter Output		kW	1.6	1.6	1.6	2.0
Chassis	Clutch Type			—	Dry, Single Plate, Diaphragm	—	Dry, Single Plate, Diaphragm
	Transmission Type			A343E	R351	A343E	R351
	Gear Ratio	In First		2.804	4.313	2.804	4.313
		In Second		1.531	2.330	1.531	2.330
		In Third		1.000	1.436	1.000	1.436
		In Fourth		0.753	1.000	0.753	1.000
		In Fifth		—	0.838	—	0.838
		In Reverse		2.393	4.220	2.393	4.220
	Differential Gear Ratio			4.556	4.300	4.556	4.100
	Differential Gear Size		mm (in.)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear		Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum
	Parking Brake Type			Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
	Brake Booster Type and Size		in.	Single, Single with BA*2 10"	Single, Single with BA*2 10"	Single, Single with BA*2 10"	Single, Single with BA*2 10"
	Proportioning Valve Type			LSP and BV	LSP and BV	LSP and BV	LSP and BV
	Suspension Type	Front		Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
		Rear		Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid
	Stabilizer Bar	Front		Standard	Standard	Standard	Standard
		Rear		—	—	—	—
	Steering Gear Type			Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
	Steering Gear Ratio (Overall)			20.84	20.84	20.84	20.84
	Power Steering Type			Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

*1: Option
*2: with ABS

	G.C.C. Countries				South Africa	
	4-door Commuter (Standard)		4-door Commuter (Super Long)		4-door Van (Standard)	5-door Van (Super Long)
	DX			GL	DX	
	KDH202L-REMDYV	KDH212L-JEMDYV	KDH222L-LEMDYV	KDH222L-LEMNYV	TRH201R-RBMDKN	TRH221R-MBMDKN
	4695 (184.8)	4840 (190.6)	5380 (211.8)	5380 (211.8)	4695 (184.8)	5380 (211.8)
	1695 (66.7)	1880 (74.0)	1880 (74.0)	1880 (74.0)	1695 (66.7)	1880 (74.0)
	1980 (78.0)	2105 (82.9)	2285 (90.0)	2285 (90.0)	1980 (78.0)	2285 (90.0)
	2570 (101.2)	2570 (101.2)	3110 (122.4)	3110 (122.4)	2570 (101.2)	3110 (122.4)
	1470 (57.9)	1655 (65.2)	1655 (65.2)	1655 (65.2)	1470 (57.9)	1655 (65.2)
	1465 (57.7)	1650 (65.0)	1650 (65.0)	1650 (65.0)	1465 (57.7)	1650 (65.0)
	3470 (136.6)	3525 (138.8)	4205 (165.6)	4250 (167.3)	910 (35.8)	910 (35.8)
	1545 (60.8)	1730 (68.1)	1730 (68.1)	1695 (66.7)	1545 (60.8)	1730 (68.1)
	1335 (52.6)	1390 (54.7)	1565 (61.6)	1565 (61.6)	1320 (52.0)	1565 (61.6)
	—	—	—	—	2930 (115.4)	3470 (136.6)
	—	—	—	—	1545 (60.8)	1730 (68.1)
	—	—	—	—	1335 (52.6)	1635 (64.4)
	1050 (41.3)	1190 (46.9)	1190 (46.9)	1190 (46.9)	1050 (41.3)	1190 (46.9)
	1075 (42.3)	1080 (42.5)	1080 (42.5)	1080 (42.5)	1075 (42.3)	1080 (42.5)
	185 (7.3)	185 (7.3)	185 (7.3)	185 (7.3)	195 (7.7)	195 (7.7)
	18.5	16.6	17.0	17.0	18.5	17.5
	19.5	19.7	19.2	19.2	19.5	19.5
	1070 - 1115 (2359 - 2458)	1110 - 1155 (2447 - 2546)	1160 - 1220 (2557 - 2690)	1195 - 1220 (2634 - 2690)	990 - 1030 (2183 - 2271)	1090 - 1095 (2403 - 2414)
	770 - 775 (1698 - 1709)	825 - 830 (1819 - 1830)	875 - 925 (1929 - 2039)	915 - 925 (2017 - 2039)	675 - 695 (1488 - 1532)	760 (1675)
	1840 - 1890 (4056 - 4167)	1935 - 1985 (4266 - 4376)	2035 - 2145 (4486 - 4729)	2110 - 2145 (4652 - 4729)	1665 - 1725 (3671 - 3803)	1850 - 1855 (4079 - 4090)
	1415 - 1450 (3120 - 3197)	1430 - 1470 (3153 - 3241)	1555 - 1590 (3428 - 3505)	1570 - 1590 (3461 - 3505)	1360 - 1390 (2988 - 3064)	1560 - 1565 (3439 - 3450)
	1550 - 1585 (3417 - 3494)	1680 - 1720 (3704 - 3792)	1710 - 1745 (3770 - 3847)	1710 - 1730 (3770 - 3814)	1410 - 1440 (3109 - 3175)	1635 - 1640 (3605 - 3616)
	3000 (6614)	3150 (6945)	3300 (7275)	3300 (7275)	2800 (6173)	3200 (7055)
	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)
	—	—	—	—	6.0	9.8
	145 (90)	135 (84)	135 (84)	135 (84)	155 (96)	155 (96)
	—	—	—	—	—	—
	32 (20)	32 (20)	32 (20)	32 (20)	38 (24)	38 (24)
	59 (37)	59 (37)	59 (37)	59 (37)	70 (43)	70 (43)
	96 (60)	96 (60)	96 (60)	96 (60)	114 (71)	114 (71)
	138 (86)	138 (86)	138 (86)	138 (86)	163 (101)	163 (101)
	5.0 (16.4)	5.3 (17.4)	6.2 (20.3)	6.2 (20.3)	5.0 (16.4)	6.2 (20.3)
	5.7 (18.7)	5.9 (19.4)	6.9 (22.6)	6.9 (22.6)	5.7 (18.7)	6.9 (22.6)
	2KD-FTV	2KD-FTV	2KD-FTV	2KD-FTV	2TR-FE	2TR-FE
	16-valve, DOHC	16-valve, DOHC	16-valve, DOHC	16-valve, DOHC	16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i
	92.0 × 93.8 (3.62 × 3.69)	92.0 × 93.8 (3.62 × 3.69)	92.0 × 93.8 (3.62 × 3.69)	92.0 × 93.8 (3.62 × 3.69)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)
	2494 (152.2)	2494 (152.2)	2494 (152.2)	2494 (152.2)	2694 (164.4)	2694 (164.4)
	18.5 : 1	18.5 : 1	18.5 : 1	18.5 : 1	9.6 : 1	9.6 : 1
	Common-rail Type	Common-rail Type	Common-rail Type	Common-rail Type	EFI	EFI
	48 or higher	48 or higher	48 or higher	48 or higher	91 or higher	91 or higher
	75/3600	75/3600	75/3600	75/3600	111/4800	111/4800
	260/1600 - 2400	260/1600 - 2400	260/1600 - 2400	260/1600 - 2400	241/3800	241/3800
	12 - 55	12 - 55, 12 - 55 × 2*1	12 - 55, 12 - 55 × 2*1	12 - 55, 12 - 55 × 2*1	12 - 48, 12 - 55*1	12 - 48, 12 - 55*1
	1200, 1560*1	1200, 1560*1	1200, 1560*1	1560	1560	1560
	2.0	2.0	2.0	2.0	1.6	1.6
	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm
	R351	R351	R351	R351	R351	R351
	4.313	4.313	4.313	4.313	4.313	4.313
	2.330	2.330	2.330	2.330	2.330	2.330
	1.436	1.436	1.436	1.436	1.436	1.436
	1.000	1.000	1.000	1.000	1.000	1.000
	0.838	0.838	0.838	0.838	0.838	0.838
	4.220	4.220	4.220	4.220	4.220	4.220
	4.100	4.100	4.100	4.100	4.300	4.300
	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)
	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum
	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
	Single, Single with BA*2 10”	Single, Single with BA*2 10”	Single, Single with BA*2 10”	Single, Single with BA*2 10”	Single with BA 10”	Single with BA 10”
	LSP and BV	LSP and BV	LSP and BV	LSP and BV	LSP and BV	LSP and BV
	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid
	Standard	Standard	Standard	Standard	Standard	Standard
	—	—	—	—	—	—
	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
	20.84	20.84	20.84	20.84	20.84	20.84
	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

Item \ Area				South Africa			
Body Type				4-door Commuter (Super Long)	4-door Commuter (Standard)	4-door Commuter (Super Long)	4-door Van (Standard)
Vehicle Grade				DX	GL		DX
Model Code				TRH223R-LEMDKN	TRH213R-JDMNKN	TRH223R-LEMNKN	KDH200R-RBMDYN
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	5380 (211.8)	4840 (190.6)	5380 (211.8)	4695 (184.8)
		Width	mm (in.)	1880 (74.0)	1880 (74.0)	1880 (74.0)	1695 (66.7)
		Height	mm (in.)	2285 (90.0)	2105 (82.9)	2285 (90.0)	1980 (78.0)
	Wheel Base		mm (in.)	3110 (122.4)	2570 (101.2)	3110 (122.4)	2570 (101.2)
	Tread	Front	mm (in.)	1655 (65.2)	1655 (65.2)	1655 (65.2)	1470 (57.9)
		Rear	mm (in.)	1650 (65.0)	1650 (65.0)	1650 (65.0)	1465 (57.7)
	Room	Length	mm (in.)	4250 (167.3)	3525 (138.8)	4250 (167.3)	910 (35.8)
		Width	mm (in.)	1730 (68.1)	1695 (66.7)	1695 (66.7)	1545 (60.8)
		Height	mm (in.)	1565 (61.6)	1390 (54.7)	1565 (61.6)	1320 (52.0)
	Cargo Space	Length	mm (in.)	—	—	—	2930 (115.4)
		Width	mm (in.)	—	—	—	1545 (60.8)
		Height	mm (in.)	—	—	—	1335 (52.6)
	Overhang	Front	mm (in.)	1190 (46.9)	1190 (46.9)	1190 (46.9)	1050 (41.3)
		Rear	mm (in.)	1080 (42.5)	1080 (42.5)	1080 (42.5)	1075 (42.3)
	Min. Running Ground Clearance		mm (in.)	185 (7.3)	185 (7.3)	185 (7.3)	195 (7.7)
	Angle of Approach		degrees	17	16.6	17	18.5
	Angle of Departure		degrees	19.2	19.7	19.2	19.5
	Curb Weight	Front	kg (lb)	1140 - 1145 (2513 - 2524)	1070 - 1095 (2359 - 2414)	1135 - 1160 (2502 - 2557)	1035 - 1085 (2282 - 2392)
		Rear	kg (lb)	930 - 935 (2050 - 2061)	815 - 825 (1767 - 1819)	925 - 935 (2039 - 2061)	695 - 725 (1532 - 1598)
		Total	kg (lb)	2070 - 2080 (4564 - 4586)	1885 - 1920 (4156 - 4233)	2060 - 2095 (4542 - 4619)	1730 - 1810 (3814 - 3990)
	Gross Vehicle Weight	Front	kg (lb)	1515 (3340)	1335 - 1355 (2943 - 2987)	1440 - 1455 (3175 - 3208)	1395 - 1430 (3075 - 3153)
		Rear	kg (lb)	1825 (4023)	1495 - 1515 (3296 - 3340)	1795 - 1810 (3957 - 3990)	1370 - 1405 (3020 - 3097)
		Total	kg (lb)	3340 (7363)	2850 (6283)	3250 (7165)	2800 (6173)
	Fuel Tank Capacity		ℓ (Imp.gal.)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)
	Luggage Compartment Capacity		m^3 (cu.ft.)	—	—	—	6.0
Performance	Max. Speed		km/h (mph)	155 (96)	155 (96)	155 (96)	135 (84)
	Max. Cruising Speed		km/h (mph)	—	—	—	—
	Max. Permissible Speed	1st Gear	km/h (mph)	38 (24)	38 (24)	38 (24)	32 (20)
		2nd Gear	km/h (mph)	70 (43)	70 (43)	70 (43)	59 (37)
		3rd Gear	km/h (mph)	114 (71)	114 (71)	114 (71)	96 (60)
		4th Gear	km/h (mph)	163 (101)	163 (101)	163 (101)	138 (86)
	Min. Turning Radius	Tire	m (ft.)	6.2 (20.3)	5.3 (17.4)	6.2 (20.3)	5.0 (16.4)
		Body	m (ft.)	6.9 (22.6)	5.9 (19.4)	6.9 (22.6)	5.7 (18.7)
Engine	Engine Type			2TR-FE	2TR-FE	2TR-FE	2KD-FTV
	Valve Mechanism			16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i	16-valve, DOHC
	Bore × Stroke		mm (in.)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	92.0 × 93.8 (3.62 × 3.69)
	Displacement		cm^3 (cu.in.)	2694 (164.4)	2694 (164.4)	2694 (164.4)	2494 (152.2)
	Compression Ratio			9.6 : 1	9.6 : 1	9.6 : 1	18.5 : 1
	Fuel System			EFI	EFI	EFI	Common-rail Type
	Research Octane No. or Cetane No. (Diesel)			91 or higher	91 or higher	91 or higher	48 or higher
	Max. Output (EEC)		kW/rpm	111/4800	111/4800	111/4800	75/3600
	Max. Torque (EEC)		N·m/rpm	241/3800	241/3800	241/3800	260/1600 - 2400
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp.hr.	12 - 60	12 - 48, 12 - 55*	12 - 48, 12 - 55*	12 - 55, 12 - 55 × 2*
	Alternator Output		Watts	1560	1560	1560	1200, 1560*
	Starter Output		kW	1.7	1.6	1.6	2.0
Chassis	Clutch Type			Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm
	Transmission Type			R351	R351	R351	R351
	Gear Ratio	In First		4.313	4.313	4.313	4.313
		In Second		2.330	2.330	2.330	2.330
		In Third		1.436	1.436	1.436	1.436
		In Fourth		1.000	1.000	1.000	1.000
		In Fifth		0.838	0.838	0.838	0.838
		In Reverse		4.220	4.220	4.220	4.220
	Differential Gear Ratio			4.300	4.300	4.300	4.100
	Differential Gear Size		mm (in.)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear		Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum
	Parking Brake Type			Leading-trailing Drum	Duo-servo Drum	Leading-trailing Drum	Duo-servo Drum
	Brake Booster Type and Size		in.	Single with BA 10"	Single with BA 10"	Single with BA 10"	Single with BA 10"
	Proportioning Valve Type			LSP and BV	LSP and BV	LSP and BV	LSP and BV
	Suspension Type	Front		Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
		Rear		Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid
	Stabilizer Bar	Front		Standard	Standard	Standard	Standard
		Rear		—	—	—	—
	Steering Gear Type			Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
	Steering Gear Ratio (Overall)			20.84	20.84	20.84	20.84
	Power Steering Type			Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

*: Option

	South Africa				Russia	
	5-door Van (Super Long)	4-door Commuter (Standard)	4-door Commuter (Super Long)			
	DX	GL	DX	GL		
	KDH220R-MBMDYN	KDH212R-JDMNYN	KDH222R-LEMDYN	KDH222R-LEMNYN	TRH223L-LEMNKX	KDH223L-LEMNYX
	5380 (211.8)	4840 (190.6)	5380 (211.8)	5380 (211.8)	5380 (211.8)	5380 (211.8)
	1880 (74.0)	1880 (74.0)	1880 (74.0)	1880 (74.0)	1880 (74.0)	1880 (74.0)
	2285 (90.0)	2105 (82.9)	2285 (90.0)	2285 (90.0)	2285 (90.0)	2285 (90.0)
	3110 (122.4)	2570 (101.2)	3110 (122.4)	3110 (122.4)	3110 (122.4)	3110 (122.4)
	1655 (65.2)	1655 (65.2)	1655 (65.2)	1655 (65.2)	1655 (65.2)	1655 (65.2)
	1650 (65.0)	1650 (65.0)	1650 (65.0)	1650 (65.0)	1650 (65.0)	1650 (65.0)
	910 (35.8)	3525 (138.8)	—	4250 (167.3)	4250 (167.3)	4250 (167.3)
	1730 (68.1)	1695 (66.7)	—	1695 (66.7)	1695 (66.7)	1695 (66.7)
	1565 (61.6)	1390 (54.7)	—	1565 (61.6)	1565 (61.6)	1565 (61.6)
	3470 (136.6)	—	—	—	—	—
	1730 (68.1)	—	—	—	—	—
	1635 (64.4)	—	—	—	—	—
	1190 (46.9)	1190 (46.9)	1190 (46.9)	1190 (46.9)	1190 (46.9)	1190 (46.9)
	1080 (42.5)	1080 (42.5)	1080 (42.5)	1080 (42.5)	1080 (42.5)	1080 (42.5)
	195 (7.7)	185 (7.3)	185 (7.3)	185 (7.3)	185 (7.3)	185 (7.3)
	17.5	16.6	—	17.0	17.0	17.0
	19.5	19.7	—	19.2	19.2	19.2
	1155 - 1160 (2546 - 2557)	1130 - 1175 (2491 - 2590)	1190 - 1195 (2623 - 2634)	1200 - 1245 (2646 - 2745)	1170 - 1175 (2579 - 2590)	1290 - 1295 (2844 - 2855)
	765 (1687)	820 - 830 (1808 - 1830)	915 - 920 (2017 - 2028)	930 - 940 (2050 - 2072)	915 - 925 (2017 - 2039)	930 - 940 (2050 - 2072)
	1920 - 1925 (4233 - 4244)	1950 - 2005 (4299 - 4420)	2105 - 2115 (4641 - 4663)	2130 - 2185 (4696 - 4817)	2085 - 2100 (4597 - 4630)	2220 - 2235 (4894 - 4927)
	1610 - 1615 (3549 - 3560)	1395 - 1430 (3075 - 3153)	1565 - 1570 (3450 - 3461)	1500 - 1530 (3307 - 3373)	1445 (3186)	1580 (3483)
	1585 - 1590 (3494 - 3505)	1470 - 1505 (3241 - 3318)	1820 - 1825 (4012 - 4023)	1770 - 1800 (3902 - 3968)	1605 (3558)	1670 (3682)
	3200 (7055)	2900 (6393)	3390 (7474)	3300 (7275)	3050 (6724)	3250 (7165)
	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)
	9.8	—	—	—	—	—
	135 (84)	135 (84)	—	135 (84)	155 (96)	140 (87)
	—	—	—	—	—	—
	32 (20)	32 (20)	—	32 (20)	38 (24)	32 (20)
	59 (37)	59 (37)	—	59 (37)	70 (43)	59 (37)
	96 (60)	96 (60)	—	96 (60)	114 (71)	96 (60)
	138 (86)	138 (86)	—	138 (86)	163 (101)	138 (86)
	6.2 (20.3)	5.3 (17.4)	—	6.2 (20.3)	6.2 (20.3)	6.2 (20.3)
	6.9 (22.6)	5.9 (19.4)	—	6.9 (22.6)	6.9 (22.6)	6.9 (22.6)
	2KD-FTV	2KD-FTV	2KD-FTV	2KD-FTV	2TR-FE	1KD-FTV
	16-valve, DOHC	16-valve, DOHC	16-valve, DOHC	16-valve, DOHC	16-valve, DOHC with VVT-i	16-valve, DOHC
	92.0 × 93.8 (3.62 × 3.69)	92.0 × 93.8 (3.62 × 3.69)	92.0 × 93.8 (3.62 × 3.69)	92.0 × 93.8 (3.62 × 3.69)	95.0 × 95.0 (3.74 × 3.74)	96.0 × 103.0 (3.78 × 4.06)
	2494 (152.2)	2494 (152.2)	2494 (152.2)	2494 (152.2)	2694 (164.4)	2982 (182.0)
	18.5 : 1	18.5 : 1	18.5 : 1	18.5 : 1	9.6 : 1	16.0 : 1
	Common-rail Type	Common-rail Type	Common-rail Type	Common-rail Type	EFI	Common-rail Type
	48 or higher	48 or higher	48 or higher	48 or higher	91 or higher	48 or higher
	75/3600	75/3600	75/3600	75/3600	111/4800	100/3400
	260/1600 - 2400	260/1600 - 2400	260/1600 - 2400	260/1600 - 2400	241/3800	300/1200 - 2400
	12 - 55, 12 - 55 × 2*	12 - 55, 12 - 55 × 2*	12 - 65	12 - 55, 12 - 55 × 2*	12 - 55	12 - 55 × 2
	1200, 1560*	1560	1200	1560	1560	1560
	2.0	2.0	2.2	2.0	1.6	3.0
	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm
	R351	R351	R351	R351	R351	R351
	4.313	4.313	4.313	4.313	4.313	4.313
	2.330	2.330	2.330	2.330	2.330	2.330
	1.436	1.436	1.436	1.436	1.436	1.436
	1.000	1.000	1.000	1.000	1.000	1.000
	0.838	0.838	0.838	0.838	0.838	0.838
	4.220	4.220	4.220	4.220	4.220	4.220
	4.100	4.100	4.100	4.100	4.300	3.727
	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)
	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum
	Duo-servo Drum	Duo-servo Drum	Leading-trailing Drum	Leading-trailing Drum	Duo-servo Drum	Duo-servo Drum
	Single with BA 10”	Single with BA 10”	Single with BA 10”	Single with BA 10”	Single with BA 10”	Single with BA 10”
	LSP and BV	LSP and BV	LSP and BV	LSP and BV	LSP and BV	LSP and BV
	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid
	Standard	Standard	Standard	Standard	Standard	Standard
	—	—	—	—	—	—
	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
	20.84	20.84	20.84	20.84	20.84	20.84
	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

Item \ Area				Thailand			
Body Type				5-door Commuter (Standard)	4-door Commuter (Super Long)	4-door Van (Standard)	4-door Commuter (Super Long)
Vehicle Grade				GL	DX		
Model Code				TRH213R-KDPNKT	TRH223R-LEMDKT	KDH201R-RBMDYT	KDH223R-LEMDYT
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	4840 (190.6)	5380 (211.8)	4695 (184.8)	5380 (211.8)
		Width	mm (in.)	1880 (74.0)	1880 (74.0)	1695 (66.7)	1880 (74.0)
		Height	mm (in.)	2105 (82.9)	2285 (90.0)	1980 (78.0)	2285 (90.0)
	Wheel Base		mm (in.)	2570 (101.2)	3110 (122.4)	2570 (101.2)	3110 (122.4)
	Tread	Front	mm (in.)	1655 (65.2)	1655 (65.2)	1470 (57.9)	1655 (65.2)
		Rear	mm (in.)	1650 (65.0)	1650 (65.0)	1465 (57.7)	1650 (65.0)
	Room	Length	mm (in.)	3525 (138.8)	4205 (165.6)	910 (35.8)	4205 (165.6)
		Width	mm (in.)	1695 (66.7)	1730 (68.1)	1545 (60.8)	1730 (68.1)
		Height	mm (in.)	1390 (54.7)	1565 (61.6)	1320 (52.0)	1565 (61.6)
	Cargo Space	Length	mm (in.)	—	—	2930 (115.4)	—
		Width	mm (in.)	—	—	1545 (60.8)	—
		Height	mm (in.)	—	—	1335 (52.6)	—
	Overhang	Front	mm (in.)	1190 (46.9)	1190 (46.9)	1050 (41.3)	1190 (46.9)
		Rear	mm (in.)	1080 (42.5)	1080 (42.5)	1075 (42.3)	1080 (42.5)
	Min. Running Ground Clearance		mm (in.)	185 (7.3)	185 (7.3)	195 (7.7)	185 (7.3)
	Angle of Approach		degrees	16.6	17.0	18.5	17.0
	Angle of Departure		degrees	19.7	19.2	19.5	19.2
	Curb Weight	Front	kg (lb)	1095 - 1110 (2414 - 2447)	1105 - 1145 (2436 - 2524)	1020 - 1055 (2249 - 2326)	1170 - 1205 (2579 - 2657)
		Rear	kg (lb)	865 - 875 (1907 - 1929)	900 - 905 (1984 - 1995)	690 - 705 (1521 - 1554)	885 - 905 (1951 - 1995)
		Total	kg (lb)	1960 - 1975 (4321 - 4354)	2005 - 2050 (4420 - 4519)	1710 - 1760 (3770 - 3880)	2055 - 2110 (4531 - 4652)
	Gross Vehicle Weight	Front	kg (lb)	1270 (2800 - 2833)	1505 - 1535 (3318 - 3384)	1380 - 1405 (3042 - 3097)	1560 - 1580 (3439 - 3483)
		Rear	kg (lb)	1580 (3450 - 3483)	1765 - 1795 (3891 - 3957)	1395 - 1420 (3075 - 3131)	1720 - 1740 (3792 - 3836)
		Total	kg (lb)	2850 (6283)	3300 (7275)	2800 (6173)	3300 (7275)
	Fuel Tank Capacity		ℓ (Imp.gal.)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)
	Luggage Compartment Capacity		m^3 (cu.ft.)	—	—	6.0	—
Performance	Max. Speed		km/h (mph)	155 (96)	—	145 (90)	140 (87)
	Max. Cruising Speed		km/h (mph)	—	—	—	—
	Max. Permissible Speed	1st Gear	km/h (mph)	54 (33)	—	32 (20)	32 (20)
		2nd Gear	km/h (mph)	98 (61)	—	59 (37)	59 (37)
		3rd Gear	km/h (mph)	150 (93)	—	96 (60)	96 (60)
		4th Gear	km/h (mph)	—	—	138 (86)	138 (86)
	Min. Turning Radius	Tire	m (ft.)	5.3 (17.4)	6.2 (20.3)	5.0 (16.4)	6.2 (20.3)
		Body	m (ft.)	5.9 (19.4)	6.9 (22.6)	5.7 (18.7)	6.9 (22.6)
Engine	Engine Type			2TR-FE	2TR-FE	1KD-FTV	1KD-FTV
	Valve Mechanism			16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i	16-valve, DOHC	16-valve, DOHC
	Bore × Stroke		mm (in.)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	96.0 × 103.0 (3.78 × 4.06)	96.0 × 103.0 (3.78 × 4.06)
	Displacement		cm^3 (cu.in.)	2694 (164.4)	2694 (164.4)	2982 (182.0)	2982 (182.0)
	Compression Ratio			9.6 : 1	9.6 : 1	16.0 : 1	16.0 : 1
	Fuel System			EFI	EFI	Common-rail Type	Common-rail Type
	Research Octane No. or Cetane No. (Diesel)			91 or higher	91 or higher	48 or higher	48 or higher
	Max. Output (EEC)		kW/rpm	111/4800	111/4800	100/3400	100/3400
	Max. Torque (EEC)		N·m/rpm	241/3800	241/3800	300/1200 - 2400	300/1200 - 2400
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp.hr.	12 - 55	12 - 48	12 - 60	12 - 60
	Alternator Output		Watts	1560	1560	1560	1560
	Starter Output		kW	1.6	1.6	2.2	2.2
Chassis	Clutch Type			—	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm
	Transmission Type			A343E	R351	R351	R351
	Gear Ratio	In First		2.804	4.313	4.313	4.313
		In Second		1.531	2.330	2.330	2.330
		In Third		1.000	1.436	1.436	1.436
		In Fourth		0.753	1.000	1.000	1.000
		In Fifth		—	0.838	0.838	0.838
		In Reverse		2.393	4.220	4.220	4.220
	Differential Gear Ratio			4.556	4.300	3.727	3.727
	Differential Gear Size		mm (in.)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear		Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum
	Parking Brake Type			Duo-servo Drum	Leading-trailing Drum	Duo-servo Drum	Leading-trailing Drum
	Brake Booster Type and Size		in.	Single with BA 10”	Single, Single with BA*3 10”	Single 10”	Single with BA 10”
	Proportioning Valve Type			LSP and BV	LSP and BV	LSP and BV	LSP and BV
	Suspension Type	Front		Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
		Rear		Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid
	Stabilizer Bar	Front		Standard	Standard	Standard	Standard
		Rear		—	—	—	—
	Steering Gear Type			Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
	Steering Gear Ratio (Overall)			20.84	20.84	20.84	20.84
	Power Steering Type			Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

*1: Folded Seat *3: with ABS
*2: Option

Thailand	Malaysia			General Countries	
4-door Commuter (Standard)		4-door Van (Standard)	4-door Commuter (Standard)	5-door Van (Standard)	
GL	DX				
KDH203R-RDMNYT	TRH203R-EDMDKE	KDH200R-RBMDYE	KDH202R-EDMDYE	TRH201R-SRMDK	TRH201R-SRPDK
4695 (184.8)	4695 (184.8)	4695 (184.8)	4695 (184.8)	4695 (184.8)	4695 (184.8)
1695 (66.7)	1695 (66.7)	1695 (66.7)	1695 (66.7)	1695 (66.7)	1695 (66.7)
1980 (78.0)	2240 (88.2)	1980 (78.0)	2240 (88.2)	1980 (78.0)	1980 (78.0)
2570 (101.2)	2570 (101.2)	2570 (101.2)	2570 (101.2)	2570 (101.2)	2570 (101.2)
1470 (57.9)	1470 (57.9)	1470 (57.9)	1470 (57.9)	1470 (57.9)	1470 (57.9)
1465 (57.7)	1465 (57.7)	1465 (57.7)	1465 (57.7)	1465 (57.7)	1465 (57.7)
3460 (136.2)	3470 (136.2)	910 (35.8)	3470 (136.2)	1905 (75.0), 910 (35.8)*1	1905 (75.0), 910 (35.8)*1
1545 (60.8)	1545 (60.8)	1545 (60.8)	1545 (60.8)	1545 (60.8)	1545 (60.8)
1335 (52.6)	1335 (52.6)	1320 (52.0)	1335 (52.6)	1320 (52.0)	1320 (52.0)
—	—	2930 (115.4)	—	1960 (77.2), 2930 (115.4)*1	1960 (77.2), 2930 (115.4)*1
—	—	1545 (60.8)	—	1545 (60.8)	1545 (60.8)
—	—	1335 (52.6)	—	1335 (52.6)	1335 (52.6)
1050 (41.3)	1050 (41.3)	1050 (41.3)	1050 (41.3)	1050 (41.3)	1050 (41.3)
1075 (42.3)	1075 (42.3)	1075 (42.3)	1075 (42.3)	1075 (42.3)	1075 (42.3)
185 (7.3)	185 (7.3)	195 (7.7)	195 (7.7)	195 (7.7)	195 (7.7)
18.5	18.5	18.5	18.5	18.5	18.5
19.5	19.5	19.5	19.5	19.5	19.5
1105 - 1115 (2436 - 2458)	1015 - 1025 (2238 - 2260)	1030 - 1040 (2271 - 2370)	1065 - 1075 (2348 - 2370)	1020 - 1060 (2249 - 2337)	1030 - 1070 (2271 - 2359)
755 (1664)	765 - 770 (1687 - 1698)	725 - 730 (1598 - 1609)	770 - 775 (1698 - 1709)	715 - 720 (1576 - 1587)	720 - 725 (1587 - 1598)
1860 - 1870 (4101 - 4123)	1780 - 1795 (3924 - 3957)	1755 - 1770 (3869 - 3902)	1835 - 1850 (4045 - 4079)	1735 - 1780 (3825 - 3924)	1750 - 1795 (3858 - 3957)
1370 - 1380 (3020 - 3042)	1355 - 1365 (2987 - 3009)	1385 - 1390 (3053 - 3064)	1405 - 1415 (3097 - 3120)	1350 - 1380 (2976 - 3042), 1340 - 1380 (2954 - 3042)*1	1355 - 1390 (2987 - 3064), 1350 - 1390 (2976 - 3064)*1
1320 - 1330 (2910 - 2932)	1385 - 1395 (3053 - 3075)	1410 - 1415 (3108 - 3120)	1385 - 1395 (3053 - 3075)	1420 - 1450 (3131 - 3197), 1420 - 1460 (3131 - 3219)*1	1410 - 1445 (3108 - 3186), 1410 - 1450 (3108 - 3197)*1
2700 (5952)	2750 (6062)	2800 (6173)	2800 (6173)	2800 (6173)	2800 (6173)
70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)
—	—	6.0	—	6.0	6.0
145 (90)	170 (105)	145 (90)	145 (90)	170 (105)	170 (105)
—	—	—	—	—	—
32 (20)	38 (24)	32 (20)	32 (20)	38 (24)	54 (33)
59 (37)	70 (43)	59 (37)	59 (37)	70 (43)	98 (61)
96 (60)	114 (71)	96 (60)	96 (60)	114 (71)	150 (93)
138 (86)	163 (101)	138 (86)	138 (86)	163 (101)	—
5.0 (16.4)	5.0 (16.4)	5.0 (16.4)	5.0 (16.4)	5.0 (16.4)	5.0 (16.4)
5.7 (18.7)	5.7 (18.7)	5.7 (18.7)	5.7 (18.7)	5.7 (18.7)	5.7 (18.7)
1KD-FTV	2TR-FE	2KD-FTV	2KD-FTV	2TR-FE	2TR-FE
16-valve, DOHC	16-valve, DOHC with VVT-i	16-valve, DOHC	16-valve, DOHC	16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i
96.0 × 103.0 (3.78 × 4.06)	95.0 × 95.0 (3.74 × 3.74)	92.0 × 93.8 (3.62 × 3.69)	92.0 × 93.8 (3.62 × 3.69)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)
2982 (182.0)	2694 (164.4)	2494 (152.2)	2494 (152.2)	2694 (164.4)	2694 (164.4)
16.0 : 1	9.6 : 1	18.5 : 1	18.5 : 1	9.6 : 1	9.6 : 1
Common-rail Type	EFI	Common-rail Type	Common-rail Type	EFI	EFI
48 or higher	91 or higher	48 or higher	48 or higher	91 or higher	91 or higher
100/3400	111/4800	75/3600	75/3600	111/4800	111/4800
300/1200 - 2400	241/3800	260/1600 - 2400	260/1600 - 2400	241/3800	241/3800
12 - 60	12 - 55	12 - 55, 12 - 55 × 2*2	12 - 55	12 - 48	12 - 48
1560	1560	1200	1560	1560	1560
2.2	1.6	2.0	2.0	1.6	1.6
Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	—
R351	R351	R351	R351	R351	A343E
4.313	4.313	4.313	4.313	4.313	2.804
2.330	2.330	2.330	2.330	2.330	1.531
1.436	1.436	1.436	1.436	1.436	1.000
1.000	1.000	1.000	1.000	1.000	0.753
0.838	0.838	0.838	0.838	0.838	—
4.220	4.220	4.220	4.220	4.220	2.393
3.727	4.300	4.100	4.100	4.300	4.556
205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)
Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum
Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
Single 10”	Single 10”	Single 10”	Single 10”	Single, Single with BA*3 10”	Single, Single with BA*3 10”
LSP and BV	LSP and BV	LSP and BV	LSP and BV	LSP and BV	LSP and BV
Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid
Standard	Standard	Standard	Standard	Standard	Standard
—	—	—	—	—	—
Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
20.84	20.84	20.84	20.84	20.84	20.84
Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

Item \ Area				General Countries			
Body Type				5-door Van (Standard)		4-door Van (Standard)	5-door Van (Super Long)
Vehicle Grade				DX			
Model Code				TRH201R-SSMDK	TRH201L-SBMDK	TRH201L-EFMDK	TRH221L-MBMDK
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	4695 (184.8)	4695 (184.8)	4695 (184.8)	5380 (211.8)
		Width	mm (in.)	1695 (66.7)	1695 (66.7)	1695 (66.7)	1880 (74.0)
		Height	mm (in.)	1980 (78.0)	1980 (78.0)	2240 (88.2)	2285 (90.0)
	Wheel Base		mm (in.)	2570 (101.2)	2570 (101.2)	2570 (101.2)	3110 (122.4)
	Tread	Front	mm (in.)	1470 (57.9)	1470 (57.9)	1470 (57.9)	1655 (65.2)
		Rear	mm (in.)	1465 (57.7)	1465 (57.7)	1465 (57.7)	1650 (65.0)
	Room	Length	mm (in.)	1905 (75.0), 910 (35.8)*1	910 (35.8)	910 (35.8)	910 (35.8)
		Width	mm (in.)	1545 (60.8)	1545 (60.8)	1545 (60.8)	1730 (68.1)
		Height	mm (in.)	1320 (52.0)	1320 (52.0)	1520 (59.8)	1565 (61.6)
	Cargo Space	Length	mm (in.)	1960 (77.2), 2930 (115.4)*1	2930 (115.4)	2930 (115.4)	3470 (136.6)
		Width	mm (in.)	1545 (60.8)	1545 (60.8)	1545 (60.8)	1730 (68.1)
		Height	mm (in.)	1335 (52.6)	1335 (52.6)	1590 (62.6)	1635 (64.4)
	Overhang	Front	mm (in.)	1050 (41.3)	1050 (41.3)	1050 (41.3)	1190 (46.9)
		Rear	mm (in.)	1075 (42.3)	1075 (42.3)	1075 (42.3)	1080 (42.5)
	Min. Running Ground Clearance		mm (in.)	195 (7.7)	195 (7.7)	195 (7.7)	195 (7.7)
	Angle of Approach		degrees	18.5	18.5	18.5	17.5
	Angle of Departure		degrees	19.5	19.5	19.5	19.5
	Curb Weight	Front	kg (lb)	1045 - 1055 (2304 - 2326)	980 - 1030 (2161 - 2271)*2, 990 - 1030 (2183 - 2271)*3	1005 - 1040 (2216 - 2293)	1080 - 1130 (2381 - 2491)*2, 1085 - 1125 (2392 - 2480)*3
		Rear	kg (lb)	715 (1576)	685 - 695 (1510 - 1532)*2, 685 - 690 (1510 - 1521)*3	715 - 720 (1576 - 1587)	755 - 765 (1664 - 1687)*2, 755 - 760 (1664 - 1675)*3
		Total	kg (lb)	1760 - 1770 (3880 - 3902)	1665 - 1725 (3671 - 3803)*2, 1675 - 1720 (3693 - 3792)*3	1720 - 1760 (3792 - 3880)	1835 - 1895 (4045 - 4178)*2, 1840 - 1885 (4056 - 4156)*3
	Gross Vehicle Weight	Front	kg (lb)	1370 - 1380 (3020 - 3042), 1365 - 1375 (3009 - 3031)*1	1350 - 1390 (2976 - 3064)*2, 1360 - 1390 (2998 - 3064)*3	1365 - 1390 (3009 - 3064)	1560 - 1595 (3439 - 3516)*2, 1565 - 1590 (3450 - 3505)*3
		Rear	kg (lb)	1420 - 1430 (3131 - 3153), 1425 - 1435 (3142 - 3164)*1	1410 - 1450 (3108 - 3197)*2, 1410 - 1440 (3108 - 3175)*3	1410 - 1435 (3108 - 3164)	1605 - 1640 (3558 - 3616)*2, 1610 - 1635 (3549 - 3605)*3
		Total	kg (lb)	2800 (6173)	2800 (6173)	2800 (6173)	3200 (7055)
	Fuel Tank Capacity		ℓ (Imp.gal.)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)
	Luggage Compartment Capacity		m³ (cu.ft.)	6.0	6.0	—	9.8
Performance	Max. Speed		km/h (mph)	170 (105)	170 (105)	170 (105)	155 (96)
	Max. Cruising Speed		km/h (mph)	—	—	—	—
	Max. Permissible Speed	1st Gear	km/h (mph)	38 (24)	38 (24)	38 (24)	38 (24)
		2nd Gear	km/h (mph)	70 (43)	70 (43)	70 (43)	70 (43)
		3rd Gear	km/h (mph)	114 (71)	114 (71)	114 (71)	114 (71)
		4th Gear	km/h (mph)	163 (101)	163 (101)	163 (101)	163 (101)
	Min. Turning Radius	Tire	m (ft.)	5.0 (16.4)	5.0 (16.4)	5.0 (16.4)	6.2 (20.3)
		Body	m (ft.)	5.7 (18.7)	5.7 (18.7)	5.7 (18.7)	6.9 (22.6)
Engine	Engine Type			2TR-FE	2TR-FE	2TR-FE	2TR-FE
	Valve Mechanism			16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i
	Bore × Stroke		mm (in.)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)
	Displacement		cm³ (cu.in.)	2694 (164.4)	2694 (164.4)	2694 (164.4)	2694 (164.4)
	Compression Ratio			9.6 : 1	9.6 : 1	9.6 : 1	9.6 : 1
	Fuel System			EFI	EFI	EFI	EFI
	Research Octane No. or Cetane No. (Diesel)			91 or higher	91 or higher	91 or higher	91 or higher
	Max. Output (EEC)		kW/rpm	111/4800	111/4800	111/4800	111/4800
	Max. Torque (EEC)		N·m/rpm	241/3800	241/3800	241/3800	241/3800
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp.hr.	12 - 48	12 - 48, 12 - 55*4	12 - 48	12 - 48, 12 - 55*4
	Alternator Output		Watts	1560	1560	1560	1560
	Starter Output		kW	1.6	1.6	1.6	1.6
Chassis	Clutch Type			Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm
	Transmission Type			R351	R351	R351	R351
	Gear Ratio	In First		4.313	4.313	4.313	4.313
		In Second		2.330	2.330	2.330	2.330
		In Third		1.436	1.436	1.436	1.436
		In Fourth		1.000	1.000	1.000	1.000
		In Fifth		0.838	0.838	0.838	0.838
		In Reverse		4.220	4.220	4.220	4.220
	Differential Gear Ratio			4.300	4.300	4.300	4.300
	Differential Gear Size		mm (in.)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear		Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum
	Parking Brake Type			Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
	Brake Booster Type and Size		in.	Single with BA 10"	Single, Single with BA*6 10"	Single, Single with BA*6 10"	Single, Single with BA*6 10"
	Proportioning Valve Type			LSP and BV	LSP and BV	LSP and BV	LSP and BV
	Suspension Type	Front		Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
		Rear		Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid
	Stabilizer Bar	Front		Standard	Standard	Standard	Standard
		Rear		—	—	—	—
	Steering Gear Type			Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
	Steering Gear Ratio (Overall)			20.84	20.84	20.84	20.84
	Power Steering Type			Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

*1: Folded Seat
*2: Except Models for Mexico Package
*3: Models for Mexico Package
*4: Option
*5: Cold Area Specification Model
*6: with ABS

General Countries					
4-door Van (Super Long)	4-door Van (Standard)		5-door Van (Standard)		
DX					
TRH221L-LFMDK	KDH200R-RBMDY	KDH200L-RBMDY	KDH200R-SBMDY	KDH200L-SBMDY	KDH201L-SBMDY
5380 (211.8)	4695 (184.8)	4695 (184.8)	4695 (184.8)	4695 (184.8)	4695 (184.8)
1880 (74.0)	1695 (66.7)	1695 (66.7)	1695 (66.7)	1695 (66.7)	1695 (66.7)
2285 (90.0)	1980 (78.0)	1980 (78.0)	1980 (78.0)	1980 (78.0)	1980 (78.0)
3110 (122.4)	2570 (101.2)	2570 (101.2)	2570 (101.2)	2570 (101.2)	2570 (101.2)
1655 (65.2)	1470 (57.9)	1470 (57.9)	1470 (57.9)	1470 (57.9)	1470 (57.9)
1650 (65.0)	1465 (57.7)	1465 (57.7)	1465 (57.7)	1465 (57.7)	1465 (57.7)
910 (35.8)	910 (35.8)	910 (35.8)	910 (35.8)	910 (35.8)	—
1730 (68.1)	1545 (60.8)	1545 (60.8)	1545 (60.8)	1545 (60.8)	—
1565 (61.6)	1320 (52.0)	1320 (52.0)	1320 (52.0)	1320 (52.0)	—
3470 (136.6)	2930 (115.4)	2930 (115.4)	2930 (115.4)	2930 (115.4)	—
1730 (68.1)	1545 (60.8)	1545 (60.8)	1545 (60.8)	1545 (60.8)	—
1635 (64.4)	1335 (52.6)	1335 (52.6)	1335 (52.6)	1335 (52.6)	—
1190 (46.9)	1050 (41.3)	1050 (41.3)	1050 (41.3)	1050 (41.3)	1050 (41.3)
1080 (42.5)	1075 (42.3)	1075 (42.3)	1075 (42.3)	1075 (42.3)	1075 (42.3)
195 (7.7)	195 (7.7)	195 (7.7)	195 (7.7)	195 (7.7)	195 (7.7)
17.5	18.5	18.5	18.5	18.5	—
19.5	19.5	19.5	19.5	19.5	—
1080 - 1115 (2381 - 2458)	1065 - 1130 (2348 - 2491)	1060 - 1125 (2337 - 2480)	1070 - 1135 (2359 - 2458)	1070 - 1115 (2359 - 2458)	1075 - 1110 (2370 - 2447)
750 - 755 (1653 - 1664)	695 - 705 (1532 - 1554)	690 - 700 (1521 - 1543)	705 - 715 (1554 - 1576)	710 - 715 (1565 - 1576)	720 - 740 (1587 - 1631)
1830 - 1870 (4034 - 4123)	1760 - 1835 (3880 - 4045)	1750 - 1825 (3858 - 4023)	1775 - 1850 (3913 - 4079)	1780 - 1830 (3924 - 4034)	1795 - 1850 (3957 - 4079)
1560 - 1585 (3439 - 3494)	1415 - 1470 (3120 - 3241)	1415 - 1465 (3120 - 3230)	1420 - 1470 (3131 - 3241)	1420 - 1455 (3131 - 3208)	1420 - 1445 (3131 - 3186)
1615 - 1640 (3560 - 3616)	1330 - 1385 (2932 - 3053)	1335 - 1385 (2943 - 3053)	1330 - 1380 (2932 - 3042)	1345 - 1380 (2965 - 3042)	1355 - 1380 (2987 - 3042)
3200 (7055)	2800 (6173)	2800 (6173)	2800 (6173)	2800 (6173)	2800 (6173)
70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)
9.8	6.0	6.0	6.0	6.0	—
155 (96)	145 (90)	145 (90)	145 (90)	145 (90)	—
—	—	—	—	—	—
38 (24)	32 (20)	32 (20)	32 (20)	32 (20)	—
70 (43)	59 (37)	59 (37)	59 (37)	59 (37)	—
114 (71)	96 (60)	96 (60)	96 (60)	96 (60)	—
163 (101)	138 (86)	138 (86)	138 (86)	138 (86)	—
6.2 (20.3)	5.0 (16.4)	5.0 (16.4)	5.0 (16.4)	5.0 (16.4)	—
6.9 (22.6)	5.7 (18.7)	5.7 (18.7)	5.7 (18.7)	5.7 (18.7)	—
2TR-FE	2KD-FTV	2KD-FTV	2KD-FTV	2KD-FTV	1KD-FTV
16-valve, DOHC with VVT-i	16-valve, DOHC	16-valve, DOHC	16-valve, DOHC	16-valve, DOHC	16-valve, DOHC
95.0 × 95.0 (3.74 × 3.74)	92.0 × 93.8 (3.62 × 3.69)	92.0 × 93.8 (3.62 × 3.69)	92.0 × 93.8 (3.62 × 3.69)	92.0 × 93.8 (3.62 × 3.69)	96.0 × 103.0 (3.78 × 4.06)
2694 (164.4)	2494 (152.2)	2494 (152.2)	2494 (152.2)	2494 (152.2)	2982 (182.0)
9.6 : 1	18.5 : 1	18.5 : 1	18.5 : 1	18.5 : 1	15.0 : 1
EFI	Common-rail Type	Common-rail Type	Common-rail Type	Common-rail Type	Common-rail Type
91 or higher	48 or higher	48 or higher	48 or higher	48 or higher	48 or higher
111/4800	75/3600	75/3600	75/3600	75/3600	106/3400
241/3800	260/1600 - 2400	260/1600 - 2400	260/1600 - 2400	260/1600 - 2400	300/1200 - 3200
12 - 48	12 - 55, 12 - 55 × 2*4	12 - 55, 12 - 55 × 2*4	12 - 55, 12 - 55 × 2*4	12 - 55, 12 - 55 × 2*4	12 - 55, 12 - 55 × 2*4
1560	1200, 1560*4	1200, 1560*4	1200, 1560*4	1200, 1560*4	1560
1.6	2.0, 2.7*5	2.0, 2.7*5	2.0, 2.7*5	2.0, 2.7*5	2.2, 2.7*5
Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm
R351	R351	R351	R351	R351	R351
4.313	4.313	4.313	4.313	4.313	4.313
2.330	2.330	2.330	2.330	2.330	2.330
1.436	1.436	1.436	1.436	1.436	1.436
1.000	1.000	1.000	1.000	1.000	1.000
0.838	0.838	0.838	0.838	0.838	0.838
4.220	4.220	4.220	4.220	4.220	4.220
4.300	4.100	4.100	4.100	4.100	3.727
205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)
Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum
Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
Single, Single with BA*6 10”	Single, Single with BA*6 10”	Single, Single with BA*6 10”	Single, Single with BA*6 10”	Single, Single with BA*6 10”	Single, Single with BA*6 10”
LSP and BV	LSP and BV	LSP and BV	LSP and BV	LSP and BV	LSP and BV
Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid
Standard	Standard	Standard	Standard	Standard	Standard
—	—	—	—	—	—
Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
20.84	20.84	20.84	20.84	20.84	20.84
Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

Item \ Area				General Countries			
Body Type				4-door Van (Standard)	5-door Van (Standard)		
Vehicle Grade				DX			
Model Code				KDH201R-RBPDY	KDH201R-SBMDY	KDH201R-SSMDY	KDH201R-SSPDY
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	4695 (184.8)	4695 (184.8)	4695 (184.8)	4695 (184.8)
		Width	mm (in.)	1695 (66.7)	1695 (66.7)	1695 (66.7)	1695 (66.7)
		Height	mm (in.)	1980 (78.0)	1980 (78.0)	1980 (78.0)	1980 (78.0)
	Wheel Base		mm (in.)	2570 (101.2)	2570 (101.2)	2570 (101.2)	2570 (101.2)
	Tread	Front	mm (in.)	1470 (57.9)	1470 (57.9)	1470 (57.9)	1470 (57.9)
		Rear	mm (in.)	1465 (57.7)	1465 (57.7)	1465 (57.7)	1465 (57.7)
	Room	Length	mm (in.)	910 (35.8)	910 (35.8)	1905 (75.0), 910 (35.8)*1	1905 (75.0), 910 (35.8)*1
		Width	mm (in.)	1545 (60.8)	1545 (60.8)	1545 (60.8)	1545 (60.8)
		Height	mm (in.)	1320 (52.0)	1320 (52.0)	1320 (52.0)	1320 (52.0)
	Cargo Space	Length	mm (in.)	2930 (115.4)	2930 (115.4)	1960 (77.2), 2930 (115.4)*1	1960 (77.2), 2930 (115.4)*1
		Width	mm (in.)	1545 (60.8)	1545 (60.8)	1545 (60.8)	1545 (60.8)
		Height	mm (in.)	1335 (52.6)	1335 (52.6)	1335 (52.6)	1335 (52.6)
	Overhang	Front	mm (in.)	1050 (41.3)	1050 (41.3)	1050 (41.3)	1050 (41.3)
		Rear	mm (in.)	1075 (42.3)	1075 (42.3)	1075 (42.3)	1075 (42.3)
	Min. Running Ground Clearance		mm (in.)	195 (7.7)	195 (7.7)	195 (7.7)	195 (7.7)
	Angle of Approach		degrees	18.5	18.5	18.5	18.5
	Angle of Departure		degrees	19.5	19.5	19.5	19.5
	Curb Weight	Front	kg (lb)	1070 - 1110 (2359 - 2447)	1090 - 1130 (2403 - 2491)	1155 - 1165 (2546 - 2568)	1165 - 1175 (2568 - 2590)
		Rear	kg (lb)	700 - 705 (1543 - 1554)	710 - 715 (1565 - 1576)	725 (1548)	730 (1609)
		Total	kg (lb)	1770 - 1815 (3902 - 4001)	1800 - 1845 (3968 - 4067)	1880 - 1890 (4145 - 4167)	1895 - 1905 (4178 - 4200)
	Gross Vehicle Weight	Front	kg (lb)	1420 - 1450 (3131 - 3197)	1435 - 1465 (3164 - 3230)	1460 - 1470 (3219 - 3241), 1475 - 1485 (3252 - 3274)*1	1470 - 1480 (3241 - 3263), 1485 - 1495 (3274 - 3296)*1
		Rear	kg (lb)	1350 - 1380 (2976 - 3042)	1335 - 1365 (2943 - 3009)	1330 - 1340 (2932 - 2954), 1315 - 1325 (2899 - 2921)*1	1320 - 1330 (2910 - 2932), 1305 - 1315 (2877 - 2899)*1
		Total	kg (lb)	2800 (6173)	2800 (6173)	2800 (6173)	2800 (6173)
	Fuel Tank Capacity		ℓ (Imp.gal.)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)
	Luggage Compartment Capacity		m^3 (cu.ft.)	6.0	6.0	6.0	6.0
Performance	Max. Speed		km/h (mph)	—	—	—	—
	Max. Cruising Speed		km/h (mph)	—	—	—	—
	Max. Permissible Speed	1st Gear	km/h (mph)	—	—	—	—
		2nd Gear	km/h (mph)	—	—	—	—
		3rd Gear	km/h (mph)	—	—	—	—
		4th Gear	km/h (mph)	—	—	—	—
	Min. Turning Radius	Tire	m (ft.)	5.0 (16.4)	5.0 (16.4)	5.0 (16.4)	5.0 (16.4)
		Body	m (ft.)	5.7 (18.7)	5.7 (18.7)	5.7 (18.7)	5.7 (18.7)
Engine	Engine Type			1KD-FTV	1KD-FTV	1KD-FTV	1KD-FTV
	Valve Mechanism			16-valve, DOHC	16-valve, DOHC	16-valve, DOHC	16-valve, DOHC
	Bore × Stroke		mm (in.)	96.0 × 103.0 (3.78 × 4.06)	96.0 × 103.0 (3.78 × 4.06)	96.0 × 103.0 (3.78 × 4.06)	96.0 × 103.0 (3.78 × 4.06)
	Displacement		cm^3 (cu.in.)	2982 (182.0)	2982 (182.0)	2982 (182.0)	2982 (182.0)
	Compression Ratio			16.0 : 1	16.0 : 1	15.0 : 1	15.0 : 1
	Fuel System			Common-rail Type	Common-rail Type	Common-rail Type	Common-rail Type
	Research Octane No. or Cetane No. (Diesel)			48 or higher	48 or higher	48 or higher	48 or higher
	Max. Output (EEC)		kW/rpm	100/3400	100/3400	106/3400	106/3400
	Max. Torque (EEC)		N·m/rpm	300/1200 - 2400	300/1200 - 2400	300/1200 - 3200	300/1200 - 3200
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp.hr.	12 - 60	12 - 60	12 - 55	12 - 55, 12 - 55 × 2*2
	Alternator Output		Watts	1560	1560	1560	1560, 1800*2
	Starter Output		kW	2.7	2.2	2.2	2.2, 2.7*2
Chassis	Clutch Type			—	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	—
	Transmission Type			A340E	R351	R351	A340E
	Gear Ratio	In First		2.804	4.313	4.313	2.804
		In Second		1.531	2.330	2.330	1.531
		In Third		1.000	1.436	1.436	1.000
		In Fourth		0.705	1.000	1.000	0.705
		In Fifth		—	0.838	0.838	—
		In Reverse		2.393	4.220	4.220	2.393
	Differential Gear Ratio			4.100	3.727	3.727	4.100
	Differential Gear Size		mm (in.)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear		Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum
	Parking Brake Type			Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
	Brake Booster Type and Size		in.	Single, Single with BA*3 10"	Single, Single with BA*3 10"	Single with BA 10"	Single with BA 10"
	Proportioning Valve Type			LSP and BV	LSP and BV	LSP and BV	LSP and BV
	Suspension Type	Front		Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
		Rear		Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid
	Stabilizer Bar	Front		Standard	Standard	Standard	Standard
		Rear		—	—	—	—
	Steering Gear Type			Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
	Steering Gear Ratio (Overall)			20.84	20.84	20.84	20.84
	Power Steering Type			Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

*1: Folded Seat *3: with ABS
*2: Option

General Countries					
5-door Van (Standard)			5-door Van (Super Long)		
GL	DX				
KDH201R-SSPNY	KDH201R-SRMDY	KDH201R-SRPDY	KDH221R-MFMDY	KDH221R-MFPDY	KDH220L-MBMDY
4695 (184.8)	4695 (184.8)	4695 (184.8)	5380 (211.8)	5380 (211.8)	5380 (211.8)
1695 (66.7)	1695 (66.7)	1695 (66.7)	1880 (74.0)	1880 (74.0)	1880 (74.0)
1980 (78.0)	1980 (78.0)	1980 (78.0)	2285 (90.0)	2285 (90.0)	2285 (90.0)
2570 (101.2)	2570 (101.2)	2570 (101.2)	3110 (122.4)	3110 (122.4)	3110 (122.4)
1470 (57.9)	1470 (57.9)	1470 (57.9)	1655 (65.2)	1655 (65.2)	1655 (65.2)
1465 (57.7)	1465 (57.7)	1465 (57.7)	1650 (65.0)	1650 (65.0)	1650 (65.0)
1905 (75.0), 910 (35.8)*1	1905 (75.0), 910 (35.8)*1	1905 (75.0), 910 (35.8)*1	910 (35.8)	910 (35.8)	910 (35.8)
1545 (60.8)	1545 (60.8)	1545 (60.8)	1730 (68.1)	1730 (68.1)	1730 (68.1)
1320 (52.0)	1320 (52.0)	1320 (52.0)	1565 (61.6)	1565 (61.6)	1565 (61.6)
1960 (77.2), 2930 (115.4)*1	1960 (77.2), 2930 (115.4)*1	1960 (77.2), 2930 (115.4)*1	3470 (136.6)	3470 (136.6)	3470 (136.6)
1545 (60.8)	1545 (60.8)	1545 (60.8)	1730 (68.1)	1730 (68.1)	1730 (68.1)
1335 (52.6)	1335 (52.6)	1335 (52.6)	1635 (64.4)	1635 (64.4)	1635 (64.4)
1050 (41.3)	1050 (41.3)	1050 (41.3)	1190 (46.9)	1190 (46.9)	1190 (46.9)
1075 (42.3)	1075 (42.3)	1075 (42.3)	1080 (42.5)	1080 (42.5)	1080 (42.5)
195 (7.7)	195 (7.7)	195 (7.7)	195 (7.7)	195 (7.7)	195 (7.7)
18.5	18.5	18.5	17.5	17.5	17.5
19.5	19.5	19.5	19.5	19.5	19.5
1165 - 1175 (2568 - 2590)	1120 - 1160 (2469 - 2557)	1125 - 1165 (2480 - 2568)	1165 - 1205 (2568 - 2657)	1170 - 1210 (2579 - 2668)	1155 - 1200 (2546 - 2646)
730 (1609)	725 - 730 (1598 - 1609)	730 - 735 (1609 - 1620)	815 - 820 (1797 - 1808)	820 - 825 (1808 - 1819)	780 - 790 (1720 - 1742)
1895 - 1905 (4178 - 4200)	1845 - 1890 (4067 - 4167)	1855 - 1900 (4090 - 4189)	1980 - 2025 (4365 - 4464)	1990 - 2035 (4387 - 4486)	1935 - 1990 (4266 - 4387)
1450 - 1460 (3197 - 3219), 1485 - 1495 (3274 - 3296)*1	1430 - 1465 (3153 - 3230), 1440 - 1480 (3175 - 3263)*1	1435 - 1470 (3164 - 3241), 1445 - 1485 (3186 - 3274)*1	1610 - 1640 (3549 - 3616)	1610 - 1640 (3549 - 3616)	1610 - 1640 (3549 - 3616)
1340 - 1350 (2954 - 2976), 1305 - 1315 (2877 - 2899)*1	1335 - 1370 (2943 - 3020), 1320 - 1360 (2910 - 2998)*1	1330 - 1365 (2932 - 3009), 1315 - 1355 (2899 - 2987)*1	1560 - 1590 (3439 - 3505)	1560 - 1590 (3436 - 3505)	1560 - 1590 (3439 - 3505)
2800 (6173)	2800 (6173)	2800 (6173)	3200 (7055)	3200 (7055)	3200 (7055)
70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)
6.0	6.0	6.0	9.8	9.8	9.8
—	—	—	—	—	145 (90)
—	—	—	—	—	—
—	—	—	—	—	32 (20)
—	—	—	—	—	59 (37)
—	—	—	—	—	96 (60)
—	—	—	—	—	138 (86)
5.0 (16.4)	5.0 (16.4)	5.0 (16.4)	6.2 (20.3)	6.2 (20.3)	6.2 (20.3)
5.7 (18.7)	5.7 (18.7)	5.7 (18.7)	6.9 (22.6)	6.9 (22.6)	6.9 (22.6)
1KD-FTV	1KD-FTV	1KD-FTV	1KD-FTV	1KD-FTV	2KD-FTV
16-valve, DOHC	16-valve, DOHC	16-valve, DOHC	16-valve, DOHC	16-valve, DOHC	16-valve, DOHC
96.0 × 103.0 (3.78 × 4.06)	96.0 × 103.0 (3.78 × 4.06)	96.0 × 103.0 (3.78 × 4.06)	96.0 × 103.0 (3.78 × 4.06)	96.0 × 103.0 (3.78 × 4.06)	92.0 × 93.8 (3.62 × 3.69)
2982 (182.0)	2982 (182.0)	2982 (182.0)	2982 (182.0)	2982 (182.0)	2494 (152.2)
15.0 : 1	16.0 : 1	16.0 : 1	16.0 : 1	16.0 : 1	18.5 : 1
Common-rail Type	Common-rail Type	Common-rail Type	Common-rail Type	Common-rail Type	Common-rail Type
48 or higher	48 or higher	48 or higher	48 or higher	48 or higher	48 or higher
106/3400	100/3400	100/3400	100/3400	100/3400	75/3600
300/1200 - 3200	300/1200 - 2400	300/1200 - 2400	300/1200 - 2400	300/1200 - 2400	260/1600 - 2400
12 - 55	12 - 60	12 - 60	12 - 60	12 - 60	12 - 55, 12 - 55 × 2*2
1560	1560	1560	1560	1560	1200, 1560*2
2.2	2.2	2.7	2.2	2.7	2.0
—	Dry, Single Plate, Diaphragm	—	Dry, Single Plate, Diaphragm	—	Dry, Single Plate, Diaphragm
A340E	R351	A340E	R351	A340E	R351
2.804	4.313	2.804	4.313	2.804	4.313
1.531	2.330	1.531	2.330	1.531	2.330
1.000	1.436	1.000	1.436	1.000	1.436
0.705	1.000	0.705	1.000	0.705	1.000
—	0.838	—	0.838	—	0.838
2.393	4.220	2.393	4.220	2.393	4.220
4.100	3.727	4.100	3.727	4.100	4.100
205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)
Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum
Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
Single with BA 10”	Single, Single with BA*3 10”	Single, Single with BA*3 10”	Single with BA 10”	Single, Single with BA*3 10”	Single, Single with BA*3 10”
LSP and BV	LSP and BV	LSP and BV	LSP and BV	LSP and BV	LSP and BV
Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid
Standard	Standard	Standard	Standard	Standard	Standard
—	—	—	—	—	—
Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
20.84	20.84	20.84	20.84	20.84	20.84
Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

Item \ Area				General Countries			
Body Type				4-door Van (Standard)		5-door Van (Standard)	4-door Commuter (Standard)
Vehicle Grade				DX			GL
Model Code				LH200R-RBMDE	LH200L-RBMDE	LH200R-SBMDE	TRH213L-JDMNK
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	4695 (184.8)	4695 (184.8)	4695 (184.8)	4840 (190.6)
		Width	mm (in.)	1695 (66.7)	1695 (66.7)	1695 (66.7)	1880 (74.0)
		Height	mm (in.)	1980 (78.0)	1980 (78.0)	1980 (78.0)	2105 (82.9)
	Wheel Base		mm (in.)	2570 (101.2)	2570 (101.2)	2570 (101.2)	2570 (101.2)
	Tread	Front	mm (in.)	1470 (57.9)	1470 (57.9)	1470 (57.9)	1655 (65.2)
		Rear	mm (in.)	1465 (57.7)	1465 (57.7)	1465 (57.7)	1650 (65.0)
	Room	Length	mm (in.)	910 (35.8)	910 (35.8)	910 (35.8)	3525 (138.8)
		Width	mm (in.)	1545 (60.8)	1545 (60.8)	1545 (60.8)	1695 (66.7)
		Height	mm (in.)	1320 (52.0)	1320 (52.0)	1320 (52.0)	1390 (54.7)
	Cargo Space	Length	mm (in.)	2930 (115.4)	2930 (115.4)	2930 (115.4)	—
		Width	mm (in.)	1545 (60.8)	1545 (60.8)	1545 (60.8)	—
		Height	mm (in.)	1335 (52.6)	1335 (52.6)	1335 (52.6)	—
	Overhang	Front	mm (in.)	1050 (41.3)	1050 (41.3)	1050 (41.3)	1190 (46.9)
		Rear	mm (in.)	1075 (42.3)	1075 (42.3)	1075 (42.3)	1080 (42.5)
	Min. Running Ground Clearance		mm (in.)	195 (7.7)	195 (7.7)	195 (7.7)	185 (7.3)
	Angle of Approach		degrees	18.5	18.5	18.5	16.6
	Angle of Departure		degrees	19.5	19.5	19.5	19.7
	Curb Weight	Front	kg (lb)	1025 - 1090 (2260 - 2403)	1025 - 1090 (2260 - 2403)	1035 - 1100 (2282 - 2425)	1115 (2458)*1, 1065 - 1085 (2348 - 2392)*2
		Rear	kg (lb)	690 - 700 (1521 - 1543)	690 - 700 (1521 - 1543)	705 - 715 (1554 - 1576)	805 (1775)*1, 850 - 855 (1874 - 1885)*2
		Total	kg (lb)	1715 - 1790 (3781 - 3946)	1715 - 1790 (3781 - 3946)	1740 - 1815 (3836 - 4001)	1920 (4233)*1, 1915 - 1940 (4222 - 4277)*2
	Gross Vehicle Weight	Front	kg (lb)	1385 - 1435 (3053 - 3164)	1385 - 1435 (3053 - 3146)	1390 - 1440 (3064 - 3175)	1350 (2976)*1, 1410 - 1425 (3108 - 3142)*2
		Rear	kg (lb)	1365 - 1415 (3009 - 3120)	1365 - 1415 (3009 - 3120)	1360 - 1410 (2998 - 3108)	1400 (3086)*1, 1575 - 1590 (3472 - 3505)*2
		Total	kg (lb)	2800 (6173)	2800 (6173)	2800 (6173)	2750 (6063)*1, 3000 (6614)*2
	Fuel Tank Capacity		ℓ (Imp.gal.)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)
	Luggage Compartment Capacity		m^3 (cu.ft.)	6.0	6.0	6.0	—
Performance	Max. Speed		km/h (mph)	140 (87)	140 (87)	140 (87)	145 (90)
	Max. Cruising Speed		km/h (mph)	—	—	—	—
	Max. Permissible Speed	1st Gear	km/h (mph)	29 (18)	29 (18)	29 (18)	38 (24)
		2nd Gear	km/h (mph)	50 (31)	50 (31)	50 (31)	70 (43)
		3rd Gear	km/h (mph)	86 (53)	86 (53)	86 (53)	114 (71)
		4th Gear	km/h (mph)	131 (81)	131 (81)	131 (81)	163 (101)
	Min. Turning Radius	Tire	m (ft.)	5.0 (16.4)	5.0 (16.4)	5.0 (16.4)	5.3 (17.4)
		Body	m (ft.)	5.7 (18.7)	5.7 (18.7)	5.7 (18.7)	5.9 (19.4)
Engine	Engine Type			5L-E	5L-E	5L-E	2TR-FE
	Valve Mechanism			8-valve, OHC	8-valve, OHC	8-valve, OHC	16-valve, DOHC with VVT-i
	Bore × Stroke		mm (in.)	99.5 × 96.0 (3.92 × 3.78)	99.5 × 96.0 (3.92 × 3.78)	99.5 × 96.0 (3.92 × 3.78)	95.0 × 95.0 (3.74 × 3.74)
	Displacement		cm^3 (cu.in.)	2986 (182.2)	2986 (182.2)	2986 (182.2)	2694 (164.4)
	Compression Ratio			22.2 : 1	22.2 : 1	22.2 : 1	9.6 : 1
	Fuel System			Distributor Type	Distributor Type	Distributor Type	EFI
	Research Octane No. or Cetane No. (Diesel)			48 or higher	48 or higher	48 or higher	91 or higher
	Max. Output (EEC)		kW/rpm	68/4000	68/4000	68/4000	111/4800
	Max. Torque (EEC)		N·m/rpm	197/2400	197/2400	197/2400	241/3800
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp.hr.	12 - 60, 12 - 55 × 2*3	12 - 60, 12 - 55 × 2*3	12 - 60, 12 - 55 × 2*3	12 - 55, 12 - 48*3
	Alternator Output		Watts	1440	1440	1440	1560
	Starter Output		kW	2.2, 2.7*4	2.2, 2.7*4	2.2, 2.7*4	2.0, 1.6*3
Chassis	Clutch Type			Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm
	Transmission Type			G55	G55	G55	R351
	Gear Ratio	In First		4.452	4.452	4.452	4.313
		In Second		2.619	2.619	2.619	2.330
		In Third		1.517	1.517	1.517	1.436
		In Fourth		1.000	1.000	1.000	1.000
		In Fifth		0.854	0.854	0.854	0.838
		In Reverse		4.472	4.472	4.472	4.220
	Differential Gear Ratio			4.300	4.300	4.300	4.300
	Differential Gear Size		mm (in.)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear		Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum
	Parking Brake Type			Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
	Brake Booster Type and Size		in.	Single, Single with BA*5 10"	Single, Single with BA*5 10"	Single, Single with BA*5 10"	Single with BA, Single*6 10"
	Proportioning Valve Type			LSP and BV	LSP and BV	LSP and BV	LSP and BV
	Suspension Type	Front		Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
		Rear		Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid
	Stabilizer Bar	Front		Standard	Standard	Standard	Standard
		Rear		—	—	—	—
	Steering Gear Type			Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
	Steering Gear Ratio (Overall)			20.84	20.84	20.84	20.84
	Power Steering Type			Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

*1: Except Models for Mexico Package
*2: Models for Mexico Package
*3: Option
*4: Cold Area Specification Model
*5: with ABS
*6: without ABS

General Countries					
4-door Commuter (Standard)				4-door Commuter (Super Long)	
DX					
TRH203R-REMDK	TRH203L-REMDK	TRH213R-JEMDK	TRH213L-JEMDK	TRH223R-LEMDK	TRH223L-LEMDK
4695 (184.8)	4695 (184.8)	4840 (190.6)	4840 (190.6)	5380 (211.8)	5380 (211.8)
1695 (66.7)	1695 (66.7)	1880 (74.0)	1880 (74.0)	1880 (74.0)	1880 (74.0)
1980 (78.0)	1980 (78.0)	2105 (82.9)	2105 (82.9)	2285 (90.0)	2285 (90.0)
2570 (101.2)	2570 (101.2)	2570 (101.2)	2570 (101.2)	3110 (122.4)	3110 (122.4)
1470 (57.9)	1470 (57.9)	1655 (65.2)	1655 (65.2)	1655 (65.2)	1655 (65.2)
1465 (57.7)	1465 (57.7)	1650 (65.0)	1650 (65.0)	1650 (65.0)	1650 (65.0)
3470 (136.6)	3470 (136.6)	3525 (138.8)	3525 (138.8)	4205 (165.6)	4205 (165.6)
1545 (60.8)	1545 (60.8)	1730 (68.1)	1695 (66.7)	1730 (68.1)	1730 (68.1)
1335 (52.6)	1335 (52.6)	1390 (54.7)	1390 (54.7)	1565 (61.6)	1565 (61.6)
—	—	—	—	—	—
—	—	—	—	—	—
—	—	—	—	—	—
1050 (41.3)	1050 (41.3)	1190 (46.9)	1190 (46.9)	1190 (46.9)	1190 (46.9)
1075 (42.3)	1075 (42.3)	1080 (42.5)	1080 (42.5)	1080 (42.5)	1080 (42.5)
185 (7.3)	185 (7.3)	185 (7.3)	185 (7.3)	185 (7.3)	185 (7.3)
18.5	18.5	16.6	16.6	17.0	17.0
19.5	19.5	19.7	19.7	19.2	19.2
975 - 1020 (2149 - 2249)	985 - 1040 (2172 - 2293)	1020 - 1070 (2249 - 2359)	1020 - 1070 (2249 - 2359)	1100 - 1165 (2425 - 2568)	1100 - 1165 (2425 - 2568)
760 - 765 (1675 - 1687)	760 - 770 (1675 - 1698)	815 - 825 (1797 - 1819)	815 - 825 (1797 - 1819)	870 - 925 (1918 - 2039)	870 - 925 (1918 - 2039)
1735 - 1785 (3825 - 3935)	1745 - 1810 (3847 - 3990)	1835 - 1895 (4045 - 4178)	1835 - 1895 (4045 - 4178)	1970 - 2090 (4343 - 4608)	1970 - 2090 (4343 - 4608)
1330 - 1365 (2932 - 3009)	1335 - 1380 (2943 - 3042)	1350 - 1390 (2976 - 3064)	1350 - 1390 (2976 - 3064)	1510 - 1545 (3329 - 3406)	1510 - 1545 (3329 - 3406)
1585 - 1620 (3494 - 3571)	1570 - 1615 (3461 - 3560)	1710 - 1750 (3770 - 3858)	1710 - 1750 (3770 - 3858)	1755 - 1790 (3869 - 3946)	1755 - 1790 (3869 - 3946)
2950 (6504)	2950 (6504)	3100 (6834)	3100 (6834)	3300 (7275)	3300 (7275)
70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)
—	—	—	—	—	—
170 (105)	170 (105)	155 (96)	155 (96)	155 (96)	155 (96)
—	—	—	—	—	—
38 (24)	38 (24)	38 (24)	38 (24)	38 (24)	38 (24)
70 (43)	70 (43)	70 (43)	70 (43)	70 (43)	70 (43)
114 (71)	114 (71)	114 (71)	114 (71)	114 (71)	114 (71)
163 (101)	163 (101)	163 (101)	163 (101)	163 (101)	163 (101)
5.0 (16.4)	5.0 (16.4)	5.3 (17.4)	5.3 (17.4)	6.2 (20.3)	6.2 (20.3)
5.7 (18.7)	5.7 (18.7)	5.9 (19.4)	5.9 (19.4)	6.9 (22.6)	6.9 (22.6)
2TR-FE	2TR-FE	2TR-FE	2TR-FE	2TR-FE	2TR-FE
16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i
95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)
2694 (164.4)	2694 (164.4)	2694 (164.4)	2694 (164.4)	2694 (164.4)	2694 (164.4)
9.6 : 1	9.6 : 1	9.6 : 1	9.6 : 1	9.6 : 1	9.6 : 1
EFI	EFI	EFI	EFI	EFI	EFI
91 or higher	91 or higher	91 or higher	91 or higher	91 or higher	91 or higher
111/4800	111/4800	111/4800	111/4800	111/4800	111/4800
241/3800	241/3800	241/3800	241/3800	241/3800	241/3800
12 - 48, 12 - 55*3	12 - 48, 12 - 55*3	12 - 48, 12 - 55*3	12 - 48, 12 - 55*3	12 - 48, 12 - 55*3	12 - 48, 12 - 55*3
1560	1560	1560	1560	1560	1560
1.6	1.6	1.6	1.6	1.6	1.6
Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm
R351	R351	R351	R351	R351	R351
4.313	4.313	4.313	4.313	4.313	4.313
2.330	2.330	2.330	2.330	2.330	2.330
1.436	1.436	1.436	1.436	1.436	1.436
1.000	1.000	1.000	1.000	1.000	1.000
0.838	0.838	0.838	0.838	0.838	0.838
4.220	4.220	4.220	4.220	4.220	4.220
4.300	4.300	4.300	4.300	4.300	4.300
205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)
Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum
Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Leading-trailing Drum	Leading-trailing Drum
Single, Single with BA*5 10”	Single, Single with BA*5 10”	Single, Single with BA*5 10”	Single, Single with BA*5 10”	Single, Single with BA*5 10”	Single, Single with BA*5 10”
LSP and BV	LSP and BV	LSP and BV	LSP and BV	LSP and BV	LSP and BV
Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid
Standard	Standard	Standard	Standard	Standard	Standard
—	—	—	—	—	—
Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
20.84	20.84	20.84	20.84	20.84	20.84
Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

Item \ Area				General Countries			
Body Type				4-door Commuter (Super Long)		4-door Commuter (Standard)	
Vehicle Grade				GL		DX	
Model Code				TRH223L-LEMNK	TRH223L-LEPNK	KDH203R-REMDY	KDH203L-RDMDY
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	5380 (211.8)	5380 (211.8)	4695 (184.8)	4695 (184.8)
		Width	mm (in.)	1880 (74.0)	1880 (74.0)	1695 (66.7)	1695 (66.7)
		Height	mm (in.)	2285 (90.0)	2285 (90.0)	1980 (78.0)	1980 (78.0)
	Wheel Base		mm (in.)	3110 (122.4)	3110 (122.4)	2570 (101.2)	2570 (101.2)
	Tread	Front	mm (in.)	1655 (65.2)	1655 (65.2)	1470 (57.9)	1470 (57.9)
		Rear	mm (in.)	1650 (65.0)	1650 (65.0)	1465 (57.7)	1465 (57.7)
	Room	Length	mm (in.)	4250 (167.3)	4250 (167.3)	4210 (165.7)	—
		Width	mm (in.)	1695 (66.7)	1695 (66.7)	1545 (60.8)	—
		Height	mm (in.)	1565 (61.6)	1565 (61.6)	1335 (52.6)	—
	Cargo Space	Length	mm (in.)	—	—	—	—
		Width	mm (in.)	—	—	—	—
		Height	mm (in.)	—	—	—	—
	Overhang	Front	mm (in.)	1190 (46.9)	1190 (46.9)	1050 (41.3)	1050 (41.3)
		Rear	mm (in.)	1080 (42.5)	1080 (42.5)	1075 (42.3)	1075 (42.3)
	Min. Running Ground Clearance		mm (in.)	185 (7.3)	185 (7.3)	185 (7.3)	185 (7.3)
	Angle of Approach		degrees	17.0	17.0	18.5	—
	Angle of Departure		degrees	19.2	19.2	19.5	—
	Curb Weight	Front	kg (lb)	1140 - 1170 (2513 - 2579)*1, 1150 - 1170 (2535 - 2579)*2	1195 (2635)	1080 - 1120 (2381 - 2469)	1090 - 1130 (2403 - 2491)
		Rear	kg (lb)	925 - 935 (2039 - 2061)*1, 915 - 920 (2017 - 2028)*2	910 (2006)	770 - 775 (1698 - 1709)	745 - 770 (1642 - 1698)
		Total	kg (lb)	2065 - 2105 (4552 - 4641)*1, 2065 - 2090 (4552 - 4608)*2	2105 (4641)	1850 - 1895 (4079 - 4178)	1835 - 1900 (4045 - 4189)
	Gross Vehicle Weight	Front	kg (lb)	1530 - 1550 (3373 - 3417)*1, 1490 - 1505 (3285 - 3318)*2	1485 (3274)	1360 - 1390 (2998 - 3064)	1430 - 1460 (3153 - 3219)
		Rear	kg (lb)	1750 - 1770 (3858 - 3902)*1, 1695 - 1710 (3737 - 3770)*2	1635 (3605)	1560 - 1590 (3439 - 3505)	1340 - 1370 (2954 - 3020)
		Total	kg (lb)	3300 (7275)*1, 3200 (7055)*2	3120 (6878)	2950 (6504)	2800 (6173)
	Fuel Tank Capacity		ℓ (Imp.gal.)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)
	Luggage Compartment Capacity		m³ (cu.ft.)	—	—	—	—
Performance	Max. Speed		km/h (mph)	155 (96)	145 (90)	145 (90)	—
	Max. Cruising Speed		km/h (mph)	—	—	—	—
	Max. Permissible Speed	1st Gear	km/h (mph)	38 (24)	54 (33)	32 (20)	—
		2nd Gear	km/h (mph)	70 (43)	98 (61)	59 (37)	—
		3rd Gear	km/h (mph)	114 (71)	150 (93)	96 (60)	—
		4th Gear	km/h (mph)	163 (101)	—	138 (86)	—
	Min. Turning Radius	Tire	m (ft.)	6.2 (20.3)	6.2 (20.3)	5.0 (16.4)	—
		Body	m (ft.)	6.9 (22.6)	6.9 (22.6)	5.7 (18.7)	—
Engine	Engine Type			2TR-FE	2TR-FE	1KD-FTV	1KD-FTV
	Valve Mechanism			16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i	16-valve, DOHC	16-valve, DOHC
	Bore × Stroke		mm (in.)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	96.0 × 103.0 (3.78 × 4.06)	96.0 × 103.0 (3.78 × 4.06)
	Displacement		cm³ (cu.in.)	2694 (164.4)	2694 (164.4)	2982 (182.0)	2982 (182.0)
	Compression Ratio			9.6 : 1	9.6 : 1	16.0 : 1	15.0 : 1
	Fuel System			EFI	EFI	Common-rail Type	Common-rail Type
	Research Octane No. or Cetane No. (Diesel)			91 or higher	91 or higher	48 or higher	48 or higher
	Max. Output (EEC)		kW/rpm	111/4800	111/4800	100/3400	106/3400
	Max. Torque (EEC)		N·m/rpm	241/3800	241/3800	300/1200 - 2400	300/1200 - 3200
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp.hr.	12 - 48, 12 - 55*3	12 - 55	12 - 60	12 - 55, 12 - 55 × 2*3
	Alternator Output		Watts	1560	1560	1560	1560
	Starter Output		kW	1.6, 2.0*3	2.0	2.2	2.2, 2.7*4
Chassis	Clutch Type			Dry, Single Plate, Diaphragm	—	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm
	Transmission Type			R351	A343E	R351	R351
	Gear Ratio	In First		4.313	2.804	4.313	4.313
		In Second		2.330	1.531	2.330	2.330
		In Third		1.436	1.000	1.436	1.436
		In Fourth		1.000	0.753	1.000	1.000
		In Fifth		0.838	—	0.838	0.838
		In Reverse		4.220	2.393	4.220	4.220
	Differential Gear Ratio			4.300	4.556	3.727	3.727
	Differential Gear Size		mm (in.)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear		Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum
	Parking Brake Type			Leading-trailing Drum, Duo-servo Drum*5	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
	Brake Booster Type and Size		in.	Single, Single with BA*6 10"	Single with BA 10"	Single, Single with BA*6 10"	Single, Single with BA*6 10"
	Proportioning Valve Type			LSP and BV	LSP and BV	LSP and BV	LSP and BV
	Suspension Type	Front		Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
		Rear		Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid
	Stabilizer Bar	Front		Standard	Standard	Standard	Standard
		Rear		—	—	—	—
	Steering Gear Type			Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
	Steering Gear Ratio (Overall)			20.84	20.84	20.84	20.84
	Power Steering Type			Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

*1: Except Models for Mexico Package
*2: Models for Mexico Package
*3: Option
*4: Cold Area Specification Model
*5: Models for China package
*6: with ABS

General Countries					
4-door Commuter (Standard)					
DX					GL
KDH202R-REMDY	KDH202L-REMDY	KDH202L-RDMDY	KDH212R-JEMDY	KDH212L-JEMDY	KDH212L-JDMNY
4695 (184.8)	4695 (184.8)	4695 (184.8)	4840 (190.6)	4840 (190.6)	4840 (190.6)
1695 (66.7)	1695 (66.7)	1695 (66.7)	1880 (74.0)	1880 (74.0)	1880 (74.0)
1980 (78.0)	1980 (78.0)	1980 (78.0)	2105 (82.9)	2105 (82.9)	2105 (82.9)
2570 (101.2)	2570 (101.2)	2570 (101.2)	2570 (101.2)	2570 (101.2)	2570 (101.2)
1470 (57.9)	1470 (57.9)	1470 (57.9)	1655 (65.2)	1655 (65.2)	1655 (65.2)
1465 (57.7)	1465 (57.7)	1465 (57.7)	1650 (65.0)	1650 (65.0)	1650 (65.0)
3470 (136.6)	3470 (136.6)	3460 (136.2)	3525 (138.8)	3525 (138.8)	3525 (138.8)
1545 (60.8)	1545 (60.8)	1545 (60.8)	1695 (66.7)	1695 (66.7)	1695 (66.7)
1335 (52.6)	1335 (52.6)	1335 (52.6)	1390 (54.7)	1390 (54.7)	1390 (54.7)
—	—	—	—	—	—
—	—	—	—	—	—
—	—	—	—	—	—
1050 (41.3)	1050 (41.3)	1050 (41.3)	1190 (46.9)	1190 (46.9)	1190 (46.9)
1075 (42.3)	1075 (42.3)	1075 (42.3)	1080 (42.5)	1080 (42.5)	1080 (42.5)
185 (7.3)	185 (7.3)	185 (7.3)	185 (7.3)	185 (7.3)	185 (7.3)
18.5	18.5	18.5	16.6	16.6	16.6
19.5	19.5	19.5	19.7	19.7	19.7
1065 - 1135 (2348 - 2502)	1070 - 1140 (2359 - 2513)	1070 - 1140 (2359 - 2513)	1110 - 1155 (2447 - 2546)	1115 - 1160 (2458 - 2557)	1130 - 1170 (2491 - 2579)
770 - 785 (1698 - 1731)	770 - 785 (1698 - 1731)	745 - 760 (1642 - 1675)	825 - 830 (1819 - 1830)	825 - 830 (1819 - 1830)	840 - 845 (1852 - 1863)
1835 - 1920 (4045 - 4233)	1840 - 1925 (4056 - 4244)	1815 - 1900 (4001 - 4189)	1935 - 1985 (4266 - 4376)	1940 - 1990 (4277 - 4387)	1970 - 2015 (4343 - 4442)
1420 - 1470 (3131 - 3241)	1420 - 1475 (3131 - 3252)	1415 - 1470 (3120 - 3241)	1430 - 1470 (3153 - 3241)	1435 - 1470 (3164 - 3241)	1415 - 1445 (3120 - 3186)
1580 - 1630 (3483 - 3593)	1575 - 1630 (3472 - 3593)	1330 - 1385 (2932 - 3053)	1680 - 1720 (3704 - 3792)	1680 - 1715 (3704 - 3781)	1455 - 1485 (3208 - 3274)
3050 (6724)	3050 (6724)	2800 (6173)	3150 (6945)	3150 (6945)	2900 (6393)
70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)
—	—	—	—	—	—
145 (90)	145 (90)	145 (90)	135 (84)	135 (84)	135 (84)
—	—	—	—	—	—
32 (20)	32 (20)	32 (20)	32 (20)	32 (20)	32 (20)
59 (37)	59 (37)	59 (37)	59 (37)	59 (37)	59 (37)
96 (60)	96 (60)	96 (60)	96 (60)	96 (60)	96 (60)
138 (86)	138 (86)	138 (86)	138 (86)	138 (86)	138 (86)
5.0 (16.4)	5.0 (16.4)	5.0 (16.4)	5.3 (17.4)	5.3 (17.4)	5.3 (17.4)
5.7 (18.7)	5.7 (18.7)	5.7 (18.7)	5.9 (19.4)	5.9 (19.4)	5.9 (19.4)
2KD-FTV	2KD-FTV	2KD-FTV	2KD-FTV	2KD-FTV	2KD-FTV
16-valve, DOHC	16-valve, DOHC	16-valve, DOHC	16-valve, DOHC	16-valve, DOHC	16-valve, DOHC
92.0 × 93.8 (3.62 × 3.69)	92.0 × 93.8 (3.62 × 3.69)	92.0 × 93.8 (3.62 × 3.69)	92.0 × 93.8 (3.62 × 3.69)	92.0 × 93.8 (3.62 × 3.69)	92.0 × 93.8 (3.62 × 3.69)
2494 (152.2)	2494 (152.2)	2494 (152.2)	2494 (152.2)	2494 (152.2)	2494 (152.2)
18.5 : 1	18.5 : 1	18.5 : 1	18.5 : 1	18.5 : 1	18.5 : 1
Common-rail Type	Common-rail Type	Common-rail Type	Common-rail Type	Common-rail Type	Common-rail Type
48 or higher	48 or higher	48 or higher	48 or higher	48 or higher	48 or higher
75/3600	75/3600	75/3600	75/3600	75/3600	75/3600
260/1600 - 2400	260/1600 - 2400	260/1600 - 2400	260/1600 - 2400	260/1600 - 2400	260/1600 - 2400
12 - 55, 12 - 55 × 2*3	12 - 55, 12 - 55 × 2*3	12 - 55, 12 - 55 × 2*3	12 - 55, 12 - 55 × 2*3	12 - 55, 12 - 55 × 2*3	12 - 55
1200, 1560*3	1200, 1560*3	1200, 1560*3	1200, 1560*3	1200, 1560*3	1560
2.0, 2.7*4	2.0, 2.7*4	2.0, 2.7*4	2.0	2.0	2.0
Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm
R351	R351	R351	R351	R351	R351
4.313	4.313	4.313	4.313	4.313	4.313
2.330	2.330	2.330	2.330	2.330	2.330
1.436	1.436	1.436	1.436	1.436	1.436
1.000	1.000	1.000	1.000	1.000	1.000
0.838	0.838	0.838	0.838	0.838	0.838
4.220	4.220	4.220	4.220	4.220	4.220
4.100	4.100	4.100	4.100	4.100	4.100
205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)
Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum
Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
Single, Single with BA*6 10”	Single, Single with BA*6 10”	Single, Single with BA*6 10”	Single, Single with BA*6 10”	Single, Single with BA*6 10”	Single, Single with BA*6 10”
LSP and BV	LSP and BV	LSP and BV	LSP and BV	LSP and BV	LSP and BV
Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid
Standard	Standard	Standard	Standard	Standard	Standard
—	—	—	—	—	—
Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
20.84	20.84	20.84	20.84	20.84	20.84
Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

Item \ Area				General Countries			
Body Type				5-door Commuter (Standard)	4-door Commuter (Super Long)		4-door Commuter (Standard)
Vehicle Grade				GL	DX		
Model Code				KDH212L-KDPNY	KDH222R-LEMDY	KDH222L-LEMDY	LH202R-REMDE
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	4840 (190.6)	5380 (211.8)	5380 (211.8)	4695 (184.8)
		Width	mm (in.)	1880 (74.0)	1880 (74.0)	1880 (74.0)	1695 (66.7)
		Height	mm (in.)	2105 (82.9)	2285 (90.0)	2285 (90.0)	1980 (78.0)
	Wheel Base		mm (in.)	2570 (101.2)	3110 (122.4)	3110 (122.4)	2570 (101.2)
	Tread	Front	mm (in.)	1655 (65.2)	1655 (65.2)	1655 (65.2)	1470 (57.9)
		Rear	mm (in.)	1650 (65.0)	1650 (65.0)	1650 (65.0)	1465 (57.7)
	Room	Length	mm (in.)	3525 (138.8)	4205 (165.6)	4205 (165.6)	4210 (165.7)
		Width	mm (in.)	1695 (66.7)	1730 (68.1)	1730 (68.1)	1545 (52.6)
		Height	mm (in.)	1390 (54.7)	1565 (61.6)	1565 (61.6)	1335 (52.6)
	Cargo Space	Length	mm (in.)	—	—	—	—
		Width	mm (in.)	—	—	—	—
		Height	mm (in.)	—	—	—	—
	Overhang	Front	mm (in.)	1190 (46.9)	1190 (46.9)	1190 (46.9)	1050 (41.3)
		Rear	mm (in.)	1080 (42.5)	1080 (42.5)	1080 (42.5)	1075 (42.3)
	Min. Running Ground Clearance		mm (in.)	185 (7.3)	185 (7.3)	185 (7.3)	185 (7.3)
	Angle of Approach		degrees	16.6	17.0	17.0	18.5
	Angle of Departure		degrees	19.7	19.2	19.2	19.5
	Curb Weight	Front	kg (lb)	1180 - 1210 (2601 - 2668)	1160 - 1220 (2557 - 2690)	1160 - 1220 (2557 - 2690)	1030 - 1100 (2271 - 2425)
		Rear	kg (lb)	875 - 880 (1929 - 1940)	870 - 925 (1918 - 2039)	870 - 925 (1918 - 2039)	765 - 780 (1687 - 1720)
		Total	kg (lb)	2055 - 2090 (4530 - 4608)	2030 - 2145 (4475 - 4729)	2030 - 2145 (4475 - 4729)	1795 - 1880 (3957 - 4145)
	Gross Vehicle Weight	Front	kg (lb)	1345 - 1370 (2965 - 3020)	1555 - 1590 (3428 - 3505)	1555 - 1590 (3428 - 3505)	1380 - 1435 (3042 - 3164)
		Rear	kg (lb)	1530 - 1555 (3373 - 3428)	1710 - 1745 (3770 - 3847)	1710 - 1745 (3770 - 3847)	1565 - 1620 (3450 - 3571)
		Total	kg (lb)	2900 (6393)	3300 (7275)	3300 (7275)	3000 (6614)
	Fuel Tank Capacity		ℓ (Imp.gal.)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)
	Luggage Compartment Capacity		m^3 (cu.ft.)	—	—	—	—
Performance	Max. Speed		km/h (mph)	135 (84)	140 (87)	135 (84)	140 (87)
	Max. Cruising Speed		km/h (mph)	—	—	—	—
	Max. Permissible Speed	1st Gear	km/h (mph)	48 (30)	32 (20)	32 (20)	29 (18)
		2nd Gear	km/h (mph)	88 (55)	59 (37)	59 (37)	50 (31)
		3rd Gear	km/h (mph)	135 (84)	96 (60)	96 (60)	86 (53)
		4th Gear	km/h (mph)	—	138 (86)	138 (86)	131 (81)
	Min. Turning Radius	Tire	m (ft.)	5.3 (17.4)	6.2 (20.3)	6.2 (20.3)	5.0 (16.4)
		Body	m (ft.)	5.9 (19.4)	6.9 (22.6)	6.9 (22.6)	5.7 (18.7)
Engine	Engine Type			2KD-FTV	2KD-FTV	2KD-FTV	5L-E
	Valve Mechanism			16-valve, DOHC	16-valve, DOHC	16-valve, DOHC	8-valve, OHC
	Bore × Stroke		mm (in.)	92.0 × 93.8 (3.62 × 3.69)	92.0 × 93.8 (3.62 × 3.69)	92.0 × 93.8 (3.62 × 3.69)	99.5 × 96.0 (3.92 × 3.78)
	Displacement		cm^3 (cu.in.)	2494 (152.2)	2494 (152.2)	2494 (152.2)	2986 (182.2)
	Compression Ratio			18.5 : 1	18.5 : 1	18.5 : 1	22.2 : 1
	Fuel System			Common-rail Type	Common-rail Type	Common-rail Type	Distributor Type
	Research Octane No. or Cetane No. (Diesel)			48 or higher	48 or higher	48 or higher	48 or higher
	Max. Output (EEC)		kW/rpm	75/3600	75/3600	75/3600	68/4000
	Max. Torque (EEC)		N·m/rpm	260/1600 - 2400	260/1600 - 2400	260/1600 - 2400	197/2400
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp.hr.	12 - 55	12 - 55	12 - 55, 12 - 55 × 2*1	12 - 60, 12 - 55 × 2*1
	Alternator Output		Watts	1560	1200, 1560*1	1200, 1560*1	1440
	Starter Output		kW	2.7	2.0	2.0	2.2, 2.7*2
Chassis	Clutch Type			—	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm
	Transmission Type			A340E	R351	R351	G55
	Gear Ratio	In First		2.804	4.313	4.313	4.452
		In Second		1.531	2.330	2.330	2.619
		In Third		1.000	1.436	1.436	1.517
		In Fourth		0.705	1.000	1.000	1.000
		In Fifth		—	0.838	0.838	0.854
		In Reverse		2.393	4.220	4.220	4.472
	Differential Gear Ratio			4.100	4.100	4.100	4.300
	Differential Gear Size		mm (in.)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear		Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum
	Parking Brake Type			Duo-servo Drum	Leading-trailing Drum	Leading-trailing Drum	Duo-servo Drum
	Brake Booster Type and Size		in.	Single with BA 10"	Single, Single with BA*3 10"	Single, Single with BA*3 10"	Single, Single with BA*3 10"
	Proportioning Valve Type			LSP and BV	LSP and BV	LSP and BV	LSP and BV
	Suspension Type	Front		Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
		Rear		Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid
	Stabilizer Bar	Front		Standard	Standard	Standard	Standard
		Rear		—	—	—	—
	Steering Gear Type			Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
	Steering Gear Ratio (Overall)			20.84	20.84	20.84	20.84
	Power Steering Type			Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

*1: Option
*2: Cold Area Specification Model
*3: with ABS

General Countries					
4-door Commuter (Standard)				4-door Commuter (Super Long)	
DX					
LH202L-REMDE	LH202L-RDMDE	LH212R-JEMDE	LH212L-JEMDE	LH222R-LEMDE	LH222L-LEMDE
4695 (184.8)	4695 (184.8)	4840 (190.6)	4840 (190.6)	5380 (211.8)	5380 (211.8)
1695 (66.7)	1695 (66.7)	1880 (74.0)	1880 (74.0)	1880 (74.0)	1880 (74.0)
1980 (78.0)	1980 (78.0)	2105 (82.9)	2105 (82.9)	2285 (90.0)	2285 (90.0)
2570 (101.2)	2570 (101.2)	2570 (101.2)	2570 (101.2)	3110 (122.4)	3110 (122.4)
1470 (57.9)	1470 (57.9)	1655 (65.2)	1655 (65.2)	1655 (65.2)	1655 (65.2)
1465 (57.7)	1465 (57.7)	1650 (65.0)	1650 (65.0)	1650 (65.0)	1650 (65.0)
4210 (165.7)	4210 (165.7)	3460 (136.2)	3460 (136.2)	4205 (165.6)	4205 (165.6)
1545 (60.8)	1545 (60.8)	1730 (68.1)	1730 (68.1)	1730 (68.1)	1730 (68.1)
1335 (52.6)	1335 (52.6)	1390 (54.7)	1390 (54.7)	1565 (61.6)	1565 (61.6)
—	—	—	—	—	—
—	—	—	—	—	—
—	—	—	—	—	—
1050 (41.3)	1050 (41.3)	1190 (46.9)	1190 (46.9)	1190 (46.9)	1190 (46.9)
1075 (42.3)	1075 (42.3)	1080 (42.5)	1080 (42.5)	1080 (42.5)	1080 (42.5)
185 (7.3)	185 (7.3)	185 (7.3)	185 (7.3)	185 (7.3)	185 (7.3)
18.5	18.5	16.6	16.6	17.0	17.0
19.5	19.5	19.7	19.7	19.2	19.2
1035 - 1105 (2282 - 2436)	1030 - 1100 (2271 - 2425)	1075 - 1110 (2370 - 2447)	1075 - 1120 (2370 - 2469)	1155 - 1215 (2546 - 2679)	1155 - 1215 (2546 - 2679)
765 - 780 (1687 - 1720)	740 - 755 (1631 - 1664)	825 - 830 (1819 - 1830)	825 - 830 (1819 - 1830)	870 - 925 (1918 - 2039)	870 - 925 (1918 - 2039)
1800 - 1885 (3968 - 4156)	1770 - 1855 (3902 - 4090)	1900 - 1940 (4189 - 4277)	1900 - 1950 (4189 - 4299)	2025 - 2140 (4464 - 4718)	2025 - 2140 (4464 - 4718)
1385 - 1440 (3053 - 3175)	1385 - 1440 (3053 - 3175)	1405 - 1430 (3097 - 3153)	1405 - 1440 (3097 - 3175)	1555 - 1585 (3428 - 3494)	1555 - 1585 (3428 - 3494)
1560 - 1615 (3439 - 3560)	1360 - 1415 (2998 - 3120)	1720 - 1745 (3792 - 3847)	1710 - 1745 (3770 - 3847)	1715 - 1745 (3781 - 3847)	1715 - 1745 (3781 - 3847)
3000 (6614)	2800 (6173)	3150 (6945)	3150 (6945)	3300 (7275)	3300 (7275)
70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)
—	—	—	—	—	—
140 (87)	140 (87)	130 (81)	130 (81)	130 (81)	130 (81)
—	—	—	—	—	—
29 (18)	29 (18)	29 (18)	29 (18)	29 (18)	29 (18)
50 (31)	50 (31)	50 (31)	50 (31)	50 (31)	50 (31)
86 (53)	86 (53)	86 (53)	86 (53)	86 (53)	86 (53)
131 (81)	131 (81)	131 (81)	131 (81)	131 (81)	131 (81)
5.0 (16.4)	5.0 (16.4)	5.3 (17.4)	5.3 (17.4)	6.2 (20.3)	6.2 (20.3)
5.7 (18.7)	5.7 (18.7)	5.9 (19.4)	5.9 (19.4)	6.9 (22.6)	6.9 (22.6)
5L-E	5L-E	5L-E	5L-E	5L-E	5L-E
8-valve, OHC	8-valve, OHC	8-valve, OHC	8-valve, OHC	8-valve, OHC	8-valve, OHC
99.5 × 96.0 (3.92 × 3.78)	99.5 × 96.0 (3.92 × 3.78)	99.5 × 96.0 (3.92 × 3.78)	99.5 × 96.0 (3.92 × 3.78)	99.5 × 96.0 (3.92 × 3.78)	99.5 × 96.0 (3.92 × 3.78)
2986 (182.2)	2986 (182.2)	2986 (182.2)	2986 (182.2)	2986 (182.2)	2986 (182.2)
22.2 : 1	22.2 : 1	22.2 : 1	22.2 : 1	22.2 : 1	22.2 : 1
Distributor Type	Distributor Type	Distributor Type	Distributor Type	Distributor Type	Distributor Type
48 or higher	48 or higher	48 or higher	48 or higher	48 or higher	48 or higher
68/4000	68/4000	68/4000	68/4000	68/4000	68/4000
197/2400	197/2400	197/2400	197/2400	197/2400	197/2400
12 - 60, 12 - 55 × 2*1	12 - 60, 12 - 55 × 2*1	12 - 60, 12 - 55 × 2*1	12 - 60, 12 - 55 × 2*1	12 - 60, 12 - 55 × 2*1	12 - 60, 12 - 55 × 2*1
1440	1440	1440	1440	1440	1440
2.2, 2.7*2	2.2, 2.7*2	2.2	2.2	2.2	2.2
Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm
G55	G55	G55	G55	G55	G55
4.452	4.452	4.452	4.452	4.452	4.452
2.619	2.619	2.619	2.619	2.619	2.619
1.517	1.517	1.517	1.517	1.517	1.517
1.000	1.000	1.000	1.000	1.000	1.000
0.854	0.854	0.854	0.854	0.854	0.854
4.472	4.472	4.472	4.472	4.472	4.472
4.300	4.300	4.300	4.300	4.300	4.300
205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)
Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum
Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Leading-trailing Drum	Leading-trailing Drum
Single, Single with BA*3 10”	Single, Single with BA*3 10”	Single 10”	Single, Single with BA*3 10”	Single, Single with BA*3 10”	Single, Single with BA*3 10”
LSP and BV	LSP and BV	LSP and BV	LSP and BV	LSP and BV	LSP and BV
Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid
Standard	Standard	Standard	Standard	Standard	Standard
—	—	—	—	—	—
Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
20.84	20.84	20.84	20.84	20.84	20.84
Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

Item \ Area				General Countries
Body Type				5-door Van (Standard)
Vehicle Grade				DX
Model Code				TRH200R-SSPDK
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	4695 (184.8)
		Width	mm (in.)	1695 (66.7)
		Height	mm (in.)	1980 (78.0)
	Wheel Base		mm (in.)	2570 (101.2)
	Tread	Front	mm (in.)	1470 (57.9)
		Rear	mm (in.)	1465 (57.7)
	Room	Length	mm (in.)	910 (35.8)
		Width	mm (in.)	1545 (60.8)
		Height	mm (in.)	1320 (52.0)
	Cargo Space	Length	mm (in.)	2930 (115.4)
		Width	mm (in.)	1545 (60.8)
		Height	mm (in.)	1335 (52.6)
	Overhang	Front	mm (in.)	1050 (41.3)
		Rear	mm (in.)	1075 (42.3)
	Min. Running Ground Clearance		mm (in.)	195 (7.7)
	Angle of Approach		degrees	18.5
	Angle of Departure		degrees	19.5
	Curb Weight	Front	kg (lb)	1030 - 1040 (2271 - 2293)
		Rear	kg (lb)	720 (1587)
		Total	kg (lb)	1750 - 1760 (3858 - 3880)
	Gross Vehicle Weight	Front	kg (lb)	1355 - 1365 (3858 - 3880)
		Rear	kg (lb)	1435 - 1450 (3164 - 3009)
		Total	kg (lb)	2800 (6173)
	Fuel Tank Capacity		ℓ (Imp.gal.)	70 (15.4)
	Luggage Compartment Capacity		m^3 (cu.ft.)	6.0
Performance	Max. Speed		km/h (mph)	170 (105)
	Max. Cruising Speed		km/h (mph)	—
	Max. Permissible Speed	1st Gear	km/h (mph)	54 (34)
		2nd Gear	km/h (mph)	102 (64)
		3rd Gear	km/h (mph)	152 (96)
		4th Gear	km/h (mph)	—
	Min. Turning Radius	Tire	m (ft.)	5.0 (16.4)
		Body	m (ft.)	5.7 (18.7)
Engine	Engine Type			1TR-FE
	Valve Mechanism			16-valve, DOHC with VVT-i
	Bore × Stroke		mm (in.)	86.0 × 86.0 (3.39 × 3.39)
	Displacement		cm^3 (cu.in.)	1998 (121.9)
	Compression Ratio			9.8 : 1
	Fuel System			EFI
	Research Octane No. or Cetane No. (Diesel)			91 or higher
	Max. Output (EEC)		kW/rpm	98/5600
	Max. Torque (EEC)		N·m/rpm	182/4000
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp.hr.	12 - 48
	Alternator Output		Watts	1560
	Starter Output		kW	1.0
Chassis	Clutch Type			—
	Transmission Type			A45DE
	Gear Ratio	In First		2.826
		In Second		1.493
		In Third		1.000
		In Fourth		0.730
		In Fifth		—
		In Reverse		2.703
	Differential Gear Ratio			5.125
	Differential Gear Size		mm (in.)	205 (8.07)
	Brake Type	Front		Ventilated Disc
		Rear		Leading-trailing Drum
	Parking Brake Type			Duo-servo Drum
	Brake Booster Type and Size		in.	Single with BA 10”
	Proportioning Valve Type			LSP and BV
	Suspension Type	Front		Double Wishbone
		Rear		Leaf Spring, Rigid
	Stabilizer Bar	Front		Standard
		Rear		—
	Steering Gear Type			Rack and Pinion
	Steering Gear Ratio (Overall)			20.84
	Power Steering Type			Hydraulic Type