MAJOR TECHNICAL SPECIFICATIONS

Item \ Area				Australia			
Body Type				4-door Van (Standard)		5-door Van (Super Long)	
Vehicle Grade				DX			
Model Code				TRH201R-RBMDKQ	TRH201R-RBTDKQ	TRH221R-MBMDKQ	TRH221R-MBTDKQ
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	4695 (184.8)	4695 (184.8)	5380 (211.8)	5380 (211.8)
		Width	mm (in.)	1695 (66.7)	1695 (66.7)	1880 (74.0)	1880 (74.0)
		Height	mm (in.)	1980 (78.0)	1980 (78.0)	2285 (90.0)	2285 (90.0)
	Wheel Base		mm (in.)	2570 (101.2)	2570 (101.2)	3110 (122.4)	3110 (122.4)
	Tread	Front	mm (in.)	1470 (57.9)	1470 (57.9)	1655 (65.2)	1655 (65.2)
		Rear	mm (in.)	1465 (57.7)	1465 (57.7)	1650 (65.0)	1650 (65.0)
	Room	Length	mm (in.)	910 (35.8)	910 (35.8)	910 (35.8)	910 (35.8)
		Width	mm (in.)	1545 (60.8)	1545 (60.8)	1730 (68.1)	1730 (68.1)
		Height	mm (in.)	1320 (52.0)	1320 (52.0)	1565 (61.6)	1565 (61.6)
	Cargo Space	Length	mm (in.)	2930 (115.4)	2930 (115.4)	3470 (136.6)	3470 (136.6)
		Width	mm (in.)	1545 (60.8)	1545 (60.8)	1730 (68.1)	1730 (68.1)
		Height	mm (in.)	1335 (52.6)	1335 (52.6)	1635 (64.4)	1635 (64.4)
	Overhang	Front	mm (in.)	1050 (41.3)	1050 (41.3)	1190 (46.9)	1190 (46.9)
		Rear	mm (in.)	1075 (42.3)	1075 (42.3)	1080 (42.5)	1080 (42.5)
	Min. Running Ground Clearance		mm (in.)	195 (7.7)	195 (7.7)	195 (7.7)	195 (7.7)
	Angle of Approach		degrees	18.5	18.5	17.5	17.5
	Angle of Departure		degrees	19.5	19.5	19.5	19.5
	Curb Weight	Front	kg (lb)	990 - 1035 (2183 - 2282)	1005 - 1050 (2216 - 2315)	1100 - 1130 (2425 - 2491)	1110 - 1140 (2447 - 2513)
		Rear	kg (lb)	675 - 685 (1488 - 1510)	675 - 685 (1488 - 1510)	755 - 760 (1664 - 1675)	760 - 765 (1675 - 1687)
		Total	kg (lb)	1665 - 1720 (3671 - 3792)	1680 - 1735 (3704 - 3825)	1855 - 1890 (4090 - 4167)	1870 - 1905 (4123 - 4200)
	Gross Vehicle Weight	Front	kg (lb)	1310 - 1345 (2888 - 2965)	1320 - 1355 (2910 - 2987)	1525 - 1545 (3362 - 3406)	1530 - 1550 (3373 - 3417)
		Rear	kg (lb)	1455 - 1490 (3208 - 3285)	1445 - 1480 (3186 - 3263)	1655 - 1675 (3649 - 3693)	1650 - 1670 (3638 - 3682)
		Total	kg (lb)	2800 (6173)	2800 (6173)	3200 (7055)	3200 (7055)
	Fuel Tank Capacity		ℓ (Imp. gal.)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)
	Luggage Compartment Capacity		m^3 (cu. ft.)	6.0	6.0	9.8	9.8
Performance	Max. Speed		km/h (mph)	170 (105)	155 (96)	155 (96)	155 (96)
	Max. Cruising Speed		km/h (mph)	—	—	—	—
	Max. Permissible Speed	1st Gear	km/h (mph)	38 (24)	41 (26)	38 (24)	41 (26)
		2nd Gear	km/h (mph)	70 (43)	70 (43)	70 (43)	70 (43)
		3rd Gear	km/h (mph)	114 (71)	98 (60)	114 (71)	98 (60)
		4th Gear	km/h (mph)	163 (101)	146 (89)	163 (101)	146 (89)
		5th Gear	km/h (mph)	—	155 (96)	—	155 (96)
		6th Gear	km/h (mph)	—	155 (96)	—	155 (96)
	Min. Turning Radius	Tire	m (ft.)	5.0 (16.4)	5.0 (16.4)	6.2 (20.3)	6.2 (20.3)
		Body	m (ft.)	5.7 (18.7)	5.7 (18.7)	6.9 (22.6)	6.9 (22.6)
Engine	Engine Type			2TR-FE	2TR-FE	2TR-FE	2TR-FE
	Valve Mechanism			16-valve, DOHC with Dual VVT-i	16-valve, DOHC with Dual VVT-i	16-valve, DOHC with Dual VVT-i	16-valve, DOHC with Dual VVT-i
	Bore × Stroke		mm (in.)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)
	Displacement		cm^3 (cu. in.)	2694 (164.3)	2694 (164.3)	2694 (164.3)	2694 (164.3)
	Compression Ratio			10.2 : 1	10.2 : 1	10.2 : 1	10.2 : 1
	Fuel System			EFI	EFI	EFI	EFI
	Research Octane No. or Cetane No. (Diesel)			91 or higher	91 or higher	91 or higher	91 or higher
	Max. Output (EEC)		kW/rpm	118/5200	118/5200	118/5200	118/5200
	Max. Torque (EEC)		N·m/rpm	243/4000	243/4000	243/4000	243/4000
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp. hr.	12 - 48	12 - 48	12 - 48	12 - 48
	Alternator Output		Watts	1560	1560	1560	1560
	Starter Output		kW	1.6	1.6	1.6	1.6
Chassis	Clutch Type			Dry, Single Plate, Diaphragm	—	Dry, Single Plate, Diaphragm	—
	Transmission Type			R351	AC60E	R351	AC60E
	Gear Ratio	In First		4.313	3.600	4.313	3.600
		In Second		2.330	2.090	2.330	2.090
		In Third		1.436	1.488	1.436	1.488
		In Fourth		1.000	1.000	1.000	1.000
		In Fifth		0.838	0.687	0.838	0.687
		In Sixth		—	0.580	—	0.580
		In Reverse		4.220	3.732	4.220	3.732
	Differential Gear Ratio			4.300	4.875	4.300	4.875
	Differential Gear Size		mm (in.)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear		Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum
	Parking Brake Type			Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
	Brake Booster Type and Size		in.	Single 10”	Single 10”	Single 10”	Single 10”
	Proportioning Valve Type			—	—	—	—
	Suspension Type	Front		Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
		Rear		Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid
	Stabilizer Bar	Front		Standard	Standard	Standard	Standard
		Rear		—	—	—	—
	Steering Gear Type			Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
	Steering Gear Ratio (Overall)			20.84	20.84	20.84	20.84
	Power Steering Type			Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

*1: 12-passenger model
*2: 5-passenger model

Australia				
4-door Commuter (Super Long)	4-door Van (Standard)		5-door Van (Standard)	
DX				
TRH223R-LETDKQ	KDH201R-RBMDYQ	KDH201R-RBPDYQ	KDH201R-SSMDYQ	KDH201R-SSPDYQ
5380 (211.8)	4695 (184.8)	4695 (184.8)	4695 (184.8)	4695 (184.8)
1880 (74.0)	1695 (66.7)	1695 (66.7)	1695 (66.7)	1695 (66.7)
2285 (90.0)	1980 (78.0)	1980 (78.0)	1980 (78.0)	1980 (78.0)
3110 (122.4)	2570 (101.2)	2570 (101.2)	2570 (101.2)	2570 (101.2)
1655 (65.2)	1470 (57.9)	1470 (57.9)	1470 (57.9)	1470 (57.9)
1650 (65.0)	1465 (57.7)	1465 (57.7)	1465 (57.7)	1465 (57.7)
4250 (167.3)	910 (35.8)	910 (35.8)	910 (35.8)	910 (35.8)
1730 (68.1)	1545 (60.8)	1545 (60.8)	1545 (60.8)	1545 (60.8)
1565 (61.6)	1320 (52.0)	1320 (52.0)	1320 (52.0)	1320 (52.0)
—	2930 (115.4)	2930 (115.4)	2930 (115.4)	2930 (115.4)
—	1545 (60.8)	1545 (60.8)	1545 (60.8)	1545 (60.8)
—	1335 (52.6)	1335 (52.6)	1335 (52.6)	1335 (52.6)
1190 (46.9)	1050 (41.3)	1050 (41.3)	1050 (41.3)	1050 (41.3)
1080 (42.5)	1075 (42.3)	1075 (42.3)	1075 (42.3)	1075 (42.3)
185 (7.3)	195 (7.7)	195 (7.7)	195 (7.7)	195 (7.7)
17.0	18.5	18.5	18.5	18.5
19.2	19.5	19.5	19.5	19.5
1160 - 1170 (2557 - 2579), 1155 - 1165 (2546 - 2568)*1	1095 - 1130 (2414 - 2491)	1105 - 1140 (2436 - 2513)	1140 - 1175 (2513 - 2590)	1150 - 1185 (2535 - 2612)
915 - 925 (2017 - 2039), 900 - 910 (1984 - 2006)*1	695 - 705 (1532 - 1554)	695 - 705 (1532 - 1554)	730 - 740 (1609 - 1631)	730 - 740 (1609 - 1631)
2075 - 2095 (4575 - 4619), 2055 - 2075 (4530 - 4575)*1	1790 - 1835 (3946 - 4045)	1800 - 1845 (3968 - 4067)	1870 - 1915 (4123 - 4222)	1880 - 1925 (4145 - 4244)
1435 - 1440 (3164 - 3175), 1460 - 1465 (3219 - 3230)*1	1390 - 1415 (3064 - 3120)	1400 - 1425 (3086 - 3142)	1395 - 1420 (3075 - 3131), 1395 - 1430 (3075 - 3153)*2	1400 - 1430 (3086 - 3153), 1405 - 1440 (3097 - 3175)*2
1710 - 1715 (3770 - 3781), 1685 - 1690 (3715 - 3726)*1	1385 - 1410 (3053 - 3108)	1375 - 1400 (3031 - 3086)	1380 - 1405 (3042 - 3097), 1370 - 1405 (3020 - 3097)*2	1370 - 1400 (3020 - 3086), 1360 - 1395 (2998 - 3075)*2
3150 (6944)	2800 (6173)	2800 (6173)	2800 (6173)	2800 (6173)
70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)
—	6.0	6.0	6.0	6.0
155 (96)	145 (90)	145 (90)	145 (90)	145 (90)
—	—	—	—	—
41 (26)	32 (20)	48 (30)	32 (20)	48 (30)
70 (43)	59 (37)	88 (55)	59 (37)	88 (55)
98 (60)	96 (60)	135 (84)	96 (60)	135 (84)
146 (89)	138 (86)	—	138 (86)	—
155 (96)	—	—	—	—
155 (96)	—	—	—	—
6.2 (20.3)	5.0 (16.4)	5.0 (16.4)	5.0 (16.4)	5.0 (16.4)
6.9 (22.6)	5.7 (18.7)	5.7 (18.7)	5.7 (18.7)	5.7 (18.7)
2TR-FE	1KD-FTV	1KD-FTV	1KD-FTV	1KD-FTV
16-valve, DOHC with Dual VVT-i	16-valve, DOHC	16-valve, DOHC	16-valve, DOHC	16-valve, DOHC
95.0 × 95.0 (3.74 × 3.74)	96.0 × 103.0 (3.78 × 4.06)	96.0 × 103.0 (3.78 × 4.06)	96.0 × 103.0 (3.78 × 4.06)	96.0 × 103.0 (3.78 × 4.06)
2694 (164.3)	2982 (182.0)	2982 (182.0)	2982 (182.0)	2982 (182.0)
10.2 : 1	15.0 : 1	15.0 : 1	15.0 : 1	15.0 : 1
EFI	Common-rail Type	Common-rail Type	Common-rail Type	Common-rail Type
91 or higher	48 or higher	48 or higher	48 or higher	48 or higher
118/5200	106/3400	106/3400	106/3400	106/3400
243/4000	300/1200 - 3200	300/1200 - 3200	300/1200 - 3200	300/1200 - 3200
12 - 48	12 - 55	12 - 55	12 - 55	12 - 55
1560	1560	1560	1560	1560
1.6	2.2	2.7	2.2	2.7
—	Dry, Single Plate, Diaphragm	—	Dry, Single Plate, Diaphragm	—
AC60E	R351	A340E	R351	A340E
3.600	4.313	2.804	4.313	2.804
2.090	2.330	1.531	2.330	1.531
1.488	1.436	1.000	1.436	1.000
1.000	1.000	0.705	1.000	0.705
0.687	0.838	—	0.838	—
0.580	—	—	—	—
3.732	4.220	2.393	4.220	2.393
4.875	3.727	4.100	3.727	4.100
205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)
Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum
Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
Single 10”	Single 10”	Single 10”	Single 10”	Single 10”
—	—	—	—	—
Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid
Standard	Standard	Standard	Standard	Standard
—	—	—	—	—
Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
20.84	20.84	20.84	20.84	20.84
Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

Item \ Area				Australia			
Body Type				5-door Van (Super Long)		4-door Commuter (Super Long)	
Vehicle Grade				DX			
Model Code				KDH221R-MBMDYQ	KDH221R-MBPDYQ	KDH223R-LEMDYQ	KDH223R-LEPDYQ
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	5380 (211.8)	5380 (211.8)	5380 (211.8)	5380 (211.8)
		Width	mm (in.)	1880 (74.0)	1880 (74.0)	1880 (74.0)	1880 (74.0)
		Height	mm (in.)	2285 (90.0)	2285 (90.0)	2285 (90.0)	2285 (90.0)
	Wheel Base		mm (in.)	3110 (122.4)	3110 (122.4)	3110 (122.4)	3110 (122.4)
	Tread	Front	mm (in.)	1655 (65.2)	1655 (65.2)	1655 (65.2)	1655 (65.2)
		Rear	mm (in.)	1650 (65.0)	1650 (65.0)	1650 (65.0)	1650 (65.0)
	Room	Length	mm (in.)	910 (35.8)	910 (35.8)	4250 (167.3)	4250 (167.3)
		Width	mm (in.)	1730 (68.1)	1730 (68.1)	1730 (68.1)	1730 (68.1)
		Height	mm (in.)	1565 (61.6)	1565 (61.6)	1565 (61.6)	1565 (61.6)
	Cargo Space	Length	mm (in.)	3470 (136.6)	3470 (136.6)	—	—
		Width	mm (in.)	1730 (68.1)	1730 (68.1)	—	—
		Height	mm (in.)	1635 (64.4)	1635 (64.4)	—	—
	Overhang	Front	mm (in.)	1190 (46.9)	1190 (46.9)	1190 (46.9)	1190 (46.9)
		Rear	mm (in.)	1080 (42.5)	1080 (42.5)	1080 (42.5)	1080 (42.5)
	Min. Running Ground Clearance		mm (in.)	195 (7.7)	195 (7.7)	185 (7.3)	185 (7.3)
	Angle of Approach		degrees	17.5	17.5	17.0	17.0
	Angle of Departure		degrees	19.5	19.5	19.2	19.2
	Curb Weight	Front	kg (lb)	1180 - 1210 (2601 - 2668)	1185 - 1215 (2612 - 2679)	1260 - 1270 (2778 - 2800)	1270 - 1280 (2800 - 2822)
		Rear	kg (lb)	800 - 805 (1764 - 1775)	805 - 810 (1775 - 1786)	925 - 935 (2039 - 2061)	925 - 935 (2039 - 2061)
		Total	kg (lb)	1980 - 2015 (4365 - 4442)	1990 - 2025 (4387 - 4464)	2185 - 2205 (4817 - 4861)	2195 - 2215 (4839 - 4883)
	Gross Vehicle Weight	Front	kg (lb)	1575 - 1595 (3472 - 3516)	1575 - 1600 (3472 - 3527)	1535 - 1540 (3384 - 3395)	1540 - 1545 (3395 - 3406)
		Rear	kg (lb)	1605 - 1625 (3538 - 3582)	1600 - 1625 (3527 - 3582)	1710 - 1715 (3770 - 3781)	1705 - 1710 (3759 - 3770)
		Total	kg (lb)	3200 (7055)	3200 (7055)	3250 (7165)	3250 (7165)
	Fuel Tank Capacity		ℓ (Imp. gal.)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)
	Luggage Compartment Capacity		m^3 (cu. ft.)	9.8	9.8	—	—
Performance	Max. Speed		km/h (mph)	140 (87)	135 (84)	140 (87)	135 (84)
	Max. Cruising Speed		km/h (mph)	—	—	—	—
	Max. Permissible Speed	1st Gear	km/h (mph)	32 (20)	48 (30)	32 (20)	48 (30)
		2nd Gear	km/h (mph)	59 (37)	88 (55)	59 (37)	88 (55)
		3rd Gear	km/h (mph)	96 (60)	135 (84)	96 (60)	135 (84)
		4th Gear	km/h (mph)	138 (86)	—	138 (86)	—
		5th Gear	km/h (mph)	—	—	—	—
		6th Gear	km/h (mph)	—	—	—	—
	Min. Turning Radius	Tire	m (ft.)	6.2 (20.3)	6.2 (20.3)	6.2 (20.3)	6.2 (20.3)
		Body	m (ft.)	6.9 (22.6)	6.9 (22.6)	6.9 (22.6)	6.9 (22.6)
Engine	Engine Type			1KD-FTV	1KD-FTV	1KD-FTV	1KD-FTV
	Valve Mechanism			16-valve, DOHC	16-valve, DOHC	16-valve, DOHC	16-valve, DOHC
	Bore × Stroke		mm (in.)	96.0 × 103.0 (3.78 × 4.06)	96.0 × 103.0 (3.78 × 4.06)	96.0 × 103.0 (3.78 × 4.06)	96.0 × 103.0 (3.78 × 4.06)
	Displacement		cm^3 (cu. in.)	2982 (182.0)	2982 (182.0)	2982 (182.0)	2982 (182.0)
	Compression Ratio			15.0 : 1	15.0 : 1	15.0 : 1	15.0 : 1
	Fuel System			Common-rail Type	Common-rail Type	Common-rail Type	Common-rail Type
	Research Octane No. or Cetane No. (Diesel)			48 or higher	48 or higher	48 or higher	48 or higher
	Max. Output (EEC)		kW/rpm	106/3400	106/3400	106/3400	106/3400
	Max. Torque (EEC)		N·m/rpm	300/1200 - 3200	300/1200 - 3200	300/1200 - 3200	300/1200 - 3200
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp. hr.	12 - 55	12 - 55	12 - 55	12 - 55
	Alternator Output		Watts	1560	1560	1560	1560
	Starter Output		kW	2.2	2.7	2.2	2.7
Chassis	Clutch Type			Dry, Single Plate, Diaphragm	—	Dry, Single Plate, Diaphragm	—
	Transmission Type			R351	A340E	R351	A340E
	Gear Ratio	In First		4.313	2.804	4.313	2.804
		In Second		2.330	1.531	2.330	1.531
		In Third		1.436	1.000	1.436	1.000
		In Fourth		1.000	0.705	1.000	0.705
		In Fifth		0.838	—	0.838	—
		In Sixth		—	—	—	—
		In Reverse		4.220	2.393	4.220	2.393
	Differential Gear Ratio			3.727	4.100	3.727	4.100
	Differential Gear Size		mm (in.)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear		Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum
	Parking Brake Type			Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
	Brake Booster Type and Size		in.	Single, Single with BA*1 10”	Single, Single with BA*1 10”	Single 10”	Single, Single with BA*1 10”
	Proportioning Valve Type			LSP and BV*1	LSP and BV*1	—	LSP and BV*1
	Suspension Type	Front		Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
		Rear		Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid
	Stabilizer Bar	Front		Standard	Standard	Standard	Standard
		Rear		—	—	—	—
	Steering Gear Type			Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
	Steering Gear Ratio (Overall)			20.84	20.84	20.84	20.84
	Power Steering Type			Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

*1: with ABS without VSC
*2: Folded seat
*3: Option

G.C.C. Countries					
5-door Van (Standard)		5-door Van (Super Long)	4-door Commuter (Standard)		
DX					
TRH201L-SBMDKV	TRH201L-SRMDKV	TRH221L-MBMDKV	TRH203L-REMDKV	TRH203L-REPDKV	TRH213L-JEMDKV
4695 (184.8)	4695 (184.8)	5380 (211.8)	4695 (184.8)	4695 (184.8)	4840 (190.6)
1695 (66.7)	1695 (66.7)	1880 (74.0)	1695 (66.7)	1695 (66.7)	1880 (74.0)
1980 (78.0)	1980 (78.0)	2285 (90.0)	1980 (78.0)	1980 (78.0)	2105 (82.9)
2570 (101.2)	2570 (101.2)	3110 (122.4)	2570 (101.2)	2570 (101.2)	2570 (101.2)
1470 (57.9)	1470 (57.9)	1655 (65.2)	1470 (57.9)	1470 (57.9)	1655 (65.2)
1465 (57.7)	1465 (57.7)	1650 (65.0)	1465 (57.7)	1465 (57.7)	1650 (65.0)
910 (35.8)	1905 (75.0), 910 (35.8)*2	910 (35.8)	3470 (136.6)	3470 (136.6)	3525 (138.8)
1545 (60.8)	1545 (60.8)	1730 (68.1)	1545 (60.8)	1545 (60.8)	1730 (68.1)
1320 (52.0)	1320 (52.0)	1565 (61.6)	1335 (52.6)	1335 (52.6)	1390 (54.7)
2930 (115.4)	1960 (77.2), 2930 (115.4)*2	3470 (136.6)	—	—	—
1545 (60.8)	1545 (60.8)	1730 (68.1)	—	—	—
1335 (52.6)	1335 (52.6)	1635 (64.4)	—	—	—
1050 (41.3)	1045 (41.1)	1190 (46.9)	1050 (41.3)	1050 (41.3)	1190 (46.9)
1075 (42.3)	1080 (42.5)	1080 (42.5)	1075 (42.3)	1075 (42.3)	1080 (42.5)
195 (7.7)	195 (7.7)	195 (7.7)	185 (7.3)	185 (7.3)	185 (7.3)
18.5	18.5	17.5	18.5	18.5	16.6
19.5	19.5	19.5	19.5	19.5	19.7
980 - 1025 (2161 - 2260)	995 - 1040 (2194 - 2293)	1080 - 1125 (2381 - 2480)	985 - 1030 (2172 - 2271)	985 - 1035 (2172 - 2282)	1020 - 1065 (2249 - 2348)
685 - 690 (1510 - 1521)	700 - 710 (1543 - 1565)	755 - 760 (1664 - 1675)	765 - 770 (1687 - 1698)	765 - 770 (1687 - 1698)	820 - 825 (1808 - 1819)
1665 - 1715 (3671 - 3781)	1695 - 1750 (3737 - 3858)	1835 - 1885 (4045 - 4156)	1750 - 1800 (3858 - 3968)	1750 - 1805 (3858 - 3979)	1840 - 1890 (4056 - 4167)
1350 - 1385 (2976 - 3053)	1330 - 1365 (2932 - 3009), 1320 - 1360 (2910 - 2998)*2	1560 - 1590 (3439 - 3505)	1335 - 1370 (2943 - 3020)	1335 - 1375 (2943 - 3031)	1350 - 1385 (2976 - 3053)
1415 - 1450 (3120 - 3197)	1435 - 1470 (3164 - 3241), 1440 - 1480 (3175 - 3263)*2	1610 - 1640 (3549 - 3616)	1580 - 1615 (3483 - 3560)	1575 - 1615 (3472 - 3560)	1715 - 1750 (3781 - 3858)
2800 (6173)	2800 (6173)	3200 (7055)	2950 (6504)	2950 (6504)	3100 (6834)
70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)
6.0	6.0	9.8	—	—	—
170 (105)	170 (105)	155 (96)	170 (105)	—	155 (96)
—	—	—	—	—	—
38 (24)	38 (24)	38 (24)	38 (24)	—	38 (24)
70 (43)	70 (43)	70 (43)	70 (43)	—	70 (43)
114 (71)	114 (71)	114 (71)	114 (71)	—	114 (71)
163 (101)	163 (101)	163 (101)	163 (101)	—	163 (101)
—	—	—	—	—	—
—	—	—	—	—	—
5.0 (16.4)	5.0 (16.4)	6.2 (20.3)	5.0 (16.4)	—	5.3 (17.4)
5.7 (18.7)	5.7 (18.7)	6.9 (22.6)	5.7 (18.7)	—	5.9 (19.4)
2TR-FE	2TR-FE	2TR-FE	2TR-FE	2TR-FE	2TR-FE
16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i
95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)
2694 (164.3)	2694 (164.3)	2694 (164.3)	2694 (164.3)	2694 (164.3)	2694 (164.3)
9.6 : 1	9.6 : 1	9.6 : 1	9.6 : 1	9.6 : 1	9.6 : 1
EFI	EFI	EFI	EFI	EFI	EFI
91 or higher	91 or higher	91 or higher	91 or higher	91 or higher	91 or higher
111/4800	111/4800	111/4800	111/4800	111/4800	111/4800
241/3800	241/3800	241/3800	241/3800	241/3800	241/3800
12 - 48, 12 - 55*3	12 - 48, 12 - 55*3	12 - 48, 12 - 55*3	12 - 48, 12 - 55*3	12 - 48, 12 - 55*3	12 - 48, 12 - 55*3
1560	1560	1560	1560	1560	1560
1.6	1.6	1.6	1.6	1.6	1.6
Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	—	Dry, Single Plate, Diaphragm
R351	R351	R351	R351	A343E	R351
4.313	4.313	4.313	4.313	2.804	4.313
2.330	2.330	2.330	2.330	1.531	2.330
1.436	1.436	1.436	1.436	1.000	1.436
1.000	1.000	1.000	1.000	0.753	1.000
0.838	0.838	0.838	0.838	—	0.838
—	—	—	—	—	—
4.220	4.220	4.220	4.220	2.393	4.220
4.300	4.300	4.300	4.300	4.556	4.300
205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)
Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum
Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
Single, Single with BA*1 10”	Single, Single with BA*1 10”	Single, Single with BA*1 10”	Single, Single with BA*1 10”	Single, Single with BA*1 10”	Single, Single with BA*1 10”
LSP and BV	LSP and BV	LSP and BV	LSP and BV	LSP and BV	LSP and BV
Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid
Standard	Standard	Standard	Standard	Standard	Standard
—	—	—	—	—	—
Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
20.84	20.84	20.84	20.84	20.84	20.84
Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

Item \ Area				G.C.C. Countries			
Body Type				4-door Commuter (Standard)	4-door Commuter (Super Long)		
Vehicle Grade					DX		GL
Model Code				TRH213L-JEPDKV	TRH223L-LEMDKV	TRH223L-LEPDKV	TRH223L-LEMNKV
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	4840 (190.6)	5380 (211.8)	5380 (211.8)	5380 (211.8)
		Width	mm (in.)	1880 (74.0)	1880 (74.0)	1880 (74.0)	1880 (74.0)
		Height	mm (in.)	2105 (82.9)	2285 (90.0)	2285 (90.0)	2285 (90.0)
	Wheel Base		mm (in.)	2570 (101.2)	3110 (122.4)	3110 (122.4)	3110 (122.4)
	Tread	Front	mm (in.)	1655 (65.2)	1655 (65.2)	1655 (65.2)	1655 (65.2)
		Rear	mm (in.)	1650 (65.0)	1650 (65.0)	1650 (65.0)	1650 (65.0)
	Room	Length	mm (in.)	3525 (138.8)	4205 (165.6)	4205 (165.6)	4250 (167.3)
		Width	mm (in.)	1730 (68.1)	1730 (68.1)	1730 (68.1)	1695 (66.7)
		Height	mm (in.)	1390 (54.7)	1565 (61.6)	1565 (61.6)	1565 (61.6)
	Cargo Space	Length	mm (in.)	—	—	—	—
		Width	mm (in.)	—	—	—	—
		Height	mm (in.)	—	—	—	—
	Overhang	Front	mm (in.)	1190 (46.9)	1190 (46.9)	1190 (46.9)	1190 (46.9)
		Rear	mm (in.)	1080 (42.5)	1080 (42.5)	1080 (42.5)	1080 (42.5)
	Min. Running Ground Clearance		mm (in.)	185 (7.3)	185 (7.3)	185 (7.3)	185 (7.3)
	Angle of Approach		degrees	16.6	17.0	17.0	17.0
	Angle of Departure		degrees	19.7	19.2	19.2	19.2
	Curb Weight	Front	kg (lb)	1025 - 1070 (2260 - 2359)	1105 - 1165 (2436 - 2568)	1110 - 1170 (2447 - 2579)	1145 - 1170 (2524 - 2579)
		Rear	kg (lb)	820 - 825 (1808 - 1819)	870 - 920 (1918 - 2028)	875 - 925 (1929 - 2039)	915 - 925 (2017 - 2039)
		Total	kg (lb)	1845 - 1895 (4067 - 4178)	1975 - 2085 (4354 - 4597)	1985 - 2095 (4376 - 4619)	2060 - 2095 (4541 - 4619)
	Gross Vehicle Weight	Front	kg (lb)	1355 - 1390 (2987 - 3064)	1515 - 1550 (3340 - 3417)	1515 - 1550 (3340 - 3417)	1535 - 1550 (3384 - 3417)
		Rear	kg (lb)	1710 - 1745 (3770 - 3847)	1750 - 1785 (3858 - 3935)	1750 - 1785 (3858 - 3935)	1750 - 1765 (3858 - 3891)
		Total	kg (lb)	3100 (6834)	3300 (7275)	3300 (7275)	3300 (7275)
	Fuel Tank Capacity		ℓ (Imp. gal.)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)
	Luggage Compartment Capacity		m^3 (cu. ft.)	—	—	—	—
Performance	Max. Speed		km/h (mph)	—	155 (96)	—	155 (96)
	Max. Cruising Speed		km/h (mph)	—	—	—	—
	Max. Permissible Speed	1st Gear	km/h (mph)	—	38 (24)	—	38 (24)
		2nd Gear	km/h (mph)	—	70 (43)	—	70 (43)
		3rd Gear	km/h (mph)	—	114 (71)	—	114 (71)
		4th Gear	km/h (mph)	—	163 (101)	—	163 (101)
		5th Gear	km/h (mph)	—	—	—	—
		6th Gear	km/h (mph)	—	—	—	—
	Min. Turning Radius	Tire	m (ft.)	—	6.2 (20.3)	—	6.2 (20.3)
		Body	m (ft.)	—	6.9 (22.6)	—	6.9 (22.6)
Engine	Engine Type			2TR-FE	2TR-FE	2TR-FE	2TR-FE
	Valve Mechanism			16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i
	Bore × Stroke		mm (in.)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)
	Displacement		cm^3 (cu. in.)	2694 (164.3)	2694 (164.3)	2694 (164.3)	2694 (164.3)
	Compression Ratio			9.6 : 1	9.6 : 1	9.6 : 1	9.6 : 1
	Fuel System			EFI	EFI	EFI	EFI
	Research Octane No. or Cetane No. (Diesel)			91 or higher	91 or higher	91 or higher	91 or higher
	Max. Output (EEC)		kW/rpm	111/4800	111/4800	111/4800	111/4800
	Max. Torque (EEC)		N·m/rpm	241/3800	241/3800	241/3800	241/3800
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp. hr.	12 - 48, 12 - 55*1	12 - 48, 12 - 55*1	12 - 48, 12 - 55*1	12 - 48, 12 - 55*1
	Alternator Output		Watts	1560	1560	1560	1560
	Starter Output		kW	1.6	1.6	1.6	1.6
Chassis	Clutch Type			—	Dry, Single Plate, Diaphragm	—	Dry, Single Plate, Diaphragm
	Transmission Type			A343E	R351	A343E	R351
	Gear Ratio	In First		2.804	4.313	2.804	4.313
		In Second		1.531	2.330	1.531	2.330
		In Third		1.000	1.436	1.000	1.436
		In Fourth		0.753	1.000	0.753	1.000
		In Fifth		—	0.838	—	0.838
		In Sixth		—	—	—	—
		In Reverse		2.393	4.220	2.393	4.220
	Differential Gear Ratio			4.556	4.300	4.556	4.300
	Differential Gear Size		mm (in.)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear		Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum
	Parking Brake Type			Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
	Brake Booster Type and Size		in.	Single, Single with BA*2 10"	Single, Single with BA*2 10"	Single, Single with BA*2 10"	Single, Single with BA*2 10"
	Proportioning Valve Type			LSP and BV	LSP and BV	LSP and BV	LSP and BV
	Suspension Type	Front		Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
		Rear		Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid
	Stabilizer Bar	Front		Standard	Standard	Standard	Standard
		Rear		—	—	—	—
	Steering Gear Type			Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
	Steering Gear Ratio (Overall)			20.84	20.84	20.84	20.84
	Power Steering Type			Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

*1: Option
*2: with ABS without VSC
*3: Cold area specification model

G.C.C. Countries					
4-door Commuter (Super Long)	5-door Van (Standard)	4-door Commuter (Standard)		4-door Commuter (Super Long)	
GL	DX				GL
TRH223L-LEPNKV	KDH200L-SBMDYV	KDH202L-REMDYV	KDH212L-JEMDYV	KDH222L-LEMDYV	KDH222L-LEMNYV
5380 (211.8)	4695 (184.8)	4695 (184.8)	4840 (190.6)	5380 (211.8)	5380 (211.8)
1880 (74.0)	1695 (66.7)	1695 (66.7)	1880 (74.0)	1880 (74.0)	1880 (74.0)
2285 (90.0)	1980 (78.0)	1980 (78.0)	2105 (82.9)	2285 (90.0)	2285 (90.0)
3110 (122.4)	2570 (101.2)	2570 (101.2)	2570 (101.2)	3110 (122.4)	3110 (122.4)
1655 (65.2)	1470 (57.9)	1470 (57.9)	1655 (65.2)	1655 (65.2)	1655 (65.2)
1650 (65.0)	1465 (57.7)	1465 (57.7)	1650 (65.0)	1650 (65.0)	1650 (65.0)
4250 (167.3)	910 (35.8)	3470 (136.6)	3525 (138.8)	4205 (165.6)	4250 (167.3)
1695 (66.7)	1545 (60.8)	1545 (60.8)	1730 (68.1)	1730 (68.1)	1695 (66.7)
1565 (61.6)	1320 (52.0)	1335 (52.6)	1390 (54.7)	1565 (61.6)	1565 (61.6)
—	2930 (115.4)	—	—	—	—
—	1545 (60.8)	—	—	—	—
—	1335 (52.6)	—	—	—	—
1190 (46.9)	1050 (41.3)	1050 (41.3)	1190 (46.9)	1190 (46.9)	1190 (46.9)
1080 (42.5)	1075 (42.3)	1075 (42.3)	1080 (42.5)	1080 (42.5)	1080 (42.5)
185 (7.3)	195 (7.7)	185 (7.3)	185 (7.3)	185 (7.3)	185 (7.3)
17.0	18.5	18.5	16.6	17.0	17.0
19.2	19.5	19.5	19.7	19.2	19.2
1150 - 1175 (2535 - 2590)	1075 - 1120 (2370 - 2469)	1070 - 1115 (2359 - 2458)	1110 - 1155 (2447 - 2546)	1160 - 1220 (2557 - 2690)	1195 - 1220 (2634 - 2690)
920 - 930 (2028 - 2050)	710 - 715 (1565 - 1576)	770 - 775 (1698 - 1709)	825 - 830 (1819 - 1830)	875 - 925 (1929 - 2039)	915 - 925 (2017 - 2039)
2070 - 2105 (4564 - 4641)	1785 - 1835 (3935 - 4045)	1840 - 1890 (4056 - 4167)	1935 - 1985 (4266 - 4376)	2035 - 2145 (4486 - 4729)	2110 - 2145 (4652 - 4729)
1535 - 1555 (3384 - 3428)	1425 - 1460 (3142 - 3219)	1415 - 1450 (3120 - 3197)	1430 - 1470 (3153 - 3241)	1555 - 1590 (3428 - 3505)	1570 - 1590 (3461 - 3505)
1745 - 1765 (3847 - 3891)	1340 - 1375 (2954 - 3031)	1550 - 1585 (3417 - 3494)	1680 - 1720 (3704 - 3792)	1710 - 1745 (3770 - 3847)	1710 - 1730 (3770 - 3814)
3300 (7275)	2800 (6173)	3000 (6614)	3150 (6944)	3300 (7275)	3300 (7275)
70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)
—	6.0	—	—	—	—
—	145 (90)	145 (90)	135 (84)	135 (84)	135 (84)
—	—	—	—	—	—
—	32 (20)	32 (20)	32 (20)	32 (20)	32 (20)
—	59 (37)	59 (37)	59 (37)	59 (37)	59 (37)
—	96 (60)	96 (60)	96 (60)	96 (60)	96 (60)
—	138 (86)	138 (86)	138 (86)	138 (86)	138 (86)
—	—	—	—	—	—
—	—	—	—	—	—
—	5.0 (16.4)	5.0 (16.4)	5.3 (17.4)	6.2 (20.3)	6.2 (20.3)
—	5.7 (18.7)	5.7 (18.7)	5.9 (19.4)	6.9 (22.6)	6.9 (22.6)
2TR-FE	2KD-FTV	2KD-FTV	2KD-FTV	2KD-FTV	2KD-FTV
16-valve, DOHC with VVT-i	16-valve, DOHC	16-valve, DOHC	16-valve, DOHC	16-valve, DOHC	16-valve, DOHC
95.0 × 95.0 (3.74 × 3.74)	92.0 × 93.8 (3.62 × 3.69)	92.0 × 93.8 (3.62 × 3.69)	92.0 × 93.8 (3.62 × 3.69)	92.0 × 93.8 (3.62 × 3.69)	92.0 × 93.8 (3.62 × 3.69)
2694 (164.3)	2494 (152.2)	2494 (152.2)	2494 (152.2)	2494 (152.2)	2494 (152.2)
9.6 : 1	18.5 : 1	18.5 : 1	18.5 : 1	18.5 : 1	18.5 : 1
EFI	Common-rail Type	Common-rail Type	Common-rail Type	Common-rail Type	Common-rail Type
91 or higher	48 or higher	48 or higher	48 or higher	48 or higher	48 or higher
111/4800	75/3600	75/3600	75/3600	75/3600	75/3600
241/3800	260/1600 - 2400	260/1600 - 2400	260/1600 - 2400	260/1600 - 2400	260/1600 - 2400
12 - 48, 12 - 55*[1]	12 - 55	12 - 55	12 - 55, 12 - 55 × 2*[1]	12 - 55, 12 - 55 × 2*[1]	12 - 55, 12 - 55 × 2*[1]
1560	1200, 1560*[1]	1200, 1560*[1]	1200, 1560*[1]	1200, 1560*[1]	1560
1.6	2.0	2.0	2.0	2.0	2.0, 2.7*[3]
—	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm
A343E	R351	R351	R351	R351	R351
2.804	4.313	4.313	4.313	4.313	4.313
1.531	2.330	2.330	2.330	2.330	2.330
1.000	1.436	1.436	1.436	1.436	1.436
0.753	1.000	1.000	1.000	1.000	1.000
—	0.838	0.838	0.838	0.838	0.838
—	—	—	—	—	—
2.393	4.220	4.220	4.220	4.220	4.220
4.556	4.100	4.100	4.100	4.100	4.100
205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)
Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum
Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
Single, Single with BA*[2] 10”	Single, Single with BA*[2] 10”	Single, Single with BA*[2] 10”	Single, Single with BA*[2] 10”	Single, Single with BA*[2] 10”	Single, Single with BA*[2] 10”
LSP and BV	LSP and BV	LSP and BV	LSP and BV	LSP and BV	LSP and BV
Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid
Standard	Standard	Standard	Standard	Standard	Standard
—	—	—	—	—	—
Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
20.84	20.84	20.84	20.84	20.84	20.84
Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

Item \ Area				South Africa			
Body Type				4-door Van (Standard)	5-door Van (Super Long)		4-door Commuter (Standard)
Vehicle Grade				DX			GL
Model Code				TRH201R-RBMDKN	TRH221R-MBMDKN	TRH221R-MSMDKN	TRH213R-JDMNKN
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	4695 (184.8)	5380 (211.8)	5380 (211.8)	4840 (190.6)
		Width	mm (in.)	1695 (66.7)	1880 (74.0)	1880 (74.0)	1880 (74.0)
		Height	mm (in.)	1980 (78.0)	2285 (90.0)	2285 (90.0)	2105 (82.9)
	Wheel Base		mm (in.)	2570 (101.2)	3110 (122.4)	3110 (122.4)	2570 (101.2)
	Tread	Front	mm (in.)	1470 (57.9)	1655 (65.2)	1655 (65.2)	1655 (65.2)
		Rear	mm (in.)	1465 (57.7)	1650 (65.0)	1650 (65.0)	1650 (65.0)
	Room	Length	mm (in.)	910 (35.8)	910 (35.8)	910 (35.8)	3525 (138.8)
		Width	mm (in.)	1545 (60.8)	1730 (68.1)	1730 (68.1)	1695 (66.7)
		Height	mm (in.)	1320 (52.0)	1565 (61.6)	1565 (61.6)	1390 (54.7)
	Cargo Space	Length	mm (in.)	2930 (115.4)	3470 (136.6)	3470 (136.6)	—
		Width	mm (in.)	1545 (60.8)	1730 (68.1)	1730 (68.1)	—
		Height	mm (in.)	1335 (52.6)	1635 (64.4)	1635 (64.4)	—
	Overhang	Front	mm (in.)	1050 (41.3)	1190 (46.9)	1190 (46.9)	1190 (46.9)
		Rear	mm (in.)	1075 (42.3)	1080 (42.5)	1080 (42.5)	1080 (42.5)
	Min. Running Ground Clearance		mm (in.)	195 (7.7)	195 (7.7)	195 (7.7)	185 (7.3)
	Angle of Approach		degrees	18.5	17.5	17.5	16.6
	Angle of Departure		degrees	19.5	19.5	19.5	19.7
	Curb Weight	Front	kg (lb)	990 - 1030 (2183 - 2271)	1085 - 1125 (2392 - 2480)	1115 - 1155 (2458 - 2546)	1070 - 1095 (2359 - 2414)
		Rear	kg (lb)	675 - 695 (1488 - 1532)	760 - 780 (1675 - 1720)	795 - 815 (1753 - 1797)	815 - 825 (1797 - 1819)
		Total	kg (lb)	1665 - 1725 (3671 - 3803)	1845 - 1905 (4067 - 4200)	1910 - 1970 (4211 - 4343)	1885 - 1920 (4156 - 4233)
	Gross Vehicle Weight	Front	kg (lb)	1360 - 1390 (2998 - 3064)	1560 - 1585 (3439 - 3494)	1545 - 1575 (3406 - 3472), 1530 - 1565 (3373 - 3450)*1	1335 - 1355 (2943 - 2987)
		Rear	kg (lb)	1410 - 1440 (3108 - 3175)	1615 - 1640 (3560 - 3616)	1625 - 1655 (3582 - 3649), 1635 - 1670 (3605 - 3682)*1	1495 - 1515 (3296 - 3340)
		Total	kg (lb)	2800 (6173)	3200 (7055)	3200 (7055)	2850 (6283)
	Fuel Tank Capacity		ℓ (Imp. gal.)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)
	Luggage Compartment Capacity		m^3 (cu. ft.)	6.0	9.8	9.8	—
Performance	Max. Speed		km/h (mph)	155 (96)	155 (96)	155 (96)	155 (96)
	Max. Cruising Speed		km/h (mph)	—	—	—	—
	Max. Permissible Speed	1st Gear	km/h (mph)	38 (24)	38 (24)	38 (24)	38 (24)
		2nd Gear	km/h (mph)	70 (43)	70 (43)	70 (43)	70 (43)
		3rd Gear	km/h (mph)	114 (71)	114 (71)	114 (71)	114 (71)
		4th Gear	km/h (mph)	163 (101)	163 (101)	163 (101)	163 (101)
		5th Gear	km/h (mph)	—	—	—	—
		6th Gear	km/h (mph)	—	—	—	—
	Min. Turning Radius	Tire	m (ft.)	5.0 (16.4)	6.2 (20.3)	6.2 (20.3)	5.3 (17.4)
		Body	m (ft.)	5.7 (18.7)	6.9 (22.6)	6.9 (22.6)	5.9 (19.4)
Engine	Engine Type			2TR-FE	2TR-FE	2TR-FE	2TR-FE
	Valve Mechanism			16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i
	Bore × Stroke		mm (in.)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)
	Displacement		cm^3 (cu. in.)	2694 (164.3)	2694 (164.3)	2694 (164.3)	2694 (164.3)
	Compression Ratio			9.6 : 1	9.6 : 1	9.6 : 1	9.6 : 1
	Fuel System			EFI	EFI	EFI	EFI
	Research Octane No. or Cetane No. (Diesel)			91 or higher	91 or higher	91 or higher	91 or higher
	Max. Output (EEC)		kW/rpm	111/4800	111/4800	111/4800	111/4800
	Max. Torque (EEC)		N·m/rpm	241/3800	241/3800	241/3800	241/3800
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp. hr.	12 - 48, 12 - 55*2	12 - 48, 12 - 55*2	12 - 48, 12 - 55*2	12 - 48, 12 - 55*2
	Alternator Output		Watts	1560	1560	1560	1560
	Starter Output		kW	1.6	1.6	1.6	1.6
Chassis	Clutch Type			Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm
	Transmission Type			R351	R351	R351	R351
	Gear Ratio	In First		4.313	4.313	4.313	4.313
		In Second		2.330	2.330	2.330	2.330
		In Third		1.436	1.436	1.436	1.436
		In Fourth		1.000	1.000	1.000	1.000
		In Fifth		0.838	0.838	0.838	0.838
		In Sixth		—	—	—	—
		In Reverse		4.220	4.220	4.220	4.220
	Differential Gear Ratio			4.300	4.300	4.300	4.300
	Differential Gear Size		mm (in.)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear		Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum
	Parking Brake Type			Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
	Brake Booster Type and Size		in.	Single with BA 10"	Single with BA 10"	Single with BA 10"	Single with BA 10"
	Proportioning Valve Type			LSP and BV	LSP and BV	LSP and BV	LSP and BV
	Suspension Type	Front		Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
		Rear		Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid
	Stabilizer Bar	Front		Standard	Standard	Standard	Standard
		Rear		—	—	—	—
	Steering Gear Type			Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
	Steering Gear Ratio (Overall)			20.84	20.84	20.84	20.84
	Power Steering Type			Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

*1: Folded seat
*2: Option

South Africa					
4-door Commuter (Super Long)		4-door Van (Standard)	5-door Van (Super Long)		4-door Commuter (Standard)
DX	GL		DX		GL
TRH223R-LEMDKN	TRH223R-LEMNKN	KDH200R-RBMDYN	KDH220R-MBMDYN	KDH220R-MSMDYN	KDH212R-JDMNYN
5380 (211.8)	5380 (211.8)	4695 (184.8)	5380 (211.8)	5380 (211.8)	4840 (190.6)
1880 (74.0)	1880 (74.0)	1695 (66.7)	1880 (74.0)	1880 (74.0)	1880 (74.0)
2285 (90.0)	2285 (90.0)	1980 (78.0)	2285 (90.0)	2285 (90.0)	2105 (82.9)
3110 (122.4)	3110 (122.4)	2570 (101.2)	3110 (122.4)	3110 (122.4)	2570 (101.2)
1655 (65.2)	1655 (65.2)	1470 (57.9)	1655 (65.2)	1655 (65.2)	1655 (65.2)
1650 (65.0)	1650 (65.0)	1465 (57.7)	1650 (65.0)	1650 (65.0)	1650 (65.0)
4250 (167.3)	4250 (167.3)	910 (35.8)	910 (35.8)	910 (35.8)	3525 (138.8)
1730 (68.1)	1695 (66.7)	1545 (60.8)	1730 (68.1)	1730 (68.1)	1695 (66.7)
1565 (61.6)	1565 (61.6)	1320 (52.0)	1565 (61.6)	1565 (61.6)	1390 (54.7)
—	—	2930 (115.4)	3470 (136.6)	3470 (136.6)	—
—	—	1545 (60.8)	1730 (68.1)	1730 (68.1)	—
—	—	1335 (52.6)	1635 (64.4)	1635 (64.4)	—
1190 (46.9)	1190 (46.9)	1050 (41.3)	1190 (46.9)	1190 (46.9)	1190 (46.9)
1080 (42.5)	1080 (42.5)	1075 (42.3)	1080 (42.5)	1080 (42.5)	1080 (42.5)
185 (7.3)	185 (7.3)	195 (7.7)	195 (7.7)	195 (7.7)	185 (7.3)
17	17	18.5	17.5	17.5	16.6
19.2	19.2	19.5	19.5	19.5	19.7
1140 - 1145 (2513 - 2524)	1135 - 1160 (2502 - 2557)	1035 - 1085 (2282 - 2392)	1150 - 1200 (2535 - 2646)	1180 - 1230 (2601 - 2712)	1130 - 1175 (2491 - 2590)
930 - 935 (2050 - 2061)	925 - 935 (2039 - 2061)	695 - 725 (1532 - 1598)	765 - 795 (1687 - 1753)	800 - 830 (1764 - 1830)	820 - 830 (1808 - 1830)
2070 - 2080 (4564 - 4586)	2060 - 2095 (4541 - 4619)	1730 - 1810 (3814 - 3990)	1915 - 1995 (4222 - 4398)	1980 - 2060 (4365 - 4541)	1950 - 2005 (4299 - 4420)
1515 (3340)	1440 - 1455 (3175 - 3208)	1395 - 1430 (3075 - 3153)	1610 - 1640 (3549 - 3616)	1595 - 1630 (3516 - 3593), 1590 - 1630 (3505 - 3593)*1	1395 - 1430 (3075 - 3153)
1825 (4023)	1795 - 1810 (3957 - 3990)	1370 - 1405 (3020 - 3097)	1560 - 1590 (3439 - 3505)	1570 - 1605 (3461 - 3538), 1570 - 1610 (3461 - 3549)*1	1470 - 1505 (3241 - 3318)
3340 (7363)	3250 (7165)	2800 (6173)	3200 (7055)	3200 (7055)	2900 (6393)
70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)
—	—	6.0	9.8	9.8	—
155 (96)	155 (96)	135 (84)	135 (84)	135 (84)	135 (84)
—	—	—	—	—	—
38 (24)	38 (24)	32 (20)	32 (20)	32 (20)	32 (20)
70 (43)	70 (43)	59 (37)	59 (37)	59 (37)	59 (37)
114 (71)	114 (71)	96 (60)	96 (60)	96 (60)	96 (60)
163 (101)	163 (101)	138 (86)	138 (86)	138 (86)	138 (86)
—	—	—	—	—	—
—	—	—	—	—	—
6.2 (20.3)	6.2 (20.3)	5.0 (16.4)	6.2 (20.3)	6.2 (20.3)	5.3 (17.4)
6.9 (22.6)	6.9 (22.6)	5.7 (18.7)	6.9 (22.6)	6.9 (22.6)	5.9 (19.4)
2TR-FE	2TR-FE	2KD-FTV	2KD-FTV	2KD-FTV	2KD-FTV
16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i	16-valve, DOHC	16-valve, DOHC	16-valve, DOHC	16-valve, DOHC
95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	92.0 × 93.8 (3.62 × 3.69)	92.0 × 93.8 (3.62 × 3.69)	92.0 × 93.8 (3.62 × 3.69)	92.0 × 93.8 (3.62 × 3.69)
2694 (164.3)	2694 (164.3)	2494 (152.2)	2494 (152.2)	2494 (152.2)	2494 (152.2)
9.6 : 1	9.6 : 1	18.5 : 1	18.5 : 1	18.5 : 1	18.5 : 1
EFI	EFI	Common-rail Type	Common-rail Type	Common-rail Type	Common-rail Type
91 or higher	91 or higher	48 or higher	48 or higher	48 or higher	48 or higher
111/4800	111/4800	75/3600	75/3600	75/3600	75/3600
241/3800	241/3800	260/1600 - 2400	260/1600 - 2400	260/1600 - 2400	260/1600 - 2400
12 - 60	12 - 48, 12 - 55*2	12 - 55, 12 - 55 × 2*2	12 - 55, 12 - 55 × 2*2	12 - 55, 12 - 55 × 2*2	12 - 55, 12 - 55 × 2*2
1560	1560	1200, 1560*2	1200, 1560*2	1200, 1560*2	1560
1.7	1.6	2.0	2.0	2.0	2.0
Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm
R351	R351	R351	R351	R351	R351
4.313	4.313	4.313	4.313	4.313	4.313
2.330	2.330	2.330	2.330	2.330	2.330
1.436	1.436	1.436	1.436	1.436	1.436
1.000	1.000	1.000	1.000	1.000	1.000
0.838	0.838	0.838	0.838	0.838	0.838
—	—	—	—	—	—
4.220	4.220	4.220	4.220	4.220	4.220
4.300	4.300	4.100	4.100	4.100	4.100
205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)
Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum
Leading-trailing Drum	Leading-trailing Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
Single with BA 10”	Single with BA 10”	Single with BA 10”	Single with BA 10”	Single with BA 10”	Single with BA 10”
LSP and BV	LSP and BV	LSP and BV	LSP and BV	LSP and BV	LSP and BV
Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid
Standard	Standard	Standard	Standard	Standard	Standard
—	—	—	—	—	—
Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
20.84	20.84	20.84	20.84	20.84	20.84
Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

Item \ Area				South Africa		Russia	
Body Type				4-door Commuter (Super Long)			
Vehicle Grade				DX	GL		
Model Code				KDH222R-LEMDYN	KDH222R-LEMNYN	TRH223L-LEMNKX	KDH223L-LEMNYX
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	5380 (211.8)	5380 (211.8)	5380 (211.8)	5380 (211.8)
		Width	mm (in.)	1880 (74.0)	1880 (74.0)	1880 (74.0)	1880 (74.0)
		Height	mm (in.)	2285 (90.0)	2285 (90.0)	2285 (90.0)	2285 (90.0)
	Wheel Base		mm (in.)	3110 (122.4)	3110 (122.4)	3110 (122.4)	3110 (122.4)
	Tread	Front	mm (in.)	1655 (65.2)	1655 (65.2)	1655 (65.2)	1655 (65.2)
		Rear	mm (in.)	1650 (65.0)	1650 (65.0)	1650 (65.0)	1650 (65.0)
	Room	Length	mm (in.)	—	4250 (167.3)	4250 (167.3)	4250 (167.3)
		Width	mm (in.)	—	1695 (66.7)	1695 (66.7)	1695 (66.7)
		Height	mm (in.)	—	1565 (61.6)	1565 (61.6)	1565 (61.6)
	Cargo Space	Length	mm (in.)	—	—	—	—
		Width	mm (in.)	—	—	—	—
		Height	mm (in.)	—	—	—	—
	Overhang	Front	mm (in.)	1190 (46.9)	1190 (46.9)	1190 (46.9)	1190 (46.9)
		Rear	mm (in.)	1080 (42.5)	1080 (42.5)	1080 (42.5)	1080 (42.5)
	Min. Running Ground Clearance		mm (in.)	185 (7.3)	185 (7.3)	185 (7.3)	185 (7.3)
	Angle of Approach		degrees	—	17.0	17.0	17.0
	Angle of Departure		degrees	—	19.2	19.2	19.2
	Curb Weight	Front	kg (lb)	1190 - 1195 (2623 - 2634)	1200 - 1245 (2646 - 2745)	1170 - 1175 (2579 - 2590)	1300 - 1305 (2866 - 2877)
		Rear	kg (lb)	915 - 920 (2017 - 2028)	930 - 940 (2050 - 2072)	915 - 925 (2017 - 2039)	930 - 940 (2050 - 2072)
		Total	kg (lb)	2105 - 2115 (4641 - 4663)	2130 - 2185 (4696 - 4817)	2085 - 2100 (4597 - 4630)	2230 - 2245 (4916 - 4949)
	Gross Vehicle Weight	Front	kg (lb)	1565 - 1570 (3450 - 3461)	1500 - 1530 (3307 - 3373)	1445 (3186)	1585 - 1590 (3494 - 3505)
		Rear	kg (lb)	1820 - 1825 (4012 - 4023)	1770 - 1800 (3902 - 3968)	1605 (3538)	1660 - 1665 (3660 - 3671)
		Total	kg (lb)	3390 (7474)	3300 (7275)	3050 (6724)	3250 (7165)
	Fuel Tank Capacity		ℓ (Imp. gal.)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)
	Luggage Compartment Capacity		m^3 (cu. ft.)	—	—	—	—
Performance	Max. Speed		km/h (mph)	—	135 (84)	155 (96)	140 (87)
	Max. Cruising Speed		km/h (mph)	—	—	—	—
	Max. Permissible Speed	1st Gear	km/h (mph)	—	32 (20)	38 (24)	32 (20)
		2nd Gear	km/h (mph)	—	59 (37)	70 (43)	59 (37)
		3rd Gear	km/h (mph)	—	96 (60)	114 (71)	96 (60)
		4th Gear	km/h (mph)	—	138 (86)	163 (101)	138 (86)
		5th Gear	km/h (mph)	—	—	—	—
		6th Gear	km/h (mph)	—	—	—	—
	Min. Turning Radius	Tire	m (ft.)	—	6.2 (20.3)	6.2 (20.3)	6.2 (20.3)
		Body	m (ft.)	—	6.9 (22.6)	6.9 (22.6)	6.9 (22.6)
Engine	Engine Type			2KD-FTV	2KD-FTV	2TR-FE	1KD-FTV
	Valve Mechanism			16-valve, DOHC	16-valve, DOHC	16-valve, DOHC with Dual VVT-i	16-valve, DOHC
	Bore × Stroke		mm (in.)	92.0 × 93.8 (3.62 × 3.69)	92.0 × 93.8 (3.62 × 3.69)	95.0 × 95.0 (3.74 × 3.74)	96.0 × 103.0 (3.78 × 4.06)
	Displacement		cm^3 (cu. in.)	2494 (152.2)	2494 (152.2)	2694 (164.3)	2982 (182.0)
	Compression Ratio			18.5 : 1	18.5 : 1	10.2 : 1	15.0 : 1, 16.0 : 1*3
	Fuel System			Common-rail Type	Common-rail Type	EFI	Common-rail Type
	Research Octane No. or Cetane No. (Diesel)			48 or higher	48 or higher	91 or higher	48 or higher
	Max. Output (EEC)		kW/rpm	75/3600	75/3600	118/5200	106/3400, 100/3400*3
	Max. Torque (EEC)		N·m/rpm	260/1600 - 2400	260/1600 - 2400	243/4000	300/1200 - 3200, 300/1200 - 2400*3
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp. hr.	12 - 65	12 - 55, 12 - 55 × 2*1	12 - 55	12 - 55 × 2
	Alternator Output		Watts	1200	1560	1560	1560
	Starter Output		kW	2.2	2.0	2.0	2.7
Chassis	Clutch Type			Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm
	Transmission Type			R351	R351	R351	R351
	Gear Ratio	In First		4.313	4.313	4.313	4.313
		In Second		2.330	2.330	2.330	2.330
		In Third		1.436	1.436	1.436	1.436
		In Fourth		1.000	1.000	1.000	1.000
		In Fifth		0.838	0.838	0.838	0.838
		In Sixth		—	—	—	—
		In Reverse		4.220	4.220	4.220	4.220
	Differential Gear Ratio			4.100	4.100	4.300	3.727
	Differential Gear Size		mm (in.)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear		Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum
	Parking Brake Type			Leading-trailing Drum	Leading-trailing Drum	Duo-servo Drum	Duo-servo Drum
	Brake Booster Type and Size		in.	Single with BA 10"	Single with BA 10"	Single 10"	Single, Single with BA*2 10"
	Proportioning Valve Type			LSP and BV	LSP and BV	—	LSP and BV*2
	Suspension Type	Front		Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
		Rear		Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid
	Stabilizer Bar	Front		Standard	Standard	Standard	Standard
		Rear		—	—	—	—
	Steering Gear Type			Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
	Steering Gear Ratio (Overall)			20.84	20.84	20.84	20.84
	Power Steering Type			Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

*1: Option
*2: with ABS without VSC
*3: Models for Azerbaijan package

Thailand					
4-door Commuter (Super Long)	5-door Commuter (Standard)	4-door Van (Standard)	4-door Commuter (Standard)	4-door Commuter (Super Long)	
DX	GL	DX	GL	DX	
TRH223R-LEMDKT	TRH213R-KDPNKT	KDH201R-RBMDYT	KDH203R-RDMNYT	KDH223R-LEMDYT	KDH223R-LEPDYT
5380 (211.8)	4840 (190.6)	4695 (184.8)	4695 (184.8)	5380 (211.8)	5380 (211.8)
1880 (74.0)	1880 (74.0)	1695 (66.7)	1695 (66.7)	1880 (74.0)	1880 (74.0)
2285 (90.0)	2105 (82.9)	1980 (78.0)	1980 (78.0)	2285 (90.0)	2285 (90.0)
3110 (122.4)	2570 (101.2)	2570 (101.2)	2570 (101.2)	3110 (122.4)	3110 (122.4)
1655 (65.2)	1655 (65.2)	1470 (57.9)	1470 (57.9)	1655 (65.2)	1655 (65.2)
1650 (65.0)	1650 (65.0)	1465 (57.7)	1465 (57.7)	1650 (65.0)	1650 (65.0)
4205 (165.6)	3525 (138.8)	910 (35.8)	3460 (136.2)	4205 (165.6)	4205 (165.6)
1730 (68.1)	1695 (66.7)	1545 (60.8)	1545 (60.8)	1730 (68.1)	1730 (68.1)
1565 (61.6)	1390 (54.7)	1320 (52.0)	1335 (52.6)	1565 (61.6)	1565 (61.6)
—	—	2930 (115.4)	—	—	—
—	—	1545 (60.8)	—	—	—
—	—	1335 (52.6)	—	—	—
1190 (46.9)	1190 (46.9)	1050 (41.3)	1050 (41.3)	1190 (46.9)	1190 (46.9)
1080 (42.5)	1080 (42.5)	1075 (42.3)	1075 (42.3)	1080 (42.5)	1080 (42.5)
185 (7.3)	185 (7.3)	195 (7.7)	185 (7.3)	185 (7.3)	185 (7.3)
17.0	16.6	18.5	18.5	17.0	17.0
19.2	19.7	19.5	19.5	19.2	19.2
1105 - 1145 (2436 - 2524)	1095 - 1100 (2414 - 2425)	1075 - 1105 (2370 - 2436)	1105 - 1115 (2436 - 2458)	1185 - 1220 (2612 - 2690)	1190 - 1225 (2623 - 2701)
900 - 905 (1984 - 1995)	865 - 875 (1907 - 1929)	695 - 700 (1532 - 1543)	755 (1664)	915 - 925 (2017 - 2039)	920 - 930 (2028 - 2050)
2005 - 2050 (4420 - 4519)	1960 - 1975 (4321 - 4354)	1770 - 1805 (3902 - 3979)	1860 - 1870 (4101 - 4123)	2100 - 2145 (4630 - 4729)	2110 - 2155 (4652 - 4751)
1505 - 1535 (3318 - 3384)	1270 (2800)	1425 - 1450 (3142 - 3197)	1370 - 1380 (3020 - 3042)	1565 - 1590 (3450 - 3505)	1565 - 1590 (3450 - 3505)
1765 - 1795 (3891 - 3957)	1580 (3483)	1350 - 1375 (2976 - 3031)	1320 - 1330 (2910 - 2932)	1710 - 1735 (3770 - 3825)	1710 - 1735 (3770 - 3825)
3300 (7275)	2850 (6283)	2800 (6173)	2700 (5952)	3300 (7275)	3300 (7275)
70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)
—	—	6.0	—	—	—
—	155 (96)	145 (90)	145 (90)	140 (87)	—
—	—	—	—	—	—
—	54 (33)	32 (20)	32 (20)	32 (20)	—
—	98 (61)	59 (37)	59 (37)	59 (37)	—
—	150 (93)	96 (60)	96 (60)	96 (60)	—
—	—	138 (86)	138 (86)	138 (86)	—
—	—	—	—	—	—
—	—	—	—	—	—
6.2 (20.3)	5.3 (17.4)	5.0 (16.4)	5.0 (16.4)	6.2 (20.3)	6.2 (20.3)
6.9 (22.6)	5.9 (19.4)	5.7 (18.7)	5.7 (18.7)	6.9 (22.6)	6.9 (22.6)
2TR-FE	2TR-FE	1KD-FTV	1KD-FTV	1KD-FTV	1KD-FTV
16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i	16-valve, DOHC	16-valve, DOHC	16-valve, DOHC	16-valve, DOHC
95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	96.0 × 103.0 (3.78 × 4.06)	96.0 × 103.0 (3.78 × 4.06)	96.0 × 103.0 (3.78 × 4.06)	96.0 × 103.0 (3.78 × 4.06)
2694 (164.3)	2694 (164.3)	2982 (182.0)	2982 (182.0)	2982 (182.0)	2982 (182.0)
9.6 : 1	9.6 : 1	16.0 : 1	16.0 : 1	16.0 : 1	16.0 : 1
EFI	EFI	Common-rail Type	Common-rail Type	Common-rail Type	Common-rail Type
91 or higher	91 or higher	48 or higher	48 or higher	48 or higher	48 or higher
111/4800	111/4800	100/3400	100/3400	100/3400	100/3400
241/3800	241/3800	300/1200 - 2400	300/1200 - 2400	300/1200 - 2400	300/1200 - 2400
12 - 48	12 - 55	12 - 60	12 - 60	12 - 60	12 - 60
1560	1560	1560	1560	1560	1560
1.6	1.6	2.2	2.2	2.2	2.7
Dry, Single Plate, Diaphragm	—	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	—
R351	A343E	R351	R351	R351	A340E
4.313	2.804	4.313	4.313	4.313	2.804
2.330	1.531	2.330	2.330	2.330	1.531
1.436	1.000	1.436	1.436	1.436	1.000
1.000	0.753	1.000	1.000	1.000	0.705
0.838	—	0.838	0.838	0.838	—
—	—	—	—	—	—
4.220	2.393	4.220	4.220	4.220	2.393
4.300	4.556	3.727	3.727	3.727	4.100
205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)
Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum
Leading-trailing Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Leading-trailing Drum	Leading-trailing Drum
Single with BA 10”	Single with BA 10”	Single with BA 10”	Single with BA 10”	Single with BA 10”	Single with BA 10”
LSP and BV	LSP and BV	LSP and BV	LSP and BV	LSP and BV	LSP and BV
Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid
Standard	Standard	Standard	Standard	Standard	Standard
—	—	—	—	—	—
Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
20.84	20.84	20.84	20.84	20.84	20.84
Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

Item \ Area				Thailand	Malaysia		
Body Type				5-door Commuter (Super Long)	4-door Commuter (Standard)	4-door Van (Standard)	4-door Commuter (Standard)
Vehicle Grade				GL	DX		
Model Code				KDH213R-KDPNYT	TRH203R-EDMDKE	KDH200R-RBMDYE	KDH202R-EDMDYE
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	4840 (190.6)	4695 (184.8)	4695 (184.8)	4695 (184.8)
		Width	mm (in.)	1880 (74.0)	1695 (66.7)	1695 (66.7)	1695 (66.7)
		Height	mm (in.)	2105 (82.9)	2240 (88.2)	1980 (78.0)	2240 (88.2)
	Wheel Base		mm (in.)	2570 (101.2)	2570 (101.2)	2570 (101.2)	2570 (101.2)
	Tread	Front	mm (in.)	1655 (65.2)	1470 (57.9)	1470 (57.9)	1470 (57.9)
		Rear	mm (in.)	1650 (65.0)	1465 (57.7)	1465 (57.7)	1465 (57.7)
	Room	Length	mm (in.)	3525 (138.8)	3470 (136.2)	910 (35.8)	3470 (136.2)
		Width	mm (in.)	1695 (66.7)	1545 (60.8)	1545 (60.8)	1545 (60.8)
		Height	mm (in.)	1390 (54.7)	1335 (52.6)	1320 (52.0)	1335 (52.6)
	Cargo Space	Length	mm (in.)	—	—	2930 (115.4)	—
		Width	mm (in.)	—	—	1545 (60.8)	—
		Height	mm (in.)	—	—	1335 (52.6)	—
	Overhang	Front	mm (in.)	1190 (46.9)	1050 (41.3)	1050 (41.3)	1050 (41.3)
		Rear	mm (in.)	1080 (42.5)	1075 (42.3)	1075 (42.3)	1075 (42.3)
	Min. Running Ground Clearance		mm (in.)	185 (7.3)	185 (7.3)	195 (7.7)	195 (7.7)
	Angle of Approach		degrees	16.6	18.5	18.5	18.5
	Angle of Departure		degrees	19.7	19.5	19.5	19.5
	Curb Weight	Front	kg (lb)	1180 - 1195 (2601 - 2634)	1015 - 1025 (2238 - 2260)	1030 - 1040 (2271 - 2293)	1065 - 1075 (2348 - 2370)
		Rear	kg (lb)	880 - 895 (1940 - 1973)	805 - 810 (1775 - 1786)	725 - 730 (1598 - 1609)	810 - 815 (1786 - 1797)
		Total	kg (lb)	2060 - 2090 (4541 - 4608)	1820 - 1835 (4012 - 4045)	1755 - 1770 (3869 - 3902)	1875 - 1890 (4134 - 4167)
	Gross Vehicle Weight	Front	kg (lb)	1345 - 1355 (2965 - 2987)	1350 - 1355 (2976 - 2987)	1385 - 1390 (3053 - 3064)	1400 - 1405 (3086 - 3097)
		Rear	kg (lb)	1545 - 1555 (3406 - 3428)	1395 - 1400 (3075 - 3086)	1410 - 1415 (3108 - 3120)	1395 - 1400 (3075 - 3086)
		Total	kg (lb)	2900 (6393)	2750 (6063)	2800 (6173)	2800 (6173)
	Fuel Tank Capacity		ℓ (Imp. gal.)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)
	Luggage Compartment Capacity		m^3 (cu. ft.)	—	—	6.0	—
Performance	Max. Speed		km/h (mph)	—	170 (105)	145 (90)	145 (90)
	Max. Cruising Speed		km/h (mph)	—	—	—	—
	Max. Permissible Speed	1st Gear	km/h (mph)	—	38 (24)	32 (20)	32 (20)
		2nd Gear	km/h (mph)	—	70 (43)	59 (37)	59 (37)
		3rd Gear	km/h (mph)	—	114 (71)	96 (60)	96 (60)
		4th Gear	km/h (mph)	—	163 (101)	138 (86)	138 (86)
		5th Gear	km/h (mph)	—	—	—	—
		6th Gear	km/h (mph)	—	—	—	—
	Min. Turning Radius	Tire	m (ft.)	5.3 (17.4)	5.0 (16.4)	5.0 (16.4)	5.0 (16.4)
		Body	m (ft.)	5.9 (19.4)	5.7 (18.7)	5.7 (18.7)	5.7 (18.7)
Engine	Engine Type			1KD-FTV	2TR-FE	2KD-FTV	2KD-FTV
	Valve Mechanism			16-valve, DOHC	16-valve, DOHC with VVT-i	16-valve, DOHC	16-valve, DOHC
	Bore × Stroke		mm (in.)	96.0 × 103.0 (3.78 × 4.06)	95.0 × 95.0 (3.74 × 3.74)	92.0 × 93.8 (3.62 × 3.69)	92.0 × 93.8 (3.62 × 3.69)
	Displacement		cm^3 (cu. in.)	2982 (182.0)	2694 (164.3)	2494 (152.2)	2494 (152.2)
	Compression Ratio			16.0 : 1	9.6 : 1	18.5 : 1	18.5 : 1
	Fuel System			Common-rail Type	EFI	Common-rail Type	Common-rail Type
	Research Octane No. or Cetane No. (Diesel)			48 or higher	91 or higher	48 or higher	48 or higher
	Max. Output (EEC)		kW/rpm	100/3400	111/4800	75/3600	75/3600
	Max. Torque (EEC)		N·m/rpm	300/1200 - 2400	241/3800	260/1600 - 2400	260/1600 - 2400
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp. hr.	12 - 60	12 - 55	12 - 55, 12 - 55 × 2*1	12 - 55
	Alternator Output		Watts	1560	1560	1200	1560
	Starter Output		kW	2.7	1.6	2.0	2.0
Chassis	Clutch Type			—	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm
	Transmission Type			A340E	R351	R351	R351
	Gear Ratio	In First		2.804	4.313	4.313	4.313
		In Second		1.531	2.330	2.330	2.330
		In Third		1.000	1.436	1.436	1.436
		In Fourth		0.705	1.000	1.000	1.000
		In Fifth		—	0.838	0.838	0.838
		In Sixth		—	—	—	—
		In Reverse		2.393	4.220	4.220	4.220
	Differential Gear Ratio			4.100	4.300	4.100	4.100
	Differential Gear Size		mm (in.)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear		Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum
	Parking Brake Type			Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
	Brake Booster Type and Size		in.	Single with BA 10"	Single 10"	Single with BA 10"	Single 10"
	Proportioning Valve Type			LSP and BV	—	LSP and BV	—
	Suspension Type	Front		Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
		Rear		Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid
	Stabilizer Bar	Front		Standard	Standard	Standard	Standard
		Rear		—	—	—	—
	Steering Gear Type			Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
	Steering Gear Ratio (Overall)			20.84	20.84	20.84	20.84
	Power Steering Type			Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

*1: Option
*2: Folded seat
*3: with ABS without VSC

General Countries					
5-door Van (Standard)	4-door Van (Super Long)	5-door Van (Standard)			5-door Van (Super Long)
DX					
TRH200R-SSTDK	TRH221L-LFMDK	TRH201R-SRMDK	TRH201R-SRTDK	TRH201L-SBMDK	TRH221L-MBMDK
4695 (184.8)	5380 (211.8)	4695 (184.8)	4695 (184.8)	4695 (184.8)	5380 (211.8)
1695 (66.7)	1880 (74.0)	1695 (66.7)	1695 (66.7)	1695 (66.7)	1880 (74.0)
1980 (78.0)	2285 (90.0)	1980 (78.0)	1980 (78.0)	1980 (78.0)	2285 (90.0)
2570 (101.2)	3110 (122.4)	2570 (101.2)	2570 (101.2)	2570 (101.2)	3110 (122.4)
1470 (57.9)	1655 (65.2)	1470 (57.9)	1470 (57.9)	1470 (57.9)	1655 (65.2)
1465 (57.7)	1650 (65.0)	1465 (57.7)	1465 (57.7)	1465 (57.7)	1650 (65.0)
910 (35.8)	910 (35.8)	1905 (75.0), 910 (35.8)*2	1905 (75.0), 910 (35.8)*2	910 (35.8)	910 (35.8)
1545 (60.8)	1730 (68.1)	1545 (60.8)	1545 (60.8)	1545 (60.8)	1730 (68.1)
1320 (52.0)	1565 (61.6)	1320 (52.0)	1320 (52.0)	1320 (52.0)	1565 (61.6)
2930 (115.4)	3470 (136.6)	1960 (77.2), 2930 (115.4)*2	1960 (77.2), 2930 (115.4)*2	2930 (115.4)	3470 (136.6)
1545 (60.8)	1730 (68.1)	1545 (60.8)	1545 (60.8)	1545 (60.8)	1730 (68.1)
1335 (52.6)	1635 (64.4)	1335 (52.6)	1335 (52.6)	1335 (52.6)	1635 (64.4)
1050 (41.3)	1190 (46.9)	1050 (41.3)	1050 (41.3)	1050 (41.3)	1190 (46.9)
1075 (42.3)	1080 (42.5)	1075 (42.3)	1075 (42.3)	1075 (42.3)	1080 (42.5)
195 (7.7)	195 (7.7)	195 (7.7)	195 (7.7)	195 (7.7)	195 (7.7)
18.5	17.5	18.5	18.5	18.5	17.5
19.5	19.5	19.5	19.5	19.5	19.5
1040 - 1050 (2293 - 2315)	1080 - 1115 (2381 - 2458)	1020 - 1060 (2249 - 2337)	1035 - 1075 (2282 - 2370)	980 - 1030 (2161 - 2271)	1080 - 1130 (2381 - 2491)
720 (1587)	750 - 755 (1653 - 1664)	715 - 720 (1576 - 1587)	720 - 725 (1587 - 1598)	685 - 695 (1510 - 1532)	755 - 765 (1664 - 1687)
1760 - 1770 (3880 - 3902)	1830 - 1870 (4034 - 4123)	1735 - 1780 (3825 - 3924)	1755 - 1800 (3869 - 3968)	1665 - 1725 (3671 - 3803)	1835 - 1895 (4045 - 4178)
1365 - 1375 (3009 - 3031), 1360 - 1370 (2998 - 3020)*2	1560 - 1585 (3439 - 3494)	1350 - 1380 (2976 - 3042), 1340 - 1380 (2954 - 3042)*2	1360 - 1395 (2998 - 3075), 1355 - 1395 (2987 - 3075)*2	1350 - 1390 (2976 - 3064)	1560 - 1595 (3439 - 3516)
1425 - 1435 (3142 - 3164), 1430 - 1440 (3153 - 3175)*2	1615 - 1640 (3560 - 3616)	1420 - 1450 (3131 - 3197), 1420 - 1460 (3131 - 3219)*2	1405 - 1440 (3097 - 3175), 1405 - 1445 (3097 - 3186)*2	1410 - 1450 (3108 - 3197)	1605 - 1640 (3538 - 3616)
2800 (6173)	3200 (7055)	2800 (6173)	2800 (6173)	2800 (6173)	3200 (7055)
70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)
6.0	9.8	6.0	6.0	6.0	9.8
155 (96)	155 (96)	170 (105)	155 (96)	170 (105)	155 (96)
—	—	—	—	—	—
41 (26)	38 (24)	38 (24)	41 (26)	38 (24)	38 (24)
70 (43)	70 (43)	70 (43)	70 (43)	70 (43)	70 (43)
98 (60)	114 (71)	114 (71)	98 (60)	114 (71)	114 (71)
146 (89)	163 (101)	163 (101)	146 (89)	163 (101)	163 (101)
155 (96)	—	—	155 (96)	—	—
155 (96)	—	—	155 (96)	—	—
5.0 (16.4)	6.2 (20.3)	5.0 (16.4)	5.0 (16.4)	5.0 (16.4)	6.2 (20.3)
5.7 (18.7)	6.9 (22.6)	5.7 (18.7)	5.7 (18.7)	5.7 (18.7)	6.9 (22.6)
1TR-FE	2TR-FE	2TR-FE	2TR-FE	2TR-FE	2TR-FE
16-valve, DOHC with Dual VVT-i	16-valve, DOHC with VVT-i	16-valve, DOHC with Dual VVT-i	16-valve, DOHC with Dual VVT-i	16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i
86.0 × 86.0 (3.39 × 3.39)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)
1998 (121.9)	2694 (164.3)	2694 (164.3)	2694 (164.3)	2694 (164.3)	2694 (164.3)
10.4 : 1	10.2 : 1	10.2 : 1	10.2 : 1	10.2 : 1	10.2 : 1
EFI	EFI	EFI	EFI	EFI	EFI
91 or higher	91 or higher	91 or higher	91 or higher	91 or higher	91 or higher
100/5600	111/4800	118/5200	118/5200	111/4800	111/4800
182/4000	241/3800	243/4000	243/4000	241/3800	241/3800
12 - 48	12 - 48	12 - 48	12 - 48	12 - 48, 12 - 55*1	12 - 48, 12 - 55*1
1560	1560	1560	1560	1560	1560
1.0	1.6	1.6	1.6	1.6	1.6
—	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	—	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm
AC60E	R351	R351	AC60E	R351	R351
3.600	4.313	4.313	3.600	4.313	4.313
2.090	2.330	2.330	2.090	2.330	2.330
1.488	1.436	1.436	1.488	1.436	1.436
1.000	1.000	1.000	1.000	1.000	1.000
0.687	0.838	0.838	0.687	0.838	0.838
0.580	—	—	0.580	—	—
3.732	4.220	4.220	3.732	4.220	4.220
5.125	4.300	4.300	4.875	4.300	4.300
205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)
Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum
Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
Single with BA 10”	Single, Single with BA*3 10”	Single 10”	Single 10”	Single, Single with BA*3 10”	Single, Single with BA*3 10”
LSP and BV	LSP and BV	—	—	LSP and BV	LSP and BV
Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid
Standard	Standard	Standard	Standard	Standard	Standard
—	—	—	—	—	—
Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
20.84	20.84	20.84	20.84	20.84	20.84
Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

Item \ Area				General Countries			
Body Type				4-door Commuter (Standard)			
Vehicle Grade				DX			
Model Code				TRH203R-REMDK	TRH203L-REMDK	TRH213R-JEMDK	TRH213L-JEMDK
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	4695 (184.8)	4695 (184.8)	4840 (190.6)	4840 (190.6)
		Width	mm (in.)	1695 (66.7)	1695 (66.7)	1880 (74.0)	1880 (74.0)
		Height	mm (in.)	1980 (78.0)	1980 (78.0)	2105 (82.9)	2105 (82.9)
	Wheel Base		mm (in.)	2570 (101.2)	2570 (101.2)	2570 (101.2)	2570 (101.2)
	Tread	Front	mm (in.)	1470 (57.9)	1470 (57.9)	1655 (65.2)	1655 (65.2)
		Rear	mm (in.)	1465 (57.7)	1465 (57.7)	1650 (65.0)	1650 (65.0)
	Room	Length	mm (in.)	3470 (136.6)	3470 (136.6)	3525 (138.8)	3525 (138.8)
		Width	mm (in.)	1545 (60.8)	1545 (60.8)	1730 (68.1)	1695 (66.7)
		Height	mm (in.)	1335 (52.6)	1335 (52.6)	1390 (54.7)	1390 (54.7)
	Cargo Space	Length	mm (in.)	—	—	—	—
		Width	mm (in.)	—	—	—	—
		Height	mm (in.)	—	—	—	—
	Overhang	Front	mm (in.)	1050 (41.3)	1050 (41.3)	1190 (46.9)	1190 (46.9)
		Rear	mm (in.)	1075 (42.3)	1075 (42.3)	1080 (42.5)	1080 (42.5)
	Min. Running Ground Clearance		mm (in.)	185 (7.3)	185 (7.3)	185 (7.3)	185 (7.3)
	Angle of Approach		degrees	18.5	18.5	16.6	16.6
	Angle of Departure		degrees	19.5	19.5	19.7	19.7
	Curb Weight	Front	kg (lb)	975 - 1020 (2149 - 2249)	985 - 1040 (2172 - 2293)	1020 - 1070 (2249 - 2359)	1020 - 1070 (2249 - 2359)
		Rear	kg (lb)	760 - 765 (1675 - 1687)	760 - 770 (1675 - 1698)	815 - 825 (1797 - 1819)	815 - 825 (1797 - 1819)
		Total	kg (lb)	1735 - 1785 (3825 - 3935)	1745 - 1810 (3847 - 3990)	1835 - 1895 (4045 - 4178)	1835 - 1895 (4045 - 4178)
	Gross Vehicle Weight	Front	kg (lb)	1330 - 1365 (2932 - 3009)	1335 - 1380 (2943 - 3042)	1350 - 1390 (2976 - 3064)	1350 - 1390 (2976 - 3064)
		Rear	kg (lb)	1585 - 1620 (3494 - 3571)	1570 - 1615 (3461 - 3560)	1710 - 1750 (3770 - 3858)	1710 - 1750 (3770 - 3858)
		Total	kg (lb)	2950 (6504)	2950 (6504)	3100 (6834)	3100 (6834)
	Fuel Tank Capacity		ℓ (Imp. gal.)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)
	Luggage Compartment Capacity		m^3 (cu. ft.)	—	—	—	—
Performance	Max. Speed		km/h (mph)	170 (105)	170 (105)	155 (96)	155 (96)
	Max. Cruising Speed		km/h (mph)	—	—	—	—
	Max. Permissible Speed	1st Gear	km/h (mph)	38 (24)	38 (24)	38 (24)	38 (24)
		2nd Gear	km/h (mph)	70 (43)	70 (43)	70 (43)	70 (43)
		3rd Gear	km/h (mph)	114 (71)	114 (71)	114 (71)	114 (71)
		4th Gear	km/h (mph)	163 (101)	163 (101)	163 (101)	163 (101)
		5th Gear	km/h (mph)	—	—	—	—
		6th Gear	km/h (mph)	—	—	—	—
	Min. Turning Radius	Tire	m (ft.)	5.0 (16.4)	5.0 (16.4)	5.3 (17.4)	5.3 (17.4)
		Body	m (ft.)	5.7 (18.7)	5.7 (18.7)	5.9 (19.4)	5.9 (19.4)
Engine	Engine Type			2TR-FE	2TR-FE	2TR-FE	2TR-FE
	Valve Mechanism			16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i
	Bore × Stroke		mm (in.)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)
	Displacement		cm^3 (cu. in.)	2694 (164.3)	2694 (164.3)	2694 (164.3)	2694 (164.3)
	Compression Ratio			9.6 : 1	9.6 : 1	9.6 : 1	9.6 : 1
	Fuel System			EFI	EFI	EFI	EFI
	Research Octane No. or Cetane No. (Diesel)			91 or higher	91 or higher	91 or higher	91 or higher
	Max. Output (EEC)		kW/rpm	111/4800	111/4800	111/4800	111/4800
	Max. Torque (EEC)		N·m/rpm	241/3800	241/3800	241/3800	241/3800
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp. hr.	12 - 48, 12 - 55*1	12 - 48, 12 - 55*1	12 - 48, 12 - 55*1	12 - 48, 12 - 55*1
	Alternator Output		Watts	1560	1560	1560	1560
	Starter Output		kW	1.6	1.6	1.6	1.6
Chassis	Clutch Type			Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm
	Transmission Type			R351	R351	R351	R351
	Gear Ratio	In First		4.313	4.313	4.313	4.313
		In Second		2.330	2.330	2.330	2.330
		In Third		1.436	1.436	1.436	1.436
		In Fourth		1.000	1.000	1.000	1.000
		In Fifth		0.838	0.838	0.838	0.838
		In Sixth		—	—	—	—
		In Reverse		4.220	4.220	4.220	4.220
	Differential Gear Ratio			4.300	4.300	4.300	4.300
	Differential Gear Size		mm (in.)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear		Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum
	Parking Brake Type			Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
	Brake Booster Type and Size		in.	Single, Single with BA*2 10"	Single, Single with BA*2 10"	Single, Single with BA*2 10"	Single, Single with BA*2 10"
	Proportioning Valve Type			LSP and BV	LSP and BV	LSP and BV	LSP and BV
	Suspension Type	Front		Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
		Rear		Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid
	Stabilizer Bar	Front		Standard	Standard	Standard	Standard
		Rear		—	—	—	—
	Steering Gear Type			Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
	Steering Gear Ratio (Overall)			20.84	20.84	20.84	20.84
	Power Steering Type			Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

*1: Option
*2: with ABS without VSC
*3: 14-passenger model
*4: 15-passenger model
*5: Cold area specification model

General Countries					
4-door Commuter (Super Long)					4-door Van (Standard)
DX		GL			DX
TRH223R-LEMDK	TRH223L-LEMDK	TRH223L-LEMNK	TRH223L-LEPNK	TRH223L-LDPNK	KDH201L-RBMDY
5380 (211.8)	5380 (211.8)	5380 (211.8)	5395 (212.4)	5395 (212.4)	4695 (184.8)
1880 (74.0)	1880 (74.0)	1880 (74.0)	1880 (74.0)	1880 (74.0)	1695 (66.7)
2285 (90.0)	2285 (90.0)	2285 (90.0)	2285 (90.0)	2285 (90.0)	1980 (78.0)
3110 (122.4)	3110 (122.4)	3110 (122.4)	3110 (122.4)	3110 (122.4)	2570 (101.2)
1655 (65.2)	1655 (65.2)	1655 (65.2)	1655 (65.2)	1655 (65.2)	1470 (57.9)
1650 (65.0)	1650 (65.0)	1650 (65.0)	1650 (65.0)	1650 (65.0)	1465 (57.7)
4205 (165.6)	4205 (165.6)	4250 (167.3)	4250 (167.3)	—	910 (35.8)
1730 (68.1)	1730 (68.1)	1695 (66.7)	1695 (66.7)	—	1545 (60.8)
1565 (61.6)	1565 (61.6)	1565 (61.6)	1565 (61.6)	—	1320 (52.0)
—	—	—	—	—	2930 (115.4)
—	—	—	—	—	1545 (60.8)
—	—	—	—	—	1335 (52.6)
1190 (46.9)	1190 (46.9)	1190 (46.9)	1190 (46.9)	1190 (46.9)	1050 (41.3)
1080 (42.5)	1080 (42.5)	1080 (42.5)	1080 (42.5)	1080 (42.5)	1075 (42.3)
185 (7.3)	185 (7.3)	185 (7.3)	185 (7.3)	185 (7.3)	195 (7.7)
17.0	17.0	17.0	17.0	17.0	18.5
19.2	19.2	19.2	19.2	19.2	19.5
1100 - 1165 (2425 - 2568)	1100 - 1165 (2425 - 2568)	1140 - 1170 (2513 - 2579)	1195 (2634)	1215 (2679)	1085 - 1120 (2392 - 2469)
870 - 925 (1918 - 2039)	870 - 925 (1918 - 2039)	925 - 935 (2039 - 2061)	910 (2006)	885 (1951)	695 - 715 (1532 - 1576)
1970 - 2090 (4343 - 4608)	1970 - 2090 (4343 - 4608)	2065 - 2105 (4552 - 4641)	2105 (4641)	2100 (4630)	1780 - 1835 (3924 - 4045)
1510 - 1545 (3329 - 3406), 1400 - 1435 (3086 - 3164)*3	1510 - 1545 (3329 - 3406), 1435 - 1470 (3164 - 3241)*4	1530 - 1550 (3373 - 3417)	1485 (3274)	1550 (3417)	1435 - 1460 (3164 - 3219)
1755 - 1790 (3869 - 3946), 1715 - 1750 (3781 - 3858)*3	1755 - 1790 (3869 - 3946), 1730 - 1765 (3814 - 3891)*4	1750 - 1770 (3858 - 3902)	1635 (3605)	1350 (2976)	1340 - 1365 (2954 - 3009)
3300 (7275), 3150 (6944)*3	3300 (7275), 3200 (7055)*4	3300 (7275)	3120 (6878)	2900 (6393)	2800 (6173)
70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)
—	—	—	—	—	6.0
155 (96)	155 (96)	155 (96)	145 (90)	145 (90)	—
—	—	—	—	—	—
38 (24)	38 (24)	38 (24)	54 (33)	54 (33)	—
70 (43)	70 (43)	70 (43)	98 (61)	98 (61)	—
114 (71)	114 (71)	114 (71)	150 (93)	150 (93)	—
163 (101)	163 (101)	163 (101)	—	—	—
—	—	—	—	—	—
—	—	—	—	—	—
6.2 (20.3)	6.2 (20.3)	6.2 (20.3)	6.2 (20.3)	6.2 (20.3)	5.0 (16.4)
6.9 (22.6)	6.9 (22.6)	6.9 (22.6)	6.9 (22.6)	6.9 (22.6)	5.7 (18.7)
2TR-FE	2TR-FE	2TR-FE	2TR-FE	2TR-FE	1KD-FTV
16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i	16-valve, DOHC with VVT-i	16-valve, DOHC
95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	95.0 × 95.0 (3.74 × 3.74)	96.0 × 103.0 (3.78 × 4.06)
2694 (164.3)	2694 (164.3)	2694 (164.3)	2694 (164.3)	2694 (164.3)	2982 (182.0)
9.6 : 1	9.6 : 1	9.6 : 1	9.6 : 1	9.6 : 1	16.0 : 1
EFI	EFI	EFI	EFI	EFI	Common-rail Type
91 or higher	91 or higher	91 or higher	91 or higher	91 or higher	48 or higher
111/4800	111/4800	111/4800	111/4800	113/4800	100/3400
241/3800	241/3800	241/3800	241/3800	241/3800	300/1200 - 2400
12 - 48, 12 - 55*1	12 - 48, 12 - 55*1	12 - 48, 12 - 55*1	12 - 55	12 - 55	12 - 60, 12 - 55 × 2*1
1560	1560	1560	1560	1560	1560
1.6	1.6	1.6	2.0	2.0	2.2, 2.7*5
Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	—	—	Dry, Single Plate, Diaphragm
R351	R351	R351	A343E	A343E	R351
4.313	4.313	4.313	2.804	2.804	4.313
2.330	2.330	2.330	1.531	1.531	2.330
1.436	1.436	1.436	1.000	1.000	1.436
1.000	1.000	1.000	0.753	0.753	1.000
0.838	0.838	0.838	—	—	0.838
—	—	—	—	—	—
4.220	4.220	4.220	2.393	2.393	4.220
4.300	4.300	4.300	4.556	4.556	3.727
205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)
Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum
Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
Single, Single with BA*2 10”	Single, Single with BA*2 10”	Single, Single with BA*2 10”	Single with BA 10”	Single with BA 10”	Single with BA 10”
LSP and BV	LSP and BV	LSP and BV	LSP and BV	LSP and BV	LSP and BV
Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid
Standard	Standard	Standard	Standard	Standard	Standard
—	—	—	—	—	—
Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
20.84	20.84	20.84	20.84	20.84	20.84
Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

Item \ Area				General Countries			
Body Type				4-door Van (Standard)	5-door Van (Standard)		
Vehicle Grade				DX			
Model Code				KDH201R-RBPDY	KDH201R-SRMDY	KDH201R-SRPDY	KDH201R-SBMDY
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	4695 (184.8)	4695 (184.8)	4695 (184.8)	4695 (184.8)
		Width	mm (in.)	1695 (66.7)	1695 (66.7)	1695 (66.7)	1695 (66.7)
		Height	mm (in.)	1980 (78.0)	1980 (78.0)	1980 (78.0)	1980 (78.0)
	Wheel Base		mm (in.)	2570 (101.2)	2570 (101.2)	2570 (101.2)	2570 (101.2)
	Tread	Front	mm (in.)	1470 (57.9)	1470 (57.9)	1470 (57.9)	1470 (57.9)
		Rear	mm (in.)	1465 (57.7)	1465 (57.7)	1465 (57.7)	1465 (57.7)
	Room	Length	mm (in.)	910 (35.8)	1905 (75.0), 910 (35.8)*1	1905 (75.0), 910 (35.8)*1	910 (35.8)
		Width	mm (in.)	1545 (60.8)	1545 (60.8)	1545 (60.8)	1545 (60.8)
		Height	mm (in.)	1320 (52.0)	1320 (52.0)	1320 (52.0)	1320 (52.0)
	Cargo Space	Length	mm (in.)	2930 (115.4)	1960 (77.2), 2930 (115.4)*1	1960 (77.2), 2930 (115.4)*1	2930 (115.4)
		Width	mm (in.)	1545 (60.8)	1545 (60.8)	1545 (60.8)	1545 (60.8)
		Height	mm (in.)	1335 (52.6)	1335 (52.6)	1335 (52.6)	1335 (52.6)
	Overhang	Front	mm (in.)	1050 (41.3)	1050 (41.3)	1050 (41.3)	1050 (41.3)
		Rear	mm (in.)	1075 (42.3)	1075 (42.3)	1075 (42.3)	1075 (42.3)
	Min. Running Ground Clearance		mm (in.)	195 (7.7)	195 (7.7)	195 (7.7)	195 (7.7)
	Angle of Approach		degrees	18.5	18.5	18.5	18.5
	Angle of Departure		degrees	19.5	19.5	19.5	19.5
	Curb Weight	Front	kg (lb)	1080 - 1120 (2381 - 2469)	1130 - 1170 (2491 - 2579)	1135 - 1175 (2502 - 2590)	1100 - 1140 (2425 - 2513)
		Rear	kg (lb)	705 - 710 (1554 - 1565)	725 - 730 (1598 - 1609)	730 - 735 (1609 - 1620)	715 - 720 (1576 - 1587)
		Total	kg (lb)	1785 - 1830 (3935 - 4034)	1855 - 1900 (4090 - 4189)	1865 - 1910 (4112 - 4211)	1815 - 1860 (4001 - 4101)
	Gross Vehicle Weight	Front	kg (lb)	1430 - 1460 (3153 - 3219)	1440 - 1475 (3175 - 3252), 1450 - 1490 (3197 - 3285)*1	1445 - 1475 (3186 - 3252), 1455 - 1495 (3208 - 3296)*1	1440 - 1475 (3175 - 3252)
		Rear	kg (lb)	1340 - 1370 (2954 - 3020)	1325 - 1360 (2921 - 2998), 1310 - 1350 (2888 - 2976)*1	1325 - 1355 (2921 - 2987), 1305 - 1345 (2877 - 2965)*1	1325 - 1360 (2921 - 2998)
		Total	kg (lb)	2800 (6173)	2800 (6173)	2800 (6173)	2800 (6173)
	Fuel Tank Capacity		ℓ (Imp. gal.)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)
	Luggage Compartment Capacity		m^3 (cu. ft.)	6.0	6.0	6.0	6.0
Performance	Max. Speed		km/h (mph)	—	—	—	—
	Max. Cruising Speed		km/h (mph)	—	—	—	—
	Max. Permissible Speed	1st Gear	km/h (mph)	—	—	—	—
		2nd Gear	km/h (mph)	—	—	—	—
		3rd Gear	km/h (mph)	—	—	—	—
		4th Gear	km/h (mph)	—	—	—	—
		5th Gear	km/h (mph)	—	—	—	—
		6th Gear	km/h (mph)	—	—	—	—
	Min. Turning Radius	Tire	m (ft.)	5.0 (16.4)	5.0 (16.4)	5.0 (16.4)	5.0 (16.4)
		Body	m (ft.)	5.7 (18.7)	5.7 (18.7)	5.7 (18.7)	5.7 (18.7)
Engine	Engine Type			1KD-FTV	1KD-FTV	1KD-FTV	1KD-FTV
	Valve Mechanism			16-valve, DOHC	16-valve, DOHC	16-valve, DOHC	16-valve, DOHC
	Bore × Stroke		mm (in.)	96.0 × 103.0 (3.78 × 4.06)	96.0 × 103.0 (3.78 × 4.06)	96.0 × 103.0 (3.78 × 4.06)	96.0 × 103.0 (3.78 × 4.06)
	Displacement		cm^3 (cu. in.)	2982 (182.0)	2982 (182.0)	2982 (182.0)	2982 (182.0)
	Compression Ratio			15.0 : 1	15.0 : 1	15.0 : 1	15.0 : 1
	Fuel System			Common-rail Type	Common-rail Type	Common-rail Type	Common-rail Type
	Research Octane No. or Cetane No. (Diesel)			48 or higher	48 or higher	48 or higher	48 or higher
	Max. Output (EEC)		kW/rpm	106/3400	106/3400	106/3400	106/3400
	Max. Torque (EEC)		N·m/rpm	300/1200 - 3200	300/1200 - 3200	300/1200 - 3200	300/1200 - 3200
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp. hr.	12 - 55	12 - 55	12 - 55	12 - 55
	Alternator Output		Watts	1560	1560	1560	1560
	Starter Output		kW	2.7	2.2	2.7	2.2
Chassis	Clutch Type			—	Dry, Single Plate, Diaphragm	—	Dry, Single Plate, Diaphragm
	Transmission Type			A340E	R351	A340E	R351
	Gear Ratio	In First		2.804	4.313	2.804	4.313
		In Second		1.531	2.330	1.531	2.330
		In Third		1.000	1.436	1.000	1.436
		In Fourth		0.705	1.000	0.705	1.000
		In Fifth		—	0.838	—	0.838
		In Sixth		—	—	—	—
		In Reverse		2.393	4.220	2.393	4.220
	Differential Gear Ratio			4.100	3.727	4.100	3.727
	Differential Gear Size		mm (in.)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear		Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum
	Parking Brake Type			Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
	Brake Booster Type and Size		in.	Single with BA 10"	Single 10"	Single 10"	Single with BA 10"
	Proportioning Valve Type			LSP and BV	—	—	LSP and BV
	Suspension Type	Front		Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
		Rear		Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid
	Stabilizer Bar	Front		Standard	Standard	Standard	Standard
		Rear		—	—	—	—
	Steering Gear Type			Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
	Steering Gear Ratio (Overall)			20.84	20.84	20.84	20.84
	Power Steering Type			Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

*1: Folded seat
*2: Option
*3: Cold area specification model
*4: with ABS without VSC

General Countries					
5-door Van (Standard)				5-door Van (Super Long)	
DX			GL	DX	
KDH201R-SSMDY	KDH201R-SSPDY	KDH201L-SBMDY	KDH201R-SSPNY	KDH221R-MFMDY	KDH221R-MFPDY
4695 (184.8)	4695 (184.8)	4695 (184.8)	4695 (184.8)	5380 (211.8)	5380 (211.8)
1695 (66.7)	1695 (66.7)	1695 (66.7)	1695 (66.7)	1880 (74.0)	1880 (74.0)
1980 (78.0)	1980 (78.0)	1980 (78.0)	1980 (78.0)	2285 (90.0)	2285 (90.0)
2570 (101.2)	2570 (101.2)	2570 (101.2)	2570 (101.2)	3110 (122.4)	3110 (122.4)
1470 (57.9)	1470 (57.9)	1470 (57.9)	1470 (57.9)	1655 (65.2)	1655 (65.2)
1465 (57.7)	1465 (57.7)	1465 (57.7)	1465 (57.7)	1650 (65.0)	1650 (65.0)
1905 (75.0), 910 (35.8)*1	1905 (75.0), 910 (35.8)*1	—	1905 (75.0), 910 (35.8)*1	910 (35.8)	910 (35.8)
1545 (60.8)	1545 (60.8)	—	1545 (60.8)	1730 (68.1)	1730 (68.1)
1320 (52.0)	1320 (52.0)	—	1320 (52.0)	1565 (61.6)	1565 (61.6)
1960 (77.2), 2930 (115.4)*1	1960 (77.2), 2930 (115.4)*1	—	1960 (77.2), 2930 (115.4)*1	3470 (136.6)	3470 (136.6)
1545 (60.8)	1545 (60.8)	—	1545 (60.8)	1730 (68.1)	1730 (68.1)
1335 (52.6)	1335 (52.6)	—	1335 (52.6)	1635 (64.4)	1635 (64.4)
1050 (41.3)	1050 (41.3)	1050 (41.3)	1050 (41.3)	1190 (46.9)	1190 (46.9)
1075 (42.3)	1075 (42.3)	1075 (42.3)	1075 (42.3)	1080 (42.5)	1080 (42.5)
195 (7.7)	195 (7.7)	195 (7.7)	195 (7.7)	195 (7.7)	195 (7.7)
18.5	18.5	—	18.5	17.5	17.5
19.5	19.5	—	19.5	19.5	19.5
1160 - 1170 (2557 - 2579)	1170 - 1180 (2579 - 2601)	1105 - 1170 (2436 - 2579)	1170 - 1180 (2579 - 2601)	1175 - 1215 (2590 - 2679)	1180 - 1220 (2601 - 2690)
730 (1609)	735 (1620)	720 - 730 (1587 - 1609)	735 (1620)	815 - 820 (1797 - 1808)	820 - 825 (1808 - 1819)
1890 - 1900 (4167 - 4189)	1905 - 1915 (4200 - 4222)	1825 - 1900 (4023 - 4189)	1905 - 1915 (4200 - 4222)	1990 - 2035 (4387 - 4486)	2000 - 2045 (4409 - 4508)
1465 - 1475 (3230 - 3252), 1480 - 1490 (3263 - 3285)*1	1475 - 1480 (3252 - 3263), 1490 - 1500 (3285 - 3307)*1	1445 - 1495 (3186 - 3296)	1455 - 1460 (3208 - 3219), 1490 - 1500 (3285 - 3307)*1	1555 - 1585 (3428 - 3494)	1555 - 1585 (3428 - 3494)
1325 - 1335 (2921 - 2943), 1310 - 1320 (2888 - 2910)*1	1320 - 1325 (2910 - 2921), 1300 - 1310 (2866 - 2888)*1	1305 - 1355 (2877 - 2987)	1340 - 1345 (2954 - 2965), 1300 - 1310 (2866 - 2888)*1	1565 - 1595 (3450 - 3516)	1565 - 1595 (3450 - 3516)
2800 (6173)	2800 (6173)	2800 (6173)	2800 (6173)	3150 (6944)	3150 (6944)
70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)
6.0	6.0	—	6.0	9.8	9.8
—	—	—	—	—	—
—	—	—	—	—	—
—	—	—	—	—	—
—	—	—	—	—	—
—	—	—	—	—	—
—	—	—	—	—	—
—	—	—	—	—	—
—	—	—	—	—	—
5.0 (16.4)	5.0 (16.4)	—	5.0 (16.4)	6.2 (20.3)	6.2 (20.3)
5.7 (18.7)	5.7 (18.7)	—	5.7 (18.7)	6.9 (22.6)	6.9 (22.6)
1KD-FTV	1KD-FTV	1KD-FTV	1KD-FTV	1KD-FTV	1KD-FTV
16-valve, DOHC	16-valve, DOHC	16-valve, DOHC	16-valve, DOHC	16-valve, DOHC	16-valve, DOHC
96.0 × 103.0 (3.78 × 4.06)	96.0 × 103.0 (3.78 × 4.06)	96.0 × 103.0 (3.78 × 4.06)	96.0 × 103.0 (3.78 × 4.06)	96.0 × 103.0 (3.78 × 4.06)	96.0 × 103.0 (3.78 × 4.06)
2982 (182.0)	2982 (182.0)	2982 (182.0)	2982 (182.0)	2982 (182.0)	2982 (182.0)
15.0 : 1	15.0 : 1	15.0 : 1	15.0 : 1	15.0 : 1	15.0 : 1
Common-rail Type	Common-rail Type	Common-rail Type	Common-rail Type	Common-rail Type	Common-rail Type
48 or higher	48 or higher	48 or higher	48 or higher	48 or higher	48 or higher
106/3400	106/3400	106/3400	106/3400	106/3400	106/3400
300/1200 - 3200	300/1200 - 3200	300/1200 - 3200	300/1200 - 3200	300/1200 - 3200	300/1200 - 3200
12 - 55	12 - 55	12 - 55, 12 - 55 × 2*2, 12 - 60*2	12 - 55	12 - 55	12 - 55
1560	1560	1560	1560	1560	1560
2.2	2.2	2.2, 2.7*3	2.2	2.2	2.7
Dry, Single Plate, Diaphragm	—	Dry, Single Plate, Diaphragm	—	Dry, Single Plate, Diaphragm	—
R351	A340E	R351	A340E	R351	A340E
4.313	2.804	4.313	2.804	4.313	2.804
2.330	1.531	2.330	1.531	2.330	1.531
1.436	1.000	1.436	1.000	1.436	1.000
1.000	0.705	1.000	0.705	1.000	0.705
0.838	—	0.838	—	0.838	—
—	—	—	—	—	—
4.220	2.393	4.220	2.393	4.220	2.393
3.727	4.100	3.727	4.100	3.727	4.100
205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)
Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum
Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
Single with BA 10”	Single with BA 10”	Single, Single with BA*4 10”	Single with BA 10”	Single 10”	Single 10”
LSP and BV	LSP and BV	LSP and BV	LSP and BV	—	—
Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid
Standard	Standard	Standard	Standard	Standard	Standard
—	—	—	—	—	—
Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
20.84	20.84	20.84	20.84	20.84	20.84
Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

Item \ Area				General Countries			
Body Type				4-door Commuter (Standard)			
Vehicle Grade				DX			GL
Model Code				KDH203R-REMDY	KDH203L-REMDY	KDH203L-RDMDY	KDH213L-JDMNY
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	4695 (184.8)	4695 (184.8)	4695 (184.8)	4840 (190.6)
		Width	mm (in.)	1695 (66.7)	1695 (66.7)	1695 (66.7)	1880 (74.0)
		Height	mm (in.)	1980 (78.0)	1980 (78.0)	1980 (78.0)	2105 (82.9)
	Wheel Base		mm (in.)	2570 (101.2)	2570 (101.2)	2570 (101.2)	2570 (101.2)
	Tread	Front	mm (in.)	1470 (57.9)	1470 (57.9)	1470 (57.9)	1655 (65.2)
		Rear	mm (in.)	1465 (57.7)	1465 (57.7)	1465 (57.7)	1650 (65.0)
	Room	Length	mm (in.)	4210 (165.7)	4210 (165.7)	—	3525 (138.8)
		Width	mm (in.)	1545 (60.8)	1545 (60.8)	—	1695 (66.7)
		Height	mm (in.)	1335 (52.6)	1335 (52.6)	—	1390 (54.7)
	Cargo Space	Length	mm (in.)	—	—	—	—
		Width	mm (in.)	—	—	—	—
		Height	mm (in.)	—	—	—	—
	Overhang	Front	mm (in.)	1050 (41.3)	1050 (41.3)	1050 (41.3)	1190 (46.9)
		Rear	mm (in.)	1075 (42.3)	1075 (42.3)	1075 (42.3)	1080 (42.5)
	Min. Running Ground Clearance		mm (in.)	185 (7.3)	185 (7.3)	185 (7.3)	185 (7.3)
	Angle of Approach		degrees	18.5	18.5	—	16.6
	Angle of Departure		degrees	19.5	19.5	—	19.7
	Curb Weight	Front	kg (lb)	1090 - 1130 (2403 - 2491)	1095 - 1140 (2414 - 2513)	1085 - 1150 (2392 - 2535)	1215 - 1235 (2679 - 2723)
		Rear	kg (lb)	775 - 780 (1709 - 1720)	775 - 780 (1709 - 1720)	750 - 765 (1653 - 1687)	815 - 835 (1797 - 1841)
		Total	kg (lb)	1865 - 1910 (4112 - 4211)	1870 - 1920 (4123 - 4233)	1835 - 1915 (4045 - 4222)	2030 - 2070 (4475 - 4564)
	Gross Vehicle Weight	Front	kg (lb)	1365 - 1400 (3009 - 3086)	1430 - 1470 (3153 - 3241)	1425 - 1475 (3142 - 3252)	1445 - 1460 (3186 - 3219)
		Rear	kg (lb)	1550 - 1585 (3417 - 3494)	1530 - 1570 (3373 - 3461)	1325 - 1375 (2921 - 3031)	1340 - 1355 (2954 - 2987)
		Total	kg (lb)	2950 (6504)	3000 (6614)	2800 (6173)	2800 (6173)
	Fuel Tank Capacity		ℓ (Imp. gal.)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)
	Luggage Compartment Capacity		m^3 (cu. ft.)	—	—	—	—
Performance	Max. Speed		km/h (mph)	145 (90)	—	—	135 (84)
	Max. Cruising Speed		km/h (mph)	—	—	—	—
	Max. Permissible Speed	1st Gear	km/h (mph)	32 (20)	—	—	48 (30)
		2nd Gear	km/h (mph)	59 (37)	—	—	88 (55)
		3rd Gear	km/h (mph)	96 (60)	—	—	135 (84)
		4th Gear	km/h (mph)	138 (86)	—	—	—
		5th Gear	km/h (mph)	—	—	—	—
		6th Gear	km/h (mph)	—	—	—	—
	Min. Turning Radius	Tire	m (ft.)	5.0 (16.4)	—	—	6.2 (20.3)
		Body	m (ft.)	5.7 (18.7)	—	—	6.9 (22.6)
Engine	Engine Type			1KD-FTV	1KD-FTV	1KD-FTV	1KD-FTV
	Valve Mechanism			16-valve, DOHC	16-valve, DOHC	16-valve, DOHC	16-valve, DOHC
	Bore × Stroke		mm (in.)	96.0 × 103.0 (3.78 × 4.06)	96.0 × 103.0 (3.78 × 4.06)	96.0 × 103.0 (3.78 × 4.06)	96.0 × 103.0 (3.78 × 4.06)
	Displacement		cm^3 (cu. in.)	2982 (182.0)	2982 (182.0)	2982 (182.0)	2982 (182.0)
	Compression Ratio			15.0 : 1	16.0 : 1	15.0 : 1	15.0 : 1, 16.0 : 1*5
	Fuel System			Common-rail Type	Common-rail Type	Common-rail Type	Common-rail Type
	Research Octane No. or Cetane No. (Diesel)			48 or higher	48 or higher	48 or higher	48 or higher
	Max. Output (EEC)		kW/rpm	106/3400	100/3400	106/3400	106/3400, 100/3400*5
	Max. Torque (EEC)		N·m/rpm	300/1200 - 3200	300/1200 - 2400	300/1200 - 3200	300/1200 - 3200, 300/1200 - 2400*5
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp. hr.	12 - 55	12 - 60	12 - 55, 12 - 55 × 2*1, 12 - 60*1	12 - 55, 12 - 55 × 2*1, 12 - 60*1
	Alternator Output		Watts	1560	1560	1560	1560
	Starter Output		kW	2.2	2.2	2.2, 2.7*2	2.2, 2.7*2
Chassis	Clutch Type			Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm
	Transmission Type			R351	R351	R351	R351
	Gear Ratio	In First		4.313	4.313	4.313	4.313
		In Second		2.330	2.330	2.330	2.330
		In Third		1.436	1.436	1.436	1.436
		In Fourth		1.000	1.000	1.000	1.000
		In Fifth		0.838	0.838	0.838	0.838
		In Sixth		—	—	—	—
		In Reverse		4.220	4.220	4.220	4.220
	Differential Gear Ratio			3.727	3.727	3.727	3.727
	Differential Gear Size		mm (in.)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear		Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum
	Parking Brake Type			Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
	Brake Booster Type and Size		in.	Single with BA 10"	Single, Single with BA*3 10"	Single, Single with BA*3 10"	Single*4, Single with BA 10"
	Proportioning Valve Type			LSP and BV	LSP and BV	LSP and BV	LSP and BV
	Suspension Type	Front		Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
		Rear		Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid
	Stabilizer Bar	Front		Standard	Standard	Standard	Standard
		Rear		—	—	—	—
	Steering Gear Type			Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
	Steering Gear Ratio (Overall)			20.84	20.84	20.84	20.84
	Power Steering Type			Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

*1: Option
*2: Cold area specification model
*3: with ABS without VSC
*4: without ABS
*5: Models for Philippines package

General Countries					
4-door Commuter (Super Long)		4-door Van (Standard)		5-door Van (Standard)	
DX	GL	DX			
KDH223L-LEMDY	KDH223L-LEPNY	KDH200R-RBMDY	KDH200L-RBMDY	KDH200R-SBMDY	KDH200L-SBMDY
5380 (211.8)	5380 (211.8)	4695 (184.8)	4695 (184.8)	4695 (184.8)	4695 (184.8)
1880 (74.0)	1880 (74.0)	1695 (66.7)	1695 (66.7)	1695 (66.7)	1695 (66.7)
2285 (90.0)	2285 (90.0)	1980 (78.0)	1980 (78.0)	1980 (78.0)	1980 (78.0)
3110 (122.4)	3110 (122.4)	2570 (101.2)	2570 (101.2)	2570 (101.2)	2570 (101.2)
1655 (65.2)	1655 (65.2)	1470 (57.9)	1470 (57.9)	1470 (57.9)	1470 (57.9)
1650 (65.0)	1650 (65.0)	1465 (57.7)	1465 (57.7)	1465 (57.7)	1465 (57.7)
4205 (165.6)	4205 (165.6)	910 (35.8)	910 (35.8)	910 (35.8)	910 (35.8)
1730 (68.1)	1730 (68.1)	1545 (60.8)	1545 (60.8)	1545 (60.8)	1545 (60.8)
1565 (61.6)	1565 (61.6)	1320 (52.0)	1320 (52.0)	1320 (52.0)	1320 (52.0)
—	—	2930 (115.4)	2930 (115.4)	2930 (115.4)	2930 (115.4)
—	—	1545 (60.8)	1545 (60.8)	1545 (60.8)	1545 (60.8)
—	—	1335 (52.6)	1335 (52.6)	1335 (52.6)	1335 (52.6)
1190 (46.9)	1190 (46.9)	1050 (41.3)	1050 (41.3)	1050 (41.3)	1050 (41.3)
1080 (42.5)	1080 (42.5)	1075 (42.3)	1075 (42.3)	1075 (42.3)	1075 (42.3)
185 (7.3)	185 (7.3)	195 (7.7)	195 (7.7)	195 (7.7)	195 (7.7)
17.0	17.0	18.5	18.5	18.5	18.5
19.2	19.2	19.5	19.5	19.5	19.5
1245 - 1255 (2745 - 2767)	1245 - 1295 (2745 - 2855)	1065 - 1130 (2348 - 2491)	1060 - 1125 (2337 - 2480)	1070 - 1135 (2359 - 2502)	1070 - 1115 (2359 - 2458)
925 - 935 (2039 - 2061)	935 - 1060 (2061 - 2337)	695 - 705 (1532 - 1554)	690 - 700 (1521 - 1543)	705 - 715 (1554 - 1576)	710 - 715 (1565 - 1576)
2170 - 2190 (4784 - 4828)	2180 - 2355 (4806 - 5192)	1760 - 1835 (3880 - 4045)	1750 - 1825 (3858 - 4023)	1775 - 1850 (3913 - 4079)	1780 - 1830 (3924 - 4034)
1545 - 1550 (3406 - 3417)	1525 - 1530 (3362 - 3373)	1415 - 1470 (3120 - 3241)	1415 - 1465 (3120 - 3230)	1420 - 1470 (3131 - 3241)	1420 - 1455 (3131 - 3208)
1700 - 1705 (3748 - 3759)	1670 - 1675 (3682 - 3693)	1330 - 1385 (2932 - 3053)	1335 - 1385 (2943 - 3053)	1330 - 1380 (2932 - 3042)	1345 - 1380 (2965 - 3042)
3250 (7165)	3200 (7055)	2800 (6173)	2800 (6173)	2800 (6173)	2800 (6173)
70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)
—	—	6.0	6.0	6.0	6.0
—	—	145 (90)	145 (90)	145 (90)	145 (90)
—	—	—	—	—	—
—	—	32 (20)	32 (20)	32 (20)	32 (20)
—	—	59 (37)	59 (37)	59 (37)	59 (37)
—	—	96 (60)	96 (60)	96 (60)	96 (60)
—	—	138 (86)	138 (86)	138 (86)	138 (86)
—	—	—	—	—	—
—	—	—	—	—	—
—	—	5.0 (16.4)	5.0 (16.4)	5.0 (16.4)	5.0 (16.4)
—	—	5.7 (18.7)	5.7 (18.7)	5.7 (18.7)	5.7 (18.7)
1KD-FTV	1KD-FTV	2KD-FTV	2KD-FTV	2KD-FTV	2KD-FTV
16-valve, DOHC	16-valve, DOHC	16-valve, DOHC	16-valve, DOHC	16-valve, DOHC	16-valve, DOHC
96.0 × 103.0 (3.78 × 4.06)	96.0 × 103.0 (3.78 × 4.06)	92.0 × 93.8 (3.62 × 3.69)	92.0 × 93.8 (3.62 × 3.69)	92.0 × 93.8 (3.62 × 3.69)	92.0 × 93.8 (3.62 × 3.69)
2982 (182.0)	2982 (182.0)	2494 (152.2)	2494 (152.2)	2494 (152.2)	2494 (152.2)
16.0 : 1	16.0 : 1	18.5 : 1	18.5 : 1	18.5 : 1	18.5 : 1
Common-rail Type	Common-rail Type	Common-rail Type	Common-rail Type	Common-rail Type	Common-rail Type
48 or higher	48 or higher	48 or higher	48 or higher	48 or higher	48 or higher
100/3400	100/3400	75/3600	75/3600	75/3600	75/3600
300/1200 - 2400	300/1200 - 2400	260/1600 - 2400	260/1600 - 2400	260/1600 - 2400	260/1600 - 2400
12 - 60, 12 - 55 × 2*[1]	12 - 60	12 - 55, 12 - 55 × 2*[1]	12 - 55, 12 - 55 × 2*[1]	12 - 55, 12 - 55 × 2*[1]	12 - 55, 12 - 55 × 2*[1]
1560	1560	1200, 1560*[1]	1200, 1560*[1]	1200, 1560*[1]	1200, 1560*[1]
2.2, 2.7*[2]	2.2	2.0, 2.7*[2]	2.0, 2.7*[2]	2.0, 2.7*[2]	2.0, 2.7*[2]
Dry, Single Plate, Diaphragm	—	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm
R351	A340E	R351	R351	R351	R351
4.313	2.804	4.313	4.313	4.313	4.313
2.330	1.531	2.330	2.330	2.330	2.330
1.436	1.000	1.436	1.436	1.436	1.436
1.000	0.705	1.000	1.000	1.000	1.000
0.838	—	0.838	0.838	0.838	0.838
—	—	—	—	—	—
4.220	2.393	4.220	4.220	4.220	4.220
3.727	4.100	4.100	4.100	4.100	4.100
205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)
Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum
Leading-trailing Drum	Leading-trailing Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
Single*[4], Single with BA 10"	Single with BA 10"	Single, Single with BA*[3] 10"	Single, Single with BA*[3] 10"	Single, Single with BA*[3] 10"	Single, Single with BA*[3] 10"
LSP and BV	LSP and BV	LSP and BV	LSP and BV	LSP and BV	LSP and BV
Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid
Standard	Standard	Standard	Standard	Standard	Standard
—	—	—	—	—	—
Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
20.84	20.84	20.84	20.84	20.84	20.84
Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

Item \ Area				General Countries			
Body Type				5-door Van (Super Long)	4-door Commuter (Standard)		
Vehicle Grade				DX			
Model Code				KDH220L-MBMDY	KDH202R-REMDY	KDH202L-REMDY	KDH202L-RDMDY
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	5380 (211.8)	4695 (184.8)	4695 (184.8)	4695 (184.8)
		Width	mm (in.)	1880 (74.0)	1695 (66.7)	1695 (66.7)	1695 (66.7)
		Height	mm (in.)	2285 (90.0)	1980 (78.0)	1980 (78.0)	1980 (78.0)
	Wheel Base		mm (in.)	3110 (122.4)	2570 (101.2)	2570 (101.2)	2570 (101.2)
	Tread	Front	mm (in.)	1655 (65.2)	1470 (57.9)	1470 (57.9)	1470 (57.9)
		Rear	mm (in.)	1650 (65.0)	1465 (57.7)	1465 (57.7)	1465 (57.7)
	Room	Length	mm (in.)	910 (35.8)	3470 (136.6)	3470 (136.6)	3460 (136.2)
		Width	mm (in.)	1730 (68.1)	1545 (60.8)	1545 (60.8)	1545 (60.8)
		Height	mm (in.)	1565 (61.6)	1335 (52.6)	1335 (52.6)	1335 (52.6)
	Cargo Space	Length	mm (in.)	3470 (136.6)	—	—	—
		Width	mm (in.)	1730 (68.1)	—	—	—
		Height	mm (in.)	1635 (64.4)	—	—	—
	Overhang	Front	mm (in.)	1190 (46.9)	1050 (41.3)	1050 (41.3)	1050 (41.3)
		Rear	mm (in.)	1080 (42.5)	1075 (42.3)	1075 (42.3)	1075 (42.3)
	Min. Running Ground Clearance		mm (in.)	195 (7.7)	185 (7.3)	185 (7.3)	185 (7.3)
	Angle of Approach		degrees	17.5	18.5	18.5	18.5
	Angle of Departure		degrees	19.5	19.5	19.5	19.5
	Curb Weight	Front	kg (lb)	1155 - 1200 (2546 - 2646)	1065 - 1135 (2348 - 2502)	1070 - 1140 (2359 - 2513)	1070 - 1140 (2359 - 2513)
		Rear	kg (lb)	780 - 790 (1720 - 1742)	770 - 785 (1698 - 1731)	770 - 785 (1698 - 1731)	745 - 760 (1642 - 1675)
		Total	kg (lb)	1935 - 1990 (4266 - 4387)	1835 - 1920 (4045 - 4233)	1840 - 1925 (4056 - 4244)	1815 - 1900 (4001 - 4189)
	Gross Vehicle Weight	Front	kg (lb)	1610 - 1640 (3549 - 3616)	1420 - 1470 (3131 - 3241)	1420 - 1475 (3131 - 3252)	1415 - 1470 (3120 - 3241)
		Rear	kg (lb)	1560 - 1590 (3439 - 3505)	1580 - 1630 (3483 - 3593)	1575 - 1630 (3472 - 3593)	1330 - 1385 (2932 - 3053)
		Total	kg (lb)	3200 (7055)	3050 (6724)	3050 (6724)	2800 (6173)
	Fuel Tank Capacity		ℓ (Imp. gal.)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)
	Luggage Compartment Capacity		m^3 (cu. ft.)	9.8	—	—	—
Performance	Max. Speed		km/h (mph)	145 (90)	145 (90)	145 (90)	145 (90)
	Max. Cruising Speed		km/h (mph)	—	—	—	—
	Max. Permissible Speed	1st Gear	km/h (mph)	32 (20)	32 (20)	32 (20)	32 (20)
		2nd Gear	km/h (mph)	59 (37)	59 (37)	59 (37)	59 (37)
		3rd Gear	km/h (mph)	96 (60)	96 (60)	96 (60)	96 (60)
		4th Gear	km/h (mph)	138 (86)	138 (86)	138 (86)	138 (86)
		5th Gear	km/h (mph)	—	—	—	—
		6th Gear	km/h (mph)	—	—	—	—
	Min. Turning Radius	Tire	m (ft.)	6.2 (20.3)	5.0 (16.4)	5.0 (16.4)	5.0 (16.4)
		Body	m (ft.)	6.9 (22.6)	5.7 (18.7)	5.7 (18.7)	5.7 (18.7)
Engine	Engine Type			2KD-FTV	2KD-FTV	2KD-FTV	2KD-FTV
	Valve Mechanism			16-valve, DOHC	16-valve, DOHC	16-valve, DOHC	16-valve, DOHC
	Bore × Stroke		mm (in.)	92.0 × 93.8 (3.62 × 3.69)	92.0 × 93.8 (3.62 × 3.69)	92.0 × 93.8 (3.62 × 3.69)	92.0 × 93.8 (3.62 × 3.69)
	Displacement		cm^3 (cu. in.)	2494 (152.2)	2494 (152.2)	2494 (152.2)	2494 (152.2)
	Compression Ratio			18.5 : 1	18.5 : 1	18.5 : 1	18.5 : 1
	Fuel System			Common-rail Type	Common-rail Type	Common-rail Type	Common-rail Type
	Research Octane No. or Cetane No. (Diesel)			48 or higher	48 or higher	48 or higher	48 or higher
	Max. Output (EEC)		kW/rpm	75/3600	75/3600	75/3600	75/3600
	Max. Torque (EEC)		N·m/rpm	260/1600 - 2400	260/1600 - 2400	260/1600 - 2400	260/1600 - 2400
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp. hr.	12 - 55, 12 - 55 × 2*1	12 - 55, 12 - 55 × 2*1	12 - 55, 12 - 55 × 2*1	12 - 55, 12 - 55 × 2*1
	Alternator Output		Watts	1200, 1560*1	1200, 1560*1	1200, 1560*1	1200, 1560*1
	Starter Output		kW	2.0, 2.7*2	2.0, 2.7*2	2.0, 2.7*2	2.0, 2.7*2
Chassis	Clutch Type			Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm
	Transmission Type			R351	R351	R351	R351
	Gear Ratio	In First		4.313	4.313	4.313	4.313
		In Second		2.330	2.330	2.330	2.330
		In Third		1.436	1.436	1.436	1.436
		In Fourth		1.000	1.000	1.000	1.000
		In Fifth		0.838	0.838	0.838	0.838
		In Sixth		—	—	—	—
		In Reverse		4.220	4.220	4.220	4.220
	Differential Gear Ratio			4.100	4.100	4.100	4.100
	Differential Gear Size		mm (in.)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear		Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum
	Parking Brake Type			Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
	Brake Booster Type and Size		in.	Single, Single with BA*3 10"	Single, Single with BA*3 10"	Single, Single with BA*3 10"	Single, Single with BA*3 10"
	Proportioning Valve Type			LSP and BV	LSP and BV	LSP and BV	LSP and BV
	Suspension Type	Front		Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
		Rear		Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid
	Stabilizer Bar	Front		Standard	Standard	Standard	Standard
		Rear		—	—	—	—
	Steering Gear Type			Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
	Steering Gear Ratio (Overall)			20.84	20.84	20.84	20.84
	Power Steering Type			Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

*1: Option
*2: Cold area specification model
*3: with ABS without VSC
*4: 14-passenger model
*5: Models with intercooler
*6: 15-passenger model

General Countries					
4-door Commuter (Standard)			5-door Commuter (Standard)	4-door Commuter (Super Long)	
DX		GL		DX	
KDH212R-JEMDY	KDH212L-JEMDY	KDH213L-JDPNY	KDH213L-KDPNY	KDH222R-LEMDY	KDH222L-LEMDY
4840 (190.6)	4840 (190.6)	4840 (190.6)	4840 (190.6)	5380 (211.8)	5380 (211.8)
1880 (74.0)	1880 (74.0)	1880 (74.0)	1880 (74.0)	1880 (74.0)	1880 (74.0)
2105 (82.9)	2105 (82.9)	2105 (82.9)	2105 (82.9)	2285 (90.0)	2285 (90.0)
2570 (101.2)	2570 (101.2)	2570 (101.2)	2570 (101.2)	3110 (122.4)	3110 (122.4)
1655 (65.2)	1655 (65.2)	1655 (65.2)	1655 (65.2)	1655 (65.2)	1655 (65.2)
1650 (65.0)	1650 (65.0)	1650 (65.0)	1650 (65.0)	1650 (65.0)	1650 (65.0)
3525 (138.8)	3525 (138.8)	3525 (138.8)	3525 (138.8)	4205 (165.6)	4205 (165.6)
1695 (66.7)	1695 (66.7)	1695 (66.7)	1695 (66.7)	1730 (68.1)	1730 (68.1)
1390 (54.7)	1390 (54.7)	1390 (54.7)	1390 (54.7)	1565 (61.6)	1565 (61.6)
—	—	—	—	—	—
—	—	—	—	—	—
—	—	—	—	—	—
1190 (46.9)	1190 (46.9)	1190 (46.9)	1190 (46.9)	1190 (46.9)	1190 (46.9)
1080 (42.5)	1080 (42.5)	1080 (42.5)	1080 (42.5)	1080 (42.5)	1080 (42.5)
185 (7.3)	185 (7.3)	185 (7.3)	185 (7.3)	185 (7.3)	185 (7.3)
16.6	16.6	16.6	16.6	17.0	17.0
19.7	19.7	19.7	19.7	19.2	19.2
1110 - 1155 (2447 - 2546)	1115 - 1160 (2458 - 2557)	1165 - 1205 (2568 - 2657)	1205 - 1245 (2657 - 2745)	1160 - 1220 (2557 - 2690)	1160 - 1220 (2557 - 2690)
825 - 830 (1819 - 1830)	825 - 830 (1819 - 1830)	860 - 865 (1896 - 1907)	880 - 890 (1940 - 1962)	870 - 925 (1918 - 2039)	870 - 925 (1918 - 2039)
1935 - 1985 (4266 - 4376)	1940 - 1990 (4277 - 4387)	2025 - 2070 (4464 - 4564)	2085 - 2135 (4597 - 4707)	2030 - 2145 (4475 - 4729)	2030 - 2145 (4475 - 4729)
1430 - 1470 (3153 - 3241)	1435 - 1470 (3164 - 3241)	1485 - 1520 (3274 - 3351)	1375 - 1405 (3031 - 3097)	1555 - 1590 (3428 - 3505), 1455 - 1490 (3208 - 3285)*4	1555 - 1590 (3428 - 3505), 1505 - 1535 (3318 - 3384)*6
1680 - 1720 (3704 - 3792)	1680 - 1715 (3704 - 3781)	1480 - 1515 (3263 - 3340)	1545 - 1575 (3406 - 3472)	1710 - 1745 (3770 - 3847)	1710 - 1745 (3770 - 3847), 1765 - 1795 (3891 - 3957)*6
3150 (6944)	3150 (6944)	3000 (6614)	2950 (6504)	3300 (7275), 3200 (7055)*4	3300 (7275)
70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)
—	—	—	—	—	—
135 (84)	135 (84)	—	—	140 (87)	135 (84)
—	—	—	—	—	—
32 (20)	32 (20)	—	—	32 (20)	32 (20)
59 (37)	59 (37)	—	—	59 (37)	59 (37)
96 (60)	96 (60)	—	—	96 (60)	96 (60)
138 (86)	138 (86)	—	—	138 (86)	138 (86)
—	—	—	—	—	—
—	—	—	—	—	—
5.3 (17.4)	5.3 (17.4)	—	—	6.2 (20.3)	6.2 (20.3)
5.9 (19.4)	5.9 (19.4)	—	—	6.9 (22.6)	6.9 (22.6)
2KD-FTV	2KD-FTV	1KD-FTV	1KD-FTV	2KD-FTV	2KD-FTV
16-valve, DOHC	16-valve, DOHC	16-valve, DOHC	16-valve, DOHC	16-valve, DOHC	16-valve, DOHC
92.0 × 93.8 (3.62 × 3.69)	92.0 × 93.8 (3.62 × 3.69)	96.0 × 103.0 (3.78 × 4.06)	96.0 × 103.0 (3.78 × 4.06)	92.0 × 93.8 (3.62 × 3.69)	92.0 × 93.8 (3.62 × 3.69)
2494 (152.2)	2494 (152.2)	2982 (182.0)	2982 (182.0)	2494 (152.2)	2494 (152.2)
18.5 : 1	18.5 : 1	16.0 : 1	16.0 : 1	18.5 : 1	18.5 : 1
Common-rail Type	Common-rail Type	Common-rail Type	Common-rail Type	Common-rail Type	Common-rail Type
48 or higher	48 or higher	48 or higher	48 or higher	48 or higher	48 or higher
75/3600	75/3600	100/3400	100/3400	75/3600, 80/3600*5	75/3600, 80/3600*5
260/1600 - 2400	260/1600 - 2400	300/1200 - 2400	300/1200 - 2400	260/1600 - 2400	260/1600 - 2400
12 - 55, 12 - 55 × 2*1	12 - 55, 12 - 55 × 2*1	12 - 60	12 - 60	12 - 55, 12 - 55 × 2*1	12 - 55, 12 - 55 × 2*1
1200, 1560*1	1200, 1560*1	1560	1560	1200, 1560*1	1200, 1560*1
2.0	2.0	2.2	2.2	2.0, 2.7*2	2.0, 2.7*2
Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	—	—	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm
R351	R351	A340E	A340E	R351	R351
4.313	4.313	2.804	2.804	4.313	4.313
2.330	2.330	1.531	1.531	2.330	2.330
1.436	1.436	1.000	1.000	1.436	1.436
1.000	1.000	0.705	0.705	1.000	1.000
0.838	0.838	—	—	0.838	0.838
—	—	—	—	—	—
4.220	4.220	2.393	2.393	4.220	4.220
4.100	4.100	4.100	4.100	4.100	4.100
205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)
Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum
Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Leading-trailing Drum	Leading-trailing Drum
Single, Single with BA*3 10"	Single, Single with BA*3 10"	Single with BA 10"	Single with BA 10"	Single, Single with BA*3 10"	Single, Single with BA*3 10"
LSP and BV	LSP and BV	LSP and BV	LSP and BV	LSP and BV	LSP and BV
Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid
Standard	Standard	Standard	Standard	Standard	Standard
—	—	—	—	—	—
Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
20.84	20.84	20.84	20.84	20.84	20.84
Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

Item \ Area				General Countries			
Body Type				4-door Commuter (Super Long)		4-door Van (Standard)	
Vehicle Grade				GL		DX	
Model Code				KDH222R-LEPNY	KDH222L-LEPNY	LH200R-RBMDE	LH200L-RBMDE
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	5380 (211.8)	5380 (211.8)	4695 (184.8)	4695 (184.8)
		Width	mm (in.)	1880 (74.0)	1880 (74.0)	1695 (66.7)	1695 (66.7)
		Height	mm (in.)	2285 (90.0)	2285 (90.0)	1980 (78.0)	1980 (78.0)
	Wheel Base		mm (in.)	3110 (122.4)	3110 (122.4)	2570 (101.2)	2570 (101.2)
	Tread	Front	mm (in.)	1655 (65.2)	1655 (65.2)	1470 (57.9)	1470 (57.9)
		Rear	mm (in.)	1650 (65.0)	1650 (65.0)	1465 (57.7)	1465 (57.7)
	Room	Length	mm (in.)	4205 (165.6)	4205 (165.6)	910 (35.8)	910 (35.8)
		Width	mm (in.)	1730 (68.1)	1730 (68.1)	1545 (60.8)	1545 (60.8)
		Height	mm (in.)	1565 (61.6)	1565 (61.6)	1320 (52.0)	1320 (52.0)
	Cargo Space	Length	mm (in.)	—	—	2930 (115.4)	2930 (115.4)
		Width	mm (in.)	—	—	1545 (60.8)	1545 (60.8)
		Height	mm (in.)	—	—	1335 (52.6)	1335 (52.6)
	Overhang	Front	mm (in.)	1190 (46.9)	1190 (46.9)	1050 (41.3)	1050 (41.3)
		Rear	mm (in.)	1080 (42.5)	1080 (42.5)	1075 (42.3)	1075 (42.3)
	Min. Running Ground Clearance		mm (in.)	185 (7.3)	185 (7.3)	195 (7.7)	195 (7.7)
	Angle of Approach		degrees	17.0	17.0	18.5	18.5
	Angle of Departure		degrees	19.2	19.2	19.5	19.5
	Curb Weight	Front	kg (lb)	1190 - 1220 (2623 - 2690)	1190 - 1220 (2623 - 2690)	1025 - 1090 (2260 - 2403)	1025 - 1090 (2260 - 2403)
		Rear	kg (lb)	920 - 930 (2028 - 2050)	920 - 930 (2028 - 2050)	690 - 700 (1521 - 1543)	690 - 700 (1521 - 1543)
		Total	kg (lb)	2110 - 2150 (4652 - 4740)	2110 - 2150 (4652 - 4740)	1715 - 1790 (3781 - 3946)	1715 - 1790 (3781 - 3946)
	Gross Vehicle Weight	Front	kg (lb)	1565 - 1585 (3450 - 3494)	1565 - 1585 (3450 - 3494)	1385 - 1435 (3053 - 3164)	1385 - 1435 (3053 - 3164)
		Rear	kg (lb)	1715 - 1735 (3781 - 3825)	1715 - 1735 (3781 - 3825)	1365 - 1415 (3009 - 3120)	1365 - 1415 (3009 - 3120)
		Total	kg (lb)	3300 (7275)	3300 (7275)	2800 (6173)	2800 (6173)
	Fuel Tank Capacity		ℓ (Imp. gal.)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)
	Luggage Compartment Capacity		m^3 (cu. ft.)	—	—	6.0	6.0
Performance	Max. Speed		km/h (mph)	—	—	140 (87)	140 (87)
	Max. Cruising Speed		km/h (mph)	—	—	—	—
	Max. Permissible Speed	1st Gear	km/h (mph)	—	—	29 (18)	29 (18)
		2nd Gear	km/h (mph)	—	—	50 (31)	50 (31)
		3rd Gear	km/h (mph)	—	—	86 (53)	86 (53)
		4th Gear	km/h (mph)	—	—	131 (81)	131 (81)
		5th Gear	km/h (mph)	—	—	—	—
		6th Gear	km/h (mph)	—	—	—	—
	Min. Turning Radius	Tire	m (ft.)	6.2 (20.3)	6.2 (20.3)	5.0 (16.4)	5.0 (16.4)
		Body	m (ft.)	6.9 (22.6)	6.9 (22.6)	5.7 (18.7)	5.7 (18.7)
Engine	Engine Type			2KD-FTV	2KD-FTV	5L-E	5L-E
	Valve Mechanism			16-valve, DOHC	16-valve, DOHC	8-valve, OHC	8-valve, OHC
	Bore × Stroke		mm (in.)	92.0 × 93.8 (3.62 × 3.69)	92.0 × 93.8 (3.62 × 3.69)	99.5 × 96.0 (3.92 × 3.78)	99.5 × 96.0 (3.92 × 3.78)
	Displacement		cm^3 (cu. in.)	2494 (152.2)	2494 (152.2)	2986 (182.2)	2986 (182.2)
	Compression Ratio			18.5 : 1	18.5 : 1	22.2 : 1	22.2 : 1
	Fuel System			Common-rail Type	Common-rail Type	Distributor Type	Distributor Type
	Research Octane No. or Cetane No. (Diesel)			48 or higher	48 or higher	48 or higher	48 or higher
	Max. Output (EEC)		kW/rpm	75/3600	75/3600	68/4000	68/4000
	Max. Torque (EEC)		N·m/rpm	260/1600 - 2400	260/1600 - 2400	197/2400	197/2400
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp. hr.	12 - 55	12 - 55, 12 - 55 × 2*1	12 - 60, 12 - 55 × 2*1	12 - 60, 12 - 55 × 2*1
	Alternator Output		Watts	1560	1560	1440	1440
	Starter Output		kW	2.7	2.7	2.2, 2.7*2	2.2, 2.7*2
Chassis	Clutch Type			—	—	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm
	Transmission Type			A340E	A340E	G55	G55
	Gear Ratio	In First		2.804	2.804	4.452	4.452
		In Second		1.531	1.531	2.619	2.619
		In Third		1.000	1.000	1.517	1.517
		In Fourth		0.705	0.705	1.000	1.000
		In Fifth		—	—	0.854	0.854
		In Sixth		—	—	—	—
		In Reverse		2.393	2.393	4.472	4.472
	Differential Gear Ratio			4.100	4.100	4.300	4.300
	Differential Gear Size		mm (in.)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)
	Brake Type	Front		Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
		Rear		Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum
	Parking Brake Type			Leading-trailing Drum	Leading-trailing Drum	Duo-servo Drum	Duo-servo Drum
	Brake Booster Type and Size		in.	Single, Single with BA*3 10"	Single, Single with BA*3 10"	Single, Single with BA*3 10"	Single, Single with BA*3 10"
	Proportioning Valve Type			LSP and BV	LSP and BV	LSP and BV	LSP and BV
	Suspension Type	Front		Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
		Rear		Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid
	Stabilizer Bar	Front		Standard	Standard	Standard	Standard
		Rear		—	—	—	—
	Steering Gear Type			Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
	Steering Gear Ratio (Overall)			20.84	20.84	20.84	20.84
	Power Steering Type			Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

*1: Option
*2: Cold area specification model
*3: with ABS without VSC

General Countries					
5-door Van (Standard)	4-door Commuter (Standard)				
	DX				
LH200R-SBMDE	LH202R-REMDE	LH202L-REMDE	LH202L-RDMDE	LH212R-JEMDE	LH212L-JEMDE
4695 (184.8)	4695 (184.8)	4695 (184.8)	4695 (184.8)	4840 (190.6)	4840 (190.6)
1695 (66.7)	1695 (66.7)	1695 (66.7)	1695 (66.7)	1880 (74.0)	1880 (74.0)
1980 (78.0)	1980 (78.0)	1980 (78.0)	1980 (78.0)	2105 (82.9)	2105 (82.9)
2570 (101.2)	2570 (101.2)	2570 (101.2)	2570 (101.2)	2570 (101.2)	2570 (101.2)
1470 (57.9)	1470 (57.9)	1470 (57.9)	1470 (57.9)	1655 (65.2)	1655 (65.2)
1465 (57.7)	1465 (57.7)	1465 (57.7)	1465 (57.7)	1650 (65.0)	1650 (65.0)
910 (35.8)	4210 (165.7)	4210 (165.7)	4210 (165.7)	3460 (136.2)	3460 (136.2)
1545 (60.8)	1545 (52.6)	1545 (60.8)	1545 (60.8)	1730 (68.1)	1730 (68.1)
1320 (52.0)	1335 (52.6)	1335 (52.6)	1335 (52.6)	1390 (54.7)	1390 (54.7)
2930 (115.4)	—	—	—	—	—
1545 (60.8)	—	—	—	—	—
1335 (52.6)	—	—	—	—	—
1050 (41.3)	1050 (41.3)	1050 (41.3)	1050 (41.3)	1190 (46.9)	1190 (46.9)
1075 (42.3)	1075 (42.3)	1075 (42.3)	1075 (42.3)	1080 (42.5)	1080 (42.5)
195 (7.7)	185 (7.3)	185 (7.3)	185 (7.3)	185 (7.3)	185 (7.3)
18.5	18.5	18.5	18.5	16.6	16.6
19.5	19.5	19.5	19.5	19.7	19.7
1035 - 1100 (2282 - 2425)	1030 - 1100 (2271 - 2425)	1035 - 1105 (2282 - 2436)	1030 - 1100 (2271 - 2425)	1075 - 1110 (2370 - 2447)	1075 - 1120 (2370 - 2469)
705 - 715 (1554 - 1576)	765 - 780 (1687 - 1720)	765 - 780 (1687 - 1720)	740 - 755 (1631 - 1664)	825 - 830 (1819 - 1830)	825 - 830 (1819 - 1830)
1740 - 1815 (3836 - 4001)	1795 - 1880 (3957 - 4145)	1800 - 1885 (3968 - 4156)	1770 - 1855 (3902 - 4090)	1900 - 1940 (4189 - 4277)	1900 - 1950 (4189 - 4299)
1390 - 1440 (3064 - 3175)	1380 - 1435 (3042 - 3164)	1385 - 1440 (3053 - 3175)	1385 - 1440 (3053 - 3175)	1405 - 1430 (3097 - 3153)	1405 - 1440 (3097 - 3175)
1360 - 1410 (2998 - 3108)	1565 - 1620 (3450 - 3571)	1560 - 1615 (3439 - 3560)	1360 - 1415 (2998 - 3120)	1720 - 1745 (3792 - 3847)	1710 - 1745 (3770 - 3847)
2800 (6173)	3000 (6614)	3000 (6614)	2800 (6173)	3150 (6944)	3150 (6944)
70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)	70 (15.4)
6.0	—	—	—	—	—
140 (87)	140 (87)	140 (87)	140 (87)	130 (81)	130 (81)
—	—	—	—	—	—
29 (18)	29 (18)	29 (18)	29 (18)	29 (18)	29 (18)
50 (31)	50 (31)	50 (31)	50 (31)	50 (31)	50 (31)
86 (53)	86 (53)	86 (53)	86 (53)	86 (53)	86 (53)
131 (81)	131 (81)	131 (81)	131 (81)	131 (81)	131 (81)
—	—	—	—	—	—
—	—	—	—	—	—
5.0 (16.4)	5.0 (16.4)	5.0 (16.4)	5.0 (16.4)	5.3 (17.4)	5.3 (17.4)
5.7 (18.7)	5.7 (18.7)	5.7 (18.7)	5.7 (18.7)	5.9 (19.4)	5.9 (19.4)
5L-E	5L-E	5L-E	5L-E	5L-E	5L-E
8-valve, OHC	8-valve, OHC	8-valve, OHC	8-valve, OHC	8-valve, OHC	8-valve, OHC
99.5 × 96.0 (3.92 × 3.78)	99.5 × 96.0 (3.92 × 3.78)	99.5 × 96.0 (3.92 × 3.78)	99.5 × 96.0 (3.92 × 3.78)	99.5 × 96.0 (3.92 × 3.78)	99.5 × 96.0 (3.92 × 3.78)
2986 (182.2)	2986 (182.2)	2986 (182.2)	2986 (182.2)	2986 (182.2)	2986 (182.2)
22.2 : 1	22.2 : 1	22.2 : 1	22.2 : 1	22.2 : 1	22.2 : 1
Distributor Type	Distributor Type	Distributor Type	Distributor Type	Distributor Type	Distributor Type
48 or higher	48 or higher	48 or higher	48 or higher	48 or higher	48 or higher
68/4000	68/4000	68/4000	68/4000	68/4000	68/4000
197/2400	197/2400	197/2400	197/2400	197/2400	197/2400
12 - 60, 12 - 55 × 2*1	12 - 60, 12 - 55 × 2*1	12 - 60, 12 - 55 × 2*1	12 - 60, 12 - 55 × 2*1	12 - 60, 12 - 55 × 2*1	12 - 60, 12 - 55 × 2*1
1440	1440	1440	1440	1440	1440
2.2, 2.7*2	2.2, 2.7*2	2.2, 2.7*2	2.2, 2.7*2	2.2	2.2
Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm
G55	G55	G55	G55	G55	G55
4.452	4.452	4.452	4.452	4.452	4.452
2.619	2.619	2.619	2.619	2.619	2.619
1.517	1.517	1.517	1.517	1.517	1.517
1.000	1.000	1.000	1.000	1.000	1.000
0.854	0.854	0.854	0.854	0.854	0.854
—	—	—	—	—	—
4.472	4.472	4.472	4.472	4.472	4.472
4.300	4.300	4.300	4.300	4.300	4.300
205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)	205 (8.07)
Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc	Ventilated Disc
Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum	Leading-trailing Drum
Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum	Duo-servo Drum
Single, Single with BA*3 10”	Single, Single with BA*3 10”	Single, Single with BA*3 10”	Single, Single with BA*3 10”	Single, Single with BA*3 10”	Single, Single with BA*3 10”
LSP and BV	LSP and BV	LSP and BV	LSP and BV	LSP and BV	LSP and BV
Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone	Double Wishbone
Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid	Leaf Spring, Rigid
Standard	Standard	Standard	Standard	Standard	Standard
—	—	—	—	—	—
Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion	Rack and Pinion
20.84	20.84	20.84	20.84	20.84	20.84
Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type	Hydraulic Type

Item \ Area				General Countries	
Body Type				4-door Commuter (Super Long)	
Vehicle Grade				DX	
Model Code				LH222R-LEMDE	LH222L-LEMDE
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	5380 (211.8)	5380 (211.8)
		Width	mm (in.)	1880 (74.0)	1880 (74.0)
		Height	mm (in.)	2285 (90.0)	2285 (90.0)
	Wheel Base		mm (in.)	3110 (122.4)	3110 (122.4)
	Tread	Front	mm (in.)	1655 (65.2)	1655 (65.2)
		Rear	mm (in.)	1650 (65.0)	1650 (65.0)
	Room	Length	mm (in.)	4205 (165.6)	4205 (165.6)
		Width	mm (in.)	1730 (68.1)	1730 (68.1)
		Height	mm (in.)	1565 (61.6)	1565 (61.6)
	Cargo Space	Length	mm (in.)	—	—
		Width	mm (in.)	—	—
		Height	mm (in.)	—	—
	Overhang	Front	mm (in.)	1190 (46.9)	1190 (46.9)
		Rear	mm (in.)	1080 (42.5)	1080 (42.5)
	Min. Running Ground Clearance		mm (in.)	185 (7.3)	185 (7.3)
	Angle of Approach		degrees	17.0	17.0
	Angle of Departure		degrees	19.2	19.2
	Curb Weight	Front	kg (lb)	1155 - 1215 (2546 - 2679)	1155 - 1215 (2546 - 2679)
		Rear	kg (lb)	870 - 925 (1918 - 2039)	870 - 925 (1918 - 2039)
		Total	kg (lb)	2025 - 2140 (4464 - 4718)	2025 - 2140 (4464 - 4718)
	Gross Vehicle Weight	Front	kg (lb)	1555 - 1585 (3428 - 3494), 1450 - 1485 (3197 - 3274)*1	1555 - 1585 (3428 - 3494), 1490 - 1520 (3285 - 3351)*2
		Rear	kg (lb)	1715 - 1745 (3781 - 3847), 1715 - 1750 (3781 - 3858)*1	1715 - 1745 (3781 - 3847), 1730 - 1760 (3814 - 3880)*2
		Total	kg (lb)	3300 (7275), 3200 (7055)*1	3300 (7275), 3250 (7165)*2
	Fuel Tank Capacity		ℓ (Imp. gal.)	70 (15.4)	70 (15.4)
	Luggage Compartment Capacity		m^3 (cu. ft.)	—	—
Performance	Max. Speed		km/h (mph)	130 (81)	130 (81)
	Max. Cruising Speed		km/h (mph)	—	—
	Max. Permissible Speed	1st Gear	km/h (mph)	29 (18)	29 (18)
		2nd Gear	km/h (mph)	50 (31)	50 (31)
		3rd Gear	km/h (mph)	86 (53)	86 (53)
		4th Gear	km/h (mph)	131 (81)	131 (81)
		5th Gear	km/h (mph)	—	—
		6th Gear	km/h (mph)	—	—
	Min. Turning Radius	Tire	m (ft.)	6.2 (20.3)	6.2 (20.3)
		Body	m (ft.)	6.9 (22.6)	6.9 (22.6)
Engine	Engine Type			5L-E	5L-E
	Valve Mechanism			8-valve, OHC	8-valve, OHC
	Bore × Stroke		mm (in.)	99.5 × 96.0 (3.92 × 3.78)	99.5 × 96.0 (3.92 × 3.78)
	Displacement		cm^3 (cu. in.)	2986 (182.2)	2986 (182.2)
	Compression Ratio			22.2 : 1	22.2 : 1
	Fuel System			Distributor Type	Distributor Type
	Research Octane No. or Cetane No. (Diesel)			48 or higher	48 or higher
	Max. Output (EEC)		kW/rpm	68/4000	68/4000
	Max. Torque (EEC)		N·m/rpm	197/2400	197/2400
Engine Electrical	Battery Capacity (5HR)		Voltage & Amp. hr.	12 - 60, 12 - 55 × 2*3	12 - 60, 12 - 55 × 2*3
	Alternator Output		Watts	1440	1440
	Starter Output		kW	2.2	2.2
Chassis	Clutch Type			Dry, Single Plate, Diaphragm	Dry, Single Plate, Diaphragm
	Transmission Type			G55	G55
	Gear Ratio	In First		4.452	4.452
		In Second		2.619	2.619
		In Third		1.517	1.517
		In Fourth		1.000	1.000
		In Fifth		0.854	0.854
		In Sixth		—	—
		In Reverse		4.472	4.472
	Differential Gear Ratio			4.300	4.300
	Differential Gear Size		mm (in.)	205 (8.07)	205 (8.07)
	Brake Type	Front		Ventilated Disc	Ventilated Disc
		Rear		Leading-trailing Drum	Leading-trailing Drum
	Parking Brake Type			Leading-trailing Drum	Leading-trailing Drum
	Brake Booster Type and Size		in.	Single, Single with BA*4 10”	Single, Single with BA*4 10”
	Proportioning Valve Type			LSP and BV	LSP and BV
	Suspension Type	Front		Double Wishbone	Double Wishbone
		Rear		Leaf Spring, Rigid	Leaf Spring, Rigid
	Stabilizer Bar	Front		Standard	Standard
		Rear		—	—
	Steering Gear Type			Rack and Pinion	Rack and Pinion
	Steering Gear Ratio (Overall)			20.84	20.84
	Power Steering Type			Hydraulic Type	Hydraulic Type

*1: 14-passenger model
*2: 15-passenger model
*3: Option
*4: with ABS without VSC